

# NAG Library Routine Document

## F06PFF (DTRMV)

**Note:** before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

### 1 Purpose

F06PFF (DTRMV) computes the matrix-vector product for a real triangular matrix or its transpose.

### 2 Specification

```
SUBROUTINE F06PFF (UPLO, TRANS, DIAG, N, A, LDA, X, INCX)
  INTEGER          N, LDA, INCX
  REAL (KIND=nag_wp) A(LDA,*), X(*)
  CHARACTER(1)    UPLO, TRANS, DIAG
```

The routine may be called by its BLAS name *dtrmv*.

### 3 Description

F06PFF (DTRMV) performs one of the matrix-vector operations

$$x \leftarrow Ax \quad \text{or} \quad x \leftarrow A^T x,$$

where  $A$  is an  $n$  by  $n$  real triangular matrix, and  $x$  is an  $n$ -element real vector.

### 4 References

None.

### 5 Arguments

- 1: UPLO – CHARACTER(1) *Input*  
*On entry:* specifies whether  $A$  is upper or lower triangular.  
 UPLO = 'U'  
 $A$  is upper triangular.  
 UPLO = 'L'  
 $A$  is lower triangular.  
*Constraint:* UPLO = 'U' or 'L'.
- 2: TRANS – CHARACTER(1) *Input*  
*On entry:* specifies the operation to be performed.  
 TRANS = 'N'  
 $x \leftarrow Ax$ .  
 TRANS = 'T' or 'C'  
 $x \leftarrow A^T x$ .  
*Constraint:* TRANS = 'N', 'T' or 'C'.

- 3:    DIAG – CHARACTER(1) *Input*  
*On entry:* specifies whether  $A$  has nonunit or unit diagonal elements.  
 DIAG = 'N'  
       The diagonal elements are stored explicitly.  
 DIAG = 'U'  
       The diagonal elements are assumed to be 1, and are not referenced.  
*Constraint:* DIAG = 'N' or 'U'.
- 4:    N – INTEGER *Input*  
*On entry:*  $n$ , the order of the matrix  $A$ .  
*Constraint:*  $N \geq 0$ .
- 5:    A(LDA,\*) – REAL (KIND=nag\_wp) array *Input*  
**Note:** the second dimension of the array  $A$  must be at least  $N$ .  
*On entry:* the  $n$  by  $n$  triangular matrix  $A$ .  
       If UPLO = 'U',  $A$  is upper triangular and the elements of the array below the diagonal are not referenced.  
       If UPLO = 'L',  $A$  is lower triangular and the elements of the array above the diagonal are not referenced.  
       If DIAG = 'U', the diagonal elements of  $A$  are assumed to be 1, and are not referenced.
- 6:    LDA – INTEGER *Input*  
*On entry:* the first dimension of the array  $A$  as declared in the (sub)program from which F06PFF (DTRMV) is called.  
*Constraint:*  $LDA \geq \max(1, N)$ .
- 7:    X(\*) – REAL (KIND=nag\_wp) array *Input/Output*  
**Note:** the dimension of the array  $X$  must be at least  $\max(1, 1 + (N - 1) \times |\text{INCX}|)$ .  
*On entry:* the  $n$ -element vector  $x$ .  
 If  $\text{INCX} > 0$ ,  $x_i$  must be stored in  $X(1 + (i-1) \times \text{INCX})$ , for  $i = 1, 2, \dots, N$ .  
 If  $\text{INCX} < 0$ ,  $x_i$  must be stored in  $X(1 - (N-i) \times \text{INCX})$ , for  $i = 1, 2, \dots, N$ .  
*On exit:* the updated vector  $x$  stored in the array elements used to supply the original vector  $x$ .
- 8:    INCX – INTEGER *Input*  
*On entry:* the increment in the subscripts of  $X$  between successive elements of  $x$ .  
*Constraint:*  $\text{INCX} \neq 0$ .

## 6 Error Indicators and Warnings

None.

## 7 Accuracy

Not applicable.

## **8 Parallelism and Performance**

F06PFF (DTRMV) is not threaded in any implementation.

## **9 Further Comments**

None.

## **10 Example**

None.

---