NAG Library Routine Document F07PVF (ZHPRFS)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of **bold italicised** terms and other implementation-dependent details.

1 Purpose

F07PVF (ZHPRFS) returns error bounds for the solution of a complex Hermitian indefinite system of linear equations with multiple right-hand sides, AX = B, using packed storage. It improves the solution by iterative refinement, in order to reduce the backward error as much as possible.

2 Specification

```
SUBROUTINE F07PVF (UPLO, N, NRHS, AP, AFP, IPIV, B, LDB, X, LDX, FERR, BERR, WORK, RWORK, INFO)

INTEGER

N, NRHS, IPIV(*), LDB, LDX, INFO

REAL (KIND=nag_wp)
FERR(NRHS), BERR(NRHS), RWORK(N)

COMPLEX (KIND=nag_wp) AP(*), AFP(*), B(LDB,*), X(LDX,*), WORK(2*N)

CHARACTER(1)

UPLO
```

The routine may be called by its LAPACK name zhprfs.

3 Description

F07PVF (ZHPRFS) returns the backward errors and estimated bounds on the forward errors for the solution of a complex Hermitian indefinite system of linear equations with multiple right-hand sides AX = B, using packed storage. The routine handles each right-hand side vector (stored as a column of the matrix B) independently, so we describe the function of F07PVF (ZHPRFS) in terms of a single right-hand side b and solution x.

Given a computed solution x, the routine computes the *component-wise backward error* β . This is the size of the smallest relative perturbation in each element of A and b such that x is the exact solution of a perturbed system

$$\begin{aligned} &(A+\delta A)x=b+\delta b\\ &|\delta a_{ij}|\leq \beta |a_{ij}| \quad \text{ and } &|\delta b_i|\leq \beta |b_i|. \end{aligned}$$

Then the routine estimates a bound for the *component-wise forward error* in the computed solution, defined by:

$$\max_{i} |x_i - \hat{x}_i| / \max_{i} |x_i|$$

where \hat{x} is the true solution.

For details of the method, see the F07 Chapter Introduction.

4 References

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

Mark 26 F07PVF.1

5 Arguments

1: UPLO - CHARACTER(1)

Input

On entry: specifies whether the upper or lower triangular part of A is stored and how A is to be factorized.

UPLO = 'U'

The upper triangular part of A is stored and A is factorized as $PUDU^{H}P^{T}$, where U is upper triangular.

UPLO = 'L'

The lower triangular part of A is stored and A is factorized as $PLDL^{H}P^{T}$, where L is lower triangular.

Constraint: UPLO = 'U' or 'L'.

2: N - INTEGER

Input

On entry: n, the order of the matrix A.

Constraint: $N \ge 0$.

3: NRHS - INTEGER

Input

On entry: r, the number of right-hand sides.

Constraint: NRHS ≥ 0 .

4: $AP(*) - COMPLEX (KIND=nag_wp) array$

Input

Note: the dimension of the array AP must be at least $max(1, N \times (N+1)/2)$.

On entry: the n by n original Hermitian matrix A as supplied to F07PRF (ZHPTRF).

5: AFP(*) - COMPLEX (KIND=nag_wp) array

Input

Note: the dimension of the array AFP must be at least $max(1, N \times (N+1)/2)$.

On entry: the factorization of A stored in packed form, as returned by F07PRF (ZHPTRF).

6: IPIV(*) – INTEGER array

Input

Note: the dimension of the array IPIV must be at least max(1, N).

On entry: details of the interchanges and the block structure of D, as returned by F07PRF (ZHPTRF).

7: B(LDB,*) - COMPLEX (KIND=nag wp) array

Input

Note: the second dimension of the array B must be at least max(1, NRHS).

On entry: the n by r right-hand side matrix B.

8: LDB – INTEGER

Input

On entry: the first dimension of the array B as declared in the (sub)program from which F07PVF (ZHPRFS) is called.

Constraint: LDB $\geq \max(1, N)$.

9: $X(LDX,*) - COMPLEX (KIND=nag_wp)$ array

Input/Output

Note: the second dimension of the array X must be at least max(1, NRHS).

On entry: the n by r solution matrix X, as returned by F07PSF (ZHPTRS).

On exit: the improved solution matrix X.

F07PVF.2 Mark 26

10: LDX - INTEGER

Input

On entry: the first dimension of the array X as declared in the (sub)program from which F07PVF (ZHPRFS) is called.

Constraint: LDX \geq max(1, N).

11: FERR(NRHS) - REAL (KIND=nag wp) array

Output

On exit: FERR(j) contains an estimated error bound for the jth solution vector, that is, the jth column of X, for j = 1, 2, ..., r.

12: BERR(NRHS) - REAL (KIND=nag wp) array

Output

On exit: BERR(j) contains the component-wise backward error bound β for the jth solution vector, that is, the jth column of X, for j = 1, 2, ..., r.

13: WORK $(2 \times N)$ – COMPLEX (KIND=nag wp) array

Workspace

14: RWORK(N) – REAL (KIND=nag wp) array

Workspace

15: INFO – INTEGER

Output

On exit: INFO = 0 unless the routine detects an error (see Section 6).

6 Error Indicators and Warnings

INFO < 0

If INFO = -i, argument i had an illegal value. An explanatory message is output, and execution of the program is terminated.

7 Accuracy

The bounds returned in FERR are not rigorous, because they are estimated, not computed exactly; but in practice they almost always overestimate the actual error.

8 Parallelism and Performance

F07PVF (ZHPRFS) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

F07PVF (ZHPRFS) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this routine. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

For each right-hand side, computation of the backward error involves a minimum of $16n^2$ real floating-point operations. Each step of iterative refinement involves an additional $24n^2$ real operations. At most five steps of iterative refinement are performed, but usually only 1 or 2 steps are required.

Estimating the forward error involves solving a number of systems of linear equations of the form Ax = b; the number is usually 5 and never more than 11. Each solution involves approximately $8n^2$ real operations.

The real analogue of this routine is F07PHF (DSPRFS).

Mark 26 F07PVF.3

10 Example

This example solves the system of equations AX = B using iterative refinement and to compute the forward and backward error bounds, where

$$A = \begin{pmatrix} -1.36 + 0.00i & 1.58 + 0.90i & 2.21 - 0.21i & 3.91 + 1.50i \\ 1.58 - 0.90i & -8.87 + 0.00i & -1.84 - 0.03i & -1.78 + 1.18i \\ 2.21 + 0.21i & -1.84 + 0.03i & -4.63 + 0.00i & 0.11 + 0.11i \\ 3.91 - 1.50i & -1.78 - 1.18i & 0.11 - 0.11i & -1.84 + 0.00i \end{pmatrix}$$

and

$$B = \begin{pmatrix} 7.79 + 5.48i & -35.39 + 18.01i \\ -0.77 - 16.05i & 4.23 - 70.02i \\ -9.58 + 3.88i & -24.79 - 8.40i \\ 2.98 - 10.18i & 28.68 - 39.89i \end{pmatrix}.$$

Here A is Hermitian indefinite, stored in packed form, and must first be factorized by F07PRF (ZHPTRF).

10.1 Program Text

```
Program f07pvfe
     FO7PVF Example Program Text
1
1
     Mark 26 Release. NAG Copyright 2016.
      .. Use Statements ..
!
     Use nag_library, Only: nag_wp, x04dbf, zhprfs, zhptrf, zhptrs
     .. Implicit None Statement ..
!
     Implicit None
     .. Parameters ..
     Integer, Parameter
                                     :: nin = 5, nout = 6
     .. Local Scalars ..
                                      :: aplen, i, ifail, info, j, ldb, ldx, &
     Integer
                                        n, nrhs
     Character (1)
                                      :: uplo
!
      .. Local Arrays ..
     Complex (Kind=nag_wp), Allocatable :: afp(:), ap(:), b(:,:), work(:),
     x(:,:)
Real (Kind=nag_wp), Allocatable :: berr(:), ferr(:), rwork(:)
     .. Executable Statements ..
!
     Write (nout,*) 'F07PVF Example Program Results'
     Skip heading in data file
!
     Read (nin,*)
     Read (nin,*) n, nrhs
     ldb = n
     ldx = n
     aplen = n*(n+1)/2
     Allocate (afp(aplen), ap(aplen), b(ldb, nrhs), work(2*n), x(ldx,n),
       berr(nrhs),ferr(nrhs),rwork(n),ipiv(n))
     Read A and B from data file, and copy A to AFP and B to X
     Read (nin,*) uplo
     If (uplo=='U') Then
       Read (nin,*)((ap(i+j*(j-1)/2),j=i,n),i=1,n)
     Else If (uplo=='L') Then
       Read (nin,*)((ap(i+(2*n-j)*(j-1)/2),j=1,i),i=1,n)
     End If
     Read (nin,*)(b(i,1:nrhs),i=1,n)
     afp(1:aplen) = ap(1:aplen)
     x(1:n,1:nrhs) = b(1:n,1:nrhs)
```

F07PVF.4 Mark 26

```
!
      Factorize A in the array AFP
!
      The NAG name equivalent of zhptrf is f07prf
      Call zhptrf(uplo,n,afp,ipiv,info)
      Write (nout,*)
      Flush (nout)
      If (info==0) Then
        Compute solution in the array X
!
        The NAG name equivalent of zhptrs is f07psf
        Call zhptrs(uplo,n,nrhs,afp,ipiv,x,ldx,info)
!
        Improve solution, and compute backward errors and
        estimated bounds on the forward errors
!
        The NAG name equivalent of zhprfs is f07puf
1
        Call zhprfs(uplo,n,nrhs,ap,afp,ipiv,b,ldb,x,ldx,ferr,berr,work,rwork, &
          info)
        Print solution
!
        ifail: behaviour on error exit
                =0 for hard exit, =1 for quiet-soft, =-1 for noisy-soft
!
        ifail = 0
        Call x04dbf('General',' ',n,nrhs,x,ldx,'Bracketed','F7.4',
           'Solution(s)','Integer',rlabs,'Integer',clabs,80,0,ifail)
        Write (nout,*)
        Write (nout,*) 'Backward errors (machine-dependent)'
        Write (nout,99999) berr(1:nrhs)
        Write (nout,*) 'Estimated forward error bounds (machine-dependent)'
        Write (nout, 99999) ferr(1:nrhs)
        Write (nout,*) 'The factor D is singular'
      End If
99999 Format ((5X,1P,4(E11.1,7X)))
    End Program f07pvfe
10.2 Program Data
FO7PVF Example Program Data
  4 2
                                                               :Values of N and NRHS
  'L'
                                                               :Value of UPLO
 (-1.36, 0.00)
 ( 1.58,-0.90) (-8.87, 0.00)
( 2.21, 0.21) (-1.84, 0.03) (-4.63, 0.00)
( 3.91,-1.50) (-1.78,-1.18) ( 0.11,-0.11) (-1.84, 0.00) :End of matrix A
 (7.79, 5.48) (-35.39, 18.01)
 (-0.77,-16.05) ( 4.23,-70.02)
 (-9.58, 3.88) (-24.79, -8.40)
 ( 2.98,-10.18) ( 28.68,-39.89)
                                                               :End of matrix B
10.3 Program Results
 FO7PVF Example Program Results
Solution(s)
 1 (1.0000,-1.0000) (3.0000,-4.0000)
 2 (-1.0000, 2.0000) (-1.0000, 5.0000)
3 (3.0000,-2.0000) (7.0000,-2.0000)
4 (2.0000, 1.0000) (-8.0000, 6.0000)
```

Mark 26 F07PVF.5 (last)

Backward errors (machine-dependent)

3.5E-17

3.0E - 15

Estimated forward error bounds (machine-dependent)

5.1E-17

2.5E-15