

NAG Library Routine Document

F07UHF (DTPRFS)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

F07UHF (DTPRFS) returns error bounds for the solution of a real triangular system of linear equations with multiple right-hand sides, $AX = B$ or $A^T X = B$, using packed storage.

2 Specification

```

SUBROUTINE F07UHF (UPLO, TRANS, DIAG, N, NRHS, AP, B, LDB, X, LDX, FERR,      &
                  BERR, WORK, IWORK, INFO)
INTEGER          N, NRHS, LDB, LDX, IWORK(N), INFO
REAL (KIND=nag_wp) AP(*), B(LDB,*), X(LDX,*), FERR(NRHS), BERR(NRHS),      &
                  WORK(3*N)
CHARACTER(1)     UPLO, TRANS, DIAG

```

The routine may be called by its LAPACK name *dtpfrfs*.

3 Description

F07UHF (DTPRFS) returns the backward errors and estimated bounds on the forward errors for the solution of a real triangular system of linear equations with multiple right-hand sides $AX = B$ or $A^T X = B$, using packed storage. The routine handles each right-hand side vector (stored as a column of the matrix B) independently, so we describe the function of F07UHF (DTPRFS) in terms of a single right-hand side b and solution x .

Given a computed solution x , the routine computes the *component-wise backward error* β . This is the size of the smallest relative perturbation in each element of A and b such that x is the exact solution of a perturbed system

$$(A + \delta A)x = b + \delta b$$

$$|\delta a_{ij}| \leq \beta |a_{ij}| \quad \text{and} \quad |\delta b_i| \leq \beta |b_i|.$$

Then the routine estimates a bound for the *component-wise forward error* in the computed solution, defined by:

$$\max_i |x_i - \hat{x}_i| / \max_i |x_i|$$

where \hat{x} is the true solution.

For details of the method, see the F07 Chapter Introduction.

4 References

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

5 Arguments

- 1: UPLO – CHARACTER(1) *Input*
On entry: specifies whether A is upper or lower triangular.
 UPLO = 'U'
 A is upper triangular.

- UPLO = 'L'
A is lower triangular.
Constraint: UPLO = 'U' or 'L'.
- 2: TRANS – CHARACTER(1) *Input*
On entry: indicates the form of the equations.
 TRANS = 'N'
 The equations are of the form $AX = B$.
 TRANS = 'T' or 'C'
 The equations are of the form $A^T X = B$.
Constraint: TRANS = 'N', 'T' or 'C'.
- 3: DIAG – CHARACTER(1) *Input*
On entry: indicates whether *A* is a nonunit or unit triangular matrix.
 DIAG = 'N'
A is a nonunit triangular matrix.
 DIAG = 'U'
A is a unit triangular matrix; the diagonal elements are not referenced and are assumed to be 1.
Constraint: DIAG = 'N' or 'U'.
- 4: N – INTEGER *Input*
On entry: *n*, the order of the matrix *A*.
Constraint: $N \geq 0$.
- 5: NRHS – INTEGER *Input*
On entry: *r*, the number of right-hand sides.
Constraint: $NRHS \geq 0$.
- 6: AP(*) – REAL (KIND=nag_wp) array *Input*
Note: the dimension of the array AP must be at least $\max(1, N \times (N + 1)/2)$.
On entry: the *n* by *n* triangular matrix *A*, packed by columns.
 More precisely,
 if UPLO = 'U', the upper triangle of *A* must be stored with element A_{ij} in
 AP($i + j(j - 1)/2$) for $i \leq j$;
 if UPLO = 'L', the lower triangle of *A* must be stored with element A_{ij} in
 AP($i + (2n - j)(j - 1)/2$) for $i \geq j$.
 If DIAG = 'U', the diagonal elements of *A* are assumed to be 1, and are not referenced; the same storage scheme is used whether DIAG = 'N' or 'U'.
- 7: B(LDB,*) – REAL (KIND=nag_wp) array *Input*
Note: the second dimension of the array B must be at least $\max(1, NRHS)$.
On entry: the *n* by *r* right-hand side matrix *B*.

- 8: LDB – INTEGER *Input*
On entry: the first dimension of the array B as declared in the (sub)program from which F07UHF (DTPRFS) is called.
Constraint: $LDB \geq \max(1, N)$.
- 9: X(LDX, *) – REAL (KIND=nag_wp) array *Input*
Note: the second dimension of the array X must be at least $\max(1, NRHS)$.
On entry: the n by r solution matrix X , as returned by F07UEF (DTPTRS).
- 10: LDX – INTEGER *Input*
On entry: the first dimension of the array X as declared in the (sub)program from which F07UHF (DTPRFS) is called.
Constraint: $LDX \geq \max(1, N)$.
- 11: FERR(NRHS) – REAL (KIND=nag_wp) array *Output*
On exit: $FERR(j)$ contains an estimated error bound for the j th solution vector, that is, the j th column of X , for $j = 1, 2, \dots, r$.
- 12: BERR(NRHS) – REAL (KIND=nag_wp) array *Output*
On exit: $BERR(j)$ contains the component-wise backward error bound β for the j th solution vector, that is, the j th column of X , for $j = 1, 2, \dots, r$.
- 13: WORK(3 × N) – REAL (KIND=nag_wp) array *Workspace*
- 14: IWORK(N) – INTEGER array *Workspace*
- 15: INFO – INTEGER *Output*
On exit: $INFO = 0$ unless the routine detects an error (see Section 6).

6 Error Indicators and Warnings

INFO < 0

If $INFO = -i$, argument i had an illegal value. An explanatory message is output, and execution of the program is terminated.

7 Accuracy

The bounds returned in FERR are not rigorous, because they are estimated, not computed exactly; but in practice they almost always overestimate the actual error.

8 Parallelism and Performance

F07UHF (DTPRFS) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

F07UHF (DTPRFS) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this routine. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

A call to F07UHF (DTPRFS), for each right-hand side, involves solving a number of systems of linear equations of the form $Ax = b$ or $A^T x = b$; the number is usually 4 or 5 and never more than 11. Each solution involves approximately n^2 floating-point operations.

The complex analogue of this routine is F07UVF (ZTPRFS).

10 Example

This example solves the system of equations $AX = B$ and to compute forward and backward error bounds, where

$$A = \begin{pmatrix} 4.30 & 0.00 & 0.00 & 0.00 \\ -3.96 & -4.87 & 0.00 & 0.00 \\ 0.40 & 0.31 & -8.02 & 0.00 \\ -0.27 & 0.07 & -5.95 & 0.12 \end{pmatrix} \quad \text{and} \quad B = \begin{pmatrix} -12.90 & -21.50 \\ 16.75 & 14.93 \\ -17.55 & 6.33 \\ -11.04 & 8.09 \end{pmatrix},$$

using packed storage for A .

10.1 Program Text

```

Program f07uhfe

!      F07UHF Example Program Text
!
!      Mark 26 Release. NAG Copyright 2016.
!
!      .. Use Statements ..
      Use nag_library, Only: dtprfs, dtptrs, nag_wp, x04caf
!      .. Implicit None Statement ..
      Implicit None
!      .. Parameters ..
      Integer, Parameter          :: nin = 5, nout = 6
      Character (1), Parameter    :: diag = 'N', trans = 'N'
!      .. Local Scalars ..
      Integer                     :: i, ifail, info, j, ldb, ldx, n, nrhs
      Character (1)               :: uplo
!      .. Local Arrays ..
      Real (Kind=nag_wp), Allocatable :: ap(:), b(:,,:), berr(:), ferr(:),      &
                                         work(:), x(:,:)
      Integer, Allocatable        :: iwork(:)
!      .. Executable Statements ..
      Write (nout,*) 'F07UHF Example Program Results'
!      Skip heading in data file
      Read (nin,*)
      Read (nin,*) n, nrhs
      ldb = n
      ldx = n
      Allocate (ap(n*(n+1)/2),b(ldb,nrhs),berr(nrhs),ferr(nrhs),work(3*n),x(      &
          ldx,n),iwork(n))

!      Read A and B from data file, and copy B to X

      Read (nin,*) uplo
      If (uplo=='U') Then
         Read (nin,*)((ap(i+j*(j-1)/2),j=i,n),i=1,n)
      Else If (uplo=='L') Then
         Read (nin,*)((ap(i+(2*n-j)*(j-1)/2),j=1,i),i=1,n)
      End If
      Read (nin,*)(b(i,1:nrhs),i=1,n)

      x(1:n,1:nrhs) = b(1:n,1:nrhs)

!      Compute solution in the array X
!      The NAG name equivalent of dtptrs is f07uef
      Call dtprfs(uplo,trans,diag,n,nrhs,ap,x,ldx,info)

```

```

!      Compute backward errors and estimated bounds on the
!      forward errors

!      The NAG name equivalent of dtpfrfs is f07uhf
!      Call dtpfrfs(uplo,trans,diag,n,nrhs,ap,b,ldb,x,ldx,ferr,berr,work,iwork, &
!      info)

!      Print solution

!      Write (nout,*)
!      Flush (nout)

!      ifail: behaviour on error exit
!      =0 for hard exit, =1 for quiet-soft, =-1 for noisy-soft
!      ifail = 0
!      Call x04caf('General',' ',n,nrhs,x,ldx,'Solution(s)',ifail)

!      Write (nout,*)
!      Write (nout,*) 'Backward errors (machine-dependent)'
!      Write (nout,99999) berr(1:nrhs)
!      Write (nout,*) 'Estimated forward error bounds (machine-dependent)'
!      Write (nout,99999) ferr(1:nrhs)

99999 Format ((3X,1P,7E11.1))
      End Program f07uhfe

```

10.2 Program Data

F07UHF Example Program Data

```

4 2          :Values of N and NRHS
'L'         :Value of UPLO
4.30
-3.96 -4.87
0.40 0.31 -8.02
-0.27 0.07 -5.95 0.12 :End of matrix A
-12.90 -21.50
16.75 14.93
-17.55 6.33
-11.04 8.09      :End of matrix B

```

10.3 Program Results

F07UHF Example Program Results

Solution(s)

	1	2
1	-3.0000	-5.0000
2	-1.0000	1.0000
3	2.0000	-1.0000
4	1.0000	6.0000

Backward errors (machine-dependent)

6.9E-17	0.0E+00
---------	---------

Estimated forward error bounds (machine-dependent)

8.3E-14	2.6E-14
---------	---------
