

# NAG Library Routine Document

## F08WAF (DGGEV)

**Note:** before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

### 1 Purpose

F08WAF (DGGEV) computes for a pair of  $n$  by  $n$  real nonsymmetric matrices ( $A, B$ ) the generalized eigenvalues and, optionally, the left and/or right generalized eigenvectors using the  $QZ$  algorithm. F08WAF (DGGEV) is marked as *deprecated* by LAPACK; the replacement routine is F08WCF (DGGEV3) which makes better use of level 3 BLAS.

### 2 Specification

```
SUBROUTINE F08WAF (JOBVL, JOBVR, N, A, LDA, B, LDB, ALPHAR, ALPHAI,           &
                  BETA, VL, LDVL, VR, LDVR, WORK, LWORK, INFO)
INTEGER          N, LDA, LDB, LDVL, LDVR, LWORK, INFO
REAL (KIND=nag_wp) A(LDA,*), B(LDB,*), ALPHAR(N), ALPHAI(N), BETA(N),      &
                   VL(LDVL,*), VR(LDVR,*), WORK(max(1,LWORK))
CHARACTER(1)     JOBVL, JOBVR
```

The routine may be called by its LAPACK name *dggev*.

### 3 Description

A generalized eigenvalue for a pair of matrices ( $A, B$ ) is a scalar  $\lambda$  or a ratio  $\alpha/\beta = \lambda$ , such that  $A - \lambda B$  is singular. It is usually represented as the pair  $(\alpha, \beta)$ , as there is a reasonable interpretation for  $\beta = 0$ , and even for both being zero.

The right eigenvector  $v_j$  corresponding to the eigenvalue  $\lambda_j$  of ( $A, B$ ) satisfies

$$Av_j = \lambda_j Bv_j.$$

The left eigenvector  $u_j$  corresponding to the eigenvalue  $\lambda_j$  of ( $A, B$ ) satisfies

$$u_j^H A = \lambda_j u_j^H B,$$

where  $u_j^H$  is the conjugate-transpose of  $u_j$ .

All the eigenvalues and, if required, all the eigenvectors of the generalized eigenproblem  $Ax = \lambda Bx$ , where  $A$  and  $B$  are real, square matrices, are determined using the  $QZ$  algorithm. The  $QZ$  algorithm consists of four stages:

1.  $A$  is reduced to upper Hessenberg form and at the same time  $B$  is reduced to upper triangular form.
2.  $A$  is further reduced to quasi-triangular form while the triangular form of  $B$  is maintained. This is the real generalized Schur form of the pair ( $A, B$ ).
3. The quasi-triangular form of  $A$  is reduced to triangular form and the eigenvalues extracted. This routine does not actually produce the eigenvalues  $\lambda_j$ , but instead returns  $\alpha_j$  and  $\beta_j$  such that

$$\lambda_j = \alpha_j/\beta_j, \quad j = 1, 2, \dots, n.$$

The division by  $\beta_j$  becomes your responsibility, since  $\beta_j$  may be zero, indicating an infinite eigenvalue. Pairs of complex eigenvalues occur with  $\alpha_j/\beta_j$  and  $\alpha_{j+1}/\beta_{j+1}$  complex conjugates, even though  $\alpha_j$  and  $\alpha_{j+1}$  are not conjugate.

4. If the eigenvectors are required they are obtained from the triangular matrices and then transformed back into the original coordinate system.

## 4 References

- Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia <http://www.netlib.org/lapack/lug>
- Golub G H and Van Loan C F (2012) *Matrix Computations* (4th Edition) Johns Hopkins University Press, Baltimore
- Wilkinson J H (1979) Kronecker's canonical form and the *QZ* algorithm *Linear Algebra Appl.* **28** 285–303

## 5 Arguments

- 1: JOBVL – CHARACTER(1) *Input*  
*On entry:* if JOBVL = 'N', do not compute the left generalized eigenvectors.  
If JOBVL = 'V', compute the left generalized eigenvectors.  
*Constraint:* JOBVL = 'N' or 'V'.
- 2: JOBVR – CHARACTER(1) *Input*  
*On entry:* if JOBVR = 'N', do not compute the right generalized eigenvectors.  
If JOBVR = 'V', compute the right generalized eigenvectors.  
*Constraint:* JOBVR = 'N' or 'V'.
- 3: N – INTEGER *Input*  
*On entry:*  $n$ , the order of the matrices  $A$  and  $B$ .  
*Constraint:*  $N \geq 0$ .
- 4: A(LDA,\*) – REAL (KIND=nag\_wp) array *Input/Output*  
**Note:** the second dimension of the array A must be at least max(1,N).  
*On entry:* the matrix  $A$  in the pair  $(A, B)$ .  
*On exit:* A has been overwritten.
- 5: LDA – INTEGER *Input*  
*On entry:* the first dimension of the array A as declared in the (sub)program from which F08WAF (DGGEV) is called.  
*Constraint:*  $LDA \geq \max(1, N)$ .
- 6: B(LDB,\*) – REAL (KIND=nag\_wp) array *Input/Output*  
**Note:** the second dimension of the array B must be at least max(1,N).  
*On entry:* the matrix  $B$  in the pair  $(A, B)$ .  
*On exit:* B has been overwritten.
- 7: LDB – INTEGER *Input*  
*On entry:* the first dimension of the array B as declared in the (sub)program from which F08WAF (DGGEV) is called.  
*Constraint:*  $LDB \geq \max(1, N)$ .

8:	ALPHAR(N) – REAL (KIND=nag_wp) array	<i>Output</i>
	<i>On exit:</i> the element ALPHAR( $j$ ) contains the real part of $\alpha_j$ .	
9:	ALPHAI(N) – REAL (KIND=nag_wp) array	<i>Output</i>
	<i>On exit:</i> the element ALPHAI( $j$ ) contains the imaginary part of $\alpha_j$ .	
10:	BETA(N) – REAL (KIND=nag_wp) array	<i>Output</i>
	<i>On exit:</i> $(\text{ALPHAR}(j) + \text{ALPHAI}(j) \times i)/\text{BETA}(j)$ , for $j = 1, 2, \dots, N$ , will be the generalized eigenvalues.	
	If ALPHAI( $j$ ) is zero, then the $j$ th eigenvalue is real; if positive, then the $j$ th and $(j+1)$ st eigenvalues are a complex conjugate pair, with ALPHAI( $j+1$ ) negative.	
	<b>Note:</b> the quotients ALPHAR( $j$ )/BETA( $j$ ) and ALPHAI( $j$ )/BETA( $j$ ) may easily overflow or underflow, and BETA( $j$ ) may even be zero. Thus, you should avoid naively computing the ratio $\alpha_j/\beta_j$ . However, $\max \alpha_j $ will always be less than and usually comparable with $\ A\ _2$ in magnitude, and $\max \beta_j $ will always be less than and usually comparable with $\ B\ _2$ .	
11:	VL(LDVL,*) – REAL (KIND=nag_wp) array	<i>Output</i>
	<b>Note:</b> the second dimension of the array VL must be at least $\max(1, N)$ if JOBVL = 'V', and at least 1 otherwise.	
	<i>On exit:</i> if JOBVL = 'V', the left eigenvectors $u_j$ are stored one after another in the columns of VL, in the same order as the corresponding eigenvalues.	
	If the $j$ th eigenvalue is real, then $u_j = VL(:, j)$ , the $j$ th column of VL.	
	If the $j$ th and $(j+1)$ th eigenvalues form a complex conjugate pair, then $u_j = VL(:, j) + i \times VL(:, j+1)$ and $u_{j+1} = VL(:, j) - i \times VL(:, j+1)$ . Each eigenvector will be scaled so the largest component has  real part  +  imag. part  = 1.	
	If JOBVL = 'N', VL is not referenced.	
12:	LDVL – INTEGER	<i>Input</i>
	<i>On entry:</i> the first dimension of the array VL as declared in the (sub)program from which F08WAF (DGGEV) is called.	
	<i>Constraints:</i>	
	if JOBVL = 'V', LDVL $\geq \max(1, N)$ ; otherwise LDVL $\geq 1$ .	
13:	VR(LDVR,*) – REAL (KIND=nag_wp) array	<i>Output</i>
	<b>Note:</b> the second dimension of the array VR must be at least $\max(1, N)$ if JOBVR = 'V', and at least 1 otherwise.	
	<i>On exit:</i> if JOBVR = 'V', the right eigenvectors $v_j$ are stored one after another in the columns of VR, in the same order as the corresponding eigenvalues.	
	If the $j$ th eigenvalue is real, then $v_j = VR(:, j)$ , the $j$ th column of VR.	
	If the $j$ th and $(j+1)$ th eigenvalues form a complex conjugate pair, then $v_j = VR(:, j) + i \times VR(:, j+1)$ and $v_{j+1} = VR(:, j) - i \times VR(:, j+1)$ . Each eigenvector will be scaled so the largest component has  real part  +  imag. part  = 1.	
	If JOBVR = 'N', VR is not referenced.	
14:	LDVR – INTEGER	<i>Input</i>
	<i>On entry:</i> the first dimension of the array VR as declared in the (sub)program from which F08WAF (DGGEV) is called.	

*Constraints:*

if  $\text{JOBVR} = \text{'V'}$ ,  $\text{LDVR} \geq \max(1, N)$ ;  
 otherwise  $\text{LDVR} \geq 1$ .

15:  $\text{WORK}(\max(1, \text{LWORK}))$  – REAL (KIND=nag\_wp) array *Workspace*

*On exit:* if  $\text{INFO} = 0$ ,  $\text{WORK}(1)$  contains the minimum value of  $\text{LWORK}$  required for optimal performance.

16:  $\text{LWORK}$  – INTEGER *Input*

*On entry:* the dimension of the array  $\text{WORK}$  as declared in the (sub)program from which F08WAF (DGGEV) is called.

If  $\text{LWORK} = -1$ , a workspace query is assumed; the routine only calculates the optimal size of the  $\text{WORK}$  array, returns this value as the first entry of the  $\text{WORK}$  array, and no error message related to  $\text{LWORK}$  is issued.

*Suggested value:* for optimal performance,  $\text{LWORK}$  must generally be larger than the minimum; increase workspace by, say,  $nb \times N$ , where  $nb$  is the optimal **block size**.

*Constraint:*  $\text{LWORK} \geq \max(1, 8 \times N)$ .

17:  $\text{INFO}$  – INTEGER *Output*

*On exit:*  $\text{INFO} = 0$  unless the routine detects an error (see Section 6).

## 6 Error Indicators and Warnings

$\text{INFO} < 0$

If  $\text{INFO} = -i$ , argument  $i$  had an illegal value. An explanatory message is output, and execution of the program is terminated.

$\text{INFO} = 1$  to  $N$

The  $QZ$  iteration failed. No eigenvectors have been calculated, but  $\text{ALPHAR}(j)$ ,  $\text{ALPHAI}(j)$ , and  $\text{BETA}(j)$  should be correct for  $j = \text{INFO} + 1, \dots, N$ .

$\text{INFO} = N + 1$

Unexpected error returned from F08XEF (DHGEQZ).

$\text{INFO} = N + 2$

Error returned from F08YKF (DTGEVC).

## 7 Accuracy

The computed eigenvalues and eigenvectors are exact for nearby matrices  $(A + E)$  and  $(B + F)$ , where

$$\|(E, F)\|_F = O(\epsilon) \|(A, B)\|_F,$$

and  $\epsilon$  is the **machine precision**. See Section 4.11 of Anderson *et al.* (1999) for further details.

**Note:** interpretation of results obtained with the  $QZ$  algorithm often requires a clear understanding of the effects of small changes in the original data. These effects are reviewed in Wilkinson (1979), in relation to the significance of small values of  $\alpha_j$  and  $\beta_j$ . It should be noted that if  $\alpha_j$  and  $\beta_j$  are **both** small for any  $j$ , it may be that no reliance can be placed on **any** of the computed eigenvalues  $\lambda_i = \alpha_i/\beta_i$ . You are recommended to study Wilkinson (1979) and, if in difficulty, to seek expert advice on determining the sensitivity of the eigenvalues to perturbations in the data.

## 8 Parallelism and Performance

F08WAF (DGGEV) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

F08WAF (DGGEV) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this routine. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

## 9 Further Comments

The total number of floating-point operations is proportional to  $n^3$ .

The complex analogue of this routine is F08WNF (ZGGEV).

## 10 Example

This example finds all the eigenvalues and right eigenvectors of the matrix pair  $(A, B)$ , where

$$A = \begin{pmatrix} 3.9 & 12.5 & -34.5 & -0.5 \\ 4.3 & 21.5 & -47.5 & 7.5 \\ 4.3 & 21.5 & -43.5 & 3.5 \\ 4.4 & 26.0 & -46.0 & 6.0 \end{pmatrix} \quad \text{and} \quad B = \begin{pmatrix} 1.0 & 2.0 & -3.0 & 1.0 \\ 1.0 & 3.0 & -5.0 & 4.0 \\ 1.0 & 3.0 & -4.0 & 3.0 \\ 1.0 & 3.0 & -4.0 & 4.0 \end{pmatrix}.$$

Note that the block size (NB) of 64 assumed in this example is not realistic for such a small problem, but should be suitable for large problems.

### 10.1 Program Text

```
Program f08wafe

!     F08WAF Example Program Text

!     Mark 26 Release. NAG Copyright 2016.

!     .. Use Statements ..
Use nag_library, Only: dggev, m01def, m01leaf, nag_wp, x02ajf, x02amf
!     .. Implicit None Statement ..
Implicit None
!     .. Parameters ..
Real (Kind=nag_wp), Parameter :: zero = 0.0_nag_wp
Integer, Parameter :: nb = 64, nin = 5, nout = 6
!     .. Local Scalars ..
Complex (Kind=nag_wp)
Real (Kind=nag_wp)
Integer
Logical
!     .. Local Arrays ..
Real (Kind=nag_wp), Allocatable :: a(:,:,), alphai(:, ), alphar(:, ),
b(:,:,), beta(:, ), vr(:,:), vr_row(:, ), work(:)
Real (Kind=nag_wp)
Integer, Allocatable :: dummy(1,1)
!     .. Intrinsic Procedures ..
Intrinsic :: abs, all, cmplx, max, maxloc, nint, &
sqrt
!     .. Executable Statements ..
Write (nout,*) 'F08WAF Example Program Results'
!     Skip heading in data file
Read (nin,*)
Read (nin,*) n
lda = n
```

```

ldb = n
ldvr = n
Allocate (a(lda,n),alphai(n),alphar(n),b(ldb,n),beta(n),vr(ldvr,n),      &
          irank(n))

! Use routine workspace query to get optimal workspace.
lwork = -1
! The NAG name equivalent of dggev is f08waf
Call dggev('No left vectors','Vectors (right)',n,a,lda,b,ldb,alphar,      &
            alphai,beta,dummy,1,vr,ldvr,dummy,lwork,info)

! Make sure that there is enough workspace for block size nb.
lwork = max((nb+7)*n,nint(dummy(1,1)))
Allocate (work(lwork))

! Read in the matrices A and B

Read (nin,*)(a(i,1:n),i=1,n)
Read (nin,*)(b(i,1:n),i=1,n)

! Solve the generalized eigenvalue problem

! The NAG name equivalent of dggev is f08waf
Call dggev('No left vectors','Vectors (right)',n,a,lda,b,ldb,alphar,      &
            alphai,beta,dummy,1,vr,ldvr,work,lwork,info)

If (info>0) Then
    Write (nout,*)
    Write (nout,99999) 'Failure in DGGEV. INFO =', info
Else
    If beta(:) > eps, Order eigenvalues by ascending real parts
    and then by ascending imaginary parts
    If (all(abs(beta(1:n))>x02ajf())) Then
        work(1:n) = alphar(1:n)/beta(1:n)
        work(n+1:2*n) = alphai(1:n)/beta(1:n)
        ifail = 0
        Call m0ldef(work,n,1,n,1,2,'Ascending',irank,ifail)
        Call m0leaf(alphar,1,n,irank,ifail)
        Call m0leaf(alphai,1,n,irank,ifail)
        Call m0leaf(beta,1,n,irank,ifail)
    Order the eigenvectors in the same way
    Allocate (vr_row(n))
    Do j = 1, n
        vr_row(1:n) = vr(j,1:n)
        Call m0leaf(vr_row,1,n,irank,ifail)
        vr(j,1:n) = vr_row(1:n)
    End Do
    Deallocate (vr_row)
End If
small = x02amf()
pair = .False.
Do j = 1, n
    Write (nout,*)
    If ((abs(alphar(j))+abs(alphai(j)))*small>=abs(beta(j))) Then
        Write (nout,99998) 'Eigenvalue(', j, ')',
        ' is numerically infinite or undetermined', 'ALPHAR(', j,
        ') = ', alphar(j), ', ALPHA(', j, ') = ', alphai(j), ', BETA(', j,
        ') = ', beta(j)
    Else
        If (alphai(j)==zero) Then
            Write (nout,99997) 'Eigenvalue(', j, ') = ', alphar(j)/beta(j)
        Else
            eig = cmplx(alphar(j),alphai(j),kind=nag_wp)/
                  cmplx(beta(j),kind=nag_wp)
            Write (nout,99996) 'Eigenvalue(', j, ') = ', eig
        End If
    End If
    Write (nout,*)
    Write (nout,99995) 'Eigenvector(', j, ')'
    If (alphai(j)==zero) Then
        Let largest element be positive
    !

```

```

      work(1:n) = abs(vr(1:n,j))
      k = maxloc(work(1:n),1)
      If (vr(k,j)<zero) Then
          vr(1:n,j) = -vr(1:n,j)
      End If
      Write (nout,99994)(vr(i,j),i=1,n)
      Else
          If (pair) Then
              Write (nout,99993)(vr(i,j-1),-vr(i,j),i=1,n)
          Else
              ! Let largest element be real (and positive).
              work(1:n) = vr(1:n,j)**2 + vr(1:n,j+1)**2
              k = maxloc(work(1:n),1)
              scal_r = vr(k,j)/sqrt(work(k))
              scal_i = -vr(k,j+1)/sqrt(work(k))
              work(1:n) = vr(1:n,j)
              vr(1:n,j) = scal_r*work(1:n) - scal_i*vr(1:n,j+1)
              vr(1:n,j+1) = scal_r*vr(1:n,j+1) + scal_i*work(1:n)
              Write (nout,99993)(vr(i,j),vr(i,j+1),i=1,n)
          End If
          pair = .Not. pair
      End If
  End Do
End If

99999 Format (1X,A,I4)
99998 Format (1X,A,I2,2A,/,1X,2(A,I2,A,1P,F11.3,3X),A,I2,A,1P,F11.3)
99997 Format (1X,A,I2,A,1P,F11.3)
99996 Format (1X,A,I2,A,'(',1P,F11.3,',',1P,F11.3,')')
99995 Format (1X,A,I2,A)
99994 Format (1X,1P,F11.5)
99993 Format (1X,'(',1P,F11.5,',',1P,F11.5,')')
End Program f08wafe

```

## 10.2 Program Data

```

F08WAF Example Program Data
 4 :Value of N
 3.9 12.5 -34.5 -0.5
 4.3 21.5 -47.5  7.5
 4.3 21.5 -43.5  3.5
 4.4 26.0 -46.0  6.0 :End of matrix A
 1.0  2.0  -3.0  1.0
 1.0  3.0  -5.0  4.0
 1.0  3.0  -4.0  3.0
 1.0  3.0  -4.0  4.0 :End of matrix B

```

## 10.3 Program Results

```

F08WAF Example Program Results

Eigenvalue( 1) =      20.000
Eigenvector( 1)
 10.00000
 0.05714
 0.62857
 0.62857

Eigenvalue( 2) = (      30.000,     -40.000)

Eigenvector( 2)
(    7.12215,      0.00000)
(   1.42443,     -0.00000)
(   0.85466,      1.13954)
(   0.85466,      1.13954)

Eigenvalue( 3) = (      30.000,      40.000)

```

```
Eigenvector( 3)
(    7.12215,      0.00000)
(    1.42443,      0.00000)
(    0.85466,     -1.13954)
(    0.85466,     -1.13954)

Eigenvalue( 4) =      40.000

Eigenvector( 4)
 10.00000
  0.11111
 -0.33333
  1.55556
```

---