NAG Library Routine Document

G10ACF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of **bold italicised** terms and other implementation-dependent details.

1 Purpose

G10ACF estimates the values of the smoothing parameter and fits a cubic smoothing spline to a set of data.

2 Specification

```
SUBROUTINE G10ACF (METHOD, WEIGHT, N, X, Y, WT, YHAT, C, LDC, RSS, DF, RES, H, CRIT, RHO, U, TOL, MAXCAL, WK, IFAIL)

INTEGER

N, LDC, MAXCAL, IFAIL

REAL (KIND=nag_wp) X(N), Y(N), WT(*), YHAT(N), C(LDC,3), RSS, DF, RES(N), H(N), CRIT, RHO, U, TOL, WK(7*(N+2))

CHARACTER(1) METHOD, WEIGHT
```

3 Description

For a set of n observations (x_i, y_i) , for i = 1, 2, ..., n, the spline provides a flexible smooth function for situations in which a simple polynomial or nonlinear regression model is not suitable.

Cubic smoothing splines arise as the unique real-valued solution function f, with absolutely continuous first derivative and squared-integrable second derivative, which minimizes

$$\sum_{i=1}^{n} w_i (y_i - f(x_i))^2 + \rho \int_{-\infty}^{\infty} (f''(x))^2 dx,$$

where w_i is the (optional) weight for the *i*th observation and ρ is the smoothing argument. This criterion consists of two parts: the first measures the fit of the curve and the second the smoothness of the curve. The value of the smoothing argument ρ weights these two aspects; larger values of ρ give a smoother fitted curve but, in general, a poorer fit. For details of how the cubic spline can be fitted see Hutchinson and de Hoog (1985) and Reinsch (1967).

The fitted values, $\hat{y} = (\hat{y}_1, \hat{y}_2, \dots, \hat{y}_n)^T$, and weighted residuals, r_i , can be written as:

$$\hat{y} = Hy$$
 and $r_i = \sqrt{w_i}(y_i - \hat{y}_i)$

for a matrix H. The residual degrees of freedom for the spline is trace(I - H) and the diagonal elements of H are the leverages.

The parameter ρ can be estimated in a number of ways.

- (i) The degrees of freedom for the spline can be specified, i.e., find ρ such that trace $(H) = \nu_0$ for given ν_0 .
- (ii) Minimize the cross-validation (CV), i.e., find ρ such that the CV is minimized, where

$$CV = \frac{1}{\sum_{i=1}^{n} w_i} \sum_{i=1}^{n} \left[\frac{r_i}{1 - h_{ii}} \right]^2.$$

(iii) Minimize the generalized cross-validation (GCV), i.e., find ρ such that the GCV is minimized, where

Mark 26 G10ACF.1

GCV =
$$\frac{n^2}{\sum_{i=1}^{n} w_i} \left[\frac{\sum_{i=1}^{n} r_i^2}{\left(\sum_{i=1}^{n} (1 - h_{ii})\right)^2} \right].$$

G10ACF requires the x_i to be strictly increasing. If two or more observations have the same x_i value then they should be replaced by a single observation with y_i equal to the (weighted) mean of the y values and weight, w_i , equal to the sum of the weights. This operation can be performed by G10ZAF.

The algorithm is based on Hutchinson (1986). C05AZF is used to solve for ρ given ν_0 and the method of E04ABF/E04ABA is used to minimize the GCV or CV.

4 References

Hastie T J and Tibshirani R J (1990) Generalized Additive Models Chapman and Hall

Hutchinson M F (1986) Algorithm 642: A fast procedure for calculating minimum cross-validation cubic smoothing splines *ACM Trans. Math. Software* 12 150–153

Hutchinson M F and de Hoog F R (1985) Smoothing noisy data with spline functions *Numer. Math.* 47 99–106

Reinsch C H (1967) Smoothing by spline functions Numer. Math. 10 177-183

5 Arguments

1: METHOD – CHARACTER(1)

Input

On entry: indicates whether the smoothing parameter is to be found by minimization of the CV or GCV functions, or by finding the smoothing parameter corresponding to a specified degrees of freedom value.

METHOD = 'C'

Cross-validation is used.

METHOD = 'D'

The degrees of freedom are specified.

METHOD = 'G'

Generalized cross-validation is used.

Constraint: METHOD = 'C', 'D' or 'G'.

2: WEIGHT – CHARACTER(1)

Input

On entry: indicates whether user-defined weights are to be used.

WEIGHT = 'W'

User-defined weights should be supplied in WT.

WEIGHT = 'U'

The data is treated as unweighted.

Constraint: WEIGHT = 'W' or 'U'.

N - INTEGER

Input

On entry: n, the number of observations.

Constraint: $N \geq 3$.

G10ACF.2 Mark 26

4: X(N) - REAL (KIND=nag wp) array

Input

On entry: the distinct and ordered values x_i , for i = 1, 2, ..., n.

Constraint: X(i) < X(i+1), for i = 1, 2, ..., n-1.

5: Y(N) - REAL (KIND=nag wp) array

Input

On entry: the values y_i , for i = 1, 2, ..., n.

6: WT(*) - REAL (KIND=nag wp) array

Input

Note: the dimension of the array WT must be at least N if WEIGHT = 'W'.

On entry: if WEIGHT = 'W', WT must contain the n weights. Otherwise WT is not referenced and unit weights are assumed.

Constraint: if WEIGHT = 'W', WT(i) > 0.0, for i = 1, 2, ..., n.

7: YHAT(N) – REAL (KIND=nag_wp) array

Output

On exit: the fitted values, \hat{y}_i , for i = 1, 2, ..., n.

8: C(LDC, 3) - REAL (KIND=nag_wp) array

Output

On exit: the spline coefficients. More precisely, the value of the spline approximation at t is given by $((C(i,3) \times d + C(i,2)) \times d + C(i,1)) \times d + \hat{y}_i$, where $x_i \le t < x_{i+1}$ and $d = t - x_i$.

9: LDC – INTEGER

Input

On entry: the first dimension of the array C as declared in the (sub)program from which G10ACF is called.

Constraint: LDC $\geq N - 1$.

10: RSS - REAL (KIND=nag wp)

Output

On exit: the (weighted) residual sum of squares.

11: DF - REAL (KIND=nag wp)

Output

On exit: the residual degrees of freedom. If METHOD = 'D' this will be n - CRIT to the required accuracy.

12: RES(N) – REAL (KIND=nag wp) array

Output

On exit: the (weighted) residuals, r_i , for i = 1, 2, ..., n.

13: H(N) - REAL (KIND=nag wp) array

Output

On exit: the leverages, h_{ii} , for i = 1, 2, ..., n.

14: CRIT – REAL (KIND=nag wp)

Input/Output

On entry: if METHOD = 'D', the required degrees of freedom for the spline.

If METHOD = 'C' or 'G', CRIT need not be set.

Constraint: $2.0 < CRIT \le N$.

On exit: if METHOD = 'C', the value of the cross-validation, or if METHOD = 'G', the value of the generalized cross-validation function, evaluated at the value of ρ returned in RHO.

15: RHO - REAL (KIND=nag wp)

Output

On exit: the smoothing parameter, ρ .

Mark 26

16: U - REAL (KIND=nag wp)

Input

On entry: the upper bound on the smoothing parameter. If $U \le TOL$, U = 1000.0 will be used instead. See Section 9 for details on how this argument is used.

17: TOL – REAL (KIND=nag wp)

Input

On entry: the accuracy to which the smoothing parameter RHO is required. TOL should preferably be not much less than $\sqrt{\epsilon}$, where ϵ is the **machine precision**. If TOL $< \epsilon$, TOL $= \sqrt{\epsilon}$ will be used instead.

18: MAXCAL – INTEGER

Input

On entry: the maximum number of spline evaluations to be used in finding the value of ρ . If MAXCAL < 3, MAXCAL = 100 will be used instead.

19: $WK(7 \times (N+2)) - REAL$ (KIND=nag wp) array

Workspace

20: IFAIL - INTEGER

Input/Output

On entry: IFAIL must be set to 0, -1 or 1. If you are unfamiliar with this argument you should refer to Section 3.4 in How to Use the NAG Library and its Documentation for details.

For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, if you are not familiar with this argument, the recommended value is 0. When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.

On exit: IFAIL = 0 unless the routine detects an error or a warning has been flagged (see Section 6).

6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL = 1

On entry, $CRIT = \langle value \rangle$.

Constraint: if METHOD = 'D', CRIT > 2.0.

On entry, $CRIT = \langle value \rangle$.

Constraint: if METHOD = 'D', CRIT \leq N.

On entry, LDC = $\langle value \rangle$ and N = $\langle value \rangle$.

Constraint: LDC $\geq N - 1$.

On entry, METHOD is not valid: METHOD = $\langle value \rangle$.

On entry, $N = \langle value \rangle$.

Constraint: N > 3.

On entry, WEIGHT is not valid: WEIGHT = $\langle value \rangle$.

IFAIL = 2

On entry, at least one element of WT ≤ 0.0 .

 $\mathsf{IFAIL} = 3$

On entry, X is not a strictly ordered array.

G10ACF.4 Mark 26

IFAIL = 4

For the specified degrees of freedom, RHO > U: $U = \langle value \rangle$.

IFAIL = 5

Accuracy of TOL cannot be achieved: $TOL = \langle value \rangle$.

IFAIL = 6

MAXCAL iterations have been performed.

IFAIL = 7

Optimum value of RHO lies above U: $U = \langle value \rangle$.

IFAIL = -99

An unexpected error has been triggered by this routine. Please contact NAG.

See Section 3.9 in How to Use the NAG Library and its Documentation for further information.

IFAIL = -399

Your licence key may have expired or may not have been installed correctly.

See Section 3.8 in How to Use the NAG Library and its Documentation for further information.

IFAIL = -999

Dynamic memory allocation failed.

See Section 3.7 in How to Use the NAG Library and its Documentation for further information.

7 Accuracy

When minimizing the cross-validation or generalized cross-validation, the error in the estimate of ρ should be within $\pm 3(\text{TOL} \times \text{RHO} + \text{TOL})$. When finding ρ for a fixed number of degrees of freedom the error in the estimate of ρ should be within $\pm 2 \times \text{TOL} \times \text{max}(1, \text{RHO})$.

Given the value of ρ , the accuracy of the fitted spline depends on the value of ρ and the position of the x values. The values of $x_i - x_{i-1}$ and w_i are scaled and ρ is transformed to avoid underflow and overflow problems.

8 Parallelism and Performance

G10ACF is not threaded in any implementation.

9 Further Comments

The time to fit the spline for a given value of ρ is of order n.

When finding the value of ρ that gives the required degrees of freedom, the algorithm examines the interval 0.0 to U. For small degrees of freedom the value of ρ can be large, as in the theoretical case of two degrees of freedom when the spline reduces to a straight line and ρ is infinite. If the CV or GCV is to be minimized then the algorithm searches for the minimum value in the interval 0.0 to U. If the function is decreasing in that range then the boundary value of U will be returned. In either case, the larger the value of U the more likely is the interval to contain the required solution, but the process will be less efficient.

Regression splines with a small (< n) number of knots can be fitted by E02BAF and E02BEF.

Mark 26 G10ACF.5

10 Example

This example uses the data given by Hastie and Tibshirani (1990), which consists of the age, x_i , and C-peptide concentration (pmol/ml), y_i , from a study of the factors affecting insulin-dependent diabetes mellitus in children. The data is input, reduced to a strictly ordered set by G10ZAF and a spline with 5 degrees of freedom is fitted by G10ACF. The fitted values and residuals are printed.

10.1 Program Text

```
Program g10acfe
!
      G10ACF Example Program Text
      Mark 26 Release. NAG Copyright 2016.
!
       . Use Statements .
1
      Use nag_library, Only: g10acf, g10zaf, nag_wp
!
      .. Implicit None Statement ..
      Implicit None
      .. Parameters ..
1
      Integer, Parameter
                                         :: nin = 5, nout = 6
      .. Local Scalars ..
!
      Real (Kind=nag_wp)
                                         :: crit, df, rho, rss, tol, u
:: i, ifail, ldc, lwk, lwt, maxcal, n, &
      Integer
                                            nord
                                         :: method, weight
      Character (1)
!
      .. Local Arrays ..
      Real (Kind=nag_wp), Allocatable :: c(:,:), h(:), res(:), wk(:), wt(:), wwt(:), x(:), xord(:), y(:),
                                            yhat(:), yord(:)
      Integer, Allocatable
                                         :: iwrk(:)
      .. Executable Statements ..
1
      Write (nout,*) 'G10ACF Example Program Results'
      Write (nout,*)
!
      Skip heading in data file
      Read (nin,*)
      Read (nin,*) method, weight, n
      If (weight=='W' .Or. weight=='w') Then
        lwt = n
      Else
        lwt = 0
      End If
      ldc = n - 1
      1wk = 7*(n+2)
      Allocate (x(n),y(n),wt(lwt),xord(n),yord(n),wwt(n),yhat(n),c(ldc,3),
        res(n),h(n),wk(lwk),iwrk(n))
!
      Read in data
      If (lwt>0) Then
       Read (nin,*)(x(i),y(i),wt(i),i=1,n)
        Read (nin,*)(x(i),y(i),i=1,n)
      End If
      Read in control parameters
      Read (nin,*) u, tol, maxcal, crit
!
      Sort data, removing ties and weighting accordingly
      ifail = 0
      Call g10zaf(weight,n,x,y,wt,nord,xord,yord,wwt,rss,iwrk,ifail)
      Fit cubic spline
      ifail = 0
      Call g10acf(method,'W',nord,xord,yord,wwt,yhat,c,ldc,rss,df,res,h,crit, &
        rho,u,tol,maxcal,wk,ifail)
      Display results
```

G10ACF.6 Mark 26

```
Write (nout,99999) 'Residual sum of squares = ', rss
Write (nout,99999) 'Degrees of freedom = ', df
Write (nout,99999) 'RHO = ', rho
Write (nout,*)
Write (nout,*) ' Input data Output results'
Write (nout,*) ' I X Y YHAT H'
Write (nout,99998)(i,xord(i),yord(i),yhat(i),h(i),i=1,nord)

99999 Format (1X,A,F10.2)
99998 Format (14,2F8.3,6X,2F8.3)
End Program g10acfe
```

10.2 Program Data

```
G10ACF Example Program Data
'D' 'U'
                                           :: METHOD, WEIGHT, N
5.2 4.8
8.8 4.1
           10.5 5.2 10.6 5.5 10.4 5.0
          12.7 3.4 15.6 4.9
2.2 3.9 4.8 4.5
0.9 3.0 11.8 4.6
                                5.8 5.6
1.8 3.4
1.9 3.7
                                  7.9 4.8
                                7.9 4.8
5.2 4.9
11.5 5.5
          10.6 4.5
                      8.5 5.3 11.1 4.7
          11.3 5.1
12.8 6.6
                      1.0 3.9 14.5 5.7
                                15.5 4.9
11.9 5.1
           8.1 5.2
                      13.8 3.7
                     12.4 5.2
4.2 5.1
                                11.1 5.1
6.9 5.1
9.8 4.8
           11.0 4.4
           4.8 3.9
5.1 4.6
13.2 6.0
           9.9 4.9
                     12.5 4.1 13.2 4.6
8.9 4.9 10.8 5.1
                                           :: End of X,Y
10000 0.001 40 12.0
                                           :: U,TOL,MAXCAL,CRIT
```

10.3 Program Results

```
G10ACF Example Program Results
```

```
Residual sum of squares = 10.35
Degrees of freedom = 25.00
RHO = 2.68
```

Input data		ta	Output results	
I	X	Y	YHAT H	
1	0.900	3.000	3.373 0.534	
2	1.000	3.900	3.406 0.427	
3	1.800	3.400	3.642 0.313	
4	1.900	3.700	3.686 0.313	
5	2.200	3.900	3.839 0.448	
6	4.200	5.100	4.614 0.564	
7	4.800	4.200	4.576 0.442	
8	5.100	4.600	4.715 0.189	
9	5.200	4.850	4.783 0.407	
10	5.800	5.600	5.193 0.455	
11	6.900	5.100	5.184 0.592	
12	7.900	4.800	4.958 0.530	
13	8.100	5.200	4.931 0.234	
14	8.500	5.300	4.845 0.245	
15	8.800	4.100	4.763 0.271	
16	8.900	4.900	4.748 0.292	
17	9.800	4.800	4.850 0.301	
18	9.900	4.900	4.875 0.276	
19	10.400	5.000	4.970 0.173	
20	10.500	5.200	4.977 0.154	
21	10.600	5.000	4.979 0.285	
22	10.800	5.100	4.970 0.136	
23	11.000	4.400	4.961 0.137	
24	11.100	4.900	4.964 0.284	
25	11.300	5.100	4.975 0.162	
26	11.500	5.500	4.975 0.186	
27	11.800	4.600	4.930 0.213	
28	11.900	5.100	4.911 0.220	
29	12.400	5.200	4.852 0.206	
30	12.500	4.100	4.857 0.196	

Mark 26 G10ACF.7

31	12.700	3.400	4.900	0.189	
32	12.800	6.600	4.932	0.193	
33	13.200	5.300	4.955	0.488	
34	13.800	3.700	4.797	0.408	
35	14.500	5.700	5.076	0.559	
36	15.500	4.900	4.979	0.445	
37	15.600	4.900	4.946	0.535	

G10ACF.8 (last)

Mark 26