# **NAG Library Routine Document**

## F04CJF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of **bold italicised** terms and other implementation-dependent details.

# 1 Purpose

F04CJF computes the solution to a complex system of linear equations AX = B, where A is an n by n complex Hermitian matrix, stored in packed format and X and B are n by r matrices. An estimate of the condition number of A and an error bound for the computed solution are also returned.

# 2 Specification

```
SUBROUTINE F04CJF (UPLO, N, NRHS, AP, IPIV, B, LDB, RCOND, ERRBND, IFAIL)

INTEGER N, NRHS, IPIV(N), LDB, IFAIL
REAL (KIND=nag_wp) RCOND, ERRBND
COMPLEX (KIND=nag_wp) AP(*), B(LDB,*)
CHARACTER(1) UPLO
```

# 3 Description

The diagonal pivoting method is used to factor A as  $A = UDU^H$ , if UPLO = 'U', or  $A = LDL^H$ , if UPLO = 'L', where U (or L) is a product of permutation and unit upper (lower) triangular matrices, and D is Hermitian and block diagonal with 1 by 1 and 2 by 2 diagonal blocks. The factored form of A is then used to solve the system of equations AX = B.

## 4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia http://www.netlib.org/lapack/lug

Higham N J (2002) Accuracy and Stability of Numerical Algorithms (2nd Edition) SIAM, Philadelphia

## 5 Arguments

#### 1: UPLO – CHARACTER(1)

Input

On entry: if UPLO = 'U', the upper triangle of the matrix A is stored.

If UPLO = 'L', the lower triangle of the matrix A is stored.

Constraint: UPLO = 'U' or 'L'.

#### 2: N – INTEGER

Input

On entry: the number of linear equations n, i.e., the order of the matrix A.

Constraint:  $N \ge 0$ .

#### 3: NRHS - INTEGER

Input

On entry: the number of right-hand sides r, i.e., the number of columns of the matrix B.

Constraint: NRHS  $\geq 0$ .

Mark 26 F04CJF.1

F04CJF NAG Library Manual

4: AP(\*) - COMPLEX (KIND=nag\_wp) array

Input/Output

**Note**: the dimension of the array AP must be at least  $max(1, N \times (N+1)/2)$ .

On entry: the n by n Hermitian matrix A, packed column-wise in a linear array. The jth column of the matrix A is stored in the array AP as follows:

More precisely,

if UPLO = 'U', the upper triangle of A must be stored with element  $A_{ij}$  in AP(i+j(j-1)/2) for  $i \leq j$ ;

if UPLO = 'L', the lower triangle of A must be stored with element  $A_{ij}$  in AP(i+(2n-j)(j-1)/2) for  $i \ge j$ .

On exit: if IFAIL  $\geq 0$ , the block diagonal matrix D and the multipliers used to obtain the factor U or L from the factorization  $A = UDU^{\rm H}$  or  $A = LDL^{\rm H}$  as computed by F07PRF (ZHPTRF), stored as a packed triangular matrix in the same storage format as A.

5: IPIV(N) - INTEGER array

Output

On exit: if IFAIL  $\geq 0$ , details of the interchanges and the block structure of D, as determined by F07PRF (ZHPTRF).

If IPIV(k) > 0, then rows and columns k and IPIV(k) were interchanged, and  $d_{kk}$  is a 1 by 1 diagonal block;

if UPLO = 'U' and IPIV(k) = IPIV(k-1) < 0, then rows and columns k-1 and -IPIV(k) were interchanged and  $d_{k-1:k,k-1:k}$  is a 2 by 2 diagonal block;

if UPLO = 'L' and IPIV(k) = IPIV(k+1) < 0, then rows and columns k+1 and -IPIV(k) were interchanged and  $d_{k:k+1,k:k+1}$  is a 2 by 2 diagonal block.

6: B(LDB, \*) - COMPLEX (KIND=nag wp) array

Input/Output

**Note**: the second dimension of the array B must be at least max(1, NRHS).

On entry: the n by r matrix of right-hand sides B.

On exit: if IFAIL = 0 or N + 1, the n by r solution matrix X.

7: LDB – INTEGER

Input

On entry: the first dimension of the array B as declared in the (sub)program from which F04CJF is called.

*Constraint*: LDB  $\geq \max(1, N)$ .

8: RCOND - REAL (KIND=nag wp)

Output

On exit: if no constraints are violated, an estimate of the reciprocal of the condition number of the matrix A, computed as  $\text{RCOND} = 1/\left(\|A\|_1 \|A^{-1}\|_1\right)$ .

9: ERRBND - REAL (KIND=nag\_wp)

Output

On exit: if IFAIL = 0 or N + 1, an estimate of the forward error bound for a computed solution  $\hat{x}$ , such that  $\|\hat{x} - x\|_1 / \|x\|_1 \le \text{ERRBND}$ , where  $\hat{x}$  is a column of the computed solution returned in the array B and x is the corresponding column of the exact solution X. If RCOND is less than **machine precision**, then ERRBND is returned as unity.

10: IFAIL - INTEGER

Input/Output

On entry: IFAIL must be set to 0, -1 or 1. If you are unfamiliar with this argument you should refer to Section 3.4 in How to Use the NAG Library and its Documentation for details.

For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then

F04CJF.2 Mark 26

the value 1 is recommended. Otherwise, if you are not familiar with this argument, the recommended value is 0. When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.

On exit: IFAIL = 0 unless the routine detects an error or a warning has been flagged (see Section 6).

# 6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

```
IFAIL > 0 and IFAIL \le N
```

Diagonal block  $\langle value \rangle$  of the block diagonal matrix is zero. The factorization has been completed, but the solution could not be computed.

```
IFAIL = N + 1
```

A solution has been computed, but RCOND is less than machine precision so that the matrix A is numerically singular.

```
IFAIL = -1
```

On entry, UPLO  $\neq$  'U' or 'L': UPLO =  $\langle value \rangle$ .

IFAIL = -2

On entry,  $N = \langle value \rangle$ . Constraint:  $N \ge 0$ .

IFAIL = -3

On entry, NRHS =  $\langle value \rangle$ . Constraint: NRHS  $\geq 0$ .

IFAIL = -7

On entry, LDB =  $\langle value \rangle$  and N =  $\langle value \rangle$ . Constraint: LDB  $\geq \max(1, N)$ .

IFAIL = -99

An unexpected error has been triggered by this routine. Please contact NAG.

See Section 3.9 in How to Use the NAG Library and its Documentation for further information.

IFAIL = -399

Your licence key may have expired or may not have been installed correctly.

See Section 3.8 in How to Use the NAG Library and its Documentation for further information.

IFAIL = -999

Dynamic memory allocation failed.

The real allocatable memory required is N, and the complex allocatable memory required is  $2 \times N$ . Allocation failed before the solution could be computed.

See Section 3.7 in How to Use the NAG Library and its Documentation for further information.

*Mark 26 F04CJF.3* 

# 7 Accuracy

The computed solution for a single right-hand side,  $\hat{x}$ , satisfies an equation of the form

$$(A+E)\hat{x} = b,$$

where

$$||E||_1 = O(\epsilon)||A||_1$$

and  $\epsilon$  is the *machine precision*. An approximate error bound for the computed solution is given by

$$\frac{\|\hat{x} - x\|_1}{\|x\|_1} \le \kappa(A) \frac{\|E\|_1}{\|A\|_1},$$

where  $\kappa(A) = \|A^{-1}\|_1 \|A\|_1$ , the condition number of A with respect to the solution of the linear equations. F04CJF uses the approximation  $\|E\|_1 = \epsilon \|A\|_1$  to estimate ERRBND. See Section 4.4 of Anderson *et al.* (1999) for further details.

### 8 Parallelism and Performance

F04CJF makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this routine. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

# 9 Further Comments

The packed storage scheme is illustrated by the following example when n=4 and UPLO = 'U'. Two-dimensional storage of the Hermitian matrix A:

$$a_{11}$$
  $a_{12}$   $a_{13}$   $a_{14}$ 
 $a_{22}$   $a_{23}$   $a_{24}$ 
 $a_{33}$   $a_{34}$ 
 $a_{44}$   $\left(a_{ij}=\bar{a}_{ji}\right).$ 

Packed storage of the upper triangle of A:

$$AP = \begin{bmatrix} a_{11}, & a_{12}, & a_{22}, & a_{13}, & a_{23}, & a_{33}, & a_{14}, & a_{24}, & a_{34}, & a_{44} \end{bmatrix}$$

The total number of floating-point operations required to solve the equations AX = B is proportional to  $\left(\frac{1}{3}n^3 + 2n^2r\right)$ . The condition number estimation typically requires between four and five solves and never more than eleven solves, following the factorization.

In practice the condition number estimator is very reliable, but it can underestimate the true condition number; see Section 15.3 of Higham (2002) for further details.

Routine F04DJF is for complex symmetric matrices, and the real analogue of F04CJF is F04BJF.

## 10 Example

This example solves the equations

$$AX = B$$
,

where A is the Hermitian indefinite matrix

$$A = \begin{pmatrix} -1.84 & 0.11 - 0.11i & -1.78 - 1.18i & 3.91 - 1.50i \\ 0.11 + 0.11i & -4.63 & -1.84 + 0.03i & 2.21 + 0.21i \\ -1.78 + 1.18i & -1.84 - 0.03i & -8.87 & 1.58 - 0.90i \\ 3.91 + 1.50i & 2.21 - 0.21i & 1.58 + 0.90i & -1.36 \end{pmatrix}$$

F04CJF.4 Mark 26

and

$$B = \begin{pmatrix} 2.98 - 10.18i & 28.68 - 39.89i \\ -9.58 + & 3.88i & -24.79 - & 8.40i \\ -0.77 - 16.05i & 4.23 - 70.02i \\ 7.79 + & 5.48i & -35.39 + 18.01i \end{pmatrix}$$

An estimate of the condition number of A and an approximate error bound for the computed solutions are also printed.

## 10.1 Program Text

```
Program f04cjfe
!
      FO4CJF Example Program Text
     Mark 26 Release. NAG Copyright 2016.
      .. Use Statements ..
     Use nag_library, Only: f04cjf, nag_wp, x04dbf, x04ddf
!
      .. Implicit None Statement ..
     Implicit None
!
      .. Parameters ..
     Integer, Parameter
                                       :: nin = 5, nout = 6
     Character (1), Parameter
                                      :: uplo = 'U'
     .. Local Scalars ..
     Real (Kind=nag_wp)
                                       :: errbnd, rcond
     Integer
                                        :: i, ierr, ifail, j, ldb, n, nrhs
1
      .. Local Arrays ..
     Complex (Kind=nag_wp), Allocatable :: ap(:), b(:,:)
Integer, Allocatable :: ipiv(:)
                                        :: clabs(1), rlabs(1)
     Character (1)
!
      .. Executable Statements ..
     Write (nout,*) 'F04CJF Example Program Results'
     Write (nout,*)
     Flush (nout)
      Skip heading in data file
     Read (nin,*)
      Read (nin,*) n, nrhs
      ldb = n
     Allocate (ap((n*(n+1))/2),b(ldb,nrhs),ipiv(n))
1
     Read the upper or lower triangular part of the matrix A from
     data file
!
      If (uplo=='U') Then
       Read (nin,*)((ap(i+(j*(j-1))/2),j=i,n),i=1,n)
      Else If (uplo=='L') Then
       Read (nin,*)((ap(i+((2*n-j)*(j-1))/2),j=1,i),i=1,n)
      End If
!
     Read B from data file
     Read (nin,*)(b(i,1:nrhs),i=1,n)
!
      Solve the equations AX = B for X
!
      ifail: behaviour on error exit
            =0 for hard exit, =1 for quiet-soft, =-1 for noisy-soft
!
      ifail = 1
      Call f04cjf(uplo,n,nrhs,ap,ipiv,b,ldb,rcond,errbnd,ifail)
      If (ifail==0) Then
!
       Print solution, estimate of condition number and approximate
1
        error bound
        ierr = 0
        Call x04dbf('General',' ',n,nrhs,b,ldb,'Bracketed',' ','Solution',
          'Integer', rlabs, 'Integer', clabs, 80,0,ierr)
        Write (nout,*)
        Write (nout,*) 'Estimate of condition number'
```

Mark 26 F04CJF.5

F04CJF NAG Library Manual

```
Write (nout,99999) 1.0E0_nag_wp/rcond
        Write (nout,*)
        Write (nout,*) 'Estimate of error bound for computed solutions'
        Write (nout, 99999) errbnd
      Else If (ifail==n+1) Then
        Matrix A is numerically singular. Print estimate of
        reciprocal of condition number and solution
        Write (nout,*)
        Write (nout, *) 'Estimate of reciprocal of condition number'
        Write (nout, 99999) rcond
        Write (nout,*)
        Flush (nout)
        ierr = 0
        Call x04dbf('General',' ',n,nrhs,b,ldb,'Bracketed',' ','Solution',
           'Integer', rlabs, 'Integer', clabs, 80,0,ierr)
      Else If (ifail>0 .And. ifail<=n) Then</pre>
        The upper triangular matrix U is exactly singular. Print
1
        details of factorization
        Write (nout,*)
        Flush (nout)
        ierr = 0
        Call x04ddf(uplo,'Non-unit diagonal',n,ap,'Bracketed','',
           'Details of factorization','Integer',rlabs,'Integer',clabs,80,0,
          ierr)
        Print pivot indices
!
        Write (nout,*)
        Write (nout,*) 'Pivot indices'
        Write (nout, 99998) ipiv(1:n)
        Write (nout,99997) ifail
      End If
99999 Format (8X,1P,E9.1)
99998 Format ((1X,7111))
99997 Format (1X,'** F04CJF returned with IFAIL = ',I5)
    End Program f04cjfe
10.2 Program Data
FO4CJF Example Program Data
    4
                                                                     : n, nrhs
 (-1.84, 0.00) (0.11, -0.11) (-1.78, -1.18) (3.91, -1.50)
                  ( -4.63 , 0.00) ( -1.84, 0.03) ( 2.21, 0.21)
( -8.87, 0.00) ( 1.58, -0.90)
                                                   ( -1.36 , 0.00) : matrix A
```

```
(2.98, -10.18) (28.68, -39.89)
(-9.58, 3.88) (-24.79, -8.40)
(-0.77,-16.05) ( 4.23,-70.02)
 7.79, 5.48) (-35.39, 18.01)
                                                              : matrix B
```

#### 10.3 Program Results

FO4CJF Example Program Results

```
Solution
        2.0000,
                                 -8.0000,
1 (
                   1.0000) (
                                            6.0000)
2 (
        3.0000,
                   -2.0000) (
                                 7.0000,
                                            -2.0000)
       -1.0000,
3 (
                   2.0000) (
                                 -1.0000,
                                            5.0000)
4 (
       1.0000,
                                 3.0000,
                  -1.0000) (
                                            -4.0000)
```

F04CJF.6 Mark 26 Estimate of condition number 6.7E+00

Estimate of error bound for computed solutions 7.4E--16

Mark 26 F04CJF.7 (last)