# **NAG Library Routine Document**

## G13CFF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of **bold italicised** terms and other implementation-dependent details.

## 1 Purpose

For a bivariate time series, G13CFF calculates the gain and phase together with lower and upper bounds from the univariate and bivariate spectra.

# 2 Specification

# 3 Description

Estimates of the gain  $G(\omega)$  and phase  $\phi(\omega)$  of the dependency of series y on series x at frequency  $\omega$  are given by

$$\begin{split} \hat{G}(\omega) &= \frac{A(\omega)}{f_{xx}(\omega)} \\ \hat{\phi}(\omega) &= \arccos\biggl(\frac{cf(\omega)}{A(\omega)}\biggr), \qquad \text{if } qf(\omega) \geq 0 \\ \hat{\phi}(\omega) &= 2\pi - \arccos\biggl(\frac{cf(\omega)}{A(\omega)}\biggr), \quad \text{if } qf(\omega) < 0. \end{split}$$

The quantities used in these definitions are obtained as in Section 3 in G13CEF.

Confidence limits are returned for both gain and phase, but should again be taken as very approximate when the coherency  $W(\omega)$ , as calculated by G13CEF, is not significant. These are based on the assumption that both  $\left(\hat{G}(\omega)/G(\omega)\right)-1$  and  $\hat{\phi}(\omega)$  are Normal with variance

$$\frac{1}{d} \left( \frac{1}{W(\omega)} - 1 \right).$$

Although the estimate of  $\phi(\omega)$  is always given in the range  $[0,2\pi)$ , no attempt is made to restrict its confidence limits to this range.

## 4 References

Bloomfield P (1976) Fourier Analysis of Time Series: An Introduction Wiley Jenkins G M and Watts D G (1968) Spectral Analysis and its Applications Holden-Day

# 5 Arguments

1: XG(NG) - REAL (KIND=nag\_wp) array Input On entry: the NG univariate spectral estimates,  $f_{xx}(\omega)$ , for the x series.

Mark 26 G13CFF.1

G13CFF NAG Library Manual

2: YG(NG) – REAL (KIND=nag wp) array

Input

On entry: the NG univariate spectral estimates,  $f_{yy}(\omega)$ , for the y series.

3: XYRG(NG) - REAL (KIND=nag\_wp) array

Input

On entry: the real parts,  $cf(\omega)$ , of the NG bivariate spectral estimates for the x and y series. The x series leads the y series.

4: XYIG(NG) - REAL (KIND=nag wp) array

Input

On entry: the imaginary parts,  $qf(\omega)$ , of the NG bivariate spectral estimates for the x and y series. The x series leads the y series.

**Note:** the two univariate and the bivariate spectra must each have been calculated using the same method of smoothing. For rectangular, Bartlett, Tukey or Parzen smoothing windows, the same cut-off point of lag window and the same frequency division of the spectral estimates must be used. For the trapezium frequency smoothing window, the frequency width and the shape of the window and the frequency division of the spectral estimates must be the same. The spectral estimates and statistics must also be unlogged.

5: NG – INTEGER Input

On entry: the number of spectral estimates in each of the arrays XG, YG, XYRG and XYIG. It is also the number of gain and phase estimates.

Constraint: NG > 1.

6: STATS(4) - REAL (KIND=nag wp) array

Input

On entry: the four associated statistics for the univariate spectral estimates for the x and y series. STATS(1) contains the degrees of freedom, STATS(2) and STATS(3) contain the lower and upper bound multiplying factors respectively and STATS(4) holds the bandwidth.

*Constraint*: STATS(1)  $\geq$  3.0.

7: GN(NG) – REAL (KIND=nag wp) array

Output

On exit: the NG gain estimates,  $\hat{G}(\omega)$ , at each frequency  $\omega$ .

8: GNLW(NG) – REAL (KIND=nag\_wp) array

Output

On exit: the NG lower bounds for the NG gain estimates.

9: GNUP(NG) – REAL (KIND=nag wp) array

Output

On exit: the NG upper bounds for the NG gain estimates.

10: PH(NG) – REAL (KIND=nag wp) array

Output

On exit: the NG phase estimates,  $\hat{\phi}(\omega)$ , at each frequency  $\omega$ .

11: PHLW(NG) – REAL (KIND=nag\_wp) array

Output

On exit: the NG lower bounds for the NG phase estimates.

12: PHUP(NG) – REAL (KIND=nag\_wp) array

Output

On exit: the NG upper bounds for the NG phase estimates.

13: IFAIL – INTEGER

Input/Output

On entry: IFAIL must be set to 0, -1 or 1. If you are unfamiliar with this argument you should refer to Section 3.4 in How to Use the NAG Library and its Documentation for details.

G13CFF.2 Mark 26

For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, if you are not familiar with this argument, the recommended value is 0. When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.

On exit: IFAIL = 0 unless the routine detects an error or a warning has been flagged (see Section 6).

# 6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

```
IFAIL = 1
```

```
On entry, NG < 1, or STATS(1) < 3.0.
```

IFAIL = 2

A bivariate spectral estimate is zero. For this frequency the gain and the phase and their bounds are set to zero.

IFAIL = 3

A univariate spectral estimate is negative. For this frequency the gain and the phase and their bounds are set to zero.

IFAIL = 4

A univariate spectral estimate is zero. For this frequency the gain and the phase and their bounds are set to zero.

IFAIL = 5

A calculated value of the squared coherency exceeds 1.0. For this frequency the squared coherency is reset to 1.0 in the formulae for the gain and phase bounds.

IFAIL = -99

An unexpected error has been triggered by this routine. Please contact NAG.

See Section 3.9 in How to Use the NAG Library and its Documentation for further information.

IFAIL = -399

Your licence key may have expired or may not have been installed correctly.

See Section 3.8 in How to Use the NAG Library and its Documentation for further information.

IFAIL = -999

Dynamic memory allocation failed.

See Section 3.7 in How to Use the NAG Library and its Documentation for further information.

If more than one failure of types 2, 3, 4 and 5 occurs then the failure type which occurred at lowest frequency is returned in IFAIL. However the actions indicated above are also carried out for failures at higher frequencies.

Mark 26 G13CFF.3

G13CFF NAG Library Manual

## 7 Accuracy

All computations are very stable and yield good accuracy.

#### 8 Parallelism and Performance

G13CFF is not threaded in any implementation.

#### **9** Further Comments

The time taken by G13CFF is approximately proportional to NG.

# 10 Example

This example reads the set of univariate spectrum statistics, the two univariate spectra and the cross spectrum at a frequency division of  $\frac{2\pi}{20}$  for a pair of time series. It calls G13CFF to calculate the gain and the phase and their bounds and prints the results.

### 10.1 Program Text

```
Program g13cffe
!
     G13CFF Example Program Text
     Mark 26 Release. NAG Copyright 2016.
!
1
      .. Use Statements ..
     Use nag_library, Only: g13cff, nag_wp
!
      .. Implicit None Statement ..
     Implicit None
!
      .. Parameters ..
     Integer, Parameter
                                       :: nin = 5, nout = 6
!
      .. Local Scalars ..
                                       :: i, ifail, j, ng
     Integer
     .. Local Arrays ..
     Real (Kind=nag_wp), Allocatable :: gn(:), gnlw(:), gnup(:), ph(:),
                                          phlw(:), phup(:), xg(:), xyig(:),
                                          xyrg(:), yg(:)
     Real (Kind=nag_wp)
                                       :: stats(4)
!
      .. Executable Statements ..
     Write (nout,*) 'G13CFF Example Program Results'
     Write (nout,*)
     Skip heading in data file
     Read (nin,*)
     Read in problem size
!
     Read (nin,*) ng
     Allocate (xg(ng),yg(ng),xyrg(ng),xyig(ng),gn(ng),gnlw(ng),gnup(ng),
       ph(ng),phlw(ng),phup(ng))
     Read in statistics
     Read (nin,*) stats(1:4)
     Read in data
     Read (nin,*)(xg(i),yg(i),xyrg(i),xyig(i),i=1,ng)
     Calculate gain and phase
      ifail = -1
     Call g13cff(xg,yg,xyrg,xyig,ng,stats,gn,gnlw,gnup,ph,phlw,phup,ifail)
     If (ifail/=0) Then
       If (ifail<2) Then
         Go To 100
       End If
```

G13CFF.4 Mark 26

```
End If
      Display results
      Write (nout,*) '
                                    The gain'
      Write (nout,*)
      Write (nout,*) '
                                           Lower
                                                      Upper'
      Write (nout,*) '
                                Value
                                                      bound'
                                          bound
      Write (nout, 99999)(j-1, gn(j), gnlw(j), gnup(j), j=1, ng)
      Write (nout,*)
      Write (nout,*) '
                                    The phase'
      Write (nout,*)
      Write (nout,*) '
                                                      Upper'
                                           Lower
      Write (nout,*) '
                                Value
                                           bound
                                                      bound'
      Write (nout, 99999)(j-1, ph(j), phlw(j), phup(j), j=1, ng)
100
    Continue
99999 Format (1X, I5, 3F10.4)
    End Program g13cffe
```

# 10.2 Program Data

```
G13CFF Example Program Data
 30.00000
           .63858 1.78670
                             .33288
 2.03490 21.97712 -6.54995 0.00000
   .51554 3.29761 .34107 -1.19030
                           .04087
                  .12335
   .07640 .28782
          .02480
                   -.00514
                             .00842
   .01068
           .00285 -.00033
   .00093
                             .00032
   .00100 .00203 -.00039 -.00001
   .00076
         .00125 -.00026 .00018
           .00107
                   .00011 -.00016
.00007 0.00000
   .00037
   .00021
           .00191
```

#### 10.3 Program Results

G13CFF Example Program Results

The gain

		Lower	Upper
	Value	bound	bound
0	3.2188	2.9722	3.4859
1	2.4018	2.1138	2.7290
2	1.7008	1.3748	2.1042
3	0.9237	0.5558	1.5350
4	0.4943	0.1327	1.8415
5	0.3901	0.1002	1.5196
6	0.4161	0.1346	1.2863
7	0.5248	0.1591	1.7306
8	0.3333	0.0103	10.8301

The phase

		Lower	Upper
	Value	bound	bound
0	3.1416	3.0619	3.2213
1	4.9915	4.8637	5.1192
2	0.3199	0.1071	0.5328
3	2.1189	1.6109	2.6268
4	2.3716	1.0563	3.6868
5	3.1672	1.8075	4.5270
6	2.5360	1.4074	3.6647
7	5.3147	4.1214	6.5079
8	0.0000	<b>-</b> 3.4809	3.4809

Mark 26 G13CFF.5 (last)