

NAG Library Function Document

nag_opt_sparse_convex_qp_init (e04npc)

1 Purpose

nag_opt_sparse_convex_qp_init (e04npc) is used to initialize the function nag_opt_sparse_convex_qp_solve (e04nqc).

2 Specification

```
#include <nag.h>
#include <nage04.h>
void nag_opt_sparse_convex_qp_init (Nag_E04State *state, NagError *fail)
```

3 Description

nag_opt_sparse_convex_qp_init (e04npc) initializes the structure **state** for the function nag_opt_sparse_convex_qp_solve (e04nqc).

4 References

None.

5 Arguments

- 1: **state** – Nag_E04State * *Communication Structure*
state contains internal information required for functions in this suite. It must not be modified in any way.
- 2: **fail** – NagError * *Input/Output*
The NAG error argument (see Section 3.6 in the Essential Introduction).

6 Error Indicators and Warnings

NE_BAD_PARAM

On entry, argument *<value>* had an illegal value.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

7 Accuracy

Not applicable.

8 Parallelism and Performance

Not applicable.

9 Further Comments

The time taken by `nag_opt_sparse_convex_qp_init` (e04npc) is negligible.

10 Example

See Section 10 in `nag_opt_sparse_convex_qp_solve` (e04nqc) and `nag_opt_sparse_convex_qp_option_set_file` (e04nrc).
