

NAG Library Function Document

nag_matop_real_symm_matrix_fun (f01efc)

1 Purpose

nag_matop_real_symm_matrix_fun (f01efc) computes the matrix function, $f(A)$, of a real symmetric n by n matrix A . $f(A)$ must also be a real symmetric matrix.

2 Specification

```
#include <nag.h>
#include <nagf01.h>
void nag_matop_real_symm_matrix_fun (Nag_OrderType order, Nag_UptoType uplo,
    Integer n, double a[], Integer pda,
    void (*f)(Integer *flag, Integer n, const double x[], double fx[],
        Nag_Comm *comm),
    Nag_Comm *comm, Integer *flag, NagError *fail)
```

3 Description

$f(A)$ is computed using a spectral factorization of A

$$A = QDQ^T,$$

where D is the diagonal matrix whose diagonal elements, d_i , are the eigenvalues of A , and Q is an orthogonal matrix whose columns are the eigenvectors of A . $f(A)$ is then given by

$$f(A) = Qf(D)Q^T,$$

where $f(D)$ is the diagonal matrix whose i th diagonal element is $f(d_i)$. See for example Section 4.5 of Higham (2008). $f(d_i)$ is assumed to be real.

4 References

Higham N J (2008) *Functions of Matrices: Theory and Computation* SIAM, Philadelphia, PA, USA

5 Arguments

1: **order** – Nag_OrderType *Input*

On entry: the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag_RowMajor. See Section 3.2.1.3 in the Essential Introduction for a more detailed explanation of the use of this argument.

Constraint: **order** = Nag_RowMajor or Nag_ColMajor.

2: **uplo** – Nag_UptoType *Input*

On entry: if **uplo** = Nag_Upper, the upper triangle of the matrix A is stored.

If **uplo** = Nag_Lower, the lower triangle of the matrix A is stored.

Constraint: **uplo** = Nag_Upper or Nag_Lower.

3:	n – Integer	<i>Input</i>
<i>On entry:</i> n , the order of the matrix A .		
<i>Constraint:</i> $n \geq 0$.		
4:	a [<i>dim</i>] – double	<i>Input/Output</i>
Note: the dimension, <i>dim</i> , of the array a must be at least pda \times n .		
<i>On entry:</i> the n by n symmetric matrix A .		
If order = 'Nag_ColMajor', A_{ij} is stored in a [($j - 1$) \times pda + $i - 1$].		
If order = 'Nag_RowMajor', A_{ij} is stored in a [($i - 1$) \times pda + $j - 1$].		
If uplo = 'Nag_Upper', the upper triangular part of A must be stored and the elements of the array below the diagonal are not referenced.		
If uplo = 'Nag_Lower', the lower triangular part of A must be stored and the elements of the array above the diagonal are not referenced.		
<i>On exit:</i> the upper or lower triangular part of the n by n matrix function, $f(A)$.		
5:	pda – Integer	<i>Input</i>
<i>On entry:</i> the stride separating row or column elements (depending on the value of order) of the matrix A in the array a .		
<i>Constraint:</i> pda $\geq \max(1, n)$.		
6:	f – function, supplied by the user	<i>External Function</i>
The function f evaluates $f(z_i)$ at a number of points z_i .		

The specification of **f** is:

```
void f (Integer *flag, Integer n, const double x[], double fx[],
        Nag_Comm *comm)
```

1:	flag – Integer *	<i>Input/Output</i>
----	-------------------------	---------------------

On entry: **flag** will be zero.

On exit: **flag** should either be unchanged from its entry value of zero, or may be set nonzero to indicate that there is a problem in evaluating the function $f(x)$; for instance $f(x)$ may not be defined, or may be complex. If **flag** is returned as nonzero then nag_matop_real_symm_matrix_fun (f01efc) will terminate the computation, with **fail.code** = NE_USER_STOP.

2:	n – Integer	<i>Input</i>
----	--------------------	--------------

On entry: n , the number of function values required.

3:	x [n] – const double	<i>Input</i>
----	--------------------------------------	--------------

On entry: the n points x_1, x_2, \dots, x_n at which the function f is to be evaluated.

4:	fx [n] – double	<i>Output</i>
----	---------------------------------	---------------

On exit: the n function values. **fx**[$i - 1$] should return the value $f(x_i)$, for $i = 1, 2, \dots, n$.

5:	comm – Nag_Comm *	<i>Communication Structure</i>
----	--------------------------	--------------------------------

Pointer to structure of type Nag_Comm; the following members are relevant to **f**.

user – double *
iuser – Integer *
p – Pointer

The type **Pointer** will be `void *`. Before calling `nag_matop_real_symm_matrix_fun (f01efc)` you may allocate memory and initialize these pointers with various quantities for use by **f** when called from `nag_matop_real_symm_matrix_fun (f01efc)` (see Section 3.2.1.1 in the Essential Introduction).

7: **comm** – Nag_Comm *

Communication Structure

The NAG communication argument (see Section 3.2.1.1 in the Essential Introduction).

8: **flag** – Integer *

Output

On exit: **flag** = 0, unless you have set **flag** nonzero inside **f**, in which case **flag** will be the value you set and **fail** will be set to **fail.code** = NE_USER_STOP.

9: **fail** – NagError *

Input/Output

The NAG error argument (see Section 3.6 in the Essential Introduction).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

NE_BAD_PARAM

On entry, argument $\langle\text{value}\rangle$ had an illegal value.

NE_CONVERGENCE

The computation of the spectral factorization failed to converge.

NE_INT

On entry, **n** = $\langle\text{value}\rangle$.

Constraint: **n** ≥ 0 .

NE_INT_2

On entry, **pda** = $\langle\text{value}\rangle$ and **n** = $\langle\text{value}\rangle$.

Constraint: **pda** $\geq \text{n}$.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An internal error occurred when computing the spectral factorization. Please contact NAG.

NE_USER_STOP

flag was set to a nonzero value in **f**.

7 Accuracy

Provided that $f(D)$ can be computed accurately then the computed matrix function will be close to the exact matrix function. See Section 10.2 of Higham (2008) for details and further discussion.

8 Parallelism and Performance

`nag_matop_real_symm_matrix_fun` (f01efc) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

`nag_matop_real_symm_matrix_fun` (f01efc) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

The cost of the algorithm is $O(n^3)$ plus the cost of evaluating $f(D)$. If $\hat{\lambda}_i$ is the i th computed eigenvalue of A , then the user-supplied function \mathbf{f} will be asked to evaluate the function f at $f(\hat{\lambda}_i)$, $i = 1, 2, \dots, n$.

For further information on matrix functions, see Higham (2008).

`nag_matop_complex_herm_matrix_fun` (f01ffc) can be used to find the matrix function $f(A)$ for a complex Hermitian matrix A .

10 Example

This example finds the matrix cosine, $\cos(A)$, of the symmetric matrix

$$A = \begin{pmatrix} 1 & 2 & 3 & 4 \\ 2 & 1 & 2 & 3 \\ 3 & 2 & 1 & 2 \\ 4 & 3 & 2 & 1 \end{pmatrix}.$$

10.1 Program Text

```
/* nag_matop_real_symm_matrix_fun (f01efc) Example Program.
 *
 * Copyright 2011, Numerical Algorithms Group.
 *
 * Mark 23, 2011.
 */
#include <math.h>
#include <nag.h>
#include <nag_stlib.h>
#include <nagf01.h>
#include <nagx04.h>

#ifndef __cplusplus
extern "C" {
#endif
static void NAG_CALL f(Integer *flag, Integer n, const double x[],
                      double fx[], Nag_Comm *comm);
#ifndef __cplusplus
}
#endif

int main(void)
{
    /* Scalars */
    Integer      exit_status = 0;
    double       k = 1.0;
    Integer      i, flag, j, n, pda;

    /* Arrays */
    char         uplo_c[40];
    Integer      iuser[1];
    double       user[1];
    double       *a = 0;
```

```

char          *outfile = 0;

/* NAG types */
Nag_UptoType    uplo;
Nag_MatrixType  matrix;
Nag_Comm        comm;
Nag_OrderType   order;
NagError       fail;

INIT_FAIL(fail);

/* Communicate constant k and initialize function counter through comm */
comm.user = user;
comm.iuser = iuser;
user[0] = k;
iuser[0] = 0;

printf("nag_matop_real_symm_matrix_fun (f01efc) Example Program Results");
printf("\n\n");
fflush(stdout);

/* Read problem parameters from data file*/
scanf("%*[^\n]%ld%*[^\n] %39s%*[^\n] ", &n, uplo_c);

/* nag_enum_name_to_value (x04nac).
 * Converts NAG enum member name to value
 */
uplo = (Nag_UptoType) nag_enum_name_to_value(uplo_c);

pda = n;
if (!(a = NAG_ALLOC((pda)*(n), double)))
{
    printf("Allocation failure\n");
    exit_status = -1;
    goto END;
}

#ifndef NAG_COLUMN_MAJOR
#define A(I, J) a[(J-1)*pda + I-1]
    order = Nag_ColMajor;
#else
#define A(I, J) a[(I-1)*pda + J-1]
    order = Nag_RowMajor;
#endif

/* Read A from data file */
if (uplo == Nag_Upper)
{
    matrix = Nag_UpperMatrix;
    for (i = 1; i <= n; i++)
        for (j = i; j <= n; j++) scanf("%lf", &a(i, j));
}
else
{
    matrix = Nag_LowerMatrix;
    for (i = 1; i <= n; i++)
        for (j = 1; j <= i; j++) scanf("%lf", &a(i, j));
}
scanf("%*[^\n]");

/* nag_matop_real_symm_matrix_fun (f01efc).
 * Function of a real symmetric matrix
 */
nag_matop_real_symm_matrix_fun(order, uplo, n, a, pda, f, &comm, &flag,
                                &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_matop_real_symm_matrix_fun (f01efc).\n%s\n",
           fail.message);
    exit_status = 1;
    goto END;
}

```

```

        }
/* Expected number of function evaluations is n. */
if (iuser[0] != n)
    printf("\nNumber of function evaluations = %ld\n\n", iuser[0]);

/* nag_gen_real_mat_print (x04cac).
 * Print real general matrix (easy-to-use)
 */
nag_gen_real_mat_print(order, matrix, Nag_NonUnitDiag, n, n, a, pda,
                       "Symmetric f(A)=cos(kA)", outfile, &fail);
if (fail.code != NE_NOERROR)
{
    printf("%s\n", fail.message);
    exit_status = 2;
    goto END;
}

END:
NAG_FREE(a);

return exit_status;
}

static void NAG_CALL f(Integer *flag, Integer n, const double x[], double fx[],
                      Nag_Comm *comm)
{
    Integer j;
    double k;
    if (!comm->user[0])
    {
        *flag = -1;
    }
    else
    {
        k = comm->user[0];
        for (j = 0; j < n; j++)
        {
            comm->iuser[0]++;
            fx[j] = cos(k*x[j]);
        }
    }
}
}

```

10.2 Program Data

```
nag_matop_real_symm_matrix_fun (f01efc) Example Program Data

4 : n
Nag_Upper : uplo

1.0 2.0 3.0 4.0
    1.0 2.0 3.0
        1.0 2.0
            1.0 : A
```

10.3 Program Results

```
nag_matop_real_symm_matrix_fun (f01efc) Example Program Results

Symmetric f(A)=cos(kA)
      1      2      3      4
1  -0.5420 -0.6612 -0.0261  0.1580
2          0.2306 -0.3396 -0.0261
3                  0.2306 -0.6612
4                  -0.5420
```
