

NAG Library Function Document

nag_matop_complex_gen_matrix_cond_usd (f01kcc)

1 Purpose

nag_matop_complex_gen_matrix_cond_usd (f01kcc) computes an estimate of the absolute condition number of a matrix function f of a complex n by n matrix A in the 1-norm, using analytical derivatives of f you have supplied.

2 Specification

```
#include <nag.h>
#include <nagf01.h>

void nag_matop_complex_gen_matrix_cond_usd (Integer n, Complex a[],
      Integer pda,
      void (*f)(Integer m, Integer *iflag, Integer nz, const Complex z[],
        Complex fz[], Nag_Comm *comm),
      Nag_Comm *comm, Integer *iflag, double *conda, double *norma,
      double *normfa, NagError *fail)
```

3 Description

The absolute condition number of f at A , $\text{cond}_{\text{abs}}(f, A)$ is given by the norm of the Fréchet derivative of f , $L(A)$, which is defined by

$$\|L(X)\| := \max_{E \neq 0} \frac{\|L(X, E)\|}{\|E\|},$$

where $L(X, E)$ is the Fréchet derivative in the direction E . $L(X, E)$ is linear in E and can therefore be written as

$$\text{vec}(L(X, E)) = K(X)\text{vec}(E),$$

where the vec operator stacks the columns of a matrix into one vector, so that $K(X)$ is $n^2 \times n^2$. nag_matop_complex_gen_matrix_cond_usd (f01kcc) computes an estimate γ such that $\gamma \leq \|K(X)\|_1$, where $\|K(X)\|_1 \in [n^{-1}\|L(X)\|_1, n\|L(X)\|_1]$. The relative condition number can then be computed via

$$\text{cond}_{\text{rel}}(f, A) = \frac{\text{cond}_{\text{abs}}(f, A)\|A\|_1}{\|f(A)\|_1}.$$

The algorithm used to find γ is detailed in Section 3.4 of Higham (2008).

4 References

Higham N J (2008) *Functions of Matrices: Theory and Computation* SIAM, Philadelphia, PA, USA

5 Arguments

- 1: **n** – Integer *Input*
On entry: n , the order of the matrix A .
Constraint: $n \geq 0$.
- 2: **a**[*dim*] – Complex *Input/Output*
Note: the dimension, *dim*, of the array **a** must be at least **pda** \times **n**.

The (i, j) th element of the matrix A is stored in $\mathbf{a}[(j-1) \times \mathbf{pda} + i - 1]$.

On entry: the n by n matrix A .

On exit: the n by n matrix, $f(A)$.

3: **pda** – Integer *Input*

On entry: the stride separating matrix row elements in the array \mathbf{a} .

Constraint: $\mathbf{pda} \geq \mathbf{n}$.

4: **f** – function, supplied by the user *External Function*

Given an integer m , the function \mathbf{f} evaluates $f^{(m)}(z_i)$ at a number of points z_i .

The specification of \mathbf{f} is:

```
void f (Integer m, Integer *iflag, Integer nz, const Complex z[],
        Complex fz[], Nag_Comm *comm)
```

1: **m** – Integer *Input*

On entry: the order, m , of the derivative required.

If $\mathbf{m} = 0$, $f(z_i)$ should be returned. For $\mathbf{m} > 0$, $f^{(m)}(z_i)$ should be returned.

2: **iflag** – Integer * *Input/Output*

On entry: **iflag** will be zero.

On exit: **iflag** should either be unchanged from its entry value of zero, or may be set nonzero to indicate that there is a problem in evaluating the function $f(z)$; for instance $f(z)$ may not be defined. If **iflag** is returned as nonzero then `nag_matop_complex_gen_matrix_cond_usd (f01kcc)` will terminate the computation, with **fail.code** = NE_USER_STOP.

3: **nz** – Integer *Input*

On entry: n_z , the number of function or derivative values required.

4: **z[nz]** – const Complex *Input*

On entry: the n_z points z_1, z_2, \dots, z_{n_z} at which the function f is to be evaluated.

5: **fz[nz]** – Complex *Output*

On exit: the n_z function or derivative values. **fz**[$i-1$] should return the value $f^{(m)}(z_i)$, for $i = 1, 2, \dots, n_z$.

6: **comm** – Nag_Comm * *Communication Structure*

Pointer to structure of type Nag_Comm; the following members are relevant to **f**.

user – double *

iuser – Integer *

p – Pointer

The type Pointer will be `void *`. Before calling `nag_matop_complex_gen_matrix_cond_usd (f01kcc)` you may allocate memory and initialize these pointers with various quantities for use by **f** when called from `nag_matop_complex_gen_matrix_cond_usd (f01kcc)` (see Section 3.2.1.1 in the Essential Introduction).

- 5: **comm** – Nag_Comm * *Communication Structure*
The NAG communication argument (see Section 3.2.1.1 in the Essential Introduction).
- 6: **iflag** – Integer * *Output*
On exit: **iflag** = 0, unless **iflag** has been set nonzero inside **f**, in which case **iflag** will be the value set and **fail** will be set to **fail.code** = NE_USER_STOP.
- 7: **conda** – double * *Output*
On exit: an estimate of the absolute condition number of f at A .
- 8: **norma** – double * *Output*
On exit: the 1-norm of A .
- 9: **normfa** – double * *Output*
On exit: the 1-norm of $f(A)$.
- 10: **fail** – NagError * *Input/Output*
The NAG error argument (see Section 3.6 in the Essential Introduction).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Allocation of memory failed.

NE_BAD_PARAM

On entry, argument $\langle value \rangle$ had an illegal value.

NE_INT

On entry, **n** = $\langle value \rangle$.
Constraint: **n** \geq 0.

NE_INT_2

On entry, **pda** = $\langle value \rangle$ and **n** = $\langle value \rangle$.
Constraint: **pda** \geq **n**.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An internal error occurred when estimating the norm of the Fréchet derivative of f at A . Please contact NAG.

An internal error occurred when evaluating the matrix function $f(A)$. You can investigate further by calling `nag_matop_complex_gen_matrix_fun_usd` (f01fmc) with the matrix A and the function f .

NE_USER_STOP

iflag has been set nonzero by the user-supplied function.

7 Accuracy

`nag_matop_complex_gen_matrix_cond_usd` (f01kcc) uses the norm estimation function `nag_linsys_complex_gen_norm_rcomm` (f04zdc) to estimate a quantity γ , where $\gamma \leq \|K(X)\|_1$ and $\|K(X)\|_1 \in [n^{-1}\|L(X)\|_1, n\|L(X)\|_1]$. For further details on the accuracy of norm estimation, see the documentation for `nag_linsys_complex_gen_norm_rcomm` (f04zdc).

8 Parallelism and Performance

`nag_matop_complex_gen_matrix_cond_usd` (f01kcc) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

`nag_matop_complex_gen_matrix_cond_usd` (f01kcc) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

In these implementations, this may make calls to the user supplied functions from within an OpenMP parallel region. Thus OpenMP directives within the user functions should be avoided, unless you are using the same OpenMP runtime library (which normally means using the same compiler) as that used to build your NAG Library implementation, as listed in the Installers' Note. You must also ensure that you use the NAG communication argument **comm** in a thread safe manner, which is best achieved by only using it to supply read-only data to the user functions.

Please consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

Approximately $6n^2$ of complex allocatable memory is required by the routine, in addition to the memory used by the underlying matrix function routine `nag_matop_complex_gen_matrix_fun_usd` (f01fmc).

`nag_matop_complex_gen_matrix_cond_usd` (f01kcc) returns the matrix function $f(A)$. This is computed using `nag_matop_complex_gen_matrix_fun_usd` (f01fmc). If only $f(A)$ is required, without an estimate of the condition number, then it is far more efficient to use `nag_matop_complex_gen_matrix_fun_usd` (f01fmc) directly.

The real analogue of this function is `nag_matop_real_gen_matrix_cond_usd` (f01jcc).

10 Example

This example estimates the absolute and relative condition numbers of the matrix function e^{3A} where

$$A = \begin{pmatrix} 1.0 + 1.0i & 0.0 + 1.0i & 1.0 + 0.0i & 2.0 + 0.0i \\ 0.0 + 0.0i & 2.0 + 0.0i & 0.0 + 2.0i & 1.0 + 0.0i \\ 0.0 + 1.0i & 0.0 + 1.0i & 0.0 + 0.0i & 2.0 + 0.0i \\ 1.0 + 0.0i & 0.0 + 1.0i & 1.0 + 0.0i & 0.0 + 1.0i \end{pmatrix}.$$

10.1 Program Text

```
/* nag_matop_complex_gen_matrix_cond_usd (f01kcc) Example Program.
 *
 * Copyright 2013 Numerical Algorithms Group.
 *
 * Mark 24, 2013.
 */
#include <math.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagf01.h>
#include <nagx02.h>
#include <nagx04.h>

#ifdef __cplusplus
```

```

extern "C" {
#endif
    static void NAG_CALL f(Integer m, Integer *iflag, Integer nz,
                          const Complex z[], Complex fz[], Nag_Comm *comm);
#ifdef __cplusplus
}
#endif

#define A(I,J) a[J*pda + I]

int main(void)
{
    /* Scalars */
    Integer      exit_status = 0;
    Integer      i, iflag, j, n, pda;
    double       conda, cond_rel, eps, norma, normfa;
    /* Arrays */
    static double ruser[1] = {-1.0};
    Complex      *a = 0;
    /* Nag Types */
    Nag_OrderType order = Nag_ColMajor;
    Nag_Comm     comm;
    NagError     fail;

    INIT_FAIL(fail);

    /* Output preamble */
    printf("nag_matop_complex_gen_matrix_cond_usd (f01kcc) ");
    printf("Example Program Results\n\n");

    /* For communication with user-supplied functions: */
    comm.user = ruser;

    fflush(stdout);

    /* Skip heading in data file */
    scanf("%*[\n] ");

    /* Read in the problem size */
    scanf("%ld%*[\n]", &n);

    pda = n;
    if (!(a = NAG_ALLOC((pda)*(n), Complex))) {
        printf("Allocation failure\n");
        exit_status = -1;
        goto END;
    }

    /* Read in the matrix A from data file */
    for (i = 0; i < n; i++)
        for (j = 0; j < n; j++) scanf(" (%lf , %lf )", &A(i, j).re, &A(i, j).im);
    scanf("%*[\n] ");

    /* Print matrix A using
     * nag_gen_complex_mat_print (x04dac)
     * Print complex general matrix (easy-to-use)
     */
    nag_gen_complex_mat_print (order, Nag_GeneralMatrix, Nag_NonUnitDiag,
                              n, n, a, pda, "A", NULL, &fail);
    if (fail.code != NE_NOERROR) {
        printf("Error from nag_gen_complex_mat_print (x04dac)\n%s\n", fail.message);
        exit_status = 2;
        goto END;
    }

    /* Find absolute condition number estimate of f(A) for complex matrix A using
     * nag_matop_complex_gen_matrix_cond_usd (f01kcc)
     * Condition number for general function of a complex matrix
     * using user-supplied derivatives.
     */
}

```

```

nag_matop_complex_gen_matrix_cond_usd (n, a, pda, f, &comm, &iflag,
                                         &conda, &norma, &normfa, &fail);
if (fail.code != NE_NOERROR) {
    printf("Error from nag_matop_complex_gen_matrix_cond_usd (f01kcc)\n%s\n",
          fail.message);
    exit_status = 1;
    goto END;
}

/* Print absolute condition number estimate */
printf("\nF(A) = exp(3A)\n");
printf("Estimated absolute condition number is: %7.2f\n",conda);

/* nag_machine_precision (x02ajc) The machine precision */
eps = nag_machine_precision;

/* Find relative condition number estimate */
if ( normfa>eps) {
    cond_rel = conda * norma/normfa;
    printf("Estimated relative condition number is: %7.2f\n",cond_rel);
}
else {
    printf("The estimated norm of f(A) is effectively zero");
    printf("and so the relative condition number is undefined.\n");
}

END:
NAG_FREE(a);
return exit_status;
}

static void NAG_CALL f(Integer m, Integer *iflag, Integer nz,
                      const Complex z[], Complex fz[], Nag_Comm *comm)
{
    /* Scalars */
    Integer j;
    if (comm->user[0] == -1.0)
    {
        printf("(User-supplied callback f, first invocation.)\n");
        comm->user[0] = 0.0;
    }
    for (j = 0; j < nz; j++) {
        /* The m`th derivative of exp 3z for complex z*/
        fz[j].re = pow(3.0,m)*exp(3.0*z[j].re)*cos(3.0*z[j].im);
        fz[j].im = pow(3.0,m)*exp(3.0*z[j].re)*sin(3.0*z[j].im);
    }
    /* Set iflag nonzero to terminate execution for any reason. */
    *iflag = 0;
}

```

10.2 Program Data

nag_matop_complex_gen_matrix_cond_usd (f01kcc) Example Program Data

```

4                                     :Value of n

(1.0, 1.0)   (0.0, 1.0)   (1.0, 0.0)   (2.0, 0.0)
(0.0, 0.0)   (2.0, 0.0)   (0.0, 2.0)   (1.0, 0.0)
(0.0, 1.0)   (0.0, 1.0)   (0.0, 0.0)   (2.0, 0.0)
(1.0, 0.0)   (0.0, 1.0)   (1.0, 0.0)   (0.0, 1.0) :End of matrix a

```

10.3 Program Results

nag_matop_complex_gen_matrix_cond_usd (f01kcc) Example Program Results

```
A
      1      2      3      4
1    1.0000  0.0000  1.0000  2.0000
    1.0000  1.0000  0.0000  0.0000
2    0.0000  2.0000  0.0000  1.0000
    0.0000  0.0000  2.0000  0.0000
3    0.0000  0.0000  0.0000  2.0000
    1.0000  1.0000  0.0000  0.0000
4    1.0000  0.0000  1.0000  0.0000
    0.0000  1.0000  0.0000  1.0000
```

(User-supplied callback f, first invocation.)

```
F(A) = exp(3A)
Estimated absolute condition number is: 9474.43
Estimated relative condition number is: 13.74
```
