

NAG Library Function Document

nag_dgbsv (f07bac)

1 Purpose

nag_dgbsv (f07bac) computes the solution to a real system of linear equations

$$AX = B,$$

where A is an n by n band matrix, with k_l subdiagonals and k_u superdiagonals, and X and B are n by r matrices.

2 Specification

```
#include <nag.h>
#include <nagf07.h>
void nag_dgbsv (Nag_OrderType order, Integer n, Integer kl, Integer ku,
                Integer nrhs, double ab[], Integer pdab, Integer ipiv[], double b[],
                Integer pdb, NagError *fail)
```

3 Description

nag_dgbsv (f07bac) uses the LU decomposition with partial pivoting and row interchanges to factor A as $A = PLU$, where P is a permutation matrix, L is a product of permutation and unit lower triangular matrices with k_l subdiagonals, and U is upper triangular with $(k_l + k_u)$ superdiagonals. The factored form of A is then used to solve the system of equations $AX = B$.

4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia <http://www.netlib.org/lapack/lug>

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

5 Arguments

1: **order** – Nag_OrderType *Input*

On entry: the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag_RowMajor. See Section 3.2.1.3 in the Essential Introduction for a more detailed explanation of the use of this argument.

Constraint: **order** = Nag_RowMajor or Nag_ColMajor.

2: **n** – Integer *Input*

On entry: n , the number of linear equations, i.e., the order of the matrix A .

Constraint: **n** ≥ 0 .

3: **kl** – Integer *Input*

On entry: k_l , the number of subdiagonals within the band of the matrix A .

Constraint: **kl** ≥ 0 .

4: **ku** – Integer *Input*

On entry: k_u , the number of superdiagonals within the band of the matrix A .

Constraint: $\mathbf{ku} \geq 0$.

5: **nrhs** – Integer *Input*

On entry: r , the number of right-hand sides, i.e., the number of columns of the matrix B .

Constraint: $\mathbf{nrhs} \geq 0$.

6: **ab**[*dim*] – double *Input/Output*

Note: the dimension, dim , of the array **ab** must be at least $\max(1, \mathbf{pdab} \times \mathbf{n})$.

On entry: the n by n coefficient matrix A .

This is stored as a notional two-dimensional array with row elements or column elements stored contiguously. The storage of elements A_{ij} , for row $i = 1, \dots, n$ and column $j = \max(1, i - k_l), \dots, \min(n, i + k_u)$, depends on the **order** argument as follows:

if **order** = 'Nag_ColMajor', A_{ij} is stored as **ab**[($j - 1$) \times **pdab** + **kl** + **ku** + $i - j$];

if **order** = 'Nag_RowMajor', A_{ij} is stored as **ab**[($i - 1$) \times **pdab** + **kl** + $j - i$].

See Section 9 for further details.

On exit: **ab** is overwritten by details of the factorization.

The elements, u_{ij} , of the upper triangular band factor U with $k_l + k_u$ super-diagonals, and the multipliers, l_{ij} , used to form the lower triangular factor L are stored. The elements u_{ij} , for $i = 1, \dots, n$ and $j = i, \dots, \min(n, i + k_l + k_u)$, and l_{ij} , for $i = 1, \dots, n$ and $j = \max(1, i - k_l), \dots, i$, are stored where A_{ij} is stored on entry.

7: **pdab** – Integer *Input*

On entry: the stride separating row or column elements (depending on the value of **order**) of the matrix A in the array **ab**.

Constraint: **pdab** $\geq 2 \times \mathbf{kl} + \mathbf{ku} + 1$.

8: **ipiv**[*n*] – Integer *Output*

On exit: if no constraints are violated, the pivot indices that define the permutation matrix P ; at the i th step row i of the matrix was interchanged with row **ipiv**[$i - 1$]. **ipiv**[$i - 1$] = i indicates a row interchange was not required.

9: **b**[*dim*] – double *Input/Output*

Note: the dimension, dim , of the array **b** must be at least

$\max(1, \mathbf{pdab} \times \mathbf{nrhs})$ when **order** = Nag_ColMajor;
 $\max(1, \mathbf{n} \times \mathbf{pdab})$ when **order** = Nag_RowMajor.

The (i, j) th element of the matrix B is stored in

b[($j - 1$) \times **pdab** + $i - 1$] when **order** = Nag_ColMajor;
b[($i - 1$) \times **pdab** + $j - 1$] when **order** = Nag_RowMajor.

On entry: the n by r right-hand side matrix B .

On exit: if **fail.code** = NE_NOERROR, the n by r solution matrix X .

10: **pdb** – Integer *Input*

On entry: the stride separating row or column elements (depending on the value of **order**) in the array **b**.

Constraints:

if **order** = Nag_ColMajor, **pdb** $\geq \max(1, \mathbf{n})$;
 if **order** = Nag_RowMajor, **pdb** $\geq \max(1, \mathbf{nrhs})$.

11: **fail** – NagError *

Input/Output

The NAG error argument (see Section 3.6 in the Essential Introduction).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

NE_BAD_PARAM

On entry, argument $\langle value \rangle$ had an illegal value.

NE_INT

On entry, **kl** = $\langle value \rangle$.

Constraint: **kl** ≥ 0 .

On entry, **ku** = $\langle value \rangle$.

Constraint: **ku** ≥ 0 .

On entry, **n** = $\langle value \rangle$.

Constraint: **n** ≥ 0 .

On entry, **nrhs** = $\langle value \rangle$.

Constraint: **nrhs** ≥ 0 .

On entry, **pdab** = $\langle value \rangle$.

Constraint: **pdab** > 0 .

On entry, **pdb** = $\langle value \rangle$.

Constraint: **pdb** > 0 .

NE_INT_2

On entry, **pdb** = $\langle value \rangle$ and **n** = $\langle value \rangle$.

Constraint: **pdb** $\geq \max(1, \mathbf{n})$.

On entry, **pdb** = $\langle value \rangle$ and **nrhs** = $\langle value \rangle$.

Constraint: **pdb** $\geq \max(1, \mathbf{nrhs})$.

NE_INT_3

On entry, **pdab** = $\langle value \rangle$, **kl** = $\langle value \rangle$ and **ku** = $\langle value \rangle$.

Constraint: **pdab** $\geq 2 \times \mathbf{kl} + \mathbf{ku} + 1$.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

NE_SINGULAR

$U(\langle value \rangle, \langle value \rangle)$ is exactly zero. The factorization has been completed, but the factor U is exactly singular, so the solution could not be computed.

7 Accuracy

The computed solution for a single right-hand side, \hat{x} , satisfies an equation of the form

$$(A + E)\hat{x} = b,$$

where

$$\|E\|_1 = O(\epsilon)\|A\|_1$$

and ϵ is the **machine precision**. An approximate error bound for the computed solution is given by

$$\frac{\|\hat{x} - x\|_1}{\|x\|_1} \leq \kappa(A) \frac{\|E\|_1}{\|A\|_1},$$

where $\kappa(A) = \|A^{-1}\|_1\|A\|_1$, the condition number of A with respect to the solution of the linear equations. See Section 4.4 of Anderson *et al.* (1999) for further details.

Following the use of nag_dgbsv (f07bac), nag_dgbcon (f07bdc) can be used to estimate the condition number of A and nag_dgbrfs (f07bhc) can be used to obtain approximate error bounds. Alternatives to nag_dgbsv (f07bac), which return condition and error estimates directly are nag_real_band_lin_solve (f04bbc) and nag_dgbsvx (f07bbc).

8 Parallelism and Performance

nag_dgbsv (f07bac) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

nag_dgbsv (f07bac) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

The band storage scheme for the array **ab** is illustrated by the following example, when $n = 6$, $k_l = 1$, and $k_u = 2$. Storage of the band matrix A in the array **ab**:

order = Nag_ColMajor	order = Nag_RowMajor				
*	*				
*	*	a_{13}	a_{24}	a_{35}	a_{46}
*	a_{12}	a_{23}	a_{34}	a_{45}	a_{56}
a_{11}	a_{22}	a_{33}	a_{44}	a_{55}	a_{66}
a_{21}	a_{32}	a_{43}	a_{54}	a_{65}	*

*	a_{11}	a_{12}	a_{13}	+
a_{21}	a_{22}	a_{23}	a_{24}	+
a_{32}	a_{33}	a_{34}	a_{35}	+
a_{43}	a_{44}	a_{45}	a_{46}	*
a_{54}	a_{55}	a_{56}	*	*
a_{65}	a_{66}	*	*	*

Array elements marked * need not be set and are not referenced by the function. Array elements marked + need not be set, but are defined on exit from the function and contain the elements u_{14} , u_{25} and u_{36} .

The total number of floating-point operations required to solve the equations $AX = B$ depends upon the pivoting required, but if $n \gg k_l + k_u$ then it is approximately bounded by $O(nk_l(k_l + k_u))$ for the factorization and $O(n(2k_l + k_u)r)$ for the solution following the factorization.

The complex analogue of this function is nag_zgbsv (f07bnc).

10 Example

This example solves the equations

$$Ax = b,$$

where A is the band matrix

$$A = \begin{pmatrix} -0.23 & 2.54 & -3.66 & 0 \\ -6.98 & 2.46 & -2.73 & -2.13 \\ 0 & 2.56 & 2.46 & 4.07 \\ 0 & 0 & -4.78 & -3.82 \end{pmatrix} \quad \text{and} \quad b = \begin{pmatrix} 4.42 \\ 27.13 \\ -6.14 \\ 10.50 \end{pmatrix}.$$

Details of the *LU* factorization of A are also output.

10.1 Program Text

```
/* nag_dgbsv (f07bac) Example Program.
*
* Copyright 2008 Numerical Algorithms Group.
*
* Mark 23, 2011.
*/
#include <stdio.h>
#include <nag.h>
#include <nagx04.h>
#include <nag_stdlib.h>
#include <nagf07.h>

int main(void)
{
    /* Scalars */
    Integer      exit_status = 0, i, j, kl, ku, n, nrhs, pdab, pdb;
    /* Arrays */
    double       *ab = 0, *b = 0;
    Integer      *ipiv = 0;
    /* Nag Types */
    NagError      fail;
    Nag_OrderType order;

#ifdef NAG_COLUMN_MAJOR
#define AB(I, J) ab[(J-1)*pdab + kl + ku + I - J]
#define B(I, J)  b[(J-1)*pdb + I - 1]
    order = Nag_ColMajor;
#else
#define AB(I, J) ab[(I-1)*pdab + kl + J - I]
#define B(I, J)  b[(I-1)*pdb + J - 1]
    order = Nag_RowMajor;
#endif

INIT_FAIL(fail);

printf("nag_dgbsv (f07bac) Example Program Results\n\n");

/* Skip heading in data file */
scanf("%*[^\n]");
scanf("%ld%ld%ld%*[^\n] ", &n, &kl, &ku);
scanf("%ld%*[^\n] ", &nrhs);
if (n < 0 || kl < 0 || ku < 0 || nrhs < 0)
{
    printf("One or more of n, kl, ku or nrhs has illegal value\n");
    exit_status = 1;
    goto END;
}

pdab = 2*kl+ku+1;

#ifdef NAG_COLUMN_MAJOR
    pdb = n;
#else
    pdb = nrhs;
#endif


```

```

/* Allocate memory */
if (!(ab = NAG_ALLOC((2*kl+ku+1)*n, double)) ||
    !(b = NAG_ALLOC(n*nrhs, double)) ||
    !(ipiv = NAG_ALLOC(n, Integer)))
{
    printf("Allocation failure\n");
    exit_status = -1;
    goto END;
}

/* Read the band matrix A and the right hand side b from data file */
for (i = 1; i <= n; ++i)
    for (j = MAX(i - kl, 1); j <= MIN(i + ku, n); ++j)
        scanf("%lf", &AB(i, j));
    scanf("%*[^\n] ");

for (i = 1; i <= n; ++i)
    for (j = 1; j <= nrhs; ++j) scanf("%lf", &B(i, j));
    scanf("%*[^\n] ");

/* Solve the equations Ax = b for x using nag_dgbsv (f07bac). */
nag_dgbsv(order, n, kl, ku, nrhs, ab, pdab, ipiv, b, pdb, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_dgbsv (f07bac).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

/* Print solution */
printf("Solution\n");
for (i = 1; i <= n; ++i)
{
    for (j = 1; j <= nrhs; ++j)
        printf("%11.4f%s", B(i, j), j%7 == 0?"\n":" ");
    printf("\n");
}

/* Print details of the factorization */
printf("\n");
fflush(stdout);
nag_band_real_mat_print(order, n, n, kl, kl+ku, ab, pdab,
                        "Details of factorization", 0, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_band_real_mat_print (x04cec).\n%s\n",
           fail.message);
    exit_status = 1;
    goto END;
}

/* Print pivot indices' */
printf("\nPivot indices\n");
for (i = 1; i <= n; ++i)
    printf("%lld%s", ipiv[i-1], i%7 == 0?"\n":" ");
printf("\n");

END:
NAG_FREE(ab);
NAG_FREE(b);
NAG_FREE(ipiv);

return exit_status;
}

#undef AB
#undef B

```

10.2 Program Data

```
nag_dgbsv (f07bac) Example Program Data

4      1      2      : n, kl, ku
1      : nrhs

-0.23  2.54  -3.66
-6.98  2.46  -2.73  -2.13
      2.56  2.46   4.07
      -4.78  -3.82  : matrix A

      4.42
27.13
-6.14
10.50      : vector b
```

10.3 Program Results

```
nag_dgbsv (f07bac) Example Program Results
```

Solution

```
-2.0000
3.0000
1.0000
-4.0000
```

Details of factorization

	1	2	3	4
1	-6.9800	2.4600	-2.7300	-2.1300
2	0.0330	2.5600	2.4600	4.0700
3		0.9605	-5.9329	-3.8391
4			0.8057	-0.7269

Pivot indices

2	3	3	4
---	---	---	---
