

NAG Library Function Document

nag_dpocon (f07fgc)

1 Purpose

nag_dpocon (f07fgc) estimates the condition number of a real symmetric positive definite matrix A , where A has been factorized by nag_dpotrf (f07fdc).

2 Specification

```
#include <nag.h>
#include <nagf07.h>

void nag_dpocon (Nag_OrderType order, Nag_UploType uplo, Integer n,
                const double a[], Integer pda, double anorm, double *rcond,
                NagError *fail)
```

3 Description

nag_dpocon (f07fgc) estimates the condition number (in the 1-norm) of a real symmetric positive definite matrix A :

$$\kappa_1(A) = \|A\|_1 \|A^{-1}\|_1.$$

Since A is symmetric, $\kappa_1(A) = \kappa_\infty(A) = \|A\|_\infty \|A^{-1}\|_\infty$.

Because $\kappa_1(A)$ is infinite if A is singular, the function actually returns an estimate of the **reciprocal** of $\kappa_1(A)$.

The function should be preceded by a call to nag_dsy_norm (f16rcc) to compute $\|A\|_1$ and a call to nag_dpotrf (f07fdc) to compute the Cholesky factorization of A . The function then uses Higham's implementation of Hager's method (see Higham (1988)) to estimate $\|A^{-1}\|_1$.

4 References

Higham N J (1988) FORTRAN codes for estimating the one-norm of a real or complex matrix, with applications to condition estimation *ACM Trans. Math. Software* **14** 381–396

5 Arguments

1: **order** – Nag_OrderType *Input*

On entry: the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag_RowMajor. See Section 3.2.1.3 in the Essential Introduction for a more detailed explanation of the use of this argument.

Constraint: **order** = Nag_RowMajor or Nag_ColMajor.

2: **uplo** – Nag_UploType *Input*

On entry: specifies how A has been factorized.

uplo = Nag_Upper

$A = U^T U$, where U is upper triangular.

uplo = Nag_Lower
 $A = LL^T$, where L is lower triangular.
 Constraint: **uplo** = Nag_Upper or Nag_Lower.

- 3: **n** – Integer *Input*
 On entry: n , the order of the matrix A .
 Constraint: $n \geq 0$.
- 4: **a**[*dim*] – const double *Input*
Note: the dimension, *dim*, of the array **a** must be at least $\max(1, \mathbf{pda} \times \mathbf{n})$.
 On entry: the Cholesky factor of A , as returned by nag_dpotr (f07fdc).
- 5: **pda** – Integer *Input*
 On entry: the stride separating row or column elements (depending on the value of **order**) of the matrix in the array **a**.
 Constraint: $\mathbf{pda} \geq \max(1, \mathbf{n})$.
- 6: **anorm** – double *Input*
 On entry: the 1-norm of the **original** matrix A , which may be computed by calling nag_dsy_norm (f16rcc) with its argument **norm** = Nag_OneNorm. **anorm** must be computed either **before** calling nag_dpotr (f07fdc) or else from a **copy** of the original matrix A .
 Constraint: $\mathbf{anorm} \geq 0.0$.
- 7: **rcond** – double * *Output*
 On exit: an estimate of the reciprocal of the condition number of A . **rcond** is set to zero if exact singularity is detected or the estimate underflows. If **rcond** is less than *machine precision*, A is singular to working precision.
- 8: **fail** – NagError * *Input/Output*
 The NAG error argument (see Section 3.6 in the Essential Introduction).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

NE_BAD_PARAM

On entry, argument $\langle value \rangle$ had an illegal value.

NE_INT

On entry, $\mathbf{n} = \langle value \rangle$.
 Constraint: $\mathbf{n} \geq 0$.

On entry, $\mathbf{pda} = \langle value \rangle$.
 Constraint: $\mathbf{pda} > 0$.

NE_INT_2

On entry, $\mathbf{pda} = \langle value \rangle$ and $\mathbf{n} = \langle value \rangle$.
 Constraint: $\mathbf{pda} \geq \max(1, \mathbf{n})$.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

NE_REAL

On entry, **anorm** = $\langle value \rangle$.
Constraint: **anorm** ≥ 0.0 .

7 Accuracy

The computed estimate **rcond** is never less than the true value ρ , and in practice is nearly always less than 10ρ , although examples can be constructed where **rcond** is much larger.

8 Parallelism and Performance

nag_dpocon (f07fgc) is not threaded by NAG in any implementation.

nag_dpocon (f07fgc) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

A call to nag_dpocon (f07fgc) involves solving a number of systems of linear equations of the form $Ax = b$; the number is usually 4 or 5 and never more than 11. Each solution involves approximately $2n^2$ floating-point operations but takes considerably longer than a call to nag_dpotsr (f07fec) with one right-hand side, because extra care is taken to avoid overflow when A is approximately singular.

The complex analogue of this function is nag_zpocon (f07fuc).

10 Example

This example estimates the condition number in the 1-norm (or ∞ -norm) of the matrix A , where

$$A = \begin{pmatrix} 4.16 & -3.12 & 0.56 & -0.10 \\ -3.12 & 5.03 & -0.83 & 1.18 \\ 0.56 & -0.83 & 0.76 & 0.34 \\ -0.10 & 1.18 & 0.34 & 1.18 \end{pmatrix}.$$

Here A is symmetric positive definite and must first be factorized by nag_dpotrf (f07fdc). The true condition number in the 1-norm is 97.32.

10.1 Program Text

```
/* nag_dpocon (f07fgc) Example Program.
 *
 * Copyright 2001 Numerical Algorithms Group.
 *
 * Mark 7, 2001.
 */

#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagf16.h>
#include <nagf07.h>
#include <nagx02.h>
```

```
int main(void)
```

```

{
/* Scalars */
double      anorm, rcond;
Integer     i, j, n, pda;
Integer     exit_status = 0;
NagError    fail;
Nag_OrderType order;
/* Arrays */
char        nag_enum_arg[40];
double      *a = 0;
Nag_UploType uplo;

#ifdef NAG_COLUMN_MAJOR
#define A(I, J) a[(J-1)*pda + I - 1]
  order = Nag_ColMajor;
#else
#define A(I, J) a[(I-1)*pda + J - 1]
  order = Nag_RowMajor;
#endif

  INIT_FAIL(fail);

  printf("nag_dpocon (f07fgc) Example Program Results\n\n");

  /* Skip heading in data file */
  scanf("%*[\n] ");
  scanf("%ld%*[\n] ", &n);
#ifdef NAG_COLUMN_MAJOR
  pda = n;
#else
  pda = n;
#endif

  /* Allocate memory */
  if (!(a = NAG_ALLOC(n * n, double)))
  {
    printf("Allocation failure\n");
    exit_status = -1;
    goto END;
  }

  /* Read A from data file */
  scanf(" %39s%*[\n] ", nag_enum_arg);
  /* nag_enum_name_to_value (x04nac).
   * Converts NAG enum member name to value
   */
  uplo = (Nag_UploType) nag_enum_name_to_value(nag_enum_arg);

  if (uplo == Nag_Upper)
  {
    for (i = 1; i <= n; ++i)
    {
      for (j = i; j <= n; ++j)
        scanf("%lf", &A(i, j));
    }
    scanf("%*[\n] ");
  }
  else
  {
    for (i = 1; i <= n; ++i)
    {
      for (j = 1; j <= i; ++j)
        scanf("%lf", &A(i, j));
    }
    scanf("%*[\n] ");
  }

  /* Compute norm of A */
  /* nag_dsy_norm (f16rcc).
   * 1-norm, infinity-norm, Frobenius norm, largest absolute
   * element, real symmetric matrix
   */

```

```

nag_dsy_norm(order, Nag_OneNorm, uplo, n, a, pda, &anorm, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_dsy_norm (f16rcc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}
/* Factorize A */
/* nag_dpotrf (f07fdc).
 * Cholesky factorization of real symmetric
 * positive-definite matrix
 */
nag_dpotrf(order, uplo, n, a, pda, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_dpotrf (f07fdc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}
/* Estimate condition number */
/* nag_dpocon (f07fgc).
 * Estimate condition number of real symmetric
 * positive-definite matrix, matrix already factorized by
 * nag_dpotrf (f07fdc)
 */
nag_dpocon(order, uplo, n, a, pda, anorm, &rcond, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_dpocon (f07fgc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

/* nag_machine_precision (x02ajc).
 * The machine precision
 */
if (rcond >= nag_machine_precision)
    printf("Estimate of condition number = %11.2e\n\n", 1.0/rcond);
else
    printf("A is singular to working precision\n");
END:
NAG_FREE(a);
return exit_status;
}

```

10.2 Program Data

```

nag_dpocon (f07fgc) Example Program Data
  4                               :Value of n
  Nag_Lower                       :Value of uplo
  4.16
-3.12   5.03
  0.56  -0.83   0.76
-0.10   1.18   0.34   1.18   :End of matrix A

```

10.3 Program Results

```

nag_dpocon (f07fgc) Example Program Results
Estimate of condition number =      9.73e+01

```
