

NAG Library Function Document

nag_zppsv (f07gnc)

1 Purpose

nag_zppsv (f07gnc) computes the solution to a complex system of linear equations

$$AX = B,$$

where A is an n by n Hermitian positive definite matrix stored in packed format and X and B are n by r matrices.

2 Specification

```
#include <nag.h>
#include <nagf07.h>
void nag_zppsv (Nag_OrderType order, Nag_UptoType uplo, Integer n,
                Integer nrhs, Complex ap[], Complex b[], Integer pdb, NagError *fail)
```

3 Description

nag_zppsv (f07gnc) uses the Cholesky decomposition to factor A as $A = U^H U$ if **uplo** = Nag_Upper or $A = LL^H$ if **uplo** = Nag_Lower, where U is an upper triangular matrix and L is a lower triangular matrix. The factored form of A is then used to solve the system of equations $AX = B$.

4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia <http://www.netlib.org/lapack/lug>

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

5 Arguments

1: **order** – Nag_OrderType *Input*

On entry: the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag_RowMajor. See Section 3.2.1.3 in the Essential Introduction for a more detailed explanation of the use of this argument.

Constraint: **order** = Nag_RowMajor or Nag_ColMajor.

2: **uplo** – Nag_UptoType *Input*

On entry: if **uplo** = Nag_Upper, the upper triangle of A is stored.

If **uplo** = Nag_Lower, the lower triangle of A is stored.

Constraint: **uplo** = Nag_Upper or Nag_Lower.

3: **n** – Integer *Input*

On entry: n , the number of linear equations, i.e., the order of the matrix A .

Constraint: **n** ≥ 0 .

4: **nrhs** – Integer *Input*

On entry: r , the number of right-hand sides, i.e., the number of columns of the matrix B .

Constraint: $\mathbf{nrhs} \geq 0$.

5: **ap**[*dim*] – Complex *Input/Output*

Note: the dimension, *dim*, of the array **ap** must be at least $\max(1, \mathbf{n} \times (\mathbf{n} + 1)/2)$.

On entry: the n by n Hermitian matrix A , packed by rows or columns.

The storage of elements A_{ij} depends on the **order** and **uplo** arguments as follows:

```
if order = 'Nag_ColMajor' and uplo = 'Nag_Upper',
     $A_{ij}$  is stored in ap[( $j - 1$ )  $\times$   $j/2 + i - 1$ ], for  $i \leq j$ ;
if order = 'Nag_ColMajor' and uplo = 'Nag_Lower',
     $A_{ij}$  is stored in ap[( $2n - j$ )  $\times$  ( $j - 1$ )/2 +  $i - 1$ ], for  $i \geq j$ ;
if order = 'Nag_RowMajor' and uplo = 'Nag_Upper',
     $A_{ij}$  is stored in ap[( $2n - i$ )  $\times$  ( $i - 1$ )/2 +  $j - 1$ ], for  $i \leq j$ ;
if order = 'Nag_RowMajor' and uplo = 'Nag_Lower',
     $A_{ij}$  is stored in ap[( $i - 1$ )  $\times$   $i/2 + j - 1$ ], for  $i \geq j$ .
```

On exit: if **fail.code** = NE_NOERROR, the factor U or L from the Cholesky factorization $A = U^H U$ or $A = LL^H$, in the same storage format as A .

6: **b**[*dim*] – Complex *Input/Output*

Note: the dimension, *dim*, of the array **b** must be at least

$\max(1, \mathbf{pdb} \times \mathbf{nrhs})$ when **order** = Nag_ColMajor;
 $\max(1, \mathbf{n} \times \mathbf{pdb})$ when **order** = Nag_RowMajor.

The (i, j) th element of the matrix B is stored in

b[($j - 1$) \times **pdb** + $i - 1$] when **order** = Nag_ColMajor;
b[($i - 1$) \times **pdb** + $j - 1$] when **order** = Nag_RowMajor.

On entry: the n by r right-hand side matrix B .

On exit: if **fail.code** = NE_NOERROR, the n by r solution matrix X .

7: **pdb** – Integer *Input*

On entry: the stride separating row or column elements (depending on the value of **order**) in the array **b**.

Constraints:

```
if order = Nag_ColMajor, pdb  $\geq \max(1, \mathbf{n})$ ;
if order = Nag_RowMajor, pdb  $\geq \max(1, \mathbf{nrhs})$ .
```

8: **fail** – NagError * *Input/Output*

The NAG error argument (see Section 3.6 in the Essential Introduction).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

NE_BAD_PARAM

On entry, argument $\langle\text{value}\rangle$ had an illegal value.

NE_INT

On entry, **n** = $\langle value \rangle$.

Constraint: **n** ≥ 0 .

On entry, **nrhs** = $\langle value \rangle$.

Constraint: **nrhs** ≥ 0 .

On entry, **pdb** = $\langle value \rangle$.

Constraint: **pdb** > 0 .

NE_INT_2

On entry, **pdb** = $\langle value \rangle$ and **n** = $\langle value \rangle$.

Constraint: **pdb** $\geq \max(1, n)$.

On entry, **pdb** = $\langle value \rangle$ and **nrhs** = $\langle value \rangle$.

Constraint: **pdb** $\geq \max(1, nrhs)$.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

NE_MAT_NOT_POS_DEF

The leading minor of order $\langle value \rangle$ of A is not positive definite, so the factorization could not be completed, and the solution has not been computed.

7 Accuracy

The computed solution for a single right-hand side, \hat{x} , satisfies an equation of the form

$$(A + E)\hat{x} = b,$$

where

$$\|E\|_1 = O(\epsilon)\|A\|_1$$

and ϵ is the *machine precision*. An approximate error bound for the computed solution is given by

$$\frac{\|\hat{x} - x\|_1}{\|x\|_1} \leq \kappa(A) \frac{\|E\|_1}{\|A\|_1},$$

where $\kappa(A) = \|A^{-1}\|_1 \|A\|_1$, the condition number of A with respect to the solution of the linear equations. See Section 4.4 of Anderson *et al.* (1999) for further details.

`nag_zppsvx` (f07gpc) is a comprehensive LAPACK driver that returns forward and backward error bounds and an estimate of the condition number. Alternatively, `nag_herm_posdef_packed_lin_solve` (f04cec) solves $Ax = b$ and returns a forward error bound and condition estimate. `nag_herm_posdef_packed_lin_solve` (f04cec) calls `nag_zppsv` (f07gnc) to solve the equations.

8 Parallelism and Performance

`nag_zppsv` (f07gnc) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

`nag_zppsv` (f07gnc) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

The total number of floating-point operations is approximately $\frac{4}{3}n^3 + 8n^2r$, where r is the number of right-hand sides.

The real analogue of this function is nag_dppsv (f07gac).

10 Example

This example solves the equations

$$Ax = b,$$

where A is the Hermitian positive definite matrix

$$A = \begin{pmatrix} 3.23 & 1.51 - 1.92i & 1.90 + 0.84i & 0.42 + 2.50i \\ 1.51 + 1.92i & 3.58 & -0.23 + 1.11i & -1.18 + 1.37i \\ 1.90 - 0.84i & -0.23 - 1.11i & 4.09 & 2.33 - 0.14i \\ 0.42 - 2.50i & -1.18 - 1.37i & 2.33 + 0.14i & 4.29 \end{pmatrix}$$

and

$$b = \begin{pmatrix} 3.93 - 6.14i \\ 6.17 + 9.42i \\ -7.17 - 21.83i \\ 1.99 - 14.38i \end{pmatrix}.$$

Details of the Cholesky factorization of A are also output.

10.1 Program Text

```
/* nag_zppsv (f07gnc) Example Program.
*
* Copyright 2004 Numerical Algorithms Group.
*
* Mark 23, 2011.
*/
#include <stdio.h>
#include <nag.h>
#include <nagx04.h>
#include <nag_stlib.h>
#include <nagf07.h>

int main(void)
{
    /* Scalars */
    Integer      exit_status = 0, i, j, n, nrhs, pdb;

    /* Arrays */
    Complex      *ap = 0, *b = 0;
    char         nag_enum_arg[40];

    /* Nag Types */
    NagError      fail;
    Nag_OrderType order;
    Nag_UptoType  uplo;

    INIT_FAIL(fail);

#ifdef NAG_COLUMN_MAJOR
#define A_UPPER(I, J) ap[J*(J-1)/2 + I - 1]
#define A_LOWER(I, J) ap[(2*n-J)*(J-1)/2 + I - 1]
#define B(I, J)       b[(J-1)*pdb + I - 1]
    order = Nag_ColMajor;
#else
#define A_LOWER(I, J) ap[I*(I-1)/2 + J - 1]

```

```

#define A_UPPER(I, J) ap[(2*n-I)*(I-1)/2 + J - 1]
#define B(I, J) b[(I-1)*pdb + J - 1]
order = Nag_RowMajor;
#endif

printf("nag_zppsv (f07gnc) Example Program Results\n\n");
/* Skip heading in data file */
scanf("%*[^\n]");
scanf("%ld%ld%*[^\n]", &n, &nrhs);
if (n < 0 || nrhs < 0)
{
    printf("Invalid n or nrhs\n");
    exit_status = 1;
    goto END;
}
scanf(" %39s%*[^\n]", nag_enum_arg);
/* nag_enum_name_to_value (x04nac).
 * Converts NAG enum member name to value
 */
uplo = (Nag_UptoType) nag_enum_name_to_value(nag_enum_arg);

/* Allocate memory */
if (!(ap = NAG_ALLOC(n*(n+1)/2, Complex)) ||
    !(b = NAG_ALLOC(n, Complex)))
{
    printf("Allocation failure\n");
    exit_status = -1;
    goto END;
}
#ifndef NAG_COLUMN_MAJOR
    pdb = n;
#else
    pdb = nrhs;
#endif

/* Read the upper or lower triangular part of the matrix A from data file */

if (uplo == Nag_Upper)
    for (i = 1; i <= n; ++i)
        for (j = i; j <= n; ++j)
            scanf("( %lf , %lf )", &A_UPPER(i, j).re, &A_UPPER(i, j).im);
else if (uplo == Nag_Lower)
    for (i = 1; i <= n; ++i)
        for (j = 1; j <= i; ++j)
            scanf("( %lf , %lf )", &A_LOWER(i, j).re, &A_LOWER(i, j).im);
scanf("%*[^\n]");

/* Read b from data file */
for (i = 1; i <= n; ++i)
    for (j = 1; j <= nrhs; ++j)
        scanf("( %lf , %lf )", &B(i, j).re, &B(i, j).im);
scanf("%*[^\n]");

/* Solve the equations Ax = b for x using nag_zppsv (f07gnc). */
nag_zppsv(order, uplo, n, nrhs, ap, b, pdb, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_zppsv (f07gnc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

/* Print solution */
printf("Solution\n");
for (i = 1; i <= n; ++i)
{
    for (j = 1; j <= nrhs; ++j)
        printf("(%.4f, %.4f)%s", B(i, j).re, B(i, j).im, j%4 == 0?"\n":" ");
    printf("\n");
}
/* Print details of factorization using

```

```

* nag_pack_complx_mat_print_comp (x04ddc).
*/
printf("\n");
fflush(stdout);
nag_pack_complx_mat_print_comp(order, uplo, Nag_NonUnitDiag, n, ap,
                                Nag_BracketForm, "%7.4f", "Cholesky factor",
                                Nag_IntegerLabels, 0, Nag_IntegerLabels, 0,
                                80, 0, 0, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_pack_complx_mat_print_comp (x04ddc).\n%s\n",
           fail.message);
    exit_status = 1;
    goto END;
}
END:
NAG_FREE(ap);
NAG_FREE(b);

return exit_status;
}

#undef A_UPPER
#undef A_LOWER
#undef B

```

10.2 Program Data

```

nag_zppsv (f07gnc) Example Program Data
        1 : n, nrhs
Nag_Upper : uplo
( 3.23,  0.00) ( 1.51, -1.92) ( 1.90,  0.84) ( 0.42,  2.50)
               ( 3.58,  0.00) (-0.23,  1.11) (-1.18,  1.37)
                           ( 4.09,  0.00) ( 2.33, -0.14)
                           ( 4.29,  0.00) : matrix A
( 3.93, -6.14) ( 6.17,  9.42) (-7.17,-21.83) ( 1.99,-14.38) : vector b

```

10.3 Program Results

```
nag_zppsv (f07gnc) Example Program Results
```

```

Solution
( 1.0000, -1.0000)
(-0.0000,  3.0000)
(-4.0000, -5.0000)
( 2.0000,  1.0000)

```

```

Cholesky factor
        1          2          3          4
1  ( 1.7972, 0.0000) ( 0.8402,-1.0683) ( 1.0572, 0.4674) ( 0.2337, 1.3910)
2              ( 1.3164, 0.0000) (-0.4702,-0.3131) ( 0.0834,-0.0368)
3                      ( 1.5604, 0.0000) ( 0.9360,-0.9900)
4                          ( 0.6603, 0.0000)

```
