

## NAG Library Function Document

### nag\_zungqr (f08atc)

## 1 Purpose

nag\_zungqr (f08atc) generates all or part of the complex unitary matrix  $Q$  from a  $QR$  factorization computed by nag\_zgeqrf (f08asc), nag\_zgeqpf (f08bsc) or nag\_zgeqp3 (f08btc).

## 2 Specification

```
#include <nag.h>
#include <nagf08.h>
void nag_zungqr (Nag_OrderType order, Integer m, Integer n, Integer k,
                 Complex a[], Integer pda, const Complex tau[], NagError *fail)
```

## 3 Description

nag\_zungqr (f08atc) is intended to be used after a call to nag\_zgeqrf (f08asc), nag\_zgeqpf (f08bsc) or nag\_zgeqp3 (f08btc), which perform a  $QR$  factorization of a complex matrix  $A$ . The unitary matrix  $Q$  is represented as a product of elementary reflectors.

This function may be used to generate  $Q$  explicitly as a square matrix, or to form only its leading columns.

Usually  $Q$  is determined from the  $QR$  factorization of an  $m$  by  $p$  matrix  $A$  with  $m \geq p$ . The whole of  $Q$  may be computed by:

```
nag_zungqr(order,m,m,p,&a,pda,tau,&fail)
```

(note that the array **a** must have at least  $m$  columns) or its leading  $p$  columns by:

```
nag_zungqr(order,m,p,p,&a,pda,tau,&fail)
```

The columns of  $Q$  returned by the last call form an orthonormal basis for the space spanned by the columns of  $A$ ; thus nag\_zgeqrf (f08asc) followed by nag\_zungqr (f08atc) can be used to orthogonalize the columns of  $A$ .

The information returned by the  $QR$  factorization functions also yields the  $QR$  factorization of the leading  $k$  columns of  $A$ , where  $k < p$ . The unitary matrix arising from this factorization can be computed by:

```
nag_zungqr(order,m,m,k,&a,pda,tau,&fail)
```

or its leading  $k$  columns by:

```
nag_zungqr(order,m,k,k,&a,pda,tau,&fail)
```

## 4 References

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

## 5 Arguments

1: **order** – Nag\_OrderType *Input*

*On entry:* the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by

**order** = Nag\_RowMajor. See Section 3.2.1.3 in the Essential Introduction for a more detailed explanation of the use of this argument.

*Constraint:* **order** = Nag\_RowMajor or Nag\_ColMajor.

2: **m** – Integer *Input*

*On entry:*  $m$ , the order of the unitary matrix  $Q$ .

*Constraint:*  $\mathbf{m} \geq 0$ .

3: **n** – Integer *Input*

*On entry:*  $n$ , the number of columns of the matrix  $Q$ .

*Constraint:*  $\mathbf{m} \geq \mathbf{n} \geq 0$ .

4: **k** – Integer *Input*

*On entry:*  $k$ , the number of elementary reflectors whose product defines the matrix  $Q$ .

*Constraint:*  $\mathbf{n} \geq \mathbf{k} \geq 0$ .

5: **a**[*dim*] – Complex *Input/Output*

**Note:** the dimension, *dim*, of the array **a** must be at least

$\max(1, \mathbf{pda} \times \mathbf{n})$  when **order** = Nag\_ColMajor;  
 $\max(1, \mathbf{m} \times \mathbf{pda})$  when **order** = Nag\_RowMajor.

*On entry:* details of the vectors which define the elementary reflectors, as returned by nag\_zgeqr (f08asc), nag\_zgeqpf (f08bsc) or nag\_zgeqp3 (f08btc).

*On exit:* the  $m$  by  $n$  matrix  $Q$ .

If **order** = 'Nag\_ColMajor', the  $(i, j)$ th element of the matrix is stored in **a**[( $j - 1$ )  $\times$  **pda** +  $i - 1$ ].

If **order** = 'Nag\_RowMajor', the  $(i, j)$ th element of the matrix is stored in **a**[( $i - 1$ )  $\times$  **pda** +  $j - 1$ ].

6: **pda** – Integer *Input*

*On entry:* the stride separating row or column elements (depending on the value of **order**) in the array **a**.

*Constraints:*

if **order** = Nag\_ColMajor, **pda**  $\geq \max(1, \mathbf{m})$ ;  
if **order** = Nag\_RowMajor, **pda**  $\geq \max(1, \mathbf{n})$ .

7: **tau**[*dim*] – const Complex *Input*

**Note:** the dimension, *dim*, of the array **tau** must be at least  $\max(1, \mathbf{k})$ .

*On entry:* further details of the elementary reflectors, as returned by nag\_zgeqr (f08asc), nag\_zgeqpf (f08bsc) or nag\_zgeqp3 (f08btc).

8: **fail** – NagError \* *Input/Output*

The NAG error argument (see Section 3.6 in the Essential Introduction).

## 6 Error Indicators and Warnings

### NE\_ALLOC\_FAIL

Dynamic memory allocation failed.

**NE\_BAD\_PARAM**

On entry, argument  $\langle value \rangle$  had an illegal value.

**NE\_INT**

On entry,  $\mathbf{m} = \langle value \rangle$ .

Constraint:  $\mathbf{m} \geq 0$ .

On entry,  $\mathbf{pda} = \langle value \rangle$ .

Constraint:  $\mathbf{pda} > 0$ .

**NE\_INT\_2**

On entry,  $\mathbf{m} = \langle value \rangle$  and  $\mathbf{n} = \langle value \rangle$ .

Constraint:  $\mathbf{m} \geq \mathbf{n} \geq 0$ .

On entry,  $\mathbf{n} = \langle value \rangle$  and  $\mathbf{k} = \langle value \rangle$ .

Constraint:  $\mathbf{n} \geq \mathbf{k} \geq 0$ .

On entry,  $\mathbf{pda} = \langle value \rangle$  and  $\mathbf{m} = \langle value \rangle$ .

Constraint:  $\mathbf{pda} \geq \max(1, \mathbf{m})$ .

On entry,  $\mathbf{pda} = \langle value \rangle$  and  $\mathbf{n} = \langle value \rangle$ .

Constraint:  $\mathbf{pda} \geq \max(1, \mathbf{n})$ .

**NE\_INTERNAL\_ERROR**

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

**7 Accuracy**

The computed matrix  $Q$  differs from an exactly unitary matrix by a matrix  $E$  such that

$$\|E\|_2 = O(\epsilon),$$

where  $\epsilon$  is the *machine precision*.

**8 Parallelism and Performance**

nag\_zungqr (f08atc) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

nag\_zungqr (f08atc) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the Users' Note for your implementation for any additional implementation-specific information.

**9 Further Comments**

The total number of real floating-point operations is approximately  $16mnk - 8(m + n)k^2 + \frac{16}{3}k^3$ ; when  $n = k$ , the number is approximately  $\frac{8}{3}n^2(3m - n)$ .

The real analogue of this function is nag\_dorgqr (f08afc).

## 10 Example

This example forms the leading 4 columns of the unitary matrix  $Q$  from the  $QR$  factorization of the matrix  $A$ , where

$$A = \begin{pmatrix} 0.96 - 0.81i & -0.03 + 0.96i & -0.91 + 2.06i & -0.05 + 0.41i \\ -0.98 + 1.98i & -1.20 + 0.19i & -0.66 + 0.42i & -0.81 + 0.56i \\ 0.62 - 0.46i & 1.01 + 0.02i & 0.63 - 0.17i & -1.11 + 0.60i \\ -0.37 + 0.38i & 0.19 - 0.54i & -0.98 - 0.36i & 0.22 - 0.20i \\ 0.83 + 0.51i & 0.20 + 0.01i & -0.17 - 0.46i & 1.47 + 1.59i \\ 1.08 - 0.28i & 0.20 - 0.12i & -0.07 + 1.23i & 0.26 + 0.26i \end{pmatrix}.$$

The columns of  $Q$  form an orthonormal basis for the space spanned by the columns of  $A$ .

### 10.1 Program Text

```
/* nag_zungqr (f08atc) Example Program.
*
* Copyright 2001 Numerical Algorithms Group.
*
* Mark 7, 2001.
*/
#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagf08.h>
#include <nagx04.h>

int main(void)
{
    /* Scalars */
    Integer      i, j, m, n, pda, tau_len;
    Integer      exit_status = 0;
    NagError     fail;
    Nag_OrderType order;
    /* Arrays */
    char          *title = 0;
    Complex       *a = 0, *tau = 0;

#ifdef NAG_COLUMN_MAJOR
#define A(I, J) a[(J - 1) * pda + I - 1]
    order = Nag_ColMajor;
#else
#define A(I, J) a[(I - 1) * pda + J - 1]
    order = Nag_RowMajor;
#endif

    INIT_FAIL(fail);

    printf("nag_zungqr (f08atc) Example Program Results\n\n");

    /* Skip heading in data file */
    scanf("%*[^\n]");
    scanf("%ld%ld%*[^\n] ", &m, &n);
#ifdef NAG_COLUMN_MAJOR
    pda = m;
#else
    pda = n;
#endif
    tau_len = MIN(m, n);

    /* Allocate memory */
    if (!(title = NAG_ALLOC(31, char)) ||
        !(a = NAG_ALLOC(m * n, Complex)) ||
        !(tau = NAG_ALLOC(tau_len, Complex)))
    {
        printf("Allocation failure\n");
        exit_status = -1;
    }
}
```

```

        goto END;
    }

/* Read A from data file */
for (i = 1; i <= m; ++i)
{
    for (j = 1; j <= n; ++j)
        scanf(" (% lf , % lf )", &A(i, j).re, &A(i, j).im);
}
scanf("%*[^\n] ");

/* Compute the QR factorization of A */
/* nag_zgeqrf (f08asc).
 * QR factorization of complex general rectangular matrix
 */
nag_zgeqrf(order, m, n, a, pda, tau, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_zgeqrf (f08asc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

/* Form the leading N columns of Q explicitly */
/* nag_zungqr (f08atc).
 * Form all or part of unitary Q from QR factorization
 * determined by nag_zgeqrf (f08asc) or nag_zgeqpf (f08bsc)
 */
nag_zungqr(order, m, n, n, a, pda, tau, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_zungqr (f08atc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

/* Print the leading N columns of Q only */
sprintf(title, "The leading %2ld columns of Q\n", n);
/* nag_gen_complx_mat_print_comp (x04dbc).
 * Print complex general matrix (comprehensive)
 */
fflush(stdout);
nag_gen_complx_mat_print_comp(order, Nag_GeneralMatrix, Nag_NonUnitDiag, m,
                               n, a, pda, Nag_BracketForm, "%7.4f", title,
                               Nag_IntegerLabels, 0, Nag_IntegerLabels, 0, 80,
                               0, 0, &fail);
if (fail.code != NE_NOERROR)
{
    printf(
        "Error from nag_gen_complx_mat_print_comp (x04dbc).\n%s\n",
        fail.message);
    exit_status = 1;
    goto END;
}
END:
NAG_FREE(title);
NAG_FREE(a);
NAG_FREE(tau);

return exit_status;
}

```

## 10.2 Program Data

```

nag_zungqr (f08atc) Example Program Data
6 4                                         :Values of M and N
( 0.96,-0.81) (-0.03, 0.96) (-0.91, 2.06) (-0.05, 0.41)
(-0.98, 1.98) (-1.20, 0.19) (-0.66, 0.42) (-0.81, 0.56)
( 0.62,-0.46) ( 1.01, 0.02) ( 0.63,-0.17) (-1.11, 0.60)
(-0.37, 0.38) ( 0.19,-0.54) (-0.98,-0.36) ( 0.22,-0.20)

```

```
( 0.83, 0.51) ( 0.20, 0.01) (-0.17,-0.46) ( 1.47, 1.59)
( 1.08,-0.28) ( 0.20,-0.12) (-0.07, 1.23) ( 0.26, 0.26) :End of matrix A
```

### 10.3 Program Results

nag\_zungqr (f08atc) Example Program Results

The leading 4 columns of Q

|   | 1                   | 2                   | 3                   | 4                   |
|---|---------------------|---------------------|---------------------|---------------------|
| 1 | ( -0.3110, 0.2624)  | ( -0.3175, 0.4835)  | ( 0.4966, -0.2997)  | ( -0.0072, -0.3718) |
| 2 | ( 0.3175, -0.6414)  | ( -0.2062, 0.1577)  | ( -0.0793, -0.3094) | ( -0.0282, -0.1491) |
| 3 | ( -0.2008, 0.1490)  | ( 0.4892, -0.0900)  | ( 0.0357, -0.0219)  | ( 0.5625, -0.0710)  |
| 4 | ( 0.1199, -0.1231)  | ( 0.2566, -0.3055)  | ( 0.4489, -0.2141)  | ( -0.1651, 0.1800)  |
| 5 | ( -0.2689, -0.1652) | ( 0.1697, -0.2491)  | ( -0.0496, 0.1158)  | ( -0.4885, -0.4540) |
| 6 | ( -0.3499, 0.0907)  | ( -0.0491, -0.3133) | ( -0.1256, -0.5300) | ( 0.1039, 0.0450)   |

---