

NAG Library Function Document

nag_zunmrz (f08bxc)

1 Purpose

nag_zunmrz (f08bxc) multiplies a general complex m by n matrix C by the complex unitary matrix Z from an RZ factorization computed by nag_ztzzrf (f08bvc).

2 Specification

```
#include <nag.h>
#include <nagf08.h>

void nag_zunmrz (Nag_OrderType order, Nag_SideType side,
                Nag_TransType trans, Integer m, Integer n, Integer k, Integer l,
                const Complex a[], Integer pda, const Complex tau[], Complex c[],
                Integer pdc, NagError *fail)
```

3 Description

nag_zunmrz (f08bxc) is intended to be used following a call to nag_ztzzrf (f08bvc), which performs an RZ factorization of a real upper trapezoidal matrix A and represents the unitary matrix Z as a product of elementary reflectors.

This function may be used to form one of the matrix products

$$ZC, \quad Z^H C, \quad CZ, \quad CZ^H,$$

overwriting the result on C , which may be any complex rectangular m by n matrix.

4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia <http://www.netlib.org/lapack/lug>

5 Arguments

1: **order** – Nag_OrderType *Input*

On entry: the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag_RowMajor. See Section 3.2.1.3 in the Essential Introduction for a more detailed explanation of the use of this argument.

Constraint: **order** = Nag_RowMajor or Nag_ColMajor.

2: **side** – Nag_SideType *Input*

On entry: indicates how Z or Z^H is to be applied to C .

side = Nag_LeftSide

Z or Z^H is applied to C from the left.

side = Nag_RightSide

Z or Z^H is applied to C from the right.

Constraint: **side** = Nag_LeftSide or Nag_RightSide.

- 3: **trans** – Nag_TransType *Input*
On entry: indicates whether Z or Z^H is to be applied to C .
trans = Nag_NoTrans
 Z is applied to C .
trans = Nag_ConjTrans
 Z^H is applied to C .
Constraint: **trans** = Nag_NoTrans or Nag_ConjTrans.
- 4: **m** – Integer *Input*
On entry: m , the number of rows of the matrix C .
Constraint: **m** \geq 0.
- 5: **n** – Integer *Input*
On entry: n , the number of columns of the matrix C .
Constraint: **n** \geq 0.
- 6: **k** – Integer *Input*
On entry: k , the number of elementary reflectors whose product defines the matrix Z .
Constraints:
if **side** = Nag_LeftSide, **m** \geq **k** \geq 0;
if **side** = Nag_RightSide, **n** \geq **k** \geq 0.
- 7: **l** – Integer *Input*
On entry: l , the number of columns of the matrix A containing the meaningful part of the Householder reflectors.
Constraints:
if **side** = Nag_LeftSide, **m** \geq **l** \geq 0;
if **side** = Nag_RightSide, **n** \geq **l** \geq 0.
- 8: **a**[*dim*] – const Complex *Input*
Note: the dimension, *dim*, of the array **a** must be at least
 $\max(1, \mathbf{pda} \times \mathbf{m})$ when **side** = Nag_LeftSide and **order** = Nag_ColMajor;
 $\max(1, \mathbf{k} \times \mathbf{pda})$ when **side** = Nag_LeftSide and **order** = Nag_RowMajor;
 $\max(1, \mathbf{pda} \times \mathbf{n})$ when **side** = Nag_RightSide and **order** = Nag_ColMajor;
 $\max(1, \mathbf{k} \times \mathbf{pda})$ when **side** = Nag_RightSide and **order** = Nag_RowMajor.
The (i, j)th element of the matrix A is stored in
a[($j - 1$) \times **pda** + $i - 1$] when **order** = Nag_ColMajor;
a[($i - 1$) \times **pda** + $j - 1$] when **order** = Nag_RowMajor.
On entry: the i th row of **a** must contain the vector which defines the elementary reflector H_i , for $i = 1, 2, \dots, k$, as returned by nag_ztrzf (f08bvc).
- 9: **pda** – Integer *Input*
On entry: the stride separating row or column elements (depending on the value of **order**) in the array **a**.

Constraints:

if **order** = Nag_ColMajor, **pda** \geq $\max(1, \mathbf{k})$;
 if **order** = Nag_RowMajor,
 if **side** = Nag_LeftSide, **pda** \geq $\max(1, \mathbf{m})$;
 if **side** = Nag_RightSide, **pda** \geq $\max(1, \mathbf{n})$..

10: **tau**[*dim*] – const Complex *Input*

Note: the dimension, *dim*, of the array **tau** must be at least $\max(1, \mathbf{k})$.

On entry: **tau**[*i* – 1] must contain the scalar factor of the elementary reflector H_i , as returned by nag_ztzzf (f08bvc).

11: **c**[*dim*] – Complex *Input/Output*

Note: the dimension, *dim*, of the array **c** must be at least

$\max(1, \mathbf{pdc} \times \mathbf{n})$ when **order** = Nag_ColMajor;
 $\max(1, \mathbf{m} \times \mathbf{pdc})$ when **order** = Nag_RowMajor.

The (*i*, *j*)th element of the matrix *C* is stored in

c[(*j* – 1) \times **pdc** + *i* – 1] when **order** = Nag_ColMajor;
c[(*i* – 1) \times **pdc** + *j* – 1] when **order** = Nag_RowMajor.

On entry: the *m* by *n* matrix *C*.

On exit: **c** is overwritten by *ZC* or $Z^H C$ or *CZ* or $Z^H C$ as specified by **side** and **trans**.

12: **pdc** – Integer *Input*

On entry: the stride separating row or column elements (depending on the value of **order**) in the array **c**.

Constraints:

if **order** = Nag_ColMajor, **pdc** \geq $\max(1, \mathbf{m})$;
 if **order** = Nag_RowMajor, **pdc** \geq $\max(1, \mathbf{n})$.

13: **fail** – NagError * *Input/Output*

The NAG error argument (see Section 3.6 in the Essential Introduction).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

NE_BAD_PARAM

On entry, argument *<value>* had an illegal value.

NE_ENUM_INT_3

On entry, **side** = *<value>*, **m** = *<value>*, **n** = *<value>* and **k** = *<value>*.
 Constraint: if **side** = Nag_LeftSide, **m** \geq **k** \geq 0;
 if **side** = Nag_RightSide, **n** \geq **k** \geq 0.

On entry, **side** = *<value>*, **m** = *<value>*, **n** = *<value>* and **l** = *<value>*.
 Constraint: if **side** = Nag_LeftSide, **m** \geq **l** \geq 0;
 if **side** = Nag_RightSide, **n** \geq **l** \geq 0.

On entry, **side** = *<value>*, **pda** = *<value>*, **m** = *<value>* and **n** = *<value>*.
 Constraint: if **side** = Nag_LeftSide, **pda** \geq max(1, **m**);
 if **side** = Nag_RightSide, **pda** \geq max(1, **n**).

NE_INT

On entry, **m** = *<value>*.
 Constraint: **m** \geq 0.

On entry, **n** = *<value>*.
 Constraint: **n** \geq 0.

On entry, **pda** = *<value>*.
 Constraint: **pda** > 0.

On entry, **pdv** = *<value>*.
 Constraint: **pdv** > 0.

NE_INT_2

On entry, **pda** = *<value>* and **k** = *<value>*.
 Constraint: **pda** \geq max(1, **k**).

On entry, **pdv** = *<value>* and **m** = *<value>*.
 Constraint: **pdv** \geq max(1, **m**).

On entry, **pdv** = *<value>* and **n** = *<value>*.
 Constraint: **pdv** \geq max(1, **n**).

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

7 Accuracy

The computed result differs from the exact result by a matrix E such that

$$\|E\|_2 = O\epsilon\|C\|_2$$

where ϵ is the *machine precision*.

8 Parallelism and Performance

nag_zunmrz (f08bxc) is not threaded by NAG in any implementation.

nag_zunmrz (f08bxc) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

The total number of floating-point operations is approximately $16nlk$ if **side** = Nag_LeftSide and $16mlk$ if **side** = Nag_RightSide.

The real analogue of this function is nag_dormrz (f08bkc).

10 Example

See Section 10 in nag_ztrzf (f08bvc).
