

NAG Library Function Document

nag_dsytrd (f08fec)

1 Purpose

nag_dsytrd (f08fec) reduces a real symmetric matrix to tridiagonal form.

2 Specification

```
#include <nag.h>
#include <nagf08.h>

void nag_dsytrd (Nag_OrderType order, Nag_UploType uplo, Integer n,
                double a[], Integer pda, double d[], double e[], double tau[],
                NagError *fail)
```

3 Description

nag_dsytrd (f08fec) reduces a real symmetric matrix A to symmetric tridiagonal form T by an orthogonal similarity transformation: $A = QTQ^T$.

The matrix Q is not formed explicitly but is represented as a product of $n - 1$ elementary reflectors (see the f08 Chapter Introduction for details). Functions are provided to work with Q in this representation (see Section 9).

4 References

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

5 Arguments

- 1: **order** – Nag_OrderType *Input*
On entry: the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag_RowMajor. See Section 3.2.1.3 in the Essential Introduction for a more detailed explanation of the use of this argument.
Constraint: **order** = Nag_RowMajor or Nag_ColMajor.
- 2: **uplo** – Nag_UploType *Input*
On entry: indicates whether the upper or lower triangular part of A is stored.
uplo = Nag_Upper
 The upper triangular part of A is stored.
uplo = Nag_Lower
 The lower triangular part of A is stored.
Constraint: **uplo** = Nag_Upper or Nag_Lower.
- 3: **n** – Integer *Input*
On entry: n , the order of the matrix A .
Constraint: $n \geq 0$.

- 4: **a**[*dim*] – double *Input/Output*
Note: the dimension, *dim*, of the array **a** must be at least $\max(1, \mathbf{pda} \times \mathbf{n})$.
On entry: the *n* by *n* symmetric matrix *A*.
If **order** = 'Nag-ColMajor', A_{ij} is stored in $\mathbf{a}[(j-1) \times \mathbf{pda} + i - 1]$.
If **order** = 'Nag-RowMajor', A_{ij} is stored in $\mathbf{a}[(i-1) \times \mathbf{pda} + j - 1]$.
If **uplo** = 'Nag-Upper', the upper triangular part of *A* must be stored and the elements of the array below the diagonal are not referenced.
If **uplo** = 'Nag-Lower', the lower triangular part of *A* must be stored and the elements of the array above the diagonal are not referenced.
On exit: **a** is overwritten by the tridiagonal matrix *T* and details of the orthogonal matrix *Q* as specified by **uplo**.
- 5: **pda** – Integer *Input*
On entry: the stride separating row or column elements (depending on the value of **order**) of the matrix *A* in the array **a**.
Constraint: $\mathbf{pda} \geq \max(1, \mathbf{n})$.
- 6: **d**[*dim*] – double *Output*
Note: the dimension, *dim*, of the array **d** must be at least $\max(1, \mathbf{n})$.
On exit: the diagonal elements of the tridiagonal matrix *T*.
- 7: **e**[*dim*] – double *Output*
Note: the dimension, *dim*, of the array **e** must be at least $\max(1, \mathbf{n} - 1)$.
On exit: the off-diagonal elements of the tridiagonal matrix *T*.
- 8: **tau**[*dim*] – double *Output*
Note: the dimension, *dim*, of the array **tau** must be at least $\max(1, \mathbf{n} - 1)$.
On exit: further details of the orthogonal matrix *Q*.
- 9: **fail** – NagError * *Input/Output*
The NAG error argument (see Section 3.6 in the Essential Introduction).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

NE_BAD_PARAM

On entry, argument $\langle \text{value} \rangle$ had an illegal value.

NE_INT

On entry, $\mathbf{n} = \langle \text{value} \rangle$.

Constraint: $\mathbf{n} \geq 0$.

On entry, $\mathbf{pda} = \langle \text{value} \rangle$.

Constraint: $\mathbf{pda} > 0$.

NE_INT_2

On entry, **pda** = $\langle value \rangle$ and **n** = $\langle value \rangle$.
 Constraint: **pda** \geq $\max(1, \mathbf{n})$.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

7 Accuracy

The computed tridiagonal matrix T is exactly similar to a nearby matrix $(A + E)$, where

$$\|E\|_2 \leq c(n)\epsilon\|A\|_2,$$

$c(n)$ is a modestly increasing function of n , and ϵ is the *machine precision*.

The elements of T themselves may be sensitive to small perturbations in A or to rounding errors in the computation, but this does not affect the stability of the eigenvalues and eigenvectors.

8 Parallelism and Performance

nag_dsytrd (f08fec) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

nag_dsytrd (f08fec) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

The total number of floating-point operations is approximately $\frac{4}{3}n^3$.

To form the orthogonal matrix Q nag_dsytrd (f08fec) may be followed by a call to nag_dorgtr (f08ffc):

```
nag_dorgtr(order, uplo, n, &a, pda, tau, &fail)
```

To apply Q to an n by p real matrix C nag_dsytrd (f08fec) may be followed by a call to nag_dormtr (f08fgc). For example,

```
nag_dormtr(order, Nag_LeftSide, uplo, Nag_NoTrans, n, p, &a, pda,
tau, &c, pdc, &fail)
```

forms the matrix product QC .

The complex analogue of this function is nag_zhetrd (f08fsc).

10 Example

This example reduces the matrix A to tridiagonal form, where

$$A = \begin{pmatrix} 2.07 & 3.87 & 4.20 & -1.15 \\ 3.87 & -0.21 & 1.87 & 0.63 \\ 4.20 & 1.87 & 1.15 & 2.06 \\ -1.15 & 0.63 & 2.06 & -1.81 \end{pmatrix}.$$

10.1 Program Text

```

/* nag_dsytrd (f08fec) Example Program.
 *
 * Copyright 2001 Numerical Algorithms Group.
 *
 * Mark 7, 2001.
 */

#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagf08.h>
#include <nagf16.h>
#include <nagx04.h>

int main(void)
{
    /* Scalars */
    Integer      i, j, n, pda, pdz, d_len, e_len, tau_len;
    Integer      exit_status = 0;
    NagError     fail;
    Nag_UploType uplo;
    Nag_OrderType order;
    /* Arrays */
    char         nag_enum_arg[40];
    double       *a = 0, *d = 0, *e = 0, *tau = 0, *z = 0;

#ifdef NAG_COLUMN_MAJOR
#define A(I, J) a[(J - 1) * pda + I - 1]
#define Z(I, J) z[(J - 1) * pdz + I - 1]
    order = Nag_ColMajor;
#else
#define A(I, J) a[(I - 1) * pda + J - 1]
#define Z(I, J) z[(I - 1) * pdz + J - 1]
    order = Nag_RowMajor;
#endif

    INIT_FAIL(fail);

    printf("nag_dsytrd (f08fec) Example Program Results\n\n");

    /* Skip heading in data file */
    scanf("%*[\n] ");
    scanf("%ld%*[\n] ", &n);

    pda = n;
    pdz = n;
    tau_len = n-1;
    d_len = n;
    e_len = n-1;
    /* Allocate memory */
    if (!(a = NAG_ALLOC(n * n, double)) ||
        !(d = NAG_ALLOC(d_len, double)) ||
        !(e = NAG_ALLOC(e_len, double)) ||
        !(tau = NAG_ALLOC(tau_len, double)) ||
        !(z = NAG_ALLOC(n * n, double)))
    {
        printf("Allocation failure\n");
        exit_status = -1;
        goto END;
    }

    /* Read A from data file */
    scanf(" %39s%*[\n] ", nag_enum_arg);
    /* nag_enum_name_to_value (x04nac).
     * Converts NAG enum member name to value
     */
    uplo = (Nag_UploType) nag_enum_name_to_value(nag_enum_arg);

    if (uplo == Nag_Upper)

```

```

    {
        for (i = 1; i <= n; ++i)
        {
            for (j = i; j <= n; ++j)
                scanf("%lf", &A(i, j));
        }
        scanf("%*[\n] ");
    }
else
    {
        for (i = 1; i <= n; ++i)
        {
            for (j = 1; j <= i; ++j)
                scanf("%lf", &A(i, j));
        }
        scanf("%*[\n] ");
    }

/* Reduce A to tridiagonal form T = (Q**T)*A*Q */
/* nag_dsytrd (f08fec).
 * Orthogonal reduction of real symmetric matrix to
 * symmetric tridiagonal form
 */
nag_dsytrd(order, uplo, n, a, pda, d, e, tau, &fail);
if (fail.code != NE_NOERROR)
    {
        printf("Error from nag_dsytrd (f08fec).\n%s\n", fail.message);
        exit_status = 1;
    }

/* Copy A into Z using nag_dtr_copy (f16qec). */
nag_dtr_copy(order, uplo, Nag_NoTrans, Nag_NonUnitDiag, n, a, pda, z, pdz,
            &fail);
if (fail.code != NE_NOERROR)
    {
        printf("Error from dtr_copy.\n%s\n", fail.message);
        exit_status = 1;
        goto END;
    }

/* Form Q explicitly, storing the result in z using nag_dorgtr (f08ffc). */
nag_dorgtr(order, uplo, n, z, pdz, tau, &fail);
if (fail.code != NE_NOERROR)
    {
        printf("Error from nag_dorgtr (f08ffc).\n%s\n", fail.message);
        exit_status = 1;
        goto END;
    }

/* Calculate all the eigenvalues and eigenvectors of matrix A */
nag_dsteqr(order, Nag_UpdateZ, n, d, e, z, pdz, &fail);
if (fail.code != NE_NOERROR)
    {
        printf("Error from nag_dsteqr (f08jec).\n%s\n", fail.message);
        exit_status = 1;
        goto END;
    }

/* Normalize the eigenvectors */
for(j=1; j<=n; j++)
    {
        for(i=n; i>=1; i--)
            {
                Z(i, j) = Z(i, j) / Z(1,j);
            }
    }

/* Print eigenvalues and eigenvectors */
printf("Eigenvalues\n");
for (i = 1; i <= n; ++i)
    printf("%8.4f%s", d[i-1], i%8 == 0?"\n":" ");

```

```

printf("\n\n");

/* nag_gen_real_mat_print (x04cac).
 * Print real general matrix (easy-to-use)
 */
fflush(stdout);
nag_gen_real_mat_print(order, Nag_GeneralMatrix, Nag_NonUnitDiag, n, n,
                       z, pdz, "Eigenvectors", 0, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_gen_real_mat_print (x04cac).\n%s\n",
          fail.message);
    exit_status = 1;
    goto END;
}
END:
NAG_FREE(a);
NAG_FREE(d);
NAG_FREE(e);
NAG_FREE(tau);
NAG_FREE(z);

return exit_status;
}

```

10.2 Program Data

```

nag_dsytrd (f08fec) Example Program Data
4                               :Value of N
Nag_Lower                       :Value of UPLO
2.07
3.87 -0.21
4.20  1.87  1.15
-1.15  0.63  2.06 -1.81 :End of matrix A

```

10.3 Program Results

```

nag_dsytrd (f08fec) Example Program Results

```

```

Eigenvalues
-5.0034 -1.9987  0.2013  8.0008

Eigenvectors
      1      2      3      4
1      1.0000      1.0000      1.0000      1.0000
2      -0.6148     -3.4333      0.4489      0.6668
3      -0.8378      1.7553     -1.3572      0.8248
4      1.0219     -1.6052     -1.8213      0.0988

```
