

# NAG Library Function Document

## nag\_dgeev (f08nac)

### 1 Purpose

nag\_dgeev (f08nac) computes the eigenvalues and, optionally, the left and/or right eigenvectors for an  $n$  by  $n$  real nonsymmetric matrix  $A$ .

### 2 Specification

```
#include <nag.h>
#include <nagf08.h>
void nag_dgeev (Nag_OrderType order, Nag_LeftVecsType jobvl,
    Nag_RightVecsType jobvr, Integer n, double a[], Integer pda,
    double wr[], double wi[], double vl[], Integer pdvl, double vr[],
    Integer pdvr, NagError *fail)
```

### 3 Description

The right eigenvector  $v_j$  of  $A$  satisfies

$$Av_j = \lambda_j v_j$$

where  $\lambda_j$  is the  $j$ th eigenvalue of  $A$ . The left eigenvector  $u_j$  of  $A$  satisfies

$$u_j^H A = \lambda_j u_j^H$$

where  $u_j^H$  denotes the conjugate transpose of  $u_j$ .

The matrix  $A$  is first reduced to upper Hessenberg form by means of orthogonal similarity transformations, and the  $QR$  algorithm is then used to further reduce the matrix to upper quasi-triangular Schur form,  $T$ , with 1 by 1 and 2 by 2 blocks on the main diagonal. The eigenvalues are computed from  $T$ , the 2 by 2 blocks corresponding to complex conjugate pairs and, optionally, the eigenvectors of  $T$  are computed and backtransformed to the eigenvectors of  $A$ .

### 4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia <http://www.netlib.org/lapack/lug>

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

### 5 Arguments

1: **order** – Nag\_OrderType *Input*

*On entry:* the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag\_RowMajor. See Section 3.2.1.3 in the Essential Introduction for a more detailed explanation of the use of this argument.

*Constraint:* **order** = Nag\_RowMajor or Nag\_ColMajor.

2: **jobvl** – Nag\_LeftVecsType *Input*

*On entry:* if **jobvl** = Nag\_NotLeftVecs, the left eigenvectors of  $A$  are not computed.

If **jobvl** = Nag\_LeftVecs, the left eigenvectors of  $A$  are computed.

*Constraint:* **jobvl** = Nag\_NotLeftVecs or Nag\_LeftVecs.

3: **jobvr** – Nag\_RightVecsType *Input*

*On entry:* if **jobvr** = Nag\_NotRightVecs, the right eigenvectors of  $A$  are not computed.

If **jobvr** = Nag\_RightVecs, the right eigenvectors of  $A$  are computed.

*Constraint:* **jobvr** = Nag\_NotRightVecs or Nag\_RightVecs.

4: **n** – Integer *Input*

*On entry:*  $n$ , the order of the matrix  $A$ .

*Constraint:* **n**  $\geq 0$ .

5: **a**[*dim*] – double *Input/Output*

**Note:** the dimension, *dim*, of the array **a** must be at least  $\max(1, \text{pda} \times \mathbf{n})$ .

The  $(i, j)$ th element of the matrix  $A$  is stored in

$$\begin{aligned} \mathbf{a}[(j-1) \times \text{pda} + i - 1] &\text{ when } \mathbf{order} = \text{Nag\_ColMajor}; \\ \mathbf{a}[(i-1) \times \text{pda} + j - 1] &\text{ when } \mathbf{order} = \text{Nag\_RowMajor}. \end{aligned}$$

*On entry:* the  $n$  by  $n$  matrix  $A$ .

*On exit:* **a** has been overwritten.

6: **pda** – Integer *Input*

*On entry:* the stride separating row or column elements (depending on the value of **order**) in the array **a**.

*Constraint:* **pda**  $\geq \max(1, \mathbf{n})$ .

7: **wr**[*dim*] – double *Output*

8: **wi**[*dim*] – double *Output*

**Note:** the dimension, *dim*, of the arrays **wr** and **wi** must be at least  $\max(1, \mathbf{n})$ .

*On exit:* **wr** and **wi** contain the real and imaginary parts, respectively, of the computed eigenvalues. Complex conjugate pairs of eigenvalues appear consecutively with the eigenvalue having the positive imaginary part first.

9: **vl**[*dim*] – double *Output*

**Note:** the dimension, *dim*, of the array **vl** must be at least

$$\begin{aligned} \max(1, \text{pdvl} \times \mathbf{n}) &\text{ when } \mathbf{jobvl} = \text{Nag\_LeftVecs}; \\ 1 &\text{ otherwise.} \end{aligned}$$

Where **VL**( $i, j$ ) appears in this document, it refers to the array element

$$\begin{aligned} \mathbf{vl}[(j-1) \times \text{pdvl} + i - 1] &\text{ when } \mathbf{order} = \text{Nag\_ColMajor}; \\ \mathbf{vl}[(i-1) \times \text{pdvl} + j - 1] &\text{ when } \mathbf{order} = \text{Nag\_RowMajor}. \end{aligned}$$

*On exit:* if **jobvl** = Nag\_LeftVecs, the left eigenvectors  $u_j$  are stored one after another in **vl**, in the same order as their corresponding eigenvalues. If the  $j$ th eigenvalue is real, then  $u_j = \mathbf{VL}(i, j)$ , for  $i = 1, 2, \dots, \mathbf{n}$ . If the  $j$ th and  $(j+1)$ st eigenvalues form a complex conjugate pair, then  $u_j = \mathbf{VL}(i, j) + i \times \mathbf{VL}(i, j+1)$  and  $u_{j+1} = \mathbf{VL}(i, j) - i \times \mathbf{VL}(i, j+1)$ , for  $i = 1, 2, \dots, \mathbf{n}$ .

If **jobvl** = Nag\_NotLeftVecs, **vl** is not referenced.

10:	<b>pdvl</b> – Integer	<i>Input</i>
<i>On entry:</i> the stride separating row or column elements (depending on the value of <b>order</b> ) in the array <b>vl</b> .		
<i>Constraints:</i>		
	if <b>jobvl</b> = Nag_LeftVecs, <b>pdvl</b> $\geq \max(1, \mathbf{n})$ ; otherwise <b>pdvl</b> $\geq 1$ .	
11:	<b>vr</b> [ <i>dim</i> ] – double	<i>Output</i>
<b>Note:</b> the dimension, <i>dim</i> , of the array <b>vr</b> must be at least $\max(1, \mathbf{pdvr} \times \mathbf{n})$ when <b>jobvr</b> = Nag_RightVecs; 1 otherwise.		
Where <b>VR</b> ( <i>i</i> , <i>j</i> ) appears in this document, it refers to the array element $\mathbf{vr}[(j - 1) \times \mathbf{pdvr} + i - 1]$ when <b>order</b> = Nag_ColMajor; $\mathbf{vr}[(i - 1) \times \mathbf{pdvr} + j - 1]$ when <b>order</b> = Nag_RowMajor.		
<i>On exit:</i> if <b>jobvr</b> = Nag_RightVecs, the right eigenvectors $v_j$ are stored one after another in <b>vr</b> , in the same order as their corresponding eigenvalues. If the <i>j</i> th eigenvalue is real, then $v_j = \mathbf{VR}(i, j)$ , for $i = 1, 2, \dots, \mathbf{n}$ . If the <i>j</i> th and ( <i>j</i> + 1)st eigenvalues form a complex conjugate pair, then $v_j = \mathbf{VR}(i, j) + i \times \mathbf{VR}(i, j + 1)$ and $v_{j+1} = \mathbf{VR}(i, j) - i \times \mathbf{VR}(i, j + 1)$ , for $i = 1, 2, \dots, \mathbf{n}$ .		
If <b>jobvr</b> = Nag_NotRightVecs, <b>vr</b> is not referenced.		
12:	<b>pdvr</b> – Integer	<i>Input</i>
<i>On entry:</i> the stride separating row or column elements (depending on the value of <b>order</b> ) in the array <b>vr</b> .		
<i>Constraints:</i>		
	if <b>jobvr</b> = Nag_RightVecs, <b>pdvr</b> $\geq \max(1, \mathbf{n})$ ; otherwise <b>pdvr</b> $\geq 1$ .	
13:	<b>fail</b> – NagError *	<i>Input/Output</i>
The NAG error argument (see Section 3.6 in the Essential Introduction).		

## 6 Error Indicators and Warnings

### NE\_ALLOC\_FAIL

Dynamic memory allocation failed.

### NE\_BAD\_PARAM

On entry, argument  $\langle\text{value}\rangle$  had an illegal value.

### NE\_CONVERGENCE

The QR algorithm failed to compute all the eigenvalues, and no eigenvectors have been computed; elements  $\langle\text{value}\rangle$  to **n** of **wr** and **wi** contain eigenvalues which have converged.

### NE\_ENUM\_INT\_2

On entry, **jobvl** =  $\langle\text{value}\rangle$ , **pdvl** =  $\langle\text{value}\rangle$  and **n** =  $\langle\text{value}\rangle$ .

Constraint: if **jobvl** = Nag\_LeftVecs, **pdvl**  $\geq \max(1, \mathbf{n})$ ;  
otherwise **pdvl**  $\geq 1$ .

On entry, **jobvr** =  $\langle\text{value}\rangle$ , **pdvr** =  $\langle\text{value}\rangle$  and **n** =  $\langle\text{value}\rangle$ .

Constraint: if **jobvr** = Nag\_RightVecs, **pdvr**  $\geq \max(1, \mathbf{n})$ ;  
otherwise **pdvr**  $\geq 1$ .

**NE\_INT**

On entry, **n** =  $\langle value \rangle$ .

Constraint: **n**  $\geq 0$ .

On entry, **pda** =  $\langle value \rangle$ .

Constraint: **pda** > 0.

On entry, **pdvl** =  $\langle value \rangle$ .

Constraint: **pdvl** > 0.

On entry, **pdvr** =  $\langle value \rangle$ .

Constraint: **pdvr** > 0.

**NE\_INT\_2**

On entry, **pda** =  $\langle value \rangle$  and **n** =  $\langle value \rangle$ .

Constraint: **pda**  $\geq \max(1, n)$ .

**NE\_INTERNAL\_ERROR**

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

## 7 Accuracy

The computed eigenvalues and eigenvectors are exact for a nearby matrix  $(A + E)$ , where

$$\|E\|_2 = O(\epsilon)\|A\|_2,$$

and  $\epsilon$  is the *machine precision*. See Section 4.8 of Anderson *et al.* (1999) for further details.

## 8 Parallelism and Performance

`nag_dgeev` (f08nac) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

`nag_dgeev` (f08nac) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the Users' Note for your implementation for any additional implementation-specific information.

## 9 Further Comments

Each eigenvector is normalized to have Euclidean norm equal to unity and the element of largest absolute value real and positive.

The total number of floating-point operations is proportional to  $n^3$ .

The complex analogue of this function is `nag_zgeev` (f08nnc).

## 10 Example

This example finds all the eigenvalues and right eigenvectors of the matrix

$$A = \begin{pmatrix} 0.35 & 0.45 & -0.14 & -0.17 \\ 0.09 & 0.07 & -0.54 & 0.35 \\ -0.44 & -0.33 & -0.03 & 0.17 \\ 0.25 & -0.32 & -0.13 & 0.11 \end{pmatrix}.$$

## 10.1 Program Text

```

/* nag_dgeev (f08nac) Example Program.
*
* Copyright 2011 Numerical Algorithms Group.
*
* Mark 23, 2011.
*/
#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagf08.h>

int main(void)
{
    /* Scalars */
    Integer      i, j, n, pda, pdvr;
    Integer      exit_status = 0;

    /* Arrays */
    double       *a = 0, *vr = 0, *wi = 0, *wr = 0;
    double       dummy [1];

    /* Nag Types */
    NagError      fail;
    Nag_OrderType order;

#define NAG_COLUMN_MAJOR
#define A(I, J)  a[(J-1)*pda + I - 1]
#define VR(I, J) vr[(J)*pdvr + I]
    order = Nag_ColMajor;
#else
#define A(I, J)  a[(I-1)*pda + J - 1]
#define VR(I, J) vr[(I)*pdvr + J]
    order = Nag_RowMajor;
#endif

    INIT_FAIL(fail);

    printf("nag_dgeev (f08nac) Example Program Results\n");

    /* Skip heading in data file */
    scanf("%*[^\n]");
    scanf("%ld%*[^\n]", &n);
    if (n < 0)
    {
        printf("Invalid n\n");
        exit_status = 1;
        goto END;
    }

    pda = n;
    pdvr = n;
    /* Allocate memory */
    if (!(a = NAG_ALLOC(n * n, double)) ||
        !(vr = NAG_ALLOC(n * n, double)) ||
        !(wi = NAG_ALLOC(n, double)) ||
        !(wr = NAG_ALLOC(n, double)))
    {
        printf("Allocation failure\n");
        exit_status = -1;
        goto END;
    }

    /* Read the matrix A from data file */
    for (i = 1; i <= n; ++i)
        for (j = 1; j <= n; ++j) scanf("%lf", &a(i, j));
    scanf("%*[^\n]");
}

```

```

/* Compute the eigenvalues and right eigenvectors only of A
 * using nag_dgeev (f08nac).
 */
nag_dgeev(order, Nag_NotLeftVecs, Nag_RightVecs, n, a, pda, wr, wi,
           dummy, 1, vr, pdvr, &fail);

if (fail.code != NE_NOERROR)
{
    printf("Error from nag_dgeev (f08nac).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

/* Print eigenvalues and right eigenvectors. */
for (j = 0; j < n; ++j)
{
    printf("\nEigenvalue %3ld = ", j+1);
    if (wi[j] == 0.0)
        printf("%13.4e\n", wr[j]);
    else
        printf(" (%13.4e, %13.4e)\n", wr[j], wi[j]);

    printf("\nEigenvector %2ld\n", j+1);
    if (wi[j] == 0.0)
        for (i = 0; i < n; ++i) printf("%17s%13.4e\n", "", VR(i, j));
    else if (wi[j] > 0.0)
        for (i = 0; i < n; ++i)
            printf("%18s(%13.4e, %13.4e)\n", "", VR(i, j), VR(i, j+1));
    else
        for (i = 0; i < n; ++i)
            printf("%18s(%13.4e, %13.4e)\n", "", VR(i, j-1), -VR(i, j));
    printf("\n");
}

END:
NAG_FREE(a);
NAG_FREE(vr);
NAG_FREE(wi);
NAG_FREE(wr);

return exit_status;
}
#endif
#endif

```

## 10.2 Program Data

```

nag_dgeev (f08nac) Example Program Data

4 : n

0.35  0.45  -0.14  -0.17
0.09  0.07  -0.54   0.35
-0.44 -0.33  -0.03   0.17
0.25  -0.32  -0.13   0.11 : matrix A

```

## 10.3 Program Results

```

nag_dgeev (f08nac) Example Program Results

```

```

Eigenvalue 1 = 7.9948e-01

Eigenvector 1
              -6.5509e-01
              -5.2363e-01
               5.3622e-01
              -9.5607e-02

Eigenvalue 2 = (-9.9412e-02, 4.0079e-01)

```

```
Eigenvector 2
( -1.9330e-01,    2.5463e-01)
( 2.5186e-01,   -5.2240e-01)
( 9.7182e-02,   -3.0838e-01)
( 6.7595e-01,    0.0000e+00)

Eigenvalue 3 = ( -9.9412e-02,   -4.0079e-01)

Eigenvector 3
( -1.9330e-01,   -2.5463e-01)
( 2.5186e-01,    5.2240e-01)
( 9.7182e-02,    3.0838e-01)
( 6.7595e-01,   -0.0000e+00)

Eigenvalue 4 = -1.0066e-01

Eigenvector 4
1.2533e-01
3.3202e-01
5.9384e-01
7.2209e-01
```

---