

## NAG Library Function Document

### nag\_dspgv (f08tac)

## 1 Purpose

nag\_dspgv (f08tac) computes all the eigenvalues and, optionally, all the eigenvectors of a real generalized symmetric-definite eigenproblem, of the form

$$Az = \lambda Bz, \quad ABz = \lambda z \quad \text{or} \quad BAz = \lambda z,$$

where  $A$  and  $B$  are symmetric, stored in packed format, and  $B$  is also positive definite.

## 2 Specification

```
#include <nag.h>
#include <nagf08.h>
void nag_dspgv (Nag_OrderType order, Integer itype, Nag_JobType job,
    Nag_UptoType uplo, Integer n, double ap[], double bp[], double w[],
    double z[], Integer pdz, NagError *fail)
```

## 3 Description

nag\_dspgv (f08tac) first performs a Cholesky factorization of the matrix  $B$  as  $B = U^T U$ , when **uplo** = Nag\_Upper or  $B = LL^T$ , when **uplo** = Nag\_Lower. The generalized problem is then reduced to a standard symmetric eigenvalue problem

$$Cx = \lambda x,$$

which is solved for the eigenvalues and, optionally, the eigenvectors; the eigenvectors are then backtransformed to give the eigenvectors of the original problem.

For the problem  $Az = \lambda Bz$ , the eigenvectors are normalized so that the matrix of eigenvectors,  $Z$ , satisfies

$$Z^T AZ = \Lambda \quad \text{and} \quad Z^T BZ = I,$$

where  $\Lambda$  is the diagonal matrix whose diagonal elements are the eigenvalues. For the problem  $ABz = \lambda z$  we correspondingly have

$$Z^{-1} A Z^{-T} = \Lambda \quad \text{and} \quad Z^T B Z = I,$$

and for  $BAz = \lambda z$  we have

$$Z^T A Z = \Lambda \quad \text{and} \quad Z^T B^{-1} Z = I.$$

## 4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia <http://www.netlib.org/lapack/lug>

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

## 5 Arguments

1: **order** – Nag\_OrderType *Input*

*On entry:* the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag\_RowMajor. See Section 3.2.1.3 in the Essential Introduction for a more detailed explanation of the use of this argument.

*Constraint:* **order** = Nag\_RowMajor or Nag\_ColMajor.

2: **itype** – Integer *Input*

*On entry:* specifies the problem type to be solved.

**itype** = 1

$$Az = \lambda z.$$

**itype** = 2

$$ABz = \lambda z.$$

**itype** = 3

$$BAz = \lambda z.$$

*Constraint:* **itype** = 1, 2 or 3.

3: **job** – Nag\_JobType *Input*

*On entry:* indicates whether eigenvectors are computed.

**job** = Nag\_EigVals

Only eigenvalues are computed.

**job** = Nag\_DoBoth

Eigenvalues and eigenvectors are computed.

*Constraint:* **job** = Nag\_EigVals or Nag\_DoBoth.

4: **uplo** – Nag\_UptoType *Input*

*On entry:* if **uplo** = Nag\_Upper, the upper triangles of  $A$  and  $B$  are stored.

If **uplo** = Nag\_Lower, the lower triangles of  $A$  and  $B$  are stored.

*Constraint:* **uplo** = Nag\_Upper or Nag\_Lower.

5: **n** – Integer *Input*

*On entry:*  $n$ , the order of the matrices  $A$  and  $B$ .

*Constraint:* **n**  $\geq 0$ .

6: **ap**[*dim*] – double *Input/Output*

**Note:** the dimension, *dim*, of the array **ap** must be at least  $\max(1, n \times (n + 1)/2)$ .

*On entry:* the upper or lower triangle of the  $n$  by  $n$  symmetric matrix  $A$ , packed by rows or columns.

The storage of elements  $A_{ij}$  depends on the **order** and **uplo** arguments as follows:

if **order** = 'Nag\_ColMajor' and **uplo** = 'Nag\_Upper',

$A_{ij}$  is stored in **ap**[( $j - 1$ )  $\times$   $j/2 + i - 1$ ], for  $i \leq j$ ;

if **order** = 'Nag\_ColMajor' and **uplo** = 'Nag\_Lower',

$A_{ij}$  is stored in **ap**[( $2n - j$ )  $\times$   $(j - 1)/2 + i - 1$ ], for  $i \geq j$ ;

if **order** = 'Nag\_RowMajor' and **uplo** = 'Nag\_Upper',

$A_{ij}$  is stored in **ap**[( $2n - i$ )  $\times$   $(i - 1)/2 + j - 1$ ], for  $i \leq j$ ;

if **order** = 'Nag\_RowMajor' and **uplo** = 'Nag\_Lower',  
 $A_{ij}$  is stored in **ap** $[(i - 1) \times i/2 + j - 1]$ , for  $i \geq j$ .

On exit: the contents of **ap** are destroyed.

7: **bp**[*dim*] – double *Input/Output*

**Note:** the dimension, *dim*, of the array **bp** must be at least  $\max(1, \mathbf{n} \times (\mathbf{n} + 1)/2)$ .

On entry: the upper or lower triangle of the *n* by *n* symmetric matrix *B*, packed by rows or columns.

The storage of elements  $B_{ij}$  depends on the **order** and **uplo** arguments as follows:

if **order** = 'Nag\_ColMajor' and **uplo** = 'Nag\_Upper',  
 $B_{ij}$  is stored in **bp** $[(j - 1) \times j/2 + i - 1]$ , for  $i \leq j$ ;  
if **order** = 'Nag\_ColMajor' and **uplo** = 'Nag\_Lower',  
 $B_{ij}$  is stored in **bp** $[(2n - j) \times (j - 1)/2 + i - 1]$ , for  $i \geq j$ ;  
if **order** = 'Nag\_RowMajor' and **uplo** = 'Nag\_Upper',  
 $B_{ij}$  is stored in **bp** $[(2n - i) \times (i - 1)/2 + j - 1]$ , for  $i \leq j$ ;  
if **order** = 'Nag\_RowMajor' and **uplo** = 'Nag\_Lower',  
 $B_{ij}$  is stored in **bp** $[(i - 1) \times i/2 + j - 1]$ , for  $i \geq j$ .

On exit: the triangular factor *U* or *L* from the Cholesky factorization  $B = U^T U$  or  $B = LL^T$ , in the same storage format as *B*.

8: **w[n]** – double *Output*

On exit: the eigenvalues in ascending order.

9: **z[dim]** – double *Output*

**Note:** the dimension, *dim*, of the array **z** must be at least

$\max(1, \mathbf{pdz} \times \mathbf{n})$  when **job** = Nag\_DoBoth;  
1 otherwise.

The  $(i, j)$ th element of the matrix *Z* is stored in

**z** $[(j - 1) \times \mathbf{pdz} + i - 1]$  when **order** = Nag\_ColMajor;  
**z** $[(i - 1) \times \mathbf{pdz} + j - 1]$  when **order** = Nag\_RowMajor.

On exit: if **job** = Nag\_DoBoth, **z** contains the matrix *Z* of eigenvectors. The eigenvectors are normalized as follows:

if **itype** = 1 or 2,  $Z^T B Z = I$ ;

if **itype** = 3,  $Z^T B^{-1} Z = I$ .

If **job** = Nag\_EigVals, **z** is not referenced.

10: **pdz** – Integer *Input*

On entry: the stride separating row or column elements (depending on the value of **order**) in the array **z**.

*Constraints:*

if **job** = Nag\_DoBoth, **pdz**  $\geq \max(1, \mathbf{n})$ ;  
otherwise **pdz**  $\geq 1$ .

11: **fail** – NagError \* *Input/Output*

The NAG error argument (see Section 3.6 in the Essential Introduction).

## 6 Error Indicators and Warnings

### NE\_ALLOC\_FAIL

Dynamic memory allocation failed.

### NE\_BAD\_PARAM

On entry, argument  $\langle value \rangle$  had an illegal value.

### NE\_CONVERGENCE

The algorithm failed to converge;  $\langle value \rangle$  off-diagonal elements of an intermediate tridiagonal form did not converge to zero.

### NE\_ENUM\_INT\_2

On entry,  $\mathbf{job} = \langle value \rangle$ ,  $\mathbf{pdz} = \langle value \rangle$  and  $\mathbf{n} = \langle value \rangle$ .

Constraint: if  $\mathbf{job} = \text{Nag\_DoBoth}$ ,  $\mathbf{pdz} \geq \max(1, \mathbf{n})$ ;  
otherwise  $\mathbf{pdz} \geq 1$ .

### NE\_INT

On entry,  $\mathbf{itype} = \langle value \rangle$ .

Constraint:  $\mathbf{itype} = 1, 2$  or  $3$ .

On entry,  $\mathbf{n} = \langle value \rangle$ .

Constraint:  $\mathbf{n} \geq 0$ .

On entry,  $\mathbf{pdz} = \langle value \rangle$ .

Constraint:  $\mathbf{pdz} > 0$ .

### NE\_INTERNAL\_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

### NE\_MAT\_NOT\_POS\_DEF

If  $\mathbf{fail.errnum} = \mathbf{n} + \langle value \rangle$ , for  $1 \leq \langle value \rangle \leq \mathbf{n}$ , then the leading minor of order  $\langle value \rangle$  of  $B$  is not positive definite. The factorization of  $B$  could not be completed and no eigenvalues or eigenvectors were computed.

## 7 Accuracy

If  $B$  is ill-conditioned with respect to inversion, then the error bounds for the computed eigenvalues and vectors may be large, although when the diagonal elements of  $B$  differ widely in magnitude the eigenvalues and eigenvectors may be less sensitive than the condition of  $B$  would suggest. See Section 4.10 of Anderson *et al.* (1999) for details of the error bounds.

The example program below illustrates the computation of approximate error bounds.

## 8 Parallelism and Performance

`nag_dspgv` (f08tac) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

`nag_dspgv` (f08tac) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the Users' Note for your implementation for any additional implementation-specific information.

## 9 Further Comments

The total number of floating-point operations is proportional to  $n^3$ .

The complex analogue of this function is nag\_zhpgv (f08tnc).

## 10 Example

This example finds all the eigenvalues and eigenvectors of the generalized symmetric eigenproblem  $Az = \lambda Bz$ , where

$$A = \begin{pmatrix} 0.24 & 0.39 & 0.42 & -0.16 \\ 0.39 & -0.11 & 0.79 & 0.63 \\ 0.42 & 0.79 & -0.25 & 0.48 \\ -0.16 & 0.63 & 0.48 & -0.03 \end{pmatrix} \quad \text{and} \quad B = \begin{pmatrix} 4.16 & -3.12 & 0.56 & -0.10 \\ -3.12 & 5.03 & -0.83 & 1.09 \\ 0.56 & -0.83 & 0.76 & 0.34 \\ -0.10 & 1.09 & 0.34 & 1.18 \end{pmatrix},$$

together with an estimate of the condition number of  $B$ , and approximate error bounds for the computed eigenvalues and eigenvectors.

The example program for nag\_dspgvd (f08tcc) illustrates solving a generalized symmetric eigenproblem of the form  $ABz = \lambda z$ .

### 10.1 Program Text

```
/* nag_dspgv (f08tac) Example Program.
*
* Copyright 2011 Numerical Algorithms Group.
*
* Mark 23, 2011.
*/
#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagf07.h>
#include <nagf08.h>
#include <nagf16.h>
#include <nagx02.h>

int main(void)
{
    /* Scalars */
    double        anorm, bnorm, eps, rcond, rcondb, t1, t2;
    Integer       i, j, n;
    Integer       exit_status = 0;

    /* Arrays */
    double        *ap = 0, *bp = 0, *dummy = 0, *eerbnd = 0, *w = 0;
    char          nag_enum_arg[40];

    /* Nag Types */
    NagError      fail;
    Nag_OrderType order;
    Nag_UptoType  uplo;

#ifdef NAG_COLUMN_MAJOR
#define A_UPPER(I, J) ap[J*(J-1)/2 + I - 1]
#define A_LOWER(I, J) ap[(2*n-J)*(J-1)/2 + I - 1]
#define B_UPPER(I, J) bp[J*(J-1)/2 + I - 1]
#define B_LOWER(I, J) bp[(2*n-J)*(J-1)/2 + I - 1]
    order = Nag_ColMajor;
#else
#define A_UPPER(I, J) ap[(2*n-I)*(I-1)/2 + J - 1]
#define A_LOWER(I, J) ap[I*(I-1)/2 + J - 1]
#define B_UPPER(I, J) bp[(2*n-I)*(I-1)/2 + J - 1]
#define B_LOWER(I, J) bp[I*(I-1)/2 + J - 1]
    order = Nag_RowMajor;
#endif
}
```

```

INIT_FAIL(fail);

printf("nag_dspgv (f08tac) Example Program Results\n\n");

/* Skip heading in data file */
scanf("%*[^\n]");
scanf("%ld%*[^\n]", &n);
if (n < 0)
{
    printf("Invalid n\n");
    exit_status = 1;
    goto END;
}
scanf(" %39s%*[^\n]", nag_enum_arg);
/* nag_enum_name_to_value (x04nac).
 * Converts NAG enum member name to value
 */
uplo = (Nag_UplType) nag_enum_name_to_value(nag_enum_arg);

/* Allocate memory */
if (!(ap      = NAG_ALLOC(n*(n+1)/2, double)) ||
    !(bp      = NAG_ALLOC(n*(n+1)/2, double)) ||
    !(dummy   = NAG_ALLOC(1 * 1, double)) ||
    !(eerbnd = NAG_ALLOC(n, double)) ||
    !(w       = NAG_ALLOC(n, double)))
{
    printf("Allocation failure\n");
    exit_status = -1;
    goto END;
}

/* Read the triangular parts of the matrices A and B from data file. */
if (uplo == Nag_Upper)
{
    for (i = 1; i <= n; ++i)
        for (j = i; j <= n; ++j) scanf("%lf", &A_UPPER(i, j));
    scanf("%*[^\n]");
    for (i = 1; i <= n; ++i)
        for (j = i; j <= n; ++j) scanf("%lf", &B_UPPER(i, j));
}
else if (uplo == Nag_Lower)
{
    for (i = 1; i <= n; ++i)
        for (j = 1; j <= i; ++j) scanf("%lf", &A_LOWER(i, j));
    scanf("%*[^\n]");
    for (i = 1; i <= n; ++i)
        for (j = 1; j <= i; ++j) scanf("%lf", &B_LOWER(i, j));
}
scanf("%*[^\n]");

/* Compute the one-norms of the symmetric matrices A and B
 * using nag_dsp_norm (f16rdc).
 */
nag_dsp_norm(order, Nag_OneNorm, uplo, n, ap, &anorm, &fail);
nag_dsp_norm(order, Nag_OneNorm, uplo, n, bp, &bnorm, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_dsp_norm (f16rdc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

/* Solve the generalized symmetric eigenvalue problem A*x = lambda*B*x
 * using nag_dspgv (f08tac).
 */
nag_dspgv(order, 1, Nag_EigVals, uplo, n, ap, bp, w, dummy, 1, &fail);

if (fail.code != NE_NOERROR)
{
    printf("Error from nag_dspgv (f08tac).\n%s\n", fail.message);
}

```

```

    exit_status = 1;
    goto END;
}

/* Print solution */
printf("Eigenvalues\n  ");
for (j = 0; j < n; ++j) printf(" %11.4f%s", w[j], j%6 == 5?"\n":"");
printf("\n");

/* Estimate the reciprocal condition number of the Cholesky factor of B.
 * nag_dtpcon (f07ugc)
 * Note that: cond(B) = 1/(rcond*rcond).
 */
nag_dtpcon(order, Nag_OneNorm, uplo, Nag_NonUnitDiag, n, bp, &rcond, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_dtpcon (f07ugc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

/* Print the reciprocal condition number of B */
rcondb = rcond * rcond;
printf("\nEstimate of reciprocal condition number for B\n      %11.1e\n",
       rcondb);

/* Get the machine precision, using nag_machine_precision (x02ajc) */
eps = nag_machine_precision;
if (rcond < eps)
{
    printf("\nB is very ill-conditioned, error estimates have not been "
           "computed\n");
}
t1 = eps / rcondb;
t2 = anorm / bnorm;
for (i = 0; i < n; ++i) eerbnd[i] = t1 * (t2 + abs(w[i]));

/* Print the approximate error bounds for the eigenvalues */
printf("\nError estimates for the eigenvalues\n  ");
for (i = 0; i < n; ++i) printf(" %11.1e%s", eerbnd[i], i%6 == 5?"\n":"");
printf("\n");

END:
NAG_FREE(ap);
NAG_FREE(bp);
NAG_FREE(dummy);
NAG_FREE(eerbnd);
NAG_FREE(w);

return exit_status;
}

```

## 10.2 Program Data

nag\_dspgv (f08tac) Example Program Data

```

4                      : n

Nag_Upper              : uplo

0.24    0.39    0.42   -0.16
     -0.11    0.79    0.63
     -0.25    0.48
     -0.03 : matrix A

4.16   -3.12    0.56   -0.10
      5.03   -0.83    1.09
      0.76    0.34
      1.18 : matrix B

```

### 10.3 Program Results

```
nag_dspgv (f08tac) Example Program Results

Eigenvalues
      -2.2254      -0.4548       0.1001      1.1270

Estimate of reciprocal condition number for B
      5.8e-03

Error estimates for the eigenvalues
      4.2e-14      3.7e-15      3.7e-15      2.3e-14
```

---