

NAG Library Function Document

nag_zhpgvd (f08tqc)

1 Purpose

nag_zhpgvd (f08tqc) computes all the eigenvalues and, optionally, the eigenvectors of a complex generalized Hermitian-definite eigenproblem, of the form

$$Az = \lambda Bz, \quad ABz = \lambda z \quad \text{or} \quad BAz = \lambda z,$$

where A and B are Hermitian, stored in packed format, and B is also positive definite. If eigenvectors are desired, it uses a divide-and-conquer algorithm.

2 Specification

```
#include <nag.h>
#include <nagf08.h>

void nag_zhpgvd (Nag_OrderType order, Integer itype, Nag_JobType job,
                Nag_UploType uplo, Integer n, Complex ap[], Complex bp[], double w[],
                Complex z[], Integer pdz, NagError *fail)
```

3 Description

nag_zhpgvd (f08tqc) first performs a Cholesky factorization of the matrix B as $B = U^H U$, when **uplo** = Nag_Upper or $B = LL^H$, when **uplo** = Nag_Lower. The generalized problem is then reduced to a standard symmetric eigenvalue problem

$$Cx = \lambda x,$$

which is solved for the eigenvalues and, optionally, the eigenvectors; the eigenvectors are then backtransformed to give the eigenvectors of the original problem.

For the problem $Az = \lambda Bz$, the eigenvectors are normalized so that the matrix of eigenvectors, z , satisfies

$$Z^H A Z = \Lambda \quad \text{and} \quad Z^H B Z = I,$$

where Λ is the diagonal matrix whose diagonal elements are the eigenvalues. For the problem $ABz = \lambda z$ we correspondingly have

$$Z^{-1} A Z^{-H} = \Lambda \quad \text{and} \quad Z^H B Z = I,$$

and for $BAz = \lambda z$ we have

$$Z^H A Z = \Lambda \quad \text{and} \quad Z^H B^{-1} Z = I.$$

4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia <http://www.netlib.org/lapack/lug>

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

5 Arguments

- 1: **order** – Nag_OrderType *Input*
On entry: the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag_RowMajor. See Section 3.2.1.3 in the Essential Introduction for a more detailed explanation of the use of this argument.
Constraint: **order** = Nag_RowMajor or Nag_ColMajor.
- 2: **itype** – Integer *Input*
On entry: specifies the problem type to be solved.
itype = 1
 $Az = \lambda Bz.$
itype = 2
 $ABz = \lambda z.$
itype = 3
 $BAz = \lambda z.$
Constraint: **itype** = 1, 2 or 3.
- 3: **job** – Nag_JobType *Input*
On entry: indicates whether eigenvectors are computed.
job = Nag_EigVals
 Only eigenvalues are computed.
job = Nag_DoBoth
 Eigenvalues and eigenvectors are computed.
Constraint: **job** = Nag_EigVals or Nag_DoBoth.
- 4: **uplo** – Nag_UploType *Input*
On entry: if **uplo** = Nag_Upper, the upper triangles of A and B are stored.
 If **uplo** = Nag_Lower, the lower triangles of A and B are stored.
Constraint: **uplo** = Nag_Upper or Nag_Lower.
- 5: **n** – Integer *Input*
On entry: n , the order of the matrices A and B .
Constraint: $n \geq 0$.
- 6: **ap**[*dim*] – Complex *Input/Output*
Note: the dimension, *dim*, of the array **ap** must be at least $\max(1, \mathbf{n} \times (\mathbf{n} + 1)/2)$.
On entry: the upper or lower triangle of the n by n Hermitian matrix A , packed by rows or columns.
 The storage of elements A_{ij} depends on the **order** and **uplo** arguments as follows:
 if **order** = 'Nag_ColMajor' and **uplo** = 'Nag_Upper',
 A_{ij} is stored in **ap**[($j - 1$) \times $j/2 + i - 1$], for $i \leq j$;
 if **order** = 'Nag_ColMajor' and **uplo** = 'Nag_Lower',
 A_{ij} is stored in **ap**[($2n - j$) \times ($j - 1$)/2 + $i - 1$], for $i \geq j$;
 if **order** = 'Nag_RowMajor' and **uplo** = 'Nag_Upper',
 A_{ij} is stored in **ap**[($2n - i$) \times ($i - 1$)/2 + $j - 1$], for $i \leq j$;

if **order** = 'Nag_RowMajor' and **uplo** = 'Nag_Lower',
 A_{ij} is stored in **ap** $[(i - 1) \times i/2 + j - 1]$, for $i \geq j$.

On exit: the contents of **ap** are destroyed.

7: **bp** $[dim]$ – Complex *Input/Output*

Note: the dimension, dim , of the array **bp** must be at least $\max(1, n \times (n + 1)/2)$.

On entry: the upper or lower triangle of the n by n Hermitian matrix B , packed by rows or columns.

The storage of elements B_{ij} depends on the **order** and **uplo** arguments as follows:

if **order** = 'Nag_ColMajor' and **uplo** = 'Nag_Upper',
 B_{ij} is stored in **bp** $[(j - 1) \times j/2 + i - 1]$, for $i \leq j$;
 if **order** = 'Nag_ColMajor' and **uplo** = 'Nag_Lower',
 B_{ij} is stored in **bp** $[(2n - j) \times (j - 1)/2 + i - 1]$, for $i \geq j$;
 if **order** = 'Nag_RowMajor' and **uplo** = 'Nag_Upper',
 B_{ij} is stored in **bp** $[(2n - i) \times (i - 1)/2 + j - 1]$, for $i \leq j$;
 if **order** = 'Nag_RowMajor' and **uplo** = 'Nag_Lower',
 B_{ij} is stored in **bp** $[(i - 1) \times i/2 + j - 1]$, for $i \geq j$.

On exit: the triangular factor U or L from the Cholesky factorization $B = U^H U$ or $B = LL^H$, in the same storage format as B .

8: **w** $[n]$ – double *Output*

On exit: the eigenvalues in ascending order.

9: **z** $[dim]$ – Complex *Output*

Note: the dimension, dim , of the array **z** must be at least

$\max(1, \mathbf{pdz} \times \mathbf{n})$ when **job** = Nag_DoBoth;
 1 otherwise.

The (i, j) th element of the matrix Z is stored in

z $[(j - 1) \times \mathbf{pdz} + i - 1]$ when **order** = Nag_ColMajor;
z $[(i - 1) \times \mathbf{pdz} + j - 1]$ when **order** = Nag_RowMajor.

On exit: if **job** = Nag_DoBoth, **z** contains the matrix Z of eigenvectors. The eigenvectors are normalized as follows:

if **itype** = 1 or 2, $Z^H B Z = I$;
 if **itype** = 3, $Z^H B^{-1} Z = I$.

If **job** = Nag_EigVals, **z** is not referenced.

10: **pdz** – Integer *Input*

On entry: the stride separating row or column elements (depending on the value of **order**) in the array **z**.

Constraints:

if **job** = Nag_DoBoth, $\mathbf{pdz} \geq \max(1, \mathbf{n})$;
 otherwise $\mathbf{pdz} \geq 1$.

11: **fail** – NagError * *Input/Output*

The NAG error argument (see Section 3.6 in the Essential Introduction).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

NE_BAD_PARAM

On entry, argument $\langle value \rangle$ had an illegal value.

NE_CONVERGENCE

The algorithm failed to converge; $\langle value \rangle$ off-diagonal elements of an intermediate tridiagonal form did not converge to zero.

NE_ENUM_INT_2

On entry, $\mathbf{job} = \langle value \rangle$, $\mathbf{pdz} = \langle value \rangle$ and $\mathbf{n} = \langle value \rangle$.
Constraint: if $\mathbf{job} = \text{Nag_DoBoth}$, $\mathbf{pdz} \geq \max(1, \mathbf{n})$;
otherwise $\mathbf{pdz} \geq 1$.

NE_INT

On entry, $\mathbf{itype} = \langle value \rangle$.
Constraint: $\mathbf{itype} = 1, 2$ or 3 .

On entry, $\mathbf{n} = \langle value \rangle$.
Constraint: $\mathbf{n} \geq 0$.

On entry, $\mathbf{pdz} = \langle value \rangle$.
Constraint: $\mathbf{pdz} > 0$.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

NE_MAT_NOT_POS_DEF

If $\mathbf{fail.errno} = \mathbf{n} + \langle value \rangle$, for $1 \leq \langle value \rangle \leq \mathbf{n}$, then the leading minor of order $\langle value \rangle$ of B is not positive definite. The factorization of B could not be completed and no eigenvalues or eigenvectors were computed.

7 Accuracy

If B is ill-conditioned with respect to inversion, then the error bounds for the computed eigenvalues and vectors may be large, although when the diagonal elements of B differ widely in magnitude the eigenvalues and eigenvectors may be less sensitive than the condition of B would suggest. See Section 4.10 of Anderson *et al.* (1999) for details of the error bounds.

The example program below illustrates the computation of approximate error bounds.

8 Parallelism and Performance

`nag_zhpgvd` (f08tqc) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

`nag_zhpgvd` (f08tqc) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

The total number of floating-point operations is proportional to n^3 .

The real analogue of this function is nag_dspgvd (f08tcc).

10 Example

This example finds all the eigenvalues and eigenvectors of the generalized Hermitian eigenproblem $ABz = \lambda z$, where

$$A = \begin{pmatrix} -7.36 & 0.77 - 0.43i & -0.64 - 0.92i & 3.01 - 6.97i \\ 0.77 + 0.43i & 3.49 & 2.19 + 4.45i & 1.90 + 3.73i \\ -0.64 + 0.92i & 2.19 - 4.45i & 0.12 & 2.88 - 3.17i \\ 3.01 + 6.97i & 1.90 - 3.73i & 2.88 + 3.17i & -2.54 \end{pmatrix}$$

and

$$B = \begin{pmatrix} 3.23 & 1.51 - 1.92i & 1.90 + 0.84i & 0.42 + 2.50i \\ 1.51 + 1.92i & 3.58 & -0.23 + 1.11i & -1.18 + 1.37i \\ 1.90 - 0.84i & -0.23 - 1.11i & 4.09 & 2.33 - 0.14i \\ 0.42 - 2.50i & -1.18 - 1.37i & 2.33 + 0.14i & 4.29 \end{pmatrix},$$

together with an estimate of the condition number of B , and approximate error bounds for the computed eigenvalues and eigenvectors.

The example program for nag_zhpgv (f08tnc) illustrates solving a generalized Hermitian eigenproblem of the form $Az = \lambda Bz$.

10.1 Program Text

```

/* nag_zhpgvd (f08tqc) Example Program.
 *
 * Copyright 2011 Numerical Algorithms Group.
 *
 * Mark 23, 2011.
 */

#include <stdio.h>
#include <math.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagf07.h>
#include <nagf08.h>
#include <nagf16.h>
#include <nagx02.h>

int main(void)
{
    /* Scalars */
    double      anorm, bnorm, eps, rcond, rcondb, t1;
    Integer     i, j, n;
    Integer     exit_status = 0;
    /* Arrays */
    Complex     *ap = 0, *bp = 0;
    Complex     dummy[1];
    double      *eerbnd = 0, *w = 0;
    char        nag_enum_arg[40];

    /* Nag Types */
    NagError    fail;
    Nag_OrderType order;
    Nag_UploType uplo;

#ifdef NAG_COLUMN_MAJOR
#define A_UPPER(I, J) ap[J*(J-1)/2 + I - 1]
#define A_LOWER(I, J) ap[(2*n-J)*(J-1)/2 + I - 1]
#define B_UPPER(I, J) bp[J*(J-1)/2 + I - 1]

```

```

#define B_LOWER(I, J) bp[(2*n-J)*(J-1)/2 + I - 1]
    order = Nag_ColMajor;
#else
#define A_UPPER(I, J) ap[(2*n-I)*(I-1)/2 + J - 1]
#define A_LOWER(I, J) ap[I*(I-1)/2 + J - 1]
#define B_UPPER(I, J) bp[(2*n-I)*(I-1)/2 + J - 1]
#define B_LOWER(I, J) bp[I*(I-1)/2 + J - 1]
    order = Nag_RowMajor;
#endif

    INIT_FAIL(fail);

    printf("nag_zhpgvd (f08tqc) Example Program Results\n\n");

    /* Skip heading in data file */
    scanf("%*[\n]");
    scanf("%ld%*[\n]", &n);
    if (n < 0)
    {
        printf("Invalid n\n");
        exit_status = 1;
        goto END;;
    }
    scanf(" %39s%*[\n]", nag_enum_arg);
    /* nag_enum_name_to_value (x04nac).
    * Converts NAG enum member name to value
    */
    uplo = (Nag_UploType) nag_enum_name_to_value(nag_enum_arg);

    /* Allocate memory */
    if (!(ap = NAG_ALLOC(n*(n+1)/2, Complex)) ||
        !(bp = NAG_ALLOC(n*(n+1)/2, Complex)) ||
        !(eerbnd = NAG_ALLOC(n, double)) ||
        !(w = NAG_ALLOC(n, double)))
    {
        printf("Allocation failure\n");
        exit_status = -1;
        goto END;
    }

    /* Read the triangular parts of the matrices A and B from data file. */
    if (uplo == Nag_Upper)
    {
        for (i = 1; i <= n; ++i)
            for (j = i; j <= n; ++j)
                scanf(" ( %lf , %lf )", &A_UPPER(i, j).re, &A_UPPER(i, j).im);
        scanf("%*[\n]");
        for (i = 1; i <= n; ++i)
            for (j = i; j <= n; ++j)
                scanf(" ( %lf , %lf )", &B_UPPER(i, j).re, &B_UPPER(i, j).im);
    }
    else if (uplo == Nag_Lower)
    {
        for (i = 1; i <= n; ++i)
            for (j = 1; j <= i; ++j)
                scanf(" ( %lf , %lf )", &A_LOWER(i, j).re, &A_LOWER(i, j).im);
        scanf("%*[\n]");
        for (i = 1; i <= n; ++i)
            for (j = 1; j <= i; ++j)
                scanf(" ( %lf , %lf )", &B_LOWER(i, j).re, &B_LOWER(i, j).im);
    }
    scanf("%*[\n]");

    /* Compute the one-norms of the symmetric matrices A and B
    * using nag_zhp_norm (f16udc).
    */
    nag_zhp_norm(order, Nag_OneNorm, uplo, n, ap, &anorm, &fail);
    nag_zhp_norm(order, Nag_OneNorm, uplo, n, bp, &bnorm, &fail);
    if (fail.code != NE_NOERROR)
    {

```

```

    printf("Error from nag_zhp_norm (f16udc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

/* Solve the generalized symmetric eigenvalue problem
 * A*B*x = lambda*x (itype = 2) using nag_zhpgvd (f08tqc).
 */
nag_zhpgvd(order, 2, Nag_EigVals, uplo, n, ap, bp, w, dummy, 1, &fail);

if (fail.code != NE_NOERROR)
{
    printf("Error from nag_zhpgvd (f08tqc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

/* Print eigensolution */
printf("Eigenvalues\n    ");
for (j = 0; j < n; ++j) printf(" %11.4f%s", w[j], j%6 == 5?"\n":""");
printf("\n\n");

/* Estimate the reciprocal condition number of the Cholesky factor of B.
 * nag_ztpcon (f07uuc).
 * Note that: cond(B) = 1/(rcond*rcond).
 */
nag_ztpcon(order, Nag_OneNorm, uplo, Nag_NonUnitDiag, n, bp, &rcond, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_ztpcon (f07uuc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

/* Print the reciprocal condition number of B */
rcondb = rcond * rcond;
printf("Estimate of reciprocal condition number for B\n    %12.1e\n", rcondb);

/* Get the machine precision, using nag_machine_precision (x02ajc) */
eps = nag_machine_precision;
if (rcond < eps)
{
    printf("\nB is very ill-conditioned, error estimates have not been"
          " computed.\n");
    goto END;
}

t1 = anorm * bnorm;
for (i = 0; i < n; ++i) eerbnd[i] = eps * (t1 + fabs(w[i])/ rcondb);

/* Print the approximate error bounds for the eigenvalues */
printf("\nError estimates for the eigenvalues\n    ");
for (i = 0; i < n; ++i) printf(" %11.1e%s", eerbnd[i], i%6 == 5?"\n":""");
printf("\n");

END:
NAG_FREE(ap);
NAG_FREE(bp);
NAG_FREE(eerbnd);
NAG_FREE(w);

return exit_status;
}

```

10.2 Program Data

nag_zhpgvd (f08tqc) Example Program Data

```

4 : n
Nag_Upper : uplo
(-7.36, 0.00) ( 0.77, -0.43) (-0.64, -0.92) ( 3.01, -6.97)
           ( 3.49, 0.00) ( 2.19, 4.45) ( 1.90, 3.73)
           ( 0.12, 0.00) ( 2.88, -3.17)
           (-2.54, 0.00) : matrix A
( 3.23, 0.00) ( 1.51, -1.92) ( 1.90, 0.84) ( 0.42, 2.50)
           ( 3.58, 0.00) (-0.23, 1.11) (-1.18, 1.37)
           ( 4.09, 0.00) ( 2.33, -0.14)
           ( 4.29, 0.00) : matrix B

```

10.3 Program Results

nag_zhpgvd (f08tqc) Example Program Results

```

Eigenvalues
  -61.7321    -6.6195     0.0725    43.1883
Estimate of reciprocal condition number for B
  2.5e-03
Error estimates for the eigenvalues
  2.7e-12    3.1e-13    2.6e-14    1.9e-12

```
