

NAG Library Function Document

nag_best_subset_given_size_revcomm (h05aac)

1 Purpose

Given a set of m features and a scoring mechanism for any subset of those features, `nag_best_subset_given_size_revcomm` (h05aac) selects the best n subsets of size p using a reverse communication branch and bound algorithm.

2 Specification

```
#include <nag.h>
#include <nagh.h>

void nag_best_subset_given_size_revcomm (Integer *irevcm, Integer mincr,
    Integer m, Integer ip, Integer nbest, Integer *drop, Integer *lz,
    Integer z[], Integer *la, Integer a[], double bscore[], Integer bz[],
    Integer mincnt, double gamma, const double acc[], Integer icomm[],
    Integer licomm, double rcomm[], Integer lrcomm, NagError *fail)
```

3 Description

Given $\Omega = \{x_i : i \in \mathbb{Z}, 1 \leq i \leq m\}$, a set of m unique features and a scoring mechanism $f(S)$ defined for all $S \subseteq \Omega$ then `nag_best_subset_given_size_revcomm` (h05aac) is designed to find $S_{o1} \subseteq \Omega, |S_{o1}| = p$, an optimal subset of size p . Here $|S_{o1}|$ denotes the cardinality of S_{o1} , the number of elements in the set.

The definition of the optimal subset depends on the properties of the scoring mechanism, if

$$f(S_i) \leq f(S_j), \quad \text{for all } S_j \subseteq \Omega \text{ and } S_i \subseteq S_j \quad (1)$$

then the optimal subset is defined as one of the solutions to

$$\underset{S \subseteq \Omega}{\text{maximize}} f(S) \quad \text{subject to} \quad |S| = p$$

else if

$$f(S_i) \geq f(S_j), \quad \text{for all } S_j \subseteq \Omega \text{ and } S_i \subseteq S_j \quad (2)$$

then the optimal subset is defined as one of the solutions to

$$\underset{S \subseteq \Omega}{\text{minimize}} f(S) \quad \text{subject to} \quad |S| = p.$$

If neither of these properties hold then `nag_best_subset_given_size_revcomm` (h05aac) cannot be used.

As well as returning the optimal subset, S_{o1} , `nag_best_subset_given_size_revcomm` (h05aac) can return the best n solutions of size p . If S_{oi} denotes the i th best subset, for $i = 1, 2, \dots, n-1$, then the $(i+1)$ th best subset is defined as the solution to either

$$\underset{S \subseteq \Omega - \{S_{oj} : j \in \mathbb{Z}, 1 \leq j \leq i\}}{\text{maximize}} f(S) \quad \text{subject to} \quad |S| = p$$

or

$$\underset{S \subseteq \Omega - \{S_{oj} : j \in \mathbb{Z}, 1 \leq j \leq i\}}{\text{minimize}} f(S) \quad \text{subject to} \quad |S| = p$$

depending on the properties of f .

The solutions are found using a branch and bound method, where each node of the tree is a subset of Ω . Assuming that (1) holds then a particular node, defined by subset S_i , can be trimmed from the tree if $f(S_i) < \hat{f}(S_{on})$ where $\hat{f}(S_{on})$ is the n th highest score we have observed so far for a subset of size p ,

i.e., our current best guess of the score for the n th best subset. In addition, because of (1) we can also drop all nodes defined by any subset S_j where $S_j \subseteq S_i$, thus avoiding the need to enumerate the whole tree. Similar short cuts can be taken if (2) holds. A full description of this branch and bound algorithm can be found in Ridout (1988).

Rather than calculate the score at a given node of the tree `nag_best_subset_given_size_revcomm` (h05aac) utilizes the fast branch and bound algorithm of Somol *et al.* (2004), and attempts to estimate the score where possible. For each feature, x_i , two values are stored, a count c_i and $\hat{\mu}_i$, an estimate of the contribution of that feature. An initial value of zero is used for both c_i and $\hat{\mu}_i$. At any stage of the algorithm where both $f(S)$ and $f(S - \{x_i\})$ have been calculated (as opposed to estimated), the estimated contribution of the feature x_i is updated to

$$\frac{c_i \hat{\mu}_i + [f(S) - f(S - \{x_i\})]}{c_i + 1}$$

and c_i is incremented by 1, therefore at each stage $\hat{\mu}_i$ is the mean contribution of x_i observed so far and c_i is the number of observations used to calculate that mean.

As long as $c_i \geq k$, for the user-supplied constant k , then rather than calculating $f(S - \{x_i\})$ this function estimates it using $\hat{f}(S - \{x_i\}) = f(S) - \gamma \hat{\mu}_i$ or $\hat{f}(S) - \gamma \hat{\mu}_i$ if $f(S)$ has been estimated, where γ is a user-supplied scaling factor. An estimated score is never used to trim a node or returned as the optimal score.

Setting $k = 0$ in this function will cause the algorithm to always calculate the scores, returning to the branch and bound algorithm of Ridout (1988). In most cases it is preferable to use the fast branch and bound algorithm, by setting $k > 0$, unless the score function is iterative in nature, i.e., $f(S)$ must have been calculated before $f(S - \{x_i\})$ can be calculated.

4 References

- Narendra P M and Fukunaga K (1977) A branch and bound algorithm for feature subset selection *IEEE Transactions on Computers* **9** 917–922
- Ridout M S (1988) Algorithm AS 233: An improved branch and bound algorithm for feature subset selection *Journal of the Royal Statistics Society, Series C (Applied Statistics) (Volume 37)* **1** 139–147
- Somol P, Pudil P and Kittler J (2004) Fast branch and bound algorithms for optimal feature selection *IEEE Transactions on Pattern Analysis and Machine Intelligence (Volume 26)* **7** 900–912

5 Arguments

Note: this function uses **reverse communication**. Its use involves an initial entry, intermediate exits and re-entries, and a final exit, as indicated by the argument **irevcm**. Between intermediate exits and re-entries, **all arguments other than bscore must remain unchanged**.

1: **irevcm** – Integer * *Input/Output*

On initial entry: must be set to 0.

On intermediate exit: **irevcm** = 1 and before re-entry the scores associated with **la** subsets must be calculated and returned in **bscore**.

The **la** subsets are constructed as follows:

drop = 1

The j th subset is constructed by *dropping* the features specified in the first **lz** elements of **z** and the single feature given in **a**[$j - 1$] from the full set of features, Ω . The subset will therefore contain **m** – **lz** – 1 features.

drop = 0

The j th subset is constructed by *adding* the features specified in the first **lz** elements of **z** and the single feature specified in **a**[$j - 1$] to the empty set, \emptyset . The subset will therefore contain **lz** + 1 features.

In both cases the individual features are referenced by the integers 1 to **m** with 1 indicating the first feature, 2 the second, etc., for some arbitrary ordering of the features. The same ordering must be used in all calls to `nag_best_subset_given_size_revcomm` (h05aac).

If **la** = 0, the score for a single subset should be returned. This subset is constructed by adding or removing only those features specified in the first **lz** elements of **z**.

If **lz** = 0, this subset will either be Ω or \emptyset .

The score associated with the *j*th subset must be returned in **bscore**[*j* – 1].

On intermediate re-entry: **irevcm** must remain unchanged.

On final exit: **irevcm** = 0, and the algorithm has terminated.

Constraint: **irevcm** = 0 or 1.

2: **mincr** – Integer *Input*

On entry: flag indicating whether the scoring function *f* is increasing or decreasing.

mincr = 1

$f(S_i) \leq f(S_j)$, i.e., the subsets with the largest score will be selected.

mincr = 0

$f(S_i) \geq f(S_j)$, i.e., the subsets with the smallest score will be selected.

For all $S_j \subseteq \Omega$ and $S_i \subseteq S_j$.

Constraint: **mincr** = 0 or 1.

3: **m** – Integer *Input*

On entry: *m*, the number of features in the full feature set.

Constraint: **m** ≥ 2.

4: **ip** – Integer *Input*

On entry: *p*, the number of features in the subset of interest.

Constraint: 1 ≤ **ip** ≤ **m**.

5: **nbest** – Integer *Input*

On entry: *n*, the maximum number of best subsets required. The actual number of subsets returned is given by **la** on final exit. If on final exit **la** ≠ **nbest** then **fail.code** = NE_TOO_MANY is returned.

Constraint: **nbest** ≥ 1.

6: **drop** – Integer * *Input/Output*

On initial entry: **drop** need not be set.

On intermediate exit: flag indicating whether the intermediate subsets should be constructed by dropping features from the full set (**drop** = 1) or adding features to the empty set (**drop** = 0). See **irevcm** for details.

On intermediate re-entry: **drop** must remain unchanged.

On final exit: **drop** is undefined.

7: **lz** – Integer * *Input/Output*

On initial entry: **lz** need not be set.

On intermediate exit: the number of features stored in **z**.

On intermediate re-entry: **lz** must remain unchanged.

- On final exit:* **lz** is undefined.
- 8: **z**[**m** – **ip**] – Integer *Input/Output*
On initial entry: **z** need not be set.
On intermediate exit: **z**[$i - 1$], for $i = 1, 2, \dots, \mathbf{la}$, contains the list of features which, along with those specified in **a**, define the subsets whose score is required. See **irevcn** for additional details.
On intermediate re-entry: **z** must remain unchanged.
On final exit: **z** is undefined.
- 9: **la** – Integer * *Input/Output*
On initial entry: **la** need not be set.
On intermediate exit: if **la** > 0, the number of subsets for which a score must be returned.
 If **la** = 0, the score for a single subset should be returned. See **irevcn** for additional details.
On intermediate re-entry: **la** must remain unchanged.
On final exit: the number of best subsets returned.
- 10: **a**[**max**(**nbest**, **m**)] – Integer *Input/Output*
On initial entry: **a** need not be set.
On intermediate exit: **a**[$j - 1$], for $j = 1, 2, \dots, \mathbf{la}$, contains the list of features which, along with those specified in **z**, define the subsets whose score is required. See **irevcn** for additional details.
On intermediate re-entry: **a** must remain unchanged.
On final exit: **a** is undefined.
- 11: **bscore**[**max**(**nbest**, **m**)] – double *Input/Output*
On initial entry: **bscore** need not be set.
On intermediate exit: **bscore** is undefined.
On intermediate re-entry: **bscore**[$j - 1$] must hold the score for the j th subset as described in **irevcn**.
On final exit: holds the score for the **la** best subsets returned in **bz**.
- 12: **bz**[(**m** – **ip**) × **nbest**] – Integer *Input/Output*
Note: where **BZ**(i, j) appears in this document, it refers to the array element **bz**[($j - 1$) × (**m** – **ip**) + $i - 1$].
On initial entry: **bz** need not be set.
On intermediate exit: **bz** is used for storage between calls to nag_best_subset_given_size_revcomm (h05aac).
On intermediate re-entry: **bz** must remain unchanged.
On final exit: the j th best subset is constructed by dropping the features specified in **BZ**(i, j), for $i = 1, 2, \dots, \mathbf{m} - \mathbf{ip}$ and $j = 1, 2, \dots, \mathbf{la}$, from the set of all features, Ω . The score for the j th best subset is given in **bscore**[$j - 1$].
- 13: **mincnt** – Integer *Input*
On entry: k , the minimum number of times the effect of each feature, x_i , must have been observed before $f(S - \{x_i\})$ is estimated from $f(S)$ as opposed to being calculated directly.
 If $k = 0$ then $f(S - \{x_i\})$ is never estimated. If **mincnt** < 0 then k is set to 1.

- 14: **gamma** – double *Input*
On entry: γ , the scaling factor used when estimating scores. If **gamma** < 0 then $\gamma = 1$ is used.
- 15: **acc[2]** – const double *Input*
On entry: a measure of the accuracy of the scoring function, f .
 Letting $a_i = \epsilon_1 |f(S_i)| + \epsilon_2$, then when confirming whether the scoring function is strictly increasing or decreasing (as described in **mincr**), or when assessing whether a node defined by subset S_i can be trimmed, then any values in the range $f(S_i) \pm a_i$ are treated as being numerically equivalent.
 If $0 \leq \mathbf{acc}[0] \leq 1$ then $\epsilon_1 = \mathbf{acc}[0]$, otherwise $\epsilon_1 = 0$.
 If $\mathbf{acc}[1] \geq 0$ then $\epsilon_2 = \mathbf{acc}[1]$, otherwise $\epsilon_2 = 0$.
 In most situations setting both ϵ_1 and ϵ_2 to zero should be sufficient. Using a nonzero value, when one is not required, can significantly increase the number of subsets that need to be evaluated.
- 16: **icomm[licomm]** – Integer *Communication Array*
On initial entry: **icomm** need not be set.
On intermediate exit: **icomm** is used for storage between calls to `nag_best_subset_given_size_revcomm` (h05aac).
On intermediate re-entry: **icomm** must remain unchanged.
On final exit: **icomm** is not defined. The first two elements, **icomm**[0] and **icomm**[1] contain the minimum required value for **licomm** and **lrcomm** respectively.
- 17: **licomm** – Integer *Input*
On entry: the length of the array **icomm**. If **licomm** is too small and **licomm** ≥ 2 then **fail.code** = `NE_ARRAY_SIZE` is returned and the minimum value for **licomm** and **lrcomm** are given by **icomm**[0] and **icomm**[1] respectively.
Constraints:
 if **mincnt** = 0
 , **licomm** $\geq 2 \times \max(\mathbf{nbest}, \mathbf{m}) + \mathbf{m}(\mathbf{m} + 2) + (\mathbf{m} + 1) \times \max(\mathbf{m} - \mathbf{ip}, 1) + 27$;
 otherwise **licomm** $\geq 2 \times \max(\mathbf{nbest}, \mathbf{m}) + \mathbf{m}(\mathbf{m} + 3) + (2\mathbf{m} + 1) \times \max(\mathbf{m} - \mathbf{ip}, 1) + 25$.
- 18: **rcomm[lrcomm]** – double *Communication Array*
On initial entry: **rcomm** need not be set.
On intermediate exit: **rcomm** is used for storage between calls to `nag_best_subset_given_size_revcomm` (h05aac).
On intermediate re-entry: **rcomm** must remain unchanged.
On final exit: **rcomm** is not defined.
- 19: **lrcomm** – Integer *Input*
On entry: the length of the array **rcomm**. If **lrcomm** is too small and **licomm** ≥ 2 then **fail.code** = `NE_ARRAY_SIZE` is returned and the minimum value for **licomm** and **lrcomm** are given by **icomm**[0] and **icomm**[1] respectively.
Constraints:
 if **mincnt** = 0, **lrcomm** $\geq 9 + \mathbf{nbest} + \mathbf{m} \times \max(\mathbf{m} - \mathbf{ip}, 1)$;
 otherwise **lrcomm** $\geq 8 + \mathbf{m} + \mathbf{nbest} + \mathbf{m} \times \max(\mathbf{m} - \mathbf{ip}, 1)$.
- 20: **fail** – NagError * *Input/Output*
 The NAG error argument (see Section 3.6 in the Essential Introduction).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

NE_ARRAY_SIZE

On entry, **licomm** = $\langle value \rangle$, **lrcomm** = $\langle value \rangle$.

Constraint: **licomm** $\geq \langle value \rangle$, **lrcomm** $\geq \langle value \rangle$.

The minimum required values for **licomm** and **lrcomm** are returned in **icomm**[0] and **icomm**[1] respectively.

NE_BAD_PARAM

On entry, argument $\langle value \rangle$ had an illegal value.

NE_ILLEGAL_COMM

icomm has been corrupted between calls.

rcomm has been corrupted between calls.

NE_INT

On entry, **irevcm** = $\langle value \rangle$.

Constraint: **irevcm** = 0 or 1.

On entry, **m** = $\langle value \rangle$.

Constraint: **m** ≥ 2 .

On entry, **mincr** = $\langle value \rangle$.

Constraint: **mincr** = 0 or 1.

On entry, **nbest** = $\langle value \rangle$.

Constraint: **nbest** ≥ 1 .

NE_INT_2

On entry, **ip** = $\langle value \rangle$ and **m** = $\langle value \rangle$.

Constraint: $1 \leq \mathbf{ip} \leq \mathbf{m}$.

NE_INT_CHANGED

drop has changed between calls.

On intermediate entry, **drop** = $\langle value \rangle$.

On initial entry, **drop** = $\langle value \rangle$.

ip has changed between calls.

On intermediate entry, **ip** = $\langle value \rangle$.

On initial entry, **ip** = $\langle value \rangle$.

la has changed between calls.

On entry, **la** = $\langle value \rangle$.

On previous exit, **la** = $\langle value \rangle$.

lz has changed between calls.

On entry, **lz** = $\langle value \rangle$.

On previous exit, **lz** = $\langle value \rangle$.

m has changed between calls.

On intermediate entry, **m** = $\langle value \rangle$.

On initial entry, **m** = $\langle value \rangle$.

mincnt has changed between calls.
 On intermediate entry, **mincnt** = $\langle value \rangle$.
 On initial entry, **mincnt** = $\langle value \rangle$.

mincr has changed between calls.
 On intermediate entry, **mincr** = $\langle value \rangle$.
 On initial entry, **mincr** = $\langle value \rangle$.

nbest has changed between calls.
 On intermediate entry, **nbest** = $\langle value \rangle$.
 On initial entry, **nbest** = $\langle value \rangle$.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

NE_REAL

bscore[$\langle value \rangle$] = $\langle value \rangle$, which is inconsistent with the score for the parent node. Score for the parent node is $\langle value \rangle$.

NE_REAL_CHANGED

acc[0] has changed between calls.
 On intermediate entry, **acc**[0] = $\langle value \rangle$.
 On initial entry, **acc**[0] = $\langle value \rangle$.

acc[1] has changed between calls.
 On intermediate entry, **acc**[1] = $\langle value \rangle$.
 On initial entry, **acc**[1] = $\langle value \rangle$.

gamma has changed between calls.
 On intermediate entry, **gamma** = $\langle value \rangle$.
 On initial entry, **gamma** = $\langle value \rangle$.

NE_TOO_MANY

On entry, **nbest** = $\langle value \rangle$.
 But only $\langle value \rangle$ best subsets could be calculated.

NE_TOO_SMALL

On entry, **licomm** = $\langle value \rangle$, **lrcomm** = $\langle value \rangle$.
 Constraint: **licomm** \geq $\langle value \rangle$, **lrcomm** \geq $\langle value \rangle$.
licomm is too small to return the required array sizes.

7 Accuracy

The subsets returned by `nag_best_subset_given_size_revcomm` (h05aac) are guaranteed to be optimal up to the accuracy of your calculated scores.

8 Parallelism and Performance

`nag_best_subset_given_size_revcomm` (h05aac) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

Please consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

The maximum number of unique subsets of size p from a set of m features is $N = \frac{m!}{(m-p)!p!}$. The efficiency of the branch and bound algorithm implemented in `nag_best_subset_given_size_revcomm` (h05aac) comes from evaluating subsets at internal nodes of the tree, that is subsets with more than p features, and where possible trimming branches of the tree based on the scores at these internal nodes as described in Narendra and Fukunaga (1977). Because of this it is possible, in some circumstances, for more than N subsets to be evaluated. This will tend to happen when most of the features have a similar effect on the subset score.

If multiple optimal subsets exist with the same score, and `nbest` is too small to return them all, then the choice of which of these optimal subsets is returned is arbitrary.

10 Example

This example finds the three linear regression models, with five variables, that have the smallest residual sums of squares when fitted to a supplied dataset. The data used in this example was simulated.

10.1 Program Text

```

/* nag_best_subset_given_size_revcomm (h05aac) Example Program.
 *
 * Copyright 2011, Numerical Algorithms Group.
 *
 * Mark 23, 2011.
 */
/* Pre-processor includes */
#include <stdio.h>
#include <math.h>
#include <string.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagg02.h>
#include <nagh05.h>

#define BZ(I,J) bz[(J)*(m - ip) + (I)]

typedef struct {
    Integer n, tdq, tdx;
    double tol;
    double *x, *y, *b, *cov, *h, *p, *q, *res, *se, *wt, *com_ar;
    Integer *sx;
    Nag_IncludeMean mean;
} calc_subset_data;

void read_subset_data(Integer m, calc_subset_data *cs);
void tidy_subset_data(calc_subset_data *cs);
void calc_subset_score(Integer m,Integer drop,Integer lz,const Integer z[],
                      Integer la,const Integer a[],double bscore[],
                      calc_subset_data *cs);

int main(void)
{
    int exit_status = 0;

    /* Integer scalar and array declarations */
    Integer cnt, drop, i, ip, irevc, j, la, licomm, lrcomm, lz, m,
        mincnt, mincr, mip, nbest;
    Integer *a = 0, *bz = 0, *ibz = 0, *icomm = 0, *z = 0, *id = 0;

    /* NAG structures */
    NagError fail;

    /* Double scalar and array declarations */
    double gamma;
    double *bscore = 0, *rcomm = 0;

```



```

double acc[2];

/* Other data types */
calc_subset_data cs;

/* Initialise the error structure */
INIT_FAIL(fail);

printf("nag_best_subset_given_size_revcomm (h05aac) Example Program Results");
printf("\n\n");
/* Skip heading in data file */
scanf("%*[\n] %*[\n] ");

/* Read in the problem size */
scanf("%ld%ld%ld%*[\n] ", &m, &ip, &nbest);

/* Read in the control parameters for the subset selection */
scanf("%ld%ld%lf%lf%lf%*[\n] ", &mincr, &mincnt, &gamma,
      &acc[0], &acc[1]);

/* Read in the data required for the score function */
read_subset_data(m, &cs);

/* Allocate memory required by the subset selection routine */
mip = m - ip;
if (!(z = NAG_ALLOC(mip, Integer)) ||
    !(a = NAG_ALLOC(MAX(nbest,m), Integer)) ||
    !(bz = NAG_ALLOC(mip*nbest, Integer)) ||
    !(bscore = NAG_ALLOC(MAX(nbest,m),double))) {
    printf("Allocation failure\n");
    exit_status = -1;
    goto END;
}

/* Allocate dummy communication arrays, as we will query the required size */
licomm = 2;
lrcomm = 0;
if (!(icomm = NAG_ALLOC(licomm, Integer)) ||
    !(rcomm = NAG_ALLOC(lrcomm,double))) {
    printf("Allocation failure\n");
    exit_status = -2;
    goto END;
}

/* Query the required length for the communication arrays */
irevcm = 0;
nag_best_subset_given_size_revcomm(&irevcm, mincr, m, ip, nbest, &drop,
                                   &lz, z, &la, a, bscore, bz, mincnt, gamma,
                                   acc, icomm, licomm, rcomm, lrcomm, &fail);

/* Extract the required sizes from the communication array */
licomm = icomm[0];
lrcomm = icomm[1];

/* Reallocate communication arrays to the correct size */
NAG_FREE(icomm);
NAG_FREE(rcomm);
if (!(icomm = NAG_ALLOC(licomm, Integer)) ||
    !(rcomm = NAG_ALLOC(lrcomm,double))) {
    printf("Allocation failure\n");
    exit_status = -3;
    goto END;
}

/* Initialise reverse communication control flag */
irevcm = 0;

/* Call the reverse communication best subset routine
   (nag_best_subset_given_size_revcomm (h05aac)) in a loop.
   The loop should terminate when irevcm = 0 on exit */
for (cnt = 0;;) {

```

```

nag_best_subset_given_size_revcomm(&irevcm, mincr, m, ip, nbest, &drop,
                                   &lz, z, &la, a, bscore, bz, mincnt,
                                   gamma, acc, icomm, licomm, rcomm,
                                   lrcomm, &fail);

if (irevcm==0) {
  if (fail.code != NE_NOERROR) {
    printf("Error from nag_best_subset_given_size_revcomm (h05aac).\n%s\n",
          fail.message);
    if (fail.code != NE_ARG_TOO_LARGE) {
      exit_status = 1;
      goto END;
    }
  }
  /* Jump out of the loop */
  break;
}

/* Calculate and return the score for the required models and keep track of
   the number of subsets evaluated */
cnt += MAX(1,la);
calc_subset_score(m,drop,lz,z,la,a,bscore,&cs);
}

/* Titles */
printf("    Score          Feature Subset\n");
printf("    -----          -\n");

/* Display the best subsets and corresponding scores.
 * nag_best_subset_given_size_revcomm returns a list of features excluded
 * from the best subsets, so this is inverted to give the set of features
 * included in each subset.
 */
if (!(id = NAG_ALLOC(m, Integer))) {
  printf("Allocation failure\n");
  exit_status = -1;
  goto END;
}
for (i = 0; i < la; i++) {
  printf("%12.5e ", bscore[i]);
  for (j = 0; j < m; j++)
    id[j] = 1;
  for (j = 0; j < mip; j++)
    id[BZ(j,i) - 1] = 0;
  for (j = 0; j < m; j++)
    if (id[j]) printf(" %5"NAG_IFMT, j+1);
  printf("\n");
}
printf("\n");
if (fail.code == NE_TOO_MANY) {
  printf("%ld subsets of the requested size do not exist,"
        " only %ld are displayed.\n", nbest,la);
}
printf("%ld subsets evaluated in total\n", cnt);

END:
NAG_FREE(z);
NAG_FREE(a);
NAG_FREE(bz);
NAG_FREE(ibz);
NAG_FREE(bscore);
NAG_FREE(icomm);
NAG_FREE(rcomm);
NAG_FREE(id);

tidy_subset_data(&cs);

return exit_status;
}

#define CSX(I, J) cs->x[(I) * cs->tdx + J]
void read_subset_data(Integer m, calc_subset_data *cs) {

```

```

/* Read in the data, from stdout, and allocate any arrays that are required
   by the scoring function calc_subset_score */
Integer i, j;
cs->sx = 0;
cs->x = cs->y = cs->b = cs->se = cs->cov = cs->res = cs->h = cs->q = 0;
cs->p = cs->com_ar = cs->wt = 0;

/* Skip heading in data file */
scanf("%*[\n] ");

/* Read in the number of observations for the data used in the linear
   regression */
scanf("%ld%[\n] ", &cs->n);

/* Read in the control parameters for the linear regression */
scanf("%lf%[\n] ", &cs->tol);

/* Read in the data */
cs->tdx = m;

if (!(cs->x = NAG_ALLOC(cs->tdx*cs->n, double)) ||
    !(cs->y = NAG_ALLOC(cs->n, double))) {
    printf("Allocation failure\n");
    tidy_subset_data(cs);
    exit(-1);
}

/* Read in the data for the linear regression */
for (i = 0; i < cs->n; i++) {
    for (j = 0; j < m; j++)
        scanf("%lf", &CSX(i,j));
    scanf("%lf%[\n] ", &cs->y[i]);
}

/* No intercept term and no weights */
cs->mean = Nag_MeanZero;

/* Allocate memory required by the regression routine */
cs->tdq = cs->n;
if (!(cs->sx = NAG_ALLOC(m, Integer)) ||
    !(cs->b = NAG_ALLOC(m, double)) ||
    !(cs->se = NAG_ALLOC(m, double)) ||
    !(cs->cov = NAG_ALLOC(m*(m+1)/2, double)) ||
    !(cs->res = NAG_ALLOC(cs->n, double)) ||
    !(cs->h = NAG_ALLOC(cs->n, double)) ||
    !(cs->q = NAG_ALLOC(cs->n*cs->tdq, double)) ||
    !(cs->p = NAG_ALLOC(2*m*m, double)) ||
    !(cs->com_ar = NAG_ALLOC(5*(m-1)*m, double))) {
    printf("Allocation failure\n");
    tidy_subset_data(cs);
    exit(-1);
}
}

void tidy_subset_data(calc_subset_data *cs) {
    /* Tidy up the data structure used by calc_subset_score */
    NAG_FREE(cs->sx);
    NAG_FREE(cs->x);
    NAG_FREE(cs->y);
    NAG_FREE(cs->b);
    NAG_FREE(cs->se);
    NAG_FREE(cs->cov);
    NAG_FREE(cs->res);
    NAG_FREE(cs->h);
    NAG_FREE(cs->q);
    NAG_FREE(cs->p);
    NAG_FREE(cs->com_ar);
    NAG_FREE(cs->wt);
}

void calc_subset_score(Integer m, Integer drop, Integer lz, const Integer z[],

```

```

        Integer la,const Integer a[],double bscore[],
        calc_subset_data *cs) {
/* Calculate the score associated with a particular set of feature subsets.
   m,drop,lz,z,la,a and bscore are all as described in the documentation
   of nag_best_subset_given_size_revcomm (h05aac).
   cs - Structure of type calc_subset_data that holds any additional data
   required by this routine

   This particular example finds the set, of a given size, of explanatory
   variables that best fit a response variable when a linear regression model
   is used. Therefore the feature set is the set of all the explanatory
   variables and the best set of features is defined as set of explanatory
   variables that gives the smallest residual sums of squares. See the
   documentation for g02dac for details on linear regression models.
*/

/* Integer scalar and array declarations */
Integer i, j, inv_drop, ip, irank;

/* NAG structures */
NagError fail;

/* Double scalar and array declarations */
double rss, df;

/* Other data types */
Nag_Boolean svd;

/* Initialise the error structure */
INIT_FAIL(fail);

/* Set up the initial feature set.
   If drop = 0, this is the Null set (i.e. no features).
   If drop = 1 then this is the full set (i.e. all features) */
for (i = 0; i < m; i++)
    cs->sx[i] = drop;

/* Add (if drop = 0) or remove (if drop = 1) the all the features specified
   in Z (note: z refers to its features with values 1 to M, therefore you
   must subtract 1 when using z as an array reference) .
*/
inv_drop = (drop == 0) ? 1 : 0;
for (i = 0; i < lz; i++)
    cs->sx[z[i] - 1] = inv_drop;

/* Loop over all the elements in a, looping at least once */
for (i = 0; i < MAX(la,1); i++) {
    if (la > 0) {
        if (i > 0) {
            /* Reset the feature altered at the last iteration */
            cs->sx[a[i-1] - 1] = drop;
        }

        /* Add or drop the I'th feature in A */
        cs->sx[a[i] - 1] = inv_drop;
    }

    /* Calculate number of parameters in the regression model */
    for (ip = j = 0; j < m; j++) ip += (cs->sx[j] == 1);

    /* Fit the regression model (g02dac) */
    nag_regsn_mult_linear(cs->mean, cs->n, cs->x, cs->tdx, m, cs->sx,
        ip, cs->y, cs->wt, &rss, &df, cs->b, cs->se,
        cs->cov, cs->res, cs->h, cs->q, cs->tdq, &svd,
        &irank, cs->p, cs->tol, cs->com_ar, &fail);

    /* Return the score (the residual sums of squares) */
    bscore[i] = rss;
}
}

```

10.2 Program Data

```

nag_best_subset_given_size_revcomm (h05aac) Example Program Data
Data required by h05aac
14 5 3          :: m,ip,nbest
0 -1 -1.0 -1.0 -1.0  :: mincr, mincnt, gamma, acc[0], acc[1]

Data required by the scoring function
40              :: n
1e-6           :: tol
-1.59  0.19  0.40  0.43 -0.40  0.79  0.06
 0.33  1.60  0.58 -1.12  1.23  1.07 -0.07      -2.44
-0.25  0.61 -0.36  1.16  0.61 -2.05 -0.02
-0.04  0.80 -0.73 -0.63 -0.75 -0.73  1.43      -2.97
-2.28  0.46 -0.65  0.33  0.16 -0.21 -1.61
-0.54  0.48  0.37 -0.95 -2.14  0.48  2.02      7.42
-0.52  1.05  0.64  0.02 -1.12  0.23  0.06
-1.26  1.40 -0.98  2.47  0.49 -0.02 -0.05      3.00
-0.84  1.86  0.10  0.73 -1.41  0.98  0.20
-0.89  1.84  2.56  0.60 -0.12  0.71  0.23      8.83
 1.12 -0.51 -0.58  0.09 -1.14  2.11 -0.11
-0.34 -1.04 -0.43 -0.01 -0.38  1.80  0.05      0.03
 0.06  0.85 -2.09  0.22 -1.35 -0.36  1.20
 0.41  0.80 -0.28  0.18  0.27  0.92  0.63      2.57
-0.48 -1.02  0.08 -0.06  0.13 -1.18  2.30
 0.03  0.45  0.62 -1.97  0.97  0.93 -0.18      8.31
 0.08 -0.31  0.43 -0.38  0.01  1.30  0.66
 0.65 -0.59  0.76  0.04  0.17 -0.76 -0.90      4.55
 0.66  1.14  0.40  2.37  1.10  0.17 -0.38
 1.15 -1.00 -0.13 -0.69 -0.62 -0.18  0.00     -23.10
-1.08 -0.21 -1.13 -0.79 -0.76 -1.58  0.38
-0.03  1.26 -0.51 -0.75  0.86  0.29  0.68      3.38
-0.74 -1.59 -0.58 -1.09  1.18 -1.70 -1.02
 0.36  1.05  1.30 -0.98 -1.36 -1.28 -1.32     -0.13
 0.40 -1.58 -1.30 -0.10 -1.34  0.65 -0.56
 0.39 -0.73 -0.32  2.19 -0.49  0.69  0.18      5.47
 0.75 -3.09 -0.61 -1.89  0.15  0.77 -0.49
-0.63  1.20 -0.04  1.02  0.31  0.81 -0.45     13.97
-0.65  1.57 -1.50 -1.45  0.21  0.06  0.24
 2.24 -1.34  0.30  1.39 -0.38 -0.71  0.48     20.94
 1.36  1.40 -1.40 -0.90  0.36 -0.21 -0.97
 0.36 -0.26  0.08  0.06 -1.49  0.43 -1.61     -12.87
-1.01  1.50 -0.61 -0.25 -1.01 -0.43  1.90
-1.33 -0.96 -0.02  0.51 -1.38 -0.78  1.82     28.26
 1.34  1.02  3.50  0.10  0.50  0.04  0.61
-0.57 -2.69 -0.64 -0.34 -0.21 -1.97 -0.19      6.89
 0.29  0.67 -0.38 -0.63 -0.24  1.21 -0.09
 0.90 -2.20  1.72  0.29  0.66  0.19 -0.57      5.37
 0.67 -0.56 -0.41  1.22 -0.30  0.77  0.82
 0.36  1.18  1.87 -1.48  0.52  1.35  0.13     -1.50
-0.40 -1.10 -0.83  0.71  1.99 -0.24  1.30
-0.34 -0.70  0.28  0.16  0.27  0.37 -1.79     -23.00
-0.78  0.60 -0.45 -0.26 -0.23  0.89  0.87
 1.01  1.20  0.28  0.79  2.76  0.35  1.31     14.09
-1.29  0.62 -0.59  1.52  0.62  0.21  1.31
 1.09 -0.36 -0.34 -0.03 -0.59 -1.70 -0.03     -11.05
 0.40 -1.45 -0.98  2.10 -1.09 -0.53 -0.38
-1.36  0.13  0.70 -1.51  0.08 -0.62 -0.64     -32.04
 0.43 -0.86  0.70 -1.07 -0.76  0.72 -0.14
-1.58  0.00  0.58 -0.21  1.30  2.02  1.52     23.36
-0.48  0.01  1.30  0.58 -0.54  1.09  0.91
 2.90  1.32 -1.20 -0.59 -0.51  0.20 -1.74     -5.58
-1.32 -1.41 -0.58 -1.29  1.61 -0.35 -0.72
-1.92 -1.09  0.56 -0.87 -0.71  1.25  0.10      2.48
 1.43  0.69  1.34 -0.32  2.84 -1.43 -0.47
-0.01  0.83 -0.72 -0.78  0.50 -1.22  0.54     -5.30
 0.82  0.46  0.15 -0.57  0.93  1.33 -0.23
-1.07  0.76  0.25 -1.96  0.39  0.24 -0.26     -7.77
-0.91  0.23 -0.19  1.58 -0.27  0.33 -0.60
-1.39 -0.30 -0.81 -0.95  0.88 -0.09 -0.35     -34.25
 0.65 -1.14  1.18 -1.06 -0.68 -0.22  0.21

```

0.94	1.08	0.81	-0.33	0.42	-0.90	0.49	26.78
-0.36	-0.50	-0.02	-0.04	0.77	0.62	-1.35	
-0.64	1.20	1.22	0.18	-1.39	-0.81	-0.99	-11.85
-1.82	1.06	0.28	0.14	0.62	-0.80	-1.08	
-2.15	1.37	1.57	-1.48	-0.79	0.28	-0.20	-8.62
1.54	0.50	0.13	-0.68	0.26	-1.13	0.62	
-0.43	0.39	1.14	0.15	1.03	0.46	0.40	12.35
-1.61	-0.61	0.93	-0.37	0.44	-1.45	0.58	
-1.77	0.72	-2.05	-0.03	-1.24	-1.40	-0.06	-1.54
-0.48	0.67	0.04	0.27	-0.84	-0.06	-3.67	
0.09	1.66	-0.30	1.67	1.08	0.00	0.43	-16.59
-1.65	-1.16	-1.17	1.12	0.11	-0.15	0.48	
-1.72	1.08	-0.94	0.49	-0.56	0.95	1.09	-8.69
-0.85	-0.02	1.18	-1.16	0.49	1.56	-0.60	
0.32	0.72	-1.20	2.52	1.78	0.16	-0.01	7.82
-0.60	-0.73	-1.23	1.50	0.40	-0.20	-0.65	
0.68	1.09	0.40	-1.50	-2.10	0.21	-0.18	-18.56
-0.66	-0.01	-0.01	0.85	-2.04	1.17	-0.56	
1.72	-0.18	1.14	-0.96	-0.92	-0.28	1.58	17.21 :: x,y

10.3 Program Results

nag_best_subset_given_size_revcomm (h05aac) Example Program Results

Score	Feature Subset				
-----	-----	-----	-----	-----	-----
1.04753e+03	4	7	8	10	14
1.05987e+03	4	5	7	8	14
1.07016e+03	4	5	7	10	14

45 subsets evaluated in total
