

# NAG Library Routine Document

## F06EVF (DGTHRZ)

**Note:** before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

### 1 Purpose

F06EVF (DGTHRZ) gathers specified (usually nonzero) elements of a real vector  $y$  in full storage form into a sparse real vector  $x$  in compressed form. The specified elements of  $y$  are set to zero.

### 2 Specification

```
SUBROUTINE F06EVF (NZ, Y, X, INDX)
```

```
INTEGER          NZ, INDX(*)
```

```
REAL (KIND=nag_wp) Y(*), X(*)
```

The routine may be called by its BLAS name *dgthrz*.

### 3 Description

F06EVF (DGTHRZ) gathers the specified elements of a vector,  $y$ , in full storage form, into the equivalent sparse vector compressed form. The gathered elements of  $y$  are set to zero.

### 4 References

Dodson D S, Grimes R G and Lewis J G (1991) Sparse extensions to the Fortran basic linear algebra subprograms *ACM Trans. Math. Software* **17** 253–263

### 5 Parameters

- |    |   |                     |
|----|---|---------------------|
| 1: | NZ – INTEGER  | <i>Input</i>        |
|    | <i>On entry:</i> the number of nonzeros in the compressed sparse vector $x$ .   |                     |
| 2: | Y(*) – REAL (KIND=nag_wp) array   | <i>Input/Output</i> |
|    | <b>Note:</b> the dimension of the array Y must be at least $\max_k\{\text{INDX}(k)\}$ .   |                     |
|    | <i>On entry:</i> the vector $y$ . Only elements corresponding to indices in INDX are accessed.  |                     |
|    | <i>On exit:</i> the elements of $y$ corresponding to indices in INDX are set to zero.   |                     |
| 3: | X(*) – REAL (KIND=nag_wp) array   | <i>Output</i>       |
|    | <b>Note:</b> the dimension of the array X must be at least $\max(1, \text{NZ})$ .   |                     |
|    | <i>On exit:</i> the compressed vector $x$ .   |                     |
| 4: | INDX(*) – INTEGER array   | <i>Input</i>        |
|    | <b>Note:</b> the dimension of the array INDX must be at least $\max(1, \text{NZ})$ .  |                     |
|    | <i>On entry:</i> $\text{INDX}(i)$ must contain the index $Y(i)$ , for $i = 1, 2, \dots, \text{NZ}$ , which is to be gathered into $x$ . |                     |
|    | <i>Constraint:</i> the indices must be distinct.  |                     |

## **6 Error Indicators and Warnings**

None.

## **7 Accuracy**

Not applicable.

## **8 Further Comments**

None.

## **9 Example**

None.

---