

NAG Library Function Document

nag_dtftri (f07wkc)

1 Purpose

nag_dtftri (f07wkc) computes the inverse of a real triangular matrix stored in Rectangular Full Packed (RFP) format.

2 Specification

```
#include <nag.h>
#include <nagf07.h>

void nag_dtftri (Nag_OrderType order, Nag_RFP_Store transr,
                Nag_UploType uplo, Nag_DiagType diag, Integer n, double ar[],
                NagError *fail)
```

3 Description

nag_dtftri (f07wkc) forms the inverse of a real triangular matrix A , stored using RFP format. The RFP storage format is described in Section 3.3.3 in the f07 Chapter Introduction. Note that the inverse of an upper (lower) triangular matrix is also upper (lower) triangular.

4 References

Du Croz J J and Higham N J (1992) Stability of methods for matrix inversion *IMA J. Numer. Anal.* **12** 1–19

Gustavson F G, Waśniewski J, Dongarra J J and Langou J (2010) Rectangular full packed format for Cholesky’s algorithm: factorization, solution, and inversion *ACM Trans. Math. Software* **37**, 2

5 Arguments

- 1: **order** – Nag_OrderType *Input*
On entry: the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag_RowMajor. See Section 3.2.1.3 in the Essential Introduction for a more detailed explanation of the use of this argument.
Constraint: **order** = Nag_RowMajor or Nag_ColMajor.
- 2: **transr** – Nag_RFP_Store *Input*
On entry: specifies whether the RFP representation of A is normal or transposed.
transr = Nag_RFP_Normal
 The matrix A is stored in normal RFP format.
transr = Nag_RFP_Trans
 The matrix A is stored in transposed RFP format.
Constraint: **transr** = Nag_RFP_Normal or Nag_RFP_Trans.

- 3: **uplo** – Nag_UploType *Input*
On entry: specifies whether A is upper or lower triangular.
uplo = Nag_Upper
 A is upper triangular.
uplo = Nag_Lower
 A is lower triangular.
Constraint: **uplo** = Nag_Upper or Nag_Lower.
- 4: **diag** – Nag_DiagType *Input*
On entry: indicates whether A is a nonunit or unit triangular matrix.
diag = Nag_NonUnitDiag
 A is a nonunit triangular matrix.
diag = Nag_UnitDiag
 A is a unit triangular matrix; the diagonal elements are not referenced and are assumed to be 1.
Constraint: **diag** = Nag_NonUnitDiag or Nag_UnitDiag.
- 5: **n** – Integer *Input*
On entry: n , the order of the matrix A .
Constraint: $n \geq 0$.
- 6: **ar**[$n \times (n + 1)/2$] – double *Input/Output*
On entry: the upper or lower triangular part (as specified by **uplo**) of the n by n symmetric matrix A , in either normal or transposed RFP format (as specified by **transr**). The storage format is described in detail in Section 3.3.3 in the f07 Chapter Introduction.
On exit: A is overwritten by A^{-1} , in the same storage format as A .
- 7: **fail** – NagError * *Input/Output*
The NAG error argument (see Section 3.6 in the Essential Introduction).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.
See Section 3.2.1.2 in the Essential Introduction for further information.

NE_BAD_PARAM

On entry, argument $\langle value \rangle$ had an illegal value.

NE_INT

On entry, $n = \langle value \rangle$.
Constraint: $n \geq 0$.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.
See Section 3.6.6 in the Essential Introduction for further information.

NE_NO_LICENCE

Your licence key may have expired or may not have been installed correctly.
See Section 3.6.5 in the Essential Introduction for further information.

NE_SINGULAR

Diagonal element $\langle value \rangle$ of A is exactly zero. A is singular its inverse cannot be computed.

7 Accuracy

The computed inverse X satisfies

$$|XA - I| \leq c(n)\epsilon|X||A|,$$

where $c(n)$ is a modest linear function of n , and ϵ is the *machine precision*.

Note that a similar bound for $|AX - I|$ cannot be guaranteed, although it is almost always satisfied.

The computed inverse satisfies the forward error bound

$$|X - A^{-1}| \leq c(n)\epsilon|A^{-1}||A||X|.$$

See Du Croz and Higham (1992).

8 Parallelism and Performance

nag_dtftri (f07wkc) is not threaded by NAG in any implementation.

nag_dtftri (f07wkc) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this function. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

The total number of floating-point operations is approximately $\frac{1}{3}n^3$.

The complex analogue of this function is nag_ztftri (f07wxc).

10 Example

This example computes the inverse of the matrix A , where

$$A = \begin{pmatrix} 4.30 & 0.00 & 0.00 & 0.00 \\ -3.96 & -4.87 & 0.00 & 0.00 \\ 0.40 & 0.31 & -8.02 & 0.00 \\ -0.27 & 0.07 & -5.95 & 0.12 \end{pmatrix}$$

and is stored using RFP format.

10.1 Program Text

```
/* nag_dtftri (f07wkc) Example Program.
 *
 * Copyright 2014 Numerical Algorithms Group.
 *
 * Mark 23, 2011.
 */

#include <nag.h>
#include <nag_stdlib.h>
```

```

#include <nagf01.h>
#include <nagf07.h>
#include <nagx04.h>

int main(void)
{
    /* Scalars*/
    Integer      exit_status = 0;
    Integer      i, j, k, lar1, lar2, lenar, n, pdar, pda, q;
    /* Arrays*/
    double       *ar = 0, *a = 0;
    char         nag_enum_arg[40];
    /* NAG types */
    Nag_RFP_Store transr;
    Nag_UploType  uplo;
    Nag_DiagType  diag;
    Nag_OrderType order;
    Nag_MatrixType matrix;
    NagError      fail;

#ifdef NAG_COLUMN_MAJOR
    order = Nag_ColMajor;
#define AR(I,J) ar[J*pdar + I]
#else
    order = Nag_RowMajor;
#define AR(I,J) ar[I*pdar + J]
#endif

    INIT_FAIL(fail);

    printf("nag_dtftri (f07wkc) Example Program Results\n\n");

    /* Skip heading in data file*/
#ifdef _WIN32
    scanf_s("%*[\n]");
#else
    scanf("%*[\n]");
#endif
#ifdef _WIN32
    scanf_s("%"NAG_IFMT"", &n);
#else
    scanf("%"NAG_IFMT"", &n);
#endif
#ifdef _WIN32
    scanf_s("%39s", nag_enum_arg, _countof(nag_enum_arg));
#else
    scanf("%39s", nag_enum_arg);
#endif
    uplo = (Nag_UploType) nag_enum_name_to_value(nag_enum_arg);
#ifdef _WIN32
    scanf_s("%39s", nag_enum_arg, _countof(nag_enum_arg));
#else
    scanf("%39s", nag_enum_arg);
#endif
    transr = (Nag_RFP_Store) nag_enum_name_to_value(nag_enum_arg);
#ifdef _WIN32
    scanf_s("%39s%*[\n]", nag_enum_arg, _countof(nag_enum_arg));
#else
    scanf("%39s%*[\n]", nag_enum_arg);
#endif
    diag = (Nag_DiagType) nag_enum_name_to_value(nag_enum_arg);

    lenar = (n * (n + 1))/2;
    if (!(ar = NAG_ALLOC((lenar), double)) ||
        !(a = NAG_ALLOC((n)*(n), double)))
    {
        printf("Allocation failure\n");
        exit_status = -1;
        goto END;
    }
    pda = n;

```

```

/* Setup dimensions of RFP array ar. */
k = n/2;
q = n - k;
if (transr==Nag_RFP_Normal) {
    lar1 = 2*k+1;
    lar2 = q;
} else {
    lar1 = q;
    lar2 = 2*k+1;
}
if (order==Nag_RowMajor) {
    pdar = lar2;
} else {
    pdar = lar1;
}
/* Read RFP array ar. */
for (i = 0; i < lar1; i++) {
    for (j = 0; j < lar2; j++) {
#ifdef _WIN32
        scanf_s("%lf ", &AR(i,j));
#else
        scanf("%lf ", &AR(i,j));
#endif
    }
}

/* Compute inverse of A using nag_dtftri (f07wkc) which Inverts a real
 * triangular matrix in Rectangular Full Packed format.
 */
nag_dtftri(order, transr, uplo, diag, n, ar, &fail);
if (fail.code != NE_NOERROR) {
    printf("%s\n", fail.message);
    exit_status = 1;
    goto END;
}

/* Convert inverse to full array form using nag_dtftr (f01vvc). */
nag_dtftr(order, transr, uplo, n, ar, a, pda, &fail);
if (fail.code != NE_NOERROR) {
    printf("%s\n", fail.message);
    exit_status = 2;
    goto END;
}

/* nag_gen_real_mat_print (x04cac).
 * Print real general matrix (easy-to-use)
 */
if (uplo == Nag_Lower)
    matrix = Nag_LowerMatrix;
else
    matrix = Nag_UpperMatrix;

nag_gen_real_mat_print(order, matrix, diag, n, n, a, pda, "Inverse", 0,
    &fail);
if (fail.code != NE_NOERROR) {
    printf("Error from nag_gen_real_mat_print (x04cac)\n%s\n", fail.message);
    exit_status = 3;
}

END:
NAG_FREE(ar);
NAG_FREE(a);
return exit_status;
}

```

10.2 Program Data

```
nag_dtftri (f07wkc) Example Program Data
  4      Nag_Lower
  Nag_RFP_Normal
  Nag_NonUnitDiag           : n, uplo, transr, diag

-8.02   -5.95
  4.30   0.12
-3.96   -4.87
  0.40   0.31
-0.27   0.07           : ar[]
```

10.3 Program Results

```
nag_dtftri (f07wkc) Example Program Results
```

```
Inverse
      1      2      3      4
1      0.2326
2     -0.1891    -0.2053
3      0.0043    -0.0079   -0.1247
4      0.8463    -0.2738   -6.1825    8.3333
```
