

## NAG Library Function Document

### nag\_dorgrq (f08cjc)

## 1 Purpose

nag\_dorgrq (f08cjc) generates all or part of the real  $n$  by  $n$  orthogonal matrix  $Q$  from an  $RQ$  factorization computed by nag\_dgerqf (f08chc).

## 2 Specification

```
#include <nag.h>
#include <nagf08.h>
void nag_dorgrq (Nag_OrderType order, Integer m, Integer n, Integer k,
                 double a[], Integer pda, const double tau[], NagError *fail)
```

## 3 Description

nag\_dorgrq (f08cjc) is intended to be used following a call to nag\_dgerqf (f08chc), which performs an  $RQ$  factorization of a real matrix  $A$  and represents the orthogonal matrix  $Q$  as a product of  $k$  elementary reflectors of order  $n$ .

This function may be used to generate  $Q$  explicitly as a square matrix, or to form only its trailing rows. Usually  $Q$  is determined from the  $RQ$  factorization of a  $p$  by  $n$  matrix  $A$  with  $p \leq n$ . The whole of  $Q$  may be computed by:

```
nag_dorgrq(order,n,n,p,a,pda,tau,info)
```

(note that the matrix  $A$  must have at least  $n$  rows), or its trailing  $p$  rows as:

```
nag_dorgrq(order,p,n,p,a,pda,tau,info)
```

The rows of  $Q$  returned by the last call form an orthonormal basis for the space spanned by the rows of  $A$ ; thus nag\_dgerqf (f08chc) followed by nag\_dorgrq (f08cjc) can be used to orthogonalize the rows of  $A$ .

The information returned by nag\_dgerqf (f08chc) also yields the  $RQ$  factorization of the trailing  $k$  rows of  $A$ , where  $k < p$ . The orthogonal matrix arising from this factorization can be computed by:

```
nag_dorgrq(order,n,n,k,a,pda,tau,info)
```

or its leading  $k$  columns by:

```
nag_dorgrq(order,k,n,k,a,pda,tau,info)
```

## 4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia <http://www.netlib.org/lapack/lug>

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

## 5 Arguments

1: <b>order</b> – Nag_OrderType	<i>Input</i>
---------------------------------	--------------

*On entry:* the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by

**order** = Nag\_RowMajor. See Section 3.2.1.3 in the Essential Introduction for a more detailed explanation of the use of this argument.

*Constraint:* **order** = Nag\_RowMajor or Nag\_ColMajor.

2: **m** – Integer *Input*

*On entry:*  $m$ , the number of rows of the matrix  $Q$ .

*Constraint:*  $\mathbf{m} \geq 0$ .

3: **n** – Integer *Input*

*On entry:*  $n$ , the number of columns of the matrix  $Q$ .

*Constraint:*  $\mathbf{n} \geq \mathbf{m}$ .

4: **k** – Integer *Input*

*On entry:*  $k$ , the number of elementary reflectors whose product defines the matrix  $Q$ .

*Constraint:*  $\mathbf{m} \geq \mathbf{k} \geq 0$ .

5: **a**[*dim*] – double *Input/Output*

**Note:** the dimension, *dim*, of the array **a** must be at least

$\max(1, \mathbf{pda} \times \mathbf{n})$  when **order** = Nag\_ColMajor;  
 $\max(1, \mathbf{m} \times \mathbf{pda})$  when **order** = Nag\_RowMajor.

*On entry:* details of the vectors which define the elementary reflectors, as returned by nag\_dgerqf (f08chc).

*On exit:* the  $m$  by  $n$  matrix  $Q$ .

If **order** = Nag\_ColMajor, the  $(i, j)$ th element of the matrix is stored in **a**[( $j - 1$ )  $\times$  **pda** +  $i - 1$ ].

If **order** = Nag\_RowMajor, the  $(i, j)$ th element of the matrix is stored in **a**[( $i - 1$ )  $\times$  **pda** +  $j - 1$ ].

6: **pda** – Integer *Input*

*On entry:* the stride separating row or column elements (depending on the value of **order**) in the array **a**.

*Constraints:*

if **order** = Nag\_ColMajor, **pda**  $\geq \max(1, \mathbf{m})$ ;  
if **order** = Nag\_RowMajor, **pda**  $\geq \max(1, \mathbf{n})$ .

7: **tau**[*dim*] – const double *Input*

**Note:** the dimension, *dim*, of the array **tau** must be at least  $\max(1, \mathbf{k})$ .

*On entry:* **tau**[ $i - 1$ ] must contain the scalar factor of the elementary reflector  $H_i$ , as returned by nag\_dgerqf (f08chc).

8: **fail** – NagError \* *Input/Output*

The NAG error argument (see Section 3.6 in the Essential Introduction).

## 6 Error Indicators and Warnings

### NE\_ALLOC\_FAIL

Dynamic memory allocation failed.

See Section 3.2.1.2 in the Essential Introduction for further information.

**NE\_BAD\_PARAM**

On entry, argument  $\langle value \rangle$  had an illegal value.

**NE\_INT**

On entry,  $\mathbf{m} = \langle value \rangle$ .

Constraint:  $\mathbf{m} \geq 0$ .

On entry,  $\mathbf{pda} = \langle value \rangle$ .

Constraint:  $\mathbf{pda} > 0$ .

**NE\_INT\_2**

On entry,  $\mathbf{m} = \langle value \rangle$  and  $\mathbf{k} = \langle value \rangle$ .

Constraint:  $\mathbf{m} \geq \mathbf{k} \geq 0$ .

On entry,  $\mathbf{n} = \langle value \rangle$  and  $\mathbf{m} = \langle value \rangle$ .

Constraint:  $\mathbf{n} \geq \mathbf{m}$ .

On entry,  $\mathbf{pda} = \langle value \rangle$  and  $\mathbf{m} = \langle value \rangle$ .

Constraint:  $\mathbf{pda} \geq \max(1, \mathbf{m})$ .

On entry,  $\mathbf{pda} = \langle value \rangle$  and  $\mathbf{n} = \langle value \rangle$ .

Constraint:  $\mathbf{pda} \geq \max(1, \mathbf{n})$ .

**NE\_INTERNAL\_ERROR**

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.

See Section 3.6.6 in the Essential Introduction for further information.

**NE\_NO\_LICENCE**

Your licence key may have expired or may not have been installed correctly.

See Section 3.6.5 in the Essential Introduction for further information.

## 7 Accuracy

The computed matrix  $Q$  differs from an exactly orthogonal matrix by a matrix  $E$  such that

$$\|E\|_2 = O\epsilon$$

and  $\epsilon$  is the *machine precision*.

## 8 Parallelism and Performance

`nag_dorgrq` (f08cjc) is not threaded by NAG in any implementation.

`nag_dorgrq` (f08cjc) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this function. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

## 9 Further Comments

The total number of floating-point operations is approximately  $4mnk - 2(m + n)k^2 + \frac{4}{3}k^3$ ; when  $m = k$  this becomes  $\frac{2}{3}m^2(3n - m)$ .

The complex analogue of this function is `nag_zungrq` (f08cwc).

## 10 Example

This example generates the first four rows of the matrix  $Q$  of the  $RQ$  factorization of  $A$  as returned by nag\_dgerqf (f08chc), where

$$A = \begin{pmatrix} -0.57 & -1.93 & 2.30 & -1.93 & 0.15 & -0.02 \\ -1.28 & 1.08 & 0.24 & 0.64 & 0.30 & 1.03 \\ -0.39 & -0.31 & 0.40 & -0.66 & 0.15 & -1.43 \\ 0.25 & -2.14 & -0.35 & 0.08 & -2.13 & 0.50 \end{pmatrix}.$$

### 10.1 Program Text

```
/* nag_dorgrq (f08cjc) Example Program.
*
* Copyright 2014 Numerical Algorithms Group.
*
* Mark 23, 2011.
*/
#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagf08.h>
#include <nagx04.h>

int main(void)
{
    /* Scalars */
    Integer i, j, m, n, pda;
    Integer exit_status = 0;
    /* Arrays */
    char *title = 0;
    double *a = 0, *tau = 0;
    /* Nag Types */
    Nag_OrderType order;
    NagError fail;

#define NAG_COLUMN_MAJOR
#define A(I, J) a[(J - 1) * pda + I - 1]
    order = Nag_ColMajor;
#else
#define A(I, J) a[(I - 1) * pda + J - 1]
    order = Nag_RowMajor;
#endif

    INIT_FAIL(fail);

    printf("nag_dorgrq (f08cjc) Example Program Results\n\n");

    /* Skip heading in data file */
#ifdef _WIN32
    scanf_s("%*[^\n]");
#else
    scanf("%*[^\n]");
#endif
#ifdef _WIN32
    scanf_s("%"NAG_IFMT%"NAG_IFMT%*[^\n]", &m, &n);
#else
    scanf("%"NAG_IFMT%"NAG_IFMT%*[^\n]", &m, &n);
#endif

    #ifdef NAG_COLUMN_MAJOR
        pda = m;
    #else
        pda = n;
    #endif

    /* Allocate memory */
    if (!(title = NAG_ALLOC(27, char)) ||
        !(a = NAG_ALLOC(m * n, double)) ||
        !(tau = NAG_ALLOC(m, double)))
        exit_status = 1;
    else
        exit_status = 0;
}
```

```

! (a = NAG_ALLOC(m*n, double)) ||
! (tau = NAG_ALLOC(m, double)))
{
    printf("Allocation failure\n");
    exit_status = -1;
    goto END;
}

/* Read A from data file */
for (i = 1; i <= m; ++i)
    for (j = 1; j <= n; ++j)
#ifdef _WIN32
    scanf_s("%lf", &A(i, j));
#else
    scanf("%lf", &A(i, j));
#endif
#ifdef _WIN32
    scanf_s("%*[^\n]");
#else
    scanf("%*[^\n]");
#endif

/* nag_dgerqf (f08chc).
 * Compute the RQ factorization of A.
 */
nag_dgerqf(order, m, n, a, pda, tau, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_dgerqf (f08chc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

/* nag_dorgrq (f08cjc).
 * Form the leading m rows of Q explicitly.
 */
nag_dorgrq(order, m, n, m, a, pda, tau, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_dorgrq (f08cjc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

/* Form the heading for x04cac */
#ifdef _WIN32
    sprintf_s(title, 27, "The leading %4"NAG_IFMT" rows of Q", m);
#else
    sprintf(title, "The leading %4"NAG_IFMT" rows of Q", m);
#endif

/* nag_gen_real_mat_print (x04cac).
 * Print the leading m rows of Q.
 */
fflush(stdout);
nag_gen_real_mat_print(order, Nag-GeneralMatrix, Nag_NonUnitDiag, m, n, a,
                      pda, title, 0, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_gen_real_mat_print (x04cac).\n%s\n",
           fail.message);
    exit_status = 1;
}

END:
NAG_FREE(title);
NAG_FREE(a);
NAG_FREE(tau);

```

```
    return exit_status;  
}  
  
#undef A
```

## 10.2 Program Data

```
nag_dorgrq (f08cjc) Example Program Data  
  
        4       6                               :Values of m and n  
  
-0.57  -1.93   2.30  -1.93   0.15  -0.02  
-1.28   1.08   0.24   0.64   0.30   1.03  
-0.39  -0.31   0.40  -0.66   0.15  -1.43  
 0.25  -2.14  -0.35   0.08  -2.13   0.50 :End of matrix A
```

## 10.3 Program Results

```
nag_dorgrq (f08cjc) Example Program Results
```

```
The leading      4 rows of Q  
      1       2       3       4       5       6  
1  -0.0833  0.2972 -0.6404  0.4461 -0.2938 -0.4575  
2   0.9100 -0.1080 -0.2351 -0.1620  0.2022 -0.1946  
3  -0.2202 -0.2706  0.2220 -0.3866  0.0015 -0.8243  
4  -0.0809  0.6922  0.1132 -0.0259  0.6890 -0.1617
```

---