

## NAG Library Function Document

### nag\_dsyrr2 (f16prc)

## 1 Purpose

nag\_dsyrr2 (f16prc) performs a rank-2 update on a real symmetric matrix.

## 2 Specification

```
#include <nag.h>
#include <nagf16.h>

void nag_dsyrr2 (Nag_OrderType order, Nag_UptoType uplo, Integer n,
                 double alpha, const double x[], Integer incx, const double y[],
                 Integer incy, double beta, double a[], Integer pda, NagError *fail)
```

## 3 Description

nag\_dsyrr2 (f16prc) performs the symmetric rank-2 update operation

$$A \leftarrow \alpha xy^T + \alpha yx^T + \beta A,$$

where  $A$  is an  $n$  by  $n$  real symmetric matrix,  $x$  and  $y$  are  $n$ -element real vectors, while  $\alpha$  and  $\beta$  are real scalars.

## 4 References

Basic Linear Algebra Subprograms Technical (BLAST) Forum (2001) *Basic Linear Algebra Subprograms Technical (BLAST) Forum Standard* University of Tennessee, Knoxville, Tennessee <http://www.netlib.org/blas/blast-forum/blas-report.pdf>

## 5 Arguments

1: **order** – Nag\_OrderType *Input*

*On entry:* the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag\_RowMajor. See Section 3.2.1.3 in the Essential Introduction for a more detailed explanation of the use of this argument.

*Constraint:* **order** = Nag\_RowMajor or Nag\_ColMajor.

2: **uplo** – Nag\_UptoType *Input*

*On entry:* specifies whether the upper or lower triangular part of  $A$  is stored.

**uplo** = Nag\_Upper

The upper triangular part of  $A$  is stored.

**uplo** = Nag\_Lower

The lower triangular part of  $A$  is stored.

*Constraint:* **uplo** = Nag\_Upper or Nag\_Lower.

3: **n** – Integer *Input*

*On entry:*  $n$ , the order of the matrix  $A$ .

*Constraint:* **n**  $\geq 0$ .

4:	<b>alpha</b> – double	<i>Input</i>
<i>On entry:</i> the scalar $\alpha$ .		
5:	<b>x</b> [ <i>dim</i> ] – const double	<i>Input</i>
<b>Note:</b> the dimension, <i>dim</i> , of the array <b>x</b> must be at least $\max(1, 1 + (\mathbf{n} - 1) \mathbf{incx} )$ .		
<i>On entry:</i> the vector $x$ .		
6:	<b>incx</b> – Integer	<i>Input</i>
<i>On entry:</i> the increment in the subscripts of <b>x</b> between successive elements of $x$ .		
<i>Constraint:</i> <b>incx</b> $\neq 0$ .		
7:	<b>y</b> [ <i>dim</i> ] – const double	<i>Input</i>
<b>Note:</b> the dimension, <i>dim</i> , of the array <b>y</b> must be at least $\max(1, 1 + (\mathbf{n} - 1) \mathbf{incy} )$ .		
<i>On entry:</i> the vector $y$ .		
8:	<b>incy</b> – Integer	<i>Input</i>
<i>On entry:</i> the increment in the subscripts of <b>y</b> between successive elements of $y$ .		
<i>Constraint:</i> <b>incy</b> $\neq 0$ .		
9:	<b>beta</b> – double	<i>Input</i>
<i>On entry:</i> the scalar $\beta$ .		
10:	<b>a</b> [ <i>dim</i> ] – double	<i>Input/Output</i>
<b>Note:</b> the dimension, <i>dim</i> , of the array <b>a</b> must be at least $\max(1, \mathbf{pda} \times \mathbf{n})$ .		
<i>On entry:</i> the $n$ by $n$ symmetric matrix $A$ .		
If <b>order</b> = Nag_ColMajor, $A_{ij}$ is stored in <b>a</b> [( <i>j</i> - 1) $\times$ <b>pda</b> + <i>i</i> - 1].		
If <b>order</b> = Nag_RowMajor, $A_{ij}$ is stored in <b>a</b> [( <i>i</i> - 1) $\times$ <b>pda</b> + <i>j</i> - 1].		
If <b>uplo</b> = Nag_Upper, the upper triangular part of $A$ must be stored and the elements of the array below the diagonal are not referenced.		
If <b>uplo</b> = Nag_Lower, the lower triangular part of $A$ must be stored and the elements of the array above the diagonal are not referenced.		
<i>On exit:</i> the updated matrix $A$ .		
11:	<b>pda</b> – Integer	<i>Input</i>
<i>On entry:</i> the stride separating row or column elements (depending on the value of <b>order</b> ) of the matrix $A$ in the array <b>a</b> .		
<i>Constraint:</i> <b>pda</b> $\geq \max(1, \mathbf{n})$ .		
12:	<b>fail</b> – NagError *	<i>Input/Output</i>
The NAG error argument (see Section 3.6 in the Essential Introduction).		

## 6 Error Indicators and Warnings

### NE\_ALLOC\_FAIL

Dynamic memory allocation failed.

See Section 3.2.1.2 in the Essential Introduction for further information.

**NE\_BAD\_PARAM**

On entry, argument  $\langle value \rangle$  had an illegal value.

**NE\_INT**

On entry, **incx** =  $\langle value \rangle$ .

Constraint: **incx**  $\neq 0$ .

On entry, **incy** =  $\langle value \rangle$ .

Constraint: **incy**  $\neq 0$ .

On entry, **n** =  $\langle value \rangle$ .

Constraint: **n**  $\geq 0$ .

**NE\_INT\_2**

On entry, **pda** =  $\langle value \rangle$ , **n** =  $\langle value \rangle$ .

Constraint: **pda**  $\geq \max(1, n)$ .

**NE\_INTERNAL\_ERROR**

An unexpected error has been triggered by this function. Please contact NAG.

See Section 3.6.6 in the Essential Introduction for further information.

**NE\_NO\_LICENCE**

Your licence key may have expired or may not have been installed correctly.

See Section 3.6.5 in the Essential Introduction for further information.

## 7 Accuracy

The BLAS standard requires accurate implementations which avoid unnecessary over/underflow (see Section 2.7 of Basic Linear Algebra Subprograms Technical (BLAST) Forum (2001)).

## 8 Parallelism and Performance

Not applicable.

## 9 Further Comments

None.

## 10 Example

Perform rank-2 update of real symmetric matrix  $A$  using vectors  $x$  and  $y$ :

$$A \leftarrow A - xy^T - yx^T,$$

where  $A$  is the 4 by 4 matrix given by

$$A = \begin{pmatrix} 4.30 & 4.00 & 0.40 & -0.28 \\ 4.00 & -4.87 & 0.31 & 0.07 \\ 0.40 & 0.31 & -8.02 & -5.95 \\ -0.28 & 0.07 & -5.95 & 0.12 \end{pmatrix},$$

$$x = (2.0, 2.0, 0.2, -0.14)^T \quad \text{and} \quad y = (1.0, 1.0, 0.1, -0.07)^T.$$

The vector  $y$  is stored in every second element of the array **y** (**incy** = 2).

## 10.1 Program Text

```

/* nag_dsyr2 (f16prc) Example Program.
*
* Copyright 2014 Numerical Algorithms Group.
*
* Mark 8, 2005.
*/
#include <stdio.h>
#include <nag.h>
#include <nag_stlib.h>
#include <nagf16.h>
#include <nagx04.h>

int main(void)
{
    /* Scalars */
    double alpha, beta;
    Integer exit_status, i, incx, incy, j, n, pda, xlen, ylen;

    /* Arrays */
    double *a = 0, *x = 0, *y = 0;
    char nag_enum_arg[40];

    /* Nag Types */
    NagError fail;
    Nag_OrderType order;
    Nag_UptoType uplo;
    Nag_MatrixType matrix;

#define NAG_COLUMN_MAJOR
#define A(I, J) a[(J-1)*pda + I - 1]
    order = Nag_ColMajor;
#else
#define A(I, J) a[(I-1)*pda + J - 1]
    order = Nag_RowMajor;
#endif

    exit_status = 0;
    INIT_FAIL(fail);

    printf("nag_dsyr2 (f16prc) Example Program Results\n\n");

    /* Skip heading in data file */
#ifdef _WIN32
    scanf_s("%*[^\n] ");
#else
    scanf("%*[^\n] ");
#endif

    /* Read the problem dimension */
#ifdef _WIN32
    scanf_s("%"NAG_IFMT"%*[^\n] ", &n);
#else
    scanf("%"NAG_IFMT"%*[^\n] ", &n);
#endif

    /* Read the uplo storage parameter */
#ifdef _WIN32
    scanf_s("%39s%*[^\n] ", nag_enum_arg, _countof(nag_enum_arg));
#else
    scanf("%39s%*[^\n] ", nag_enum_arg);
#endif
    /* nag_enum_name_to_value (x04nac).
     * Converts NAG enum member name to value
     */
    uplo = (Nag_UptoType) nag_enum_name_to_value(nag_enum_arg);

    /* Read scalar parameters */

```

```

#define _WIN32
    scanf_s("%lf%lf%*[^\n] ", &alpha, &beta);
#else
    scanf("%lf%lf%*[^\n] ", &alpha, &beta);
#endif
/* Read increment parameters */
#define _WIN32
    scanf_s("%"NAG_IFMT%"NAG_IFMT"%*[^\n] ", &incx, &incy);
#else
    scanf("%"NAG_IFMT%"NAG_IFMT"%*[^\n] ", &incx, &incy);
#endif

pda = n;

xlen = MAX(1, 1 + (n - 1)*ABS(incx));
ylen = MAX(1, 1 + (n - 1)*ABS(incy));

if (n > 0)
{
    /* Allocate memory */
    if (!(a = NAG_ALLOC(pda*n, double)) ||
        !(x = NAG_ALLOC(xlen, double)) ||
        !(y = NAG_ALLOC(ylen, double)))
    {
        printf("Allocation failure\n");
        exit_status = -1;
        goto END;
    }
}
else
{
    printf("Invalid n\n");
    exit_status = 1;
    goto END;
}

/* Input matrix A and vector x */

if (uplo == Nag_Upper)
{
    for (i = 1; i <= n; ++i)
    {
        for (j = i; j <= n; ++j)
#ifdef _WIN32
            scanf_s("%lf", &A(i, j));
#else
            scanf("%lf", &A(i, j));
#endif
#ifdef _WIN32
            scanf_s("%*[^\n] ");
#else
            scanf("%*[^\n] ");
#endif
    }
}
else
{
    for (i = 1; i <= n; ++i)
    {
        for (j = 1; j <= i; ++j)
#ifdef _WIN32
            scanf_s("%lf", &A(i, j));
#else
            scanf("%lf", &A(i, j));
#endif
#ifdef _WIN32
            scanf_s("%*[^\n] ");
#else
            scanf("%*[^\n] ");
#endif
    }
}

```

```

        }
        for (i = 0; i < xlen; ++i)
#ifndef _WIN32
        scanf_s("%lf%*[^\n] ", &x[i]);
#else
        scanf("%lf%*[^\n] ", &x[i]);
#endif
        for (i = 0; i < ylen; ++i)
#ifndef _WIN32
        scanf_s("%lf%*[^\n] ", &y[i]);
#else
        scanf("%lf%*[^\n] ", &y[i]);
#endif

/* nag_dsyr2 (f16prc).
 * Rank two update of real symmetric matrix.
 */
nag_dsyr2(order, uplo, n, alpha, x, incx, y, incy, beta, a, pda,
           &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_dsyr2 (f16prc).\\n%s\\n", fail.message);
    exit_status = 1;
    goto END;
}

if (uplo == Nag_Upper)
{
    matrix = Nag_UpperMatrix;
}
else
{
    matrix = Nag_LowerMatrix;
}
/* Print updated matrix A */
/* nag_gen_real_mat_print (x04cac).
 * Print real general matrix (easy-to-use)
 */
fflush(stdout);
nag_gen_real_mat_print(order, matrix, Nag_NonUnitDiag, n,
                       n, a, pda, "Updated Matrix A", 0, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_gen_real_mat_print (x04cac).\\n%s\\n",
           fail.message);
    exit_status = 1;
    goto END;
}

END:
NAG_FREE(a);
NAG_FREE(x);
NAG_FREE(y);

return exit_status;
}

```

## 10.2 Program Data

```

nag_dsyr2 (f16prc) Example Program Data
 4                               :Value of n
 Nag_Lower                      :Storage of A
 -1.0   1.0                      :Values of alpha and beta
 1   2                           :Values of incx and incy
 4.30
 4.00  -4.87
 0.40   0.31  -8.02
 -0.28   0.07  -5.95   0.12   :End of matrix A

```

```
2.00
2.00
0.20
-0.14          :End of vector x
1.00
0.00
1.00
0.00
0.10
0.00
-0.07         :End of vector y
```

### 10.3 Program Results

nag\_dsyr2 (f16prc) Example Program Results

Updated Matrix A				
	1	2	3	4
1	0.3000			
2	0.0000	-8.8700		
3	0.0000	-0.0900	-8.0600	
4	0.0000	0.3500	-5.9220	0.1004

---