

# NAG Library Function Document

## nag\_rand\_bb\_inc\_init (g05xcc)

### 1 Purpose

nag\_rand\_bb\_inc\_init (g05xcc) initializes the Brownian bridge increments generator nag\_rand\_bb\_inc (g05xdc). It must be called before any calls to nag\_rand\_bb\_inc (g05xdc).

### 2 Specification

```
#include <nag.h>
#include <nagg05.h>

void nag_rand_bb_inc_init (double t0, double tend, const double times[],
                          Integer ntimes, double rcomm[], NagError *fail)
```

### 3 Description

#### 3.1 Brownian Bridge Algorithm

Details on the Brownian bridge algorithm and the Brownian bridge process (sometimes also called a non-free Wiener process) can be found in Section 2.6 in the g05 Chapter Introduction. We briefly recall some notation and definitions.

Fix two times  $t_0 < T$  and let  $(t_i)_{1 \leq i \leq N}$  be any set of time points satisfying  $t_0 < t_1 < t_2 < \dots < t_N < T$ . Let  $(X_{t_i})_{1 \leq i \leq N}$  denote a  $d$ -dimensional Wiener sample path at these time points, and let  $C$  be any  $d$  by  $d$  matrix such that  $CC^T$  is the desired covariance structure for the Wiener process. Each point  $X_{t_i}$  of the sample path is constructed according to the Brownian bridge interpolation algorithm (see Glasserman (2004) or Section 2.6 in the g05 Chapter Introduction). We always start at some fixed point  $X_{t_0} = x \in \mathbb{R}^d$ . If we set  $X_T = x + C\sqrt{T-t_0}Z$  where  $Z$  is any  $d$ -dimensional standard Normal random variable, then  $X$  will behave like a normal (free) Wiener process. However if we fix the terminal value  $X_T = w \in \mathbb{R}^d$ , then  $X$  will behave like a non-free Wiener process.

The Brownian bridge increments generator uses the Brownian bridge algorithm to construct sample paths for the (free or non-free) Wiener process  $X$ , and then uses this to compute the *scaled Wiener increments*

$$\frac{X_{t_1} - X_{t_0}}{t_1 - t_0}, \frac{X_{t_2} - X_{t_1}}{t_2 - t_1}, \dots, \frac{X_{t_N} - X_{t_{N-1}}}{t_N - t_{N-1}}, \frac{X_T - X_{t_N}}{T - t_N}.$$

Such increments can be useful in computing numerical solutions to stochastic differential equations driven by (free or non-free) Wiener processes.

#### 3.2 Implementation

Conceptually, the output of the Wiener increments generator is the same as if nag\_rand\_bb\_init (g05xac) and nag\_rand\_bb (g05xbc) were called first, and the scaled increments then constructed from their output. The implementation adopts a much more efficient approach whereby the scaled increments are computed directly without first constructing the Wiener sample path.

Given the start and end points of the process, the order in which successive interpolation times  $t_j$  are chosen is called the *bridge construction order*. The construction order is given by the array **times**. Further information on construction orders is given in Section 2.6.2 in the g05 Chapter Introduction. For clarity we consider here the common scenario where the Brownian bridge algorithm is used with quasi-random points. If pseudorandom numbers are used instead, these details can be ignored.

Suppose we require the increments of  $P$  Wiener sample paths each of dimension  $d$ . The main input to the Brownian bridge increments generator is then an array of quasi-random points  $Z^1, Z^2, \dots, Z^P$  where each point  $Z^p = (Z_1^p, Z_2^p, \dots, Z_D^p)$  has dimension  $D = d(N + 1)$  or  $D = dN$  depending on whether a

free or non-free Wiener process is required. When `nag_rand_bb_inc` (g05xdc) is called, the  $p$ th sample path for  $1 \leq p \leq P$  is constructed as follows: if a non-free Wiener process is required set  $X_T$  equal to the terminal value  $w$ , otherwise construct  $X_T$  as

$$X_T = X_{t_0} + C\sqrt{T-t_0} \begin{bmatrix} Z_1^p \\ \vdots \\ Z_d^p \end{bmatrix}$$

where  $C$  is the matrix described in Section 3.1. The array **times** holds the remaining time points  $t_1, t_2, \dots, t_N$  in the order in which the bridge is to be constructed. For each  $j = 1, \dots, N$  set  $r = \mathbf{times}[j-1]$ , find

$$q = \max\{t_0, \mathbf{times}[i-1] : 1 \leq i < j, \mathbf{times}[i-1] < r\}$$

and

$$s = \min\{T, \mathbf{times}[i-1] : 1 \leq i < j, \mathbf{times}[i-1] > r\}$$

and construct the point  $X_r$  as

$$X_r = \frac{X_q(s-r) + X_s(r-q)}{s-q} + C\sqrt{\frac{(s-r)(r-q)}{(s-q)}} \begin{bmatrix} Z_{jd-ad+1}^p \\ \vdots \\ Z_{jd-ad+d}^p \end{bmatrix}$$

where  $a = 0$  or  $a = 1$  depending on whether a free or non-free Wiener process is required. The function `nag_rand_bb_make_bridge_order` (g05xec) can be used to initialize the **times** array for several predefined bridge construction orders. Lastly, the scaled Wiener increments

$$\frac{X_{t_1} - X_{t_0}}{t_1 - t_0}, \frac{X_{t_2} - X_{t_1}}{t_2 - t_1}, \dots, \frac{X_{t_N} - X_{t_{N-1}}}{t_N - t_{N-1}}, \frac{X_T - X_{t_N}}{T - t_N}$$

are computed.

## 4 References

Glasserman P (2004) *Monte Carlo Methods in Financial Engineering* Springer

## 5 Arguments

1: **t0** – double *Input*  
*On entry:* the starting value  $t_0$  of the time interval.

2: **tend** – double *Input*  
*On entry:* the end value  $T$  of the time interval.  
*Constraint:* **tend** > **t0**.

3: **times[ntimes]** – const double *Input*  
*On entry:* the points in the time interval  $(t_0, T)$  at which the Wiener process is to be constructed. The order in which points are listed in **times** determines the bridge construction order. The function `nag_rand_bb_make_bridge_order` (g05xec) can be used to create predefined bridge construction orders from a set of input times.

*Constraints:*

$$\begin{aligned} &\mathbf{t0} < \mathbf{times}[i-1] < \mathbf{tend}, \text{ for } i = 1, 2, \dots, \mathbf{ntimes}; \\ &\mathbf{times}[i-1] \neq \mathbf{times}[j-1], \text{ for } i, j = 1, 2, \dots, \mathbf{ntimes} \text{ and } i \neq j. \end{aligned}$$

- 4: **ntimes** – Integer *Input*  
*On entry:* the length of **times**, denoted by  $N$  in Section 3.1.  
*Constraint:* **ntimes**  $\geq 1$ .
- 5: **rcomm**[ $12 \times (\mathbf{ntimes} + 1)$ ] – double *Communication Array*  
*On exit:* communication array, used to store information between calls to nag\_rand\_bb\_inc (g05xdc). This array MUST NOT be directly modified.
- 6: **fail** – NagError \* *Input/Output*  
The NAG error argument (see Section 3.6 in the Essential Introduction).

## 6 Error Indicators and Warnings

### NE\_ALLOC\_FAIL

Dynamic memory allocation failed.  
See Section 3.2.1.2 in the Essential Introduction for further information.

### NE\_BAD\_PARAM

On entry, argument  $\langle value \rangle$  had an illegal value.

### NE\_INT

On entry, **ntimes** =  $\langle value \rangle$ .  
*Constraint:* **ntimes**  $\geq 1$ .

### NE\_INTERNAL\_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.  
See Section 3.6.6 in the Essential Introduction for further information.

### NE\_NO\_LICENCE

Your licence key may have expired or may not have been installed correctly.  
See Section 3.6.5 in the Essential Introduction for further information.

### NE\_REAL

On entry, **tend** =  $\langle value \rangle$  and **t0** =  $\langle value \rangle$ .  
*Constraint:* **tend**  $>$  **t0**.

### NE\_REAL\_ARRAY

On entry, **times**[ $i - 1$ ] = **times**[ $j - 1$ ] =  $\langle value \rangle$ , for  $i = \langle value \rangle$  and  $j = \langle value \rangle$ .  
*Constraint:* all elements of **times** must be unique.

On entry, **times**[ $\langle value \rangle$ ] =  $\langle value \rangle$ , **t0** =  $\langle value \rangle$  and **tend** =  $\langle value \rangle$ .  
*Constraint:* **t0**  $<$  **times**[ $i - 1$ ]  $<$  **tend** for all  $i$ .

## 7 Accuracy

Not applicable.

## 8 Parallelism and Performance

Not applicable.

## 9 Further Comments

The efficient implementation of a Brownian bridge algorithm requires the use of a workspace array called the *working stack*. Since previously computed points will be used to interpolate new points, they should be kept close to the hardware processing units so that the data can be accessed quickly. Ideally the whole stack should be held in hardware cache. Different bridge construction orders may require different amounts of working stack. Indeed, a naive bridge algorithm may require a stack of size  $\frac{N}{4}$  or even  $\frac{N}{2}$ , which could be very inefficient when  $N$  is large. `nag_rand_bb_inc_init` (g05xcc) performs a detailed analysis of the bridge construction order specified by **times**. Heuristics are used to find an execution strategy which requires a small working stack, while still constructing the bridge in the order required.

## 10 Example

The following example program calls `nag_rand_bb_init` (g05xac) and `nag_rand_bb` (g05xbc) to generate two sample paths from a two-dimensional free Wiener process. It then calls `nag_rand_bb_inc_init` (g05xcc) and `nag_rand_bb_inc` (g05xdc) with the same input arguments to obtain the scaled increments of the Wiener sample paths. Lastly, the program prints the Wiener sample paths from `nag_rand_bb` (g05xbc), the scaled increments from `nag_rand_bb_inc` (g05xdc), and the cumulative sum of the unscaled increments side by side. Note that the cumulative sum of the unscaled increments is identical to the output of `nag_rand_bb` (g05xbc).

Please see Section 10 in `nag_rand_bb_inc` (g05xdc) for additional examples.

### 10.1 Program Text

```

/* nag_rand_bb_inc_init (g05xcc) Example Program.
 *
 * Copyright 2014 Numerical Algorithms Group.
 *
 * Mark 24, 2013.
 */
#include <stdio.h>
#include <math.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagg05.h>
#include <nagf07.h>
int get_z(Integer nelements, double * z);
void display_results(Nag_OrderType order, Integer npaths, double t0,
                   double tend, Integer ntimes, double intime[],
                   Integer d, double start[], double bb[],
                   double bd[], Integer pdb);

#define CHECK_FAIL(name, fail) if(fail.code != NE_NOERROR) { \
    printf("Error calling %s\n%s\n", name, fail.message); exit_status=-1; goto END;}

int main(void)
{
#define C(I,J) c[(J-1)*d + I-1]
    Integer exit_status = 0;
    NagError fail;
    /* Scalars */
    double t0, tend;
    Integer a, d, pdb, pdc, pdz, nmove, npaths, ntimes, i ;
    /* Arrays */
    double *bb = 0, *c = 0, *intime = 0, *rcommb = 0, *start = 0,
           *term = 0, *times = 0, *zb = 0, *rcommd = 0, *zd = 0,
           *diff = 0, *bd = 0;
    Integer *move = 0;
    INIT_FAIL(fail);

    /* Parameters which determine the bridge */
    ntimes = 10;
    t0 = 0.0;
    npaths = 2;

```

```

a = 0;
nmove = 0;
d = 2;
pdz = npaths;
pdb = npaths;
pdc = d;
/* Allocate memory */
if (
    !( intime = NAG_ALLOC((ntimes), double)) ||
    !( times = NAG_ALLOC((ntimes), double)) ||
    !( rcommb = NAG_ALLOC((12 * (ntimes + 1)), double)) ||
    !( rcommd = NAG_ALLOC((12 * (ntimes + 1)), double)) ||
    !( start = NAG_ALLOC(d, double)) ||
    !( term = NAG_ALLOC(d, double)) ||
    !( diff = NAG_ALLOC(d, double)) ||
    !( c = NAG_ALLOC(pdc * d, double)) ||
    !( zb = NAG_ALLOC(pdz * d * (ntimes+1-a), double)) ||
    !( zd = NAG_ALLOC(pdz * d * (ntimes+1-a), double)) ||
    !( bb = NAG_ALLOC(pdb * d * (ntimes+1), double)) ||
    !( bd = NAG_ALLOC(pdb * d * (ntimes+1), double)) ||
    !( move = NAG_ALLOC(nmove, Integer))
)
{
    printf("Allocation failure\n");
    exit_status = -1;
    goto END;
}

/* Fix the time points at which the bridge is required */
for ( i=0; i<ntimes; i++) {
    intime[i] = t0 + (double)(i+1);
}
tend = t0 + (double)(ntimes + 1);

/* g05xec. Creates a Brownian bridge construction order out of a set of */
/* input times */
nag_rand_bb_make_bridge_order(Nag_RLRoundDown, t0, tend, ntimes, intime,
                             nmove, move, times, &fail);
CHECK_FAIL("nag_rand_bb_make_bridge_order",fail);

/* g05xac. Initializes the Brownian bridge generator */
nag_rand_bb_init(t0, tend, times, ntimes, rcommb, &fail);
CHECK_FAIL("nag_rand_bb_init",fail);

start[0] = 0.0, start[1] = 2.0;
/* We want the following covariance matrix*/
C( 1,1 ) = 6.0;
C( 2,1 ) = -1.0;
C( 1,2 ) = -1.0;
C( 2,2 ) = 5.0;
/* nag_rand_bb uses Cholesky factorization of the covariance matrix C */

/* f07fdc. Cholesky factorization of real positive definite matrix */
nag_dpotrf(Nag_ColMajor, Nag_Lower, d, c, d, &fail);
CHECK_FAIL("nag_dpotrf",fail);

/* Generate the random numbers */
if( get_z(npaths*d*(ntimes+1-a), zb) != 0)
{
    printf("Error generating random numbers\n");
    exit_status = -1;
    goto END;
}

/* Copy the random numbers for call to g05xdc */
for (i=0 ; i<npaths*d*(ntimes+1-a); i++) zd[i] = zb[i];

/* g05xbc. Generate paths for a free or non-free Wiener process using the */
/* Brownian bridge algorithm */
nag_rand_bb(Nag_ColMajor, npaths, d, start, a, term, zb, pdz, c, pdc, bb, pdb,
            rcommb, &fail);

```

```

CHECK_FAIL("nag_rand_bb",fail);

/* nag_rand_bb_inc_init (g05xcc). Initialises the generator which backs out
 * the increments of sample paths generated by a Brownian bridge algorithm */
nag_rand_bb_inc_init(t0, tend, times, ntimes, rcommd, &fail);
CHECK_FAIL("nag_rand_bb_inc_init",fail);

/* g05xdc. Backs out the increments from sample paths generated by a */
/* Brownian bridge algorithm */
nag_rand_bb_inc(Nag_ColMajor, npaths, d, a, diff, zd, pdz, c, pdc, bd, pdb,
               rcommd, &fail);
CHECK_FAIL("nag_rand_bb_inc",fail);

/* Display the results*/
display_results(Nag_ColMajor, npaths, t0, tend,
               ntimes, intime, d, start, bb, bd, pdb);
END:
;
NAG_FREE(bb);
NAG_FREE(bd);
NAG_FREE(c);
NAG_FREE(intime);
NAG_FREE(rcommb);
NAG_FREE(rcommd);
NAG_FREE(start);
NAG_FREE(term);
NAG_FREE(diff);
NAG_FREE(times);
NAG_FREE(zb);
NAG_FREE(zd);
NAG_FREE(move);
return exit_status;
#undef C
}

int get_z(Integer nelements, double * z)
{
    NagError fail;
    Integer lseed, lstate, exit_status=0;
    /* Arrays */
    Integer seed[1];
    Integer state[80];
    lstate = 80;
    lseed = 1;
    INIT_FAIL(fail);

    /* We now need to generate the input pseudorandom numbers */
    seed[0] = 1023401;
    /* g05kfc. Initializes a pseudorandom number generator */
    /* to give a repeatable sequence */
    nag_rand_init_repeatable(Nag_MRG32k3a, 0, seed, lseed, state, &lstate, &fail);
    CHECK_FAIL("nag_rand_init_repeatable",fail);

    /* nag_rand_normal. Generates a vector of pseudorandom numbers from */
    /* a Normal distribution */
    nag_rand_normal(nelements, 0.0, 1.0, state, z, &fail);
    CHECK_FAIL("nag_rand_normal",fail);

    END: ;
    return exit_status;
}

void display_results(Nag_OrderType order, Integer npaths, double t0,
                   double tend, Integer ntimes, double intime[],
                   Integer d, double start[], double bb[],
                   double bd[], Integer pdb)
{
    // Order consistend with Nag_RowMajor
    #define BB(I,J) bb[(I-1)*pdb + J-1]
    #define BD(I,J) bd[(I-1)*pdb + J-1]

```

```

#define CUM(I)  cum[I-1]

Integer i,p,k;
double *cum = 0;
if (
    !(cum = NAG_ALLOC(d, double)) ) {
    printf("Error allocating memory in display_results\n");
    return;
}

printf("nag_rand_bb_inc_init (g05xcc) Example Program Results\n\n");
for ( p=1; p<=npaths; p++) {
    printf("Weiner Path  ");
    printf("%3"NAG_IFMT" ", p);
    printf(",  ");
    printf("%3"NAG_IFMT" ", ntimes + 1);
    printf(" time steps,  ");
    printf("%3"NAG_IFMT" ",d);
    printf(" dimensions \n");
    printf("          Output of g05xbc          Output of g05xdc          Sum of g05xdc \n");

    for(k=1; k<=d; k++) CUM(k) = start[k-1];
    /* Print first point */
    i = 0;
    printf("%2"NAG_IFMT" ", i+1);
    if (order==Nag_RowMajor) {
        for(k=1; k<=d; k++) CUM(k) += BD(p, k) * (intime[i] - t0);
        for(k=1; k<=d; k++) printf("  %8.4f", BB(p, k));
        for(k=1; k<=d; k++) printf("  %8.4f", BD(p, k));
        for(k=1; k<=d; k++) printf("  %8.4f", CUM(k));
    } else {
        for(k=1; k<=d; k++) CUM(k) += BD(k, p) * (intime[i] - t0);
        for(k=1; k<=d; k++) printf("  %8.4f", BB(k, p));
        for(k=1; k<=d; k++) printf("  %8.4f", BD(k, p));
        for(k=1; k<=d; k++) printf("  %8.4f", CUM(k));
    }
    printf("\n");

    /* Print intermediate points */
    for (i=1; i<ntimes; i++) {
        printf("%2"NAG_IFMT" ", i+1);
        if (order==Nag_RowMajor) {
            for(k=1; k<=d; k++) CUM(k)+=BD(p,i*d+k)*(intime[i]-intime[i-1]);
            for(k=1; k<=d; k++) printf("  %8.4f", BB(p, i*d+k));
            for(k=1; k<=d; k++) printf("  %8.4f", BD(p, i*d+k));
            for(k=1; k<=d; k++) printf("  %8.4f", CUM(k));
        } else {
            for(k=1; k<=d; k++) CUM(k)+=BD(i*d+k,p)*(intime[i]-intime[i-1]);
            for(k=1; k<=d; k++) printf("  %8.4f", BB(i*d+k, p));
            for(k=1; k<=d; k++) printf("  %8.4f", BD(i*d+k, p));
            for(k=1; k<=d; k++) printf("  %8.4f", CUM(k));
        }
        printf("\n");
    }

    /* Print final point */
    i = ntimes;
    printf("%2"NAG_IFMT" ", i+1);
    if (order==Nag_RowMajor) {
        for(k=1; k<=d; k++) CUM(k) += BD(p, i*d+k)*(tend - intime[i-1]);
        for(k=1; k<=d; k++) printf("  %8.4f", BB(p, i*d+k));
        for(k=1; k<=d; k++) printf("  %8.4f", BD(p, i*d+k));
        for(k=1; k<=d; k++) printf("  %8.4f", CUM(k));
    } else {
        for(k=1; k<=d; k++) CUM(k) += BD(i*d+k, p)*(tend - intime[i-1]);
        for(k=1; k<=d; k++) printf("  %8.4f", BB(i*d+k, p));
        for(k=1; k<=d; k++) printf("  %8.4f", BD(i*d+k, p));
        for(k=1; k<=d; k++) printf("  %8.4f", CUM(k));
    }
}

```

```

    printf("\n\n");
}
NAG_FREE(cum);
}

```

## 10.2 Program Data

None.

## 10.3 Program Results

nag\_rand\_bb\_inc\_init (g05xcc) Example Program Results

Weiner Path		1	,	11	time steps,	2	dimensions		
	Output of	g05xbc		Output of	g05xdc		Sum of	g05xdc	
1	-2.2323	1.6656		-2.2323	-0.3344		-2.2323	1.6656	
2	-5.2301	1.2812		-2.9978	-0.3844		-5.2301	1.2812	
3	-0.9025	-1.2421		4.3276	-2.5234		-0.9025	-1.2421	
4	-3.6799	-0.3972		-2.7774	0.8449		-3.6799	-0.3972	
5	-6.5789	-2.0358		-2.8990	-1.6386		-6.5789	-2.0358	
6	-11.2879	-1.1972		-4.7090	0.8385		-11.2879	-1.1972	
7	-8.8959	-1.6751		2.3919	-0.4779		-8.8959	-1.6751	
8	-9.7103	-2.0523		-0.8144	-0.3772		-9.7103	-2.0523	
9	-8.5720	-3.3306		1.1383	-1.2783		-8.5720	-3.3306	
10	-9.8245	-3.2035		-1.2524	0.1271		-9.8245	-3.2035	
11	-4.9941	-8.3506		4.8304	-5.1471		-4.9941	-8.3506	

Weiner Path		2	,	11	time steps,	2	dimensions		
	Output of	g05xbc		Output of	g05xdc		Sum of	g05xdc	
1	-1.4101	0.0576		-1.4101	-1.9424		-1.4101	0.0576	
2	-3.5738	0.2519		-2.1637	0.1943		-3.5738	0.2519	
3	-5.2528	1.7232		-1.6790	1.4713		-5.2528	1.7232	
4	-0.8540	1.0897		4.3988	-0.6335		-0.8540	1.0897	
5	0.4905	-0.9098		1.3445	-1.9995		0.4905	-0.9098	
6	2.3322	1.3415		1.8417	2.2514		2.3322	1.3415	
7	3.0105	-4.3312		0.6783	-5.6728		3.0105	-4.3312	
8	2.6776	-3.4437		-0.3329	0.8875		2.6776	-3.4437	
9	0.6546	-2.7291		-2.0230	0.7146		0.6546	-2.7291	
10	-1.3175	-3.8166		-1.9721	-1.0875		-1.3175	-3.8166	
11	-3.0214	-3.5439		-1.7039	0.2727		-3.0214	-3.5439	

---