

NAG Library Function Document

nag_tsa_options_init (g13bxc)

1 Purpose

nag_tsa_options_init (g13bxc) initializes the structure **options**. This structure is used by some functions in Chapter g13. This function must be called before any direct assignments are made to members of the options structure.

2 Specification

```
#include <nag.h>
#include <nagg13.h>
void nag_tsa_options_init (Nag_G13_Opt *options)
```

3 Description

A number of optional arguments are applicable to several functions in Chapter g13. These arguments are set by means of a structure of type Nag_G13_Opt. This initialization function sets the members of the structure to null values indicating that the default values should be used for these arguments. If argument values other than the default values are required, they must be assigned to the appropriate members of the options structure in the calling program.

This assignment of optional arguments values to the options structure **must** be preceded by a call to nag_tsa_options_init (g13bxc).

4 References

None.

5 Arguments

1: **options** – Nag_G13_Opt * *Output*
On exit: the initialized option structure.

6 Error Indicators and Warnings

None.

7 Accuracy

Not applicable.

8 Parallelism and Performance

Not applicable.

9 Further Comments

None.

10 Example

See `nag_tsa_multi_inp_model_estim` (g13bec) and `nag_tsa_multi_inp_model_forecast` (g13bjc) for examples of how `nag_tsa_options_init` (g13bxc) is used.
