

NAG Library Routine Document

C06EAF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

C06EAF calculates the discrete Fourier transform of a sequence of n real data values. (No extra workspace required.)

2 Specification

```
SUBROUTINE C06EAF (X, N, IFAIL)
  INTEGER          N, IFAIL
  REAL (KIND=nag_wp) X(N)
```

3 Description

Given a sequence of n real data values x_j , for $j = 0, 1, \dots, n - 1$, C06EAF calculates their discrete Fourier transform defined by

$$\hat{z}_k = \frac{1}{\sqrt{n}} \sum_{j=0}^{n-1} x_j \times \exp\left(-i \frac{2\pi jk}{n}\right), \quad k = 0, 1, \dots, n - 1.$$

(Note the scale factor of $\frac{1}{\sqrt{n}}$ in this definition.) The transformed values \hat{z}_k are complex, but they form a Hermitian sequence (i.e., \hat{z}_{n-k} is the complex conjugate of \hat{z}_k), so they are completely determined by n real numbers (see also the C06 Chapter Introduction).

To compute the inverse discrete Fourier transform defined by

$$\hat{w}_k = \frac{1}{\sqrt{n}} \sum_{j=0}^{n-1} x_j \times \exp\left(+i \frac{2\pi jk}{n}\right),$$

this routine should be followed by a call of C06GBF to form the complex conjugates of the \hat{z}_k .

C06EAF uses the fast Fourier transform (FFT) algorithm (see Brigham (1974)). There are some restrictions on the value of n (see Section 5).

4 References

Brigham E O (1974) *The Fast Fourier Transform* Prentice–Hall

5 Parameters

1: X(N) – REAL (KIND=nag_wp) array *Input/Output*

On entry: if X is declared with bounds (0 : N - 1) in the subroutine from which C06EAF is called, then X(j) must contain x_j , for $j = 0, 1, \dots, n - 1$.

On exit: the discrete Fourier transform stored in Hermitian form. If the components of the transform \hat{z}_k are written as $a_k + ib_k$, and if X is declared with bounds (0 : N - 1) in the subroutine from which C06EAF is called, then for $0 \leq k \leq n/2$, a_k is contained in X(k), and for $1 \leq k \leq (n - 1)/2$, b_k is contained in X(n - k). (See also Section 2.1.2 in the C06 Chapter Introduction and Section 10.)

2: N – INTEGER *Input*

On entry: n , the number of data values. The largest prime factor of N must not exceed 19, and the total number of prime factors of N , counting repetitions, must not exceed 20.

Constraint: $N > 1$.

3: IFAIL – INTEGER *Input/Output*

On entry: IFAIL must be set to 0, -1 or 1. If you are unfamiliar with this parameter you should refer to Section 3.3 in the Essential Introduction for details.

For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, if you are not familiar with this parameter, the recommended value is 0. **When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.**

On exit: IFAIL = 0 unless the routine detects an error or a warning has been flagged (see Section 6).

6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL = 1

At least one of the prime factors of N is greater than 19.

IFAIL = 2

N has more than 20 prime factors.

IFAIL = 3

On entry, $N \leq 1$.

IFAIL = 4

An unexpected error has occurred in an internal call. Check all subroutine calls and array dimensions. Seek expert help.

IFAIL = -99

An unexpected error has been triggered by this routine. Please contact NAG.

See Section 3.8 in the Essential Introduction for further information.

IFAIL = -399

Your licence key may have expired or may not have been installed correctly.

See Section 3.7 in the Essential Introduction for further information.

IFAIL = -999

Dynamic memory allocation failed.

See Section 3.6 in the Essential Introduction for further information.

7 Accuracy

Some indication of accuracy can be obtained by performing a subsequent inverse transform and comparing the results with the original sequence (in exact arithmetic they would be identical).

8 Parallelism and Performance

Not applicable.

9 Further Comments

The time taken is approximately proportional to $n \times \log(n)$, but also depends on the factorization of n . C06EAF is faster if the only prime factors of n are 2, 3 or 5; and fastest of all if n is a power of 2.

On the other hand, C06EAF is particularly slow if n has several unpaired prime factors, i.e., if the ‘square-free’ part of n has several factors. For such values of n , C06FAF (which requires additional real workspace) is considerably faster.

10 Example

This example reads in a sequence of real data values and prints their discrete Fourier transform (as computed by C06EAF), after expanding it from Hermitian form into a full complex sequence. It then performs an inverse transform using C06GBF followed by C06EBF, and prints the sequence so obtained alongside the original data values.

10.1 Program Text

```

Program c06eafe

!      C06EAF Example Program Text

!      Mark 25 Release. NAG Copyright 2014.

!      .. Use Statements ..
Use nag_library, Only: c06eaf, c06ebf, c06gbf, c06gsf, nag_wp
!      .. Implicit None Statement ..
Implicit None
!      .. Parameters ..
Integer, Parameter          :: nin = 5, nout = 6
!      .. Local Scalars ..
Integer                     :: ieof, ifail, j, m, n
!      .. Local Arrays ..
Real (Kind=nag_wp), Allocatable :: a(:), b(:), x(:), xx(:)
!      .. Executable Statements ..
Write (nout,*) 'C06EAF Example Program Results'
!      Skip heading in data file
Read (nin,*)

loop: Do
  Read (nin,*,Iostat=ieof) n
  If (ieof<0) Exit loop
  Allocate (a(0:n-1),b(0:n-1),x(0:n-1),xx(0:n-1))
  Read (nin,*) x(0:n-1)
  xx(0:n-1) = x(0:n-1)

!      ifail: behaviour on error exit
!      =0 for hard exit, =1 for quiet-soft, =-1 for noisy-soft
  ifail = 0
  Call c06eaf(x,n,ifail)

  Write (nout,*)
  Write (nout,*) 'Components of discrete Fourier transform'
  Write (nout,*)
  Write (nout,*) '          Real          Imag'
  Write (nout,*)

```

```

!      Convert x to separated real and imaginary parts for printing.
      ifail = 0
      m = 1
      Call c06gsf(m,n,x,a,b,ifail)
      Write (nout,99999)(j,a(j),b(j),j=0,n-1)

      Call c06gbf(x,n,ifail)
      Call c06ebf(x,n,ifail)

      Write (nout,*)
      Write (nout,*) 'Original sequence as restored by inverse transform'
      Write (nout,*)
      Write (nout,*) '          Original   Restored'
      Write (nout,*)
      Write (nout,99999)(j,xx(j),x(j),j=0,n-1)
      Deallocate (a,b,x,xx)
      End Do loop

99999 Format (1X,I5,2F10.5)
      End Program c06eafe

```

10.2 Program Data

```

C06EAF Example Program Data
  7          : n
  0.34907
  0.54890
  0.74776
  0.94459
  1.13850
  1.32850
  1.51370   : x

```

10.3 Program Results

C06EAF Example Program Results

Components of discrete Fourier transform

	Real	Imag
0	2.48361	0.00000
1	-0.26599	0.53090
2	-0.25768	0.20298
3	-0.25636	0.05806
4	-0.25636	-0.05806
5	-0.25768	-0.20298
6	-0.26599	-0.53090

Original sequence as restored by inverse transform

	Original	Restored
0	0.34907	0.34907
1	0.54890	0.54890
2	0.74776	0.74776
3	0.94459	0.94459
4	1.13850	1.13850
5	1.32850	1.32850
6	1.51370	1.51370
