NAG Library Routine Document

C06FBF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

C06FBF calculates the discrete Fourier transform of a Hermitian sequence of n complex data values (using a work array for extra speed).

2 Specification

```
SUBROUTINE CO6FBF (X, N, WORK, IFAIL)
INTEGER N, IFAIL
REAL (KIND=nag_wp) X(N), WORK(N)
```

3 Description

Given a Hermitian sequence of n complex data values z_j (i.e., a sequence such that z_0 is real and z_{n-j} is the complex conjugate of z_j , for j = 1, 2, ..., n - 1), C06FBF calculates their discrete Fourier transform defined by

$$\hat{x}_k = \frac{1}{\sqrt{n}} \sum_{j=0}^{n-1} z_j \times \exp\left(-i\frac{2\pi jk}{n}\right), \quad k = 0, 1, \dots, n-1.$$

(Note the scale factor of $\frac{1}{\sqrt{n}}$ in this definition.) The transformed values \hat{x}_k are purely real (see also the C06 Chapter Introduction).

To compute the inverse discrete Fourier transform defined by

$$\hat{y}_k = \frac{1}{\sqrt{n}} \sum_{j=0}^{n-1} z_j \times \exp\left(+i \frac{2\pi j k}{n}\right),$$

this routine should be preceded by forming the complex conjugates of the \hat{z}_k ; that is, x(k) = -x(k), for k = n/2 + 2, ..., n.

C06FBF uses the fast Fourier transform (FFT) algorithm (see Brigham (1974)). There are some restrictions on the value of n (see Section 5).

4 References

Brigham E O (1974) The Fast Fourier Transform Prentice-Hall

5 Parameters

1: X(N) - REAL (KIND=nag_wp) array

On entry: the sequence to be transformed stored in Hermitian form. If the data values z_j are written as $x_j + iy_j$, and if X is declared with bounds (0: N - 1) in the subroutine from which C06FBF is called, then for $0 \le j \le n/2$, x_j is contained in X(j), and for $1 \le j \le (n-1)/2$, y_j is contained in X(n - j). (See also Section 2.1.2 in the C06 Chapter Introduction and Section 10.)

On exit: the components of the discrete Fourier transform \hat{x}_k . If X is declared with bounds (0: N-1) in the subroutine from which C06FBF is called, then \hat{x}_k is stored in X(k), for k = 0, 1, ..., n-1.

Input/Output

2: N – INTEGER

On entry: *n*, the number of data values. The largest prime factor of N must not exceed 19, and the total number of prime factors of N, counting repetitions, must not exceed 20.

Constraint: N > 1.

- 3: WORK(N) REAL (KIND=nag_wp) array
- 4: IFAIL INTEGER

On entry: IFAIL must be set to 0, -1 or 1. If you are unfamiliar with this parameter you should refer to Section 3.3 in the Essential Introduction for details.

For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, if you are not familiar with this parameter, the recommended value is 0. When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.

On exit: IFAIL = 0 unless the routine detects an error or a warning has been flagged (see Section 6).

6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL = 1

At least one of the prime factors of N is greater than 19.

 $\mathrm{IFAIL}=2$

N has more than 20 prime factors.

IFAIL = 3

On entry, $N \leq 1$.

IFAIL = 4

An unexpected error has occurred in an internal call. Check all subroutine calls and array dimensions. Seek expert help.

IFAIL = -99

An unexpected error has been triggered by this routine. Please contact NAG.

See Section 3.8 in the Essential Introduction for further information.

IFAIL = -399

Your licence key may have expired or may not have been installed correctly.

See Section 3.7 in the Essential Introduction for further information.

IFAIL = -999

Dynamic memory allocation failed.

See Section 3.6 in the Essential Introduction for further information.

Input

Workspace Input/Output

7 Accuracy

Some indication of accuracy can be obtained by performing a subsequent inverse transform and comparing the results with the original sequence (in exact arithmetic they would be identical).

8 Parallelism and Performance

Not applicable.

9 Further Comments

The time taken is approximately proportional to $n \times \log(n)$, but also depends on the factorization of n. C06FBF is faster if the only prime factors of n are 2, 3 or 5; and fastest of all if n is a power of 2.

10 Example

This example reads in a sequence of real data values which is assumed to be a Hermitian sequence of complex data values stored in Hermitian form. The input sequence is expanded into a full complex sequence and printed alongside the original sequence. The discrete Fourier transform (as computed by C06FBF) is printed out. It then performs an inverse transform using C06FAF and conjugation, and prints the sequence so obtained alongside the original data values.

10.1 Program Text

Program c06fbfe

```
1
     CO6FBF Example Program Text
     Mark 25 Release. NAG Copyright 2014.
1
1
      .. Use Statements ..
     Use nag_library, Only: cO6faf, cO6fbf, cO6gbf, cO6gsf, nag_wp
1
      .. Implicit None Statement ..
      Implicit None
1
      .. Parameters ..
                                        :: nin = 5, nout = 6
     Integer, Parameter
1
      .. Local Scalars ..
                                        :: ieof, ifail, j, m, n
      Integer
1
      .. Local Arrays ..
     Real (Kind=nag_wp), Allocatable :: u(:), v(:), work(:), x(:), xx(:)
      .. Executable Statements ..
1
     Write (nout,*) 'CO6FBF Example Program Results'
     Skip heading in data file
1
     Read (nin,*)
loop: Do
        Read (nin,*,Iostat=ieof) n
        If (ieof<0) Exit loop
        Allocate (u(0:n-1), v(0:n-1), x(0:n-1), xx(0:n-1), work(n))
        Read (nin,*) x(0:n-1)
        xx(0:n-1) = x(0:n-1)
1
        Convert x to separated real and imaginary parts for printing.
        ifail = 0
        m = 1
        Call c06gsf(m,n,x,u,v,ifail)
!
        ifail: behaviour on error exit
1
               =0 for hard exit, =1 for quiet-soft, =-1 for noisy-soft
        ifail = 0
        Call c06fbf(x,n,work,ifail)
        Write (nout,*)
        Write (nout,*) 'Original sequence and corresponding complex sequence'
        Write (nout,*)
        Write (nout,*) '
                                                 Real
                                                            Imaq'
                                  Data
```

```
Write (nout,*)
        Write (nout,99999)(j,xx(j),' ',u(j),v(j),j=0,n-1)
        Write (nout,*)
        Write (nout,*) 'Components of discrete Fourier transform'
       Write (nout,*)
       Write (nout,99998)(j,x(j),j=0,n-1)
        Call c06faf(x,n,work,ifail)
        Call c06gbf(x,n,ifail)
       Write (nout,*)
        Write (nout,*) 'Original sequence as restored by inverse transform'
        Write (nout,*)
       Write (nout,*) '
                               Original Restored'
       Write (nout,*)
       Write (nout,99997)(j,xx(j),x(j),j=0,n-1)
        Deallocate (u,v,x,xx,work)
     End Do loop
99999 Format (1X, I5, F10.5, A, 2F10.5)
99998 Format (1X, I5, F10.5)
99997 Format (1X, I5, 2F10.5)
   End Program cO6fbfe
```

10.2 Program Data

CO6FBF Example Program Data 7 : n 0.34907 0.54890 0.74776 0.94459 1.13850 1.32850 1.51370 : x 10.3 Program Results

CO6FBF Example Program Results

Original sequence and corresponding complex sequence

	Data	Real	Imag
0 1 2 3 4 5 6	0.34907 0.54890 0.74776 0.94459 1.13850 1.32850 1.51370	0.34907 0.54890 0.74776 0.94459 0.94459 0.74776 0.54890	0.00000 1.51370 1.32850 1.13850 -1.13850 -1.32850 -1.51370

Components of discrete Fourier transform

0	1.82616
1	1.86862
2	-0.01750
3	0.50200
4	-0.59873
5	-0.03144
6	-2.62557

Original sequence as restored by inverse transform

Original Restored 0 0.34907 0.34907 1 0.54890 0.54890

2	0.74776	0.74776
3	0.94459	0.94459
4	1.13850	1.13850
5	1.32850	1.32850
6	1.51370	1.51370