

NAG Library Routine Document

F06PQF (DSPR)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

F06PQF (DSPR) computes the rank-1 update of a real symmetric matrix stored in packed form.

2 Specification

```
SUBROUTINE F06PQF (UPLO, N, ALPHA, X, INCX, AP)
  INTEGER          N, INCX
  REAL (KIND=nag_wp) ALPHA, X(*), AP(*)
  CHARACTER(1)    UPLO
```

The routine may be called by its BLAS name *dspr*.

3 Description

F06PQF (DSPR) performs the symmetric rank-1 update operation

$$A \leftarrow \alpha x x^T + A,$$

where A is an n by n real symmetric matrix, stored in packed form, x is an n -element real vector, and α is a real scalar.

4 References

None.

5 Parameters

- | | | |
|----|---|--------------|
| 1: | UPLO – CHARACTER(1) | <i>Input</i> |
| | <i>On entry:</i> specifies whether the upper or lower triangular part of A is stored. | |
| | UPLO = 'U'
The upper triangular part of A is stored. | |
| | UPLO = 'L'
The lower triangular part of A is stored. | |
| | <i>Constraint:</i> UPLO = 'U' or 'L'. | |
| 2: | N – INTEGER | <i>Input</i> |
| | <i>On entry:</i> n , the order of the matrix A . | |
| | <i>Constraint:</i> $N \geq 0$. | |
| 3: | ALPHA – REAL (KIND=nag_wp) | <i>Input</i> |
| | <i>On entry:</i> the scalar α . | |
| 4: | X(*) – REAL (KIND=nag_wp) array | <i>Input</i> |
| | Note: the dimension of the array X must be at least $\max(1, 1 + (N - 1) \times INCX)$. | |
| | <i>On entry:</i> the n -element vector x . | |

If $\text{INCX} > 0$, x_i must be stored in $X(1 + (i - 1) \times \text{INCX})$, for $i = 1, 2, \dots, N$.

If $\text{INCX} < 0$, x_i must be stored in $X(1 - (N - i) \times \text{INCX})$, for $i = 1, 2, \dots, N$.

Intermediate elements of X are not referenced.

5: INCX – INTEGER

Input

On entry: the increment in the subscripts of X between successive elements of x .

Constraint: $\text{INCX} \neq 0$.

6: $\text{AP}(\ast)$ – REAL (KIND=nag_wp) array

Input/Output

Note: the dimension of the array AP must be at least $N \times (N + 1)/2$.

On entry: the n by n symmetric matrix A , packed by columns.

More precisely,

if $\text{UPLO} = 'U'$, the upper triangle of A must be stored with element A_{ij} in $\text{AP}(i + j(j - 1)/2)$ for $i \leq j$;

if $\text{UPLO} = 'L'$, the lower triangle of A must be stored with element A_{ij} in $\text{AP}(i + (2n - j)(j - 1)/2)$ for $i \geq j$.

On exit: the updated matrix A .

6 Error Indicators and Warnings

None.

7 Accuracy

Not applicable.

8 Parallelism and Performance

Not applicable.

9 Further Comments

None.

10 Example

None.
