

NAG Library Routine Document

F06RKF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

F06RKF returns, via the function name, the value of the 1-norm, the ∞ -norm, the Frobenius norm, or the maximum absolute value of the elements of a real n by n triangular matrix, stored in packed form.

2 Specification

```
FUNCTION F06RKF (NORM, UPLO, DIAG, N, AP, WORK)
REAL (KIND=nag_wp) F06RKF
INTEGER                N
REAL (KIND=nag_wp) AP(*), WORK(*)
CHARACTER(1)          NORM, UPLO, DIAG
```

3 Description

None.

4 References

None.

5 Parameters

- 1: NORM – CHARACTER(1) *Input*
On entry: specifies the value to be returned.
 NORM = '1' or 'O'
 The 1-norm.
 NORM = 'I'
 The ∞ -norm.
 NORM = 'F' or 'E'
 The Frobenius (or Euclidean) norm.
 NORM = 'M'
 The value $\max_{i,j} |a_{ij}|$ (not a norm).
Constraint: NORM = '1', 'O', 'I', 'F', 'E' or 'M'.
- 2: UPLO – CHARACTER(1) *Input*
On entry: specifies whether A is upper or lower triangular.
 UPLO = 'U'
 A is upper triangular.
 UPLO = 'L'
 A is lower triangular.
Constraint: UPLO = 'U' or 'L'.

- 3: DIAG – CHARACTER(1) *Input*
On entry: specifies whether A has nonunit or unit diagonal elements.
 DIAG = 'N'
 The diagonal elements are stored explicitly.
 DIAG = 'U'
 The diagonal elements are assumed to be 1, and are not referenced.
Constraint: DIAG = 'N' or 'U'.
- 4: N – INTEGER *Input*
On entry: n , the order of the matrix A .
 When $N = 0$, F06RKF returns zero.
Constraint: $N \geq 0$.
- 5: AP(*) – REAL (KIND=nag_wp) array *Input*
Note: the dimension of the array AP must be at least $N \times (N + 1)/2$.
On entry: the n by n triangular matrix A , packed by columns.
 More precisely,
 if UPLO = 'U', the upper triangle of A must be stored with element A_{ij} in
 AP($i + j(j - 1)/2$) for $i \leq j$;
 if UPLO = 'L', the lower triangle of A must be stored with element A_{ij} in
 AP($i + (2n - j)(j - 1)/2$) for $i \geq j$.
 If DIAG = 'U', the diagonal elements of A are assumed to be 1, and are not referenced; the same
 storage scheme is used whether DIAG = 'N' or 'U'.
- 6: WORK(*) – REAL (KIND=nag_wp) array *Workspace*
Note: the dimension of the array WORK must be at least $\max(1, N)$ if NORM = 'I', and at least 1
 otherwise.

6 Error Indicators and Warnings

None.

7 Accuracy

Not applicable.

8 Parallelism and Performance

Not applicable.

9 Further Comments

None.

10 Example

None.
