

NAG Library Routine Document

F08FCF (DSYEVD)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

Warning. The specification of the parameters LWORK and LIWORK changed at Mark 20 in the case where JOB = 'V' and $N > 1$: the minimum dimension of the array WORK has been reduced whereas the minimum dimension of the array IWORK has been increased.

1 Purpose

F08FCF (DSYEVD) computes all the eigenvalues and, optionally, all the eigenvectors of a real symmetric matrix. If the eigenvectors are requested, then it uses a divide-and-conquer algorithm to compute eigenvalues and eigenvectors. However, if only eigenvalues are required, then it uses the Pal–Walker–Kahan variant of the QL or QR algorithm.

2 Specification

```
SUBROUTINE F08FCF (JOB, UPLO, N, A, LDA, W, WORK, LWORK, IWORK, LIWORK,      &
                  INFO)
INTEGER          N, LDA, LWORK, IWORK(max(1,LIWORK)), LIWORK, INFO
REAL (KIND=nag_wp) A(LDA,*), W(*), WORK(max(1,LWORK))
CHARACTER(1)    JOB, UPLO
```

The routine may be called by its LAPACK name *dsyevd*.

3 Description

F08FCF (DSYEVD) computes all the eigenvalues and, optionally, all the eigenvectors of a real symmetric matrix A . In other words, it can compute the spectral factorization of A as

$$A = Z\Lambda Z^T,$$

where Λ is a diagonal matrix whose diagonal elements are the eigenvalues λ_i , and Z is the orthogonal matrix whose columns are the eigenvectors z_i . Thus

$$Az_i = \lambda_i z_i, \quad i = 1, 2, \dots, n.$$

4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia <http://www.netlib.org/lapack/lug>

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

5 Parameters

- 1: JOB – CHARACTER(1) *Input*
On entry: indicates whether eigenvectors are computed.
 JOB = 'N'
 Only eigenvalues are computed.

- JOB = 'V'
Eigenvalues and eigenvectors are computed.
Constraint: JOB = 'N' or 'V'.
- 2: UPLO – CHARACTER(1) *Input*
On entry: indicates whether the upper or lower triangular part of A is stored.
UPLO = 'U'
The upper triangular part of A is stored.
UPLO = 'L'
The lower triangular part of A is stored.
Constraint: UPLO = 'U' or 'L'.
- 3: N – INTEGER *Input*
On entry: n , the order of the matrix A .
Constraint: $N \geq 0$.
- 4: A(LDA,*) – REAL (KIND=nag_wp) array *Input/Output*
Note: the second dimension of the array A must be at least $\max(1, N)$.
On entry: the n by n symmetric matrix A .
If UPLO = 'U', the upper triangular part of A must be stored and the elements of the array below the diagonal are not referenced.
If UPLO = 'L', the lower triangular part of A must be stored and the elements of the array above the diagonal are not referenced.
On exit: if JOB = 'V', A is overwritten by the orthogonal matrix Z which contains the eigenvectors of A .
- 5: LDA – INTEGER *Input*
On entry: the first dimension of the array A as declared in the (sub)program from which F08FCF (DSYEVD) is called.
Constraint: $LDA \geq \max(1, N)$.
- 6: W(*) – REAL (KIND=nag_wp) array *Output*
Note: the dimension of the array W must be at least $\max(1, N)$.
On exit: the eigenvalues of the matrix A in ascending order.
- 7: WORK(max(1,LWORK)) – REAL (KIND=nag_wp) array *Workspace*
On exit: if INFO = 0, WORK(1) contains the required minimal size of LWORK.
- 8: LWORK – INTEGER *Input*
On entry: the dimension of the array WORK as declared in the (sub)program from which F08FCF (DSYEVD) is called.
If LWORK = -1, a workspace query is assumed; the routine only calculates the minimum dimension of the WORK array, returns this value as the first entry of the WORK array, and no error message related to LWORK is issued.
Constraints:
if $N \leq 1$, LWORK ≥ 1 or LWORK = -1;
if JOB = 'N' and $N > 1$, LWORK $\geq 2 \times N + 1$ or LWORK = -1;

if JOB = 'V' and $N > 1$, $LWORK \geq 2 \times N^2 + 6 \times N + 1$ or $LWORK = -1$.

9: IWORK(max(1, LIWORK)) – INTEGER array Workspace

On exit: if INFO = 0, IWORK(1) contains the required minimal size of LIWORK.

10: LIWORK – INTEGER Input

On entry: the dimension of the array IWORK as declared in the (sub)program from which F08FCF (DSYEVD) is called.

If LIWORK = -1, a workspace query is assumed; the routine only calculates the minimum dimension of the IWORK array, returns this value as the first entry of the IWORK array, and no error message related to LIWORK is issued.

Constraints:

if $N \leq 1$, $LIWORK \geq 1$ or $LIWORK = -1$;

if JOB = 'N' and $N > 1$, $LIWORK \geq 1$ or $LIWORK = -1$;

if JOB = 'V' and $N > 1$, $LIWORK \geq 5 \times N + 3$ or $LIWORK = -1$.

11: INFO – INTEGER Output

On exit: INFO = 0 unless the routine detects an error (see Section 6).

6 Error Indicators and Warnings

INFO < 0

If INFO = - i , argument i had an illegal value. An explanatory message is output, and execution of the program is terminated.

INFO > 0

if INFO = i and JOB = 'N', the algorithm failed to converge; i elements of an intermediate tridiagonal form did not converge to zero; if INFO = i and JOB = 'V', then the algorithm failed to compute an eigenvalue while working on the submatrix lying in rows and column $i/(N + 1)$ through $i \bmod (N + 1)$.

7 Accuracy

The computed eigenvalues and eigenvectors are exact for a nearby matrix $(A + E)$, where

$$\|E\|_2 = O(\epsilon)\|A\|_2,$$

and ϵ is the *machine precision*. See Section 4.7 of Anderson *et al.* (1999) for further details.

8 Parallelism and Performance

F08FCF (DSYEVD) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

F08FCF (DSYEVD) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this routine. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

The complex analogue of this routine is F08FQF (ZHEEVD).

10 Example

This example computes all the eigenvalues and eigenvectors of the symmetric matrix A , where

$$A = \begin{pmatrix} 1.0 & 2.0 & 3.0 & 4.0 \\ 2.0 & 2.0 & 3.0 & 4.0 \\ 3.0 & 3.0 & 3.0 & 4.0 \\ 4.0 & 4.0 & 4.0 & 4.0 \end{pmatrix}.$$

10.1 Program Text

```

Program f08fcfe

!      F08FCF Example Program Text

!      Mark 25 Release. NAG Copyright 2014.

!      .. Use Statements ..
      Use nag_library, Only: dsyevd, nag_wp, x04caf
!      .. Implicit None Statement ..
      Implicit None
!      .. Parameters ..
      Integer, Parameter          :: nin = 5, nout = 6
!      .. Local Scalars ..
      Integer                     :: i, ifail, info, lda, liwork, lwork, n
      Character (1)               :: job, uplo
!      .. Local Arrays ..
      Real (Kind=nag_wp), Allocatable :: a(:,,:), w(:,), work(:)
      Integer, Allocatable        :: iwork(:)
!      .. Executable Statements ..
      Write (nout,*) 'F08FCF Example Program Results'
!      Skip heading in data file
      Read (nin,*)
      Read (nin,*) n
      lda = n
      liwork = 5*n + 3
      lwork = 2*n*n + 6*n + 1
      Allocate (a(lda,n),w(n),work(lwork),iwork(liwork))

!      Read A from data file

      Read (nin,*) uplo
      If (uplo=='U') Then
         Read (nin,*)(a(i,i:n),i=1,n)
      Else If (uplo=='L') Then
         Read (nin,*)(a(i,1:i),i=1,n)
      End If

      Read (nin,*) job

!      Calculate all the eigenvalues and eigenvectors of A
!      The NAG name equivalent of dsyevd is f08fcf
      Call dsyevd(job,uplo,n,a,lda,w,work,lwork,iwork,liwork,info)

      Write (nout,*)
      If (info>0) Then
         Write (nout,*) 'Failure to converge.'
      Else

!      Print eigenvalues and eigenvectors

         Write (nout,*) 'Eigenvalues'
         Write (nout,99999) w(1:n)
         Write (nout,*)
         Flush (nout)

!      ifail: behaviour on error exit
!      =0 for hard exit, =1 for quiet-soft, =-1 for noisy-soft
      ifail = 0

```

```

      Call x04caf('General', ' ', n, n, a, lda, 'Eigenvectors', ifail)
    End If
99999 Format (3X, (8F8.4))
    End Program f08fcfe

```

10.2 Program Data

```

F08FCF Example Program Data
  4                               :Value of N
  'L'                             :Value of UPLO
  1.0
  2.0  2.0
  3.0  3.0  3.0
  4.0  4.0  4.0  4.0           :End of matrix A
  'V'                             :Value of JOB

```

10.3 Program Results

F08FCF Example Program Results

```

Eigenvalues
  -2.0531 -0.5146 -0.2943 12.8621

```

```

Eigenvectors
      1      2      3      4
1  -0.7003 -0.5144 -0.2767 -0.4103
2  -0.3592  0.4851  0.6634 -0.4422
3   0.1569  0.5420 -0.6504 -0.5085
4   0.5965 -0.4543  0.2457 -0.6144

```
