

NAG Library Routine Document

D02PSF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

D02PSF computes the solution of a system of ordinary differential equations using interpolation anywhere on an integration step taken by D02PFF.

2 Specification

```

SUBROUTINE D02PSF (N, TWANT, IDERIV, NWANT, YWANT, YPWANT, F, WCOMM,      &
                  LWCOMM, IUSER, RUSER, IWSAV, RWSAV, IFAIL)
INTEGER           N, IDERIV, NWANT, LWCOMM, IUSER(*), IWSAV(130),      &
                  IFAIL
REAL (KIND=nag_wp) TWANT, YWANT(NWANT), YPWANT(NWANT), WCOMM(LWCOMM),  &
                  RUSER(*), RWSAV(32*N+350)
EXTERNAL         F

```

3 Description

D02PSF and its associated routines (D02PFF, D02PQF, D02PRF, D02PTF and D02PUF) solve the initial value problem for a first-order system of ordinary differential equations. The routines, based on Runge–Kutta methods and derived from RKSUITE (see Brankin *et al.* (1991)), integrate

$$y' = f(t, y) \quad \text{given} \quad y(t_0) = y_0$$

where y is the vector of n solution components and t is the independent variable.

D02PFF computes the solution at the end of an integration step. Using the information computed on that step D02PSF computes the solution by interpolation at any point on that step. It cannot be used if METHOD = 3 or -3 was specified in the call to setup routine D02PQF.

4 References

Brankin R W, Gladwell I and Shampine L F (1991) RKSUITE: A suite of Runge–Kutta codes for the initial value problems for ODEs *SoftReport 91-S1* Southern Methodist University

5 Arguments

- 1: N – INTEGER *Input*
On entry: n , the number of ordinary differential equations in the system to be solved by the integration routine.
Constraint: $N \geq 1$.
- 2: TWANT – REAL (KIND=nag_wp) *Input*
On entry: t , the value of the independent variable where a solution is desired.
- 3: IDERIV – INTEGER *Input*
On entry: determines whether the solution and/or its first derivative are to be computed
 IDERIV = 0
 compute approximate solution.

IDERIV = 1
compute approximate first derivative.

IDERIV = 2
compute approximate solution and first derivative.

Constraint: IDERIV = 0, 1 or 2.

- 4: NWANT – INTEGER *Input*
On entry: the number of components of the solution to be computed. The first NWANT components are evaluated.
Constraint: $1 \leq \text{NWANT} \leq N$.
- 5: YWANT(NWANT) – REAL (KIND=nag_wp) array *Output*
On exit: an approximation to the first NWANT components of the solution at TWANT if IDERIV = 0 or 2. Otherwise YWANT is not defined.
- 6: YPWANT(NWANT) – REAL (KIND=nag_wp) array *Output*
On exit: an approximation to the first NWANT components of the first derivative at TWANT if IDERIV = 1 or 2. Otherwise YPWANT is not defined.
- 7: F – SUBROUTINE, supplied by the user. *External Procedure*
F must evaluate the functions f_i (that is the first derivatives y'_i) for given values of the arguments t, y_i . It must be the same procedure as supplied to D02PFF.

The specification of F is:

```
SUBROUTINE F (T, N, Y, YP, IUSER, RUSER)
```

```
INTEGER N, IUSER(*)
```

```
REAL (KIND=nag_wp) T, Y(N), YP(N), RUSER(*)
```

1: T – REAL (KIND=nag_wp) *Input*

On entry: t , the current value of the independent variable.

2: N – INTEGER *Input*

On entry: n , the number of ordinary differential equations in the system to be solved.

3: Y(N) – REAL (KIND=nag_wp) array *Input*

On entry: the current values of the dependent variables, y_i , for $i = 1, 2, \dots, n$.

4: YP(N) – REAL (KIND=nag_wp) array *Output*

On exit: the values of f_i , for $i = 1, 2, \dots, n$.

5: IUSER(*) – INTEGER array *User Workspace*

6: RUSER(*) – REAL (KIND=nag_wp) array *User Workspace*

F is called with the arguments IUSER and RUSER as supplied to D02PSF. You should use the arrays IUSER and RUSER to supply information to F.

F must either be a module subprogram USED by, or declared as EXTERNAL in, the (sub) program from which D02PSF is called. Arguments denoted as *Input* must **not** be changed by this procedure.

- 8: WCOMM(LWCOMM) – REAL (KIND=nag_wp) array *Communication Array*
On entry: this array stores information that can be utilized on subsequent calls to D02PSF.

- 9: LWCOMM – INTEGER *Input*
On entry: length of WCOMM.
 If in a previous call to D02PQF:
 METHOD = 1 or –1 then LWCOMM must be at least 1.
 METHOD = 2 or –2 then LWCOMM must be at least $N + \max(N, 5 \times \text{NWANT})$.
 METHOD = 3 or –3 then WCOMM and LWCOMM are not referenced.
- 10: IUSER(*) – INTEGER array *User Workspace*
 11: RUSER(*) – REAL (KIND=nag_wp) array *User Workspace*
 IUSER and RUSER are not used by D02PSF, but are passed directly to F and should be used to pass information to this routine.
- 12: IWSAV(130) – INTEGER array *Communication Array*
 13: RWSAV($32 \times N + 350$) – REAL (KIND=nag_wp) array *Communication Array*
On entry: these must be the same arrays supplied in a previous call D02PFF. They must remain unchanged between calls.
On exit: information about the integration for use on subsequent calls to D02PFF, D02PSF or other associated routines.
- 14: IFAIL – INTEGER *Input/Output*
On entry: IFAIL must be set to 0, –1 or 1. If you are unfamiliar with this argument you should refer to Section 3.4 in How to Use the NAG Library and its Documentation for details.
 For environments where it might be inappropriate to halt program execution when an error is detected, the value –1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, if you are not familiar with this argument, the recommended value is 0. **When the value –1 or 1 is used it is essential to test the value of IFAIL on exit.**
On exit: IFAIL = 0 unless the routine detects an error or a warning has been flagged (see Section 6).

6 Error Indicators and Warnings

If on entry IFAIL = 0 or –1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL = 1

METHOD = –3 or 3 in setup, but interpolation is not available for this method. Either use METHOD = –2 or 2 in setup or use reset routine to force the integrator to step to particular points.

On entry, a previous call to the setup routine has not been made or the communication arrays have become corrupted, or a catastrophic error has already been detected elsewhere. You cannot continue integrating the problem.

On entry, IDERIV = *value*.
 Constraint: IDERIV = 0, 1 or 2.

On entry, LWCOMM = *value*, N = *value* and NWANT = *value*.
 Constraint: for METHOD = –2 or 2, $\text{LWCOMM} \geq N + \max(N, 5 \times \text{NWANT})$.

On entry, LWCOMM = *value*.
 Constraint: for METHOD = –1 or 1, $\text{LWCOMM} \geq 1$.

On entry, $N = \langle value \rangle$, but the value passed to the setup routine was $N = \langle value \rangle$.

On entry, $NWANT = \langle value \rangle$ and $N = \langle value \rangle$.

Constraint: $1 \leq NWANT \leq N$.

You cannot call this routine after the integrator has returned an error.

You cannot call this routine before you have called the step integrator.

You cannot call this routine when you have specified, in the setup routine, that the range integrator will be used.

IFAIL = -99

An unexpected error has been triggered by this routine. Please contact NAG.

See Section 3.9 in How to Use the NAG Library and its Documentation for further information.

IFAIL = -399

Your licence key may have expired or may not have been installed correctly.

See Section 3.8 in How to Use the NAG Library and its Documentation for further information.

IFAIL = -999

Dynamic memory allocation failed.

See Section 3.7 in How to Use the NAG Library and its Documentation for further information.

7 Accuracy

The computed values will be of a similar accuracy to that computed by D02PFF.

8 Parallelism and Performance

D02PSF makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this routine. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

None.

10 Example

This example solves the equation

$$y'' = -y, \quad y(0) = 0, \quad y'(0) = 1$$

reposed as

$$y'_1 = y_2$$

$$y'_2 = -y_1$$

over the range $[0, 2\pi]$ with initial conditions $y_1 = 0.0$ and $y_2 = 1.0$. Relative error control is used with threshold values of $1.0E-8$ for each solution component. D02PFF is used to integrate the problem one step at a time and D02PSF is used to compute the first component of the solution and its derivative at intervals of length $\pi/8$ across the range whenever these points lie in one of those integration steps. A

low order Runge–Kutta method (METHOD = -1) is also used with tolerances TOL = 1.0E-4 and TOL = 1.0E-5 in turn so that solutions may be compared.

10.1 Program Text

```

!   D02PSF Example Program Text
!   Mark 26 Release. NAG Copyright 2016.

Module d02psfe_mod

!   D02PSF Example Program Module:
!       Parameters and User-defined Routines

!   .. Use Statements ..
Use nag_library, Only: nag_wp
!   .. Implicit None Statement ..
Implicit None
!   .. Accessibility Statements ..
Private
Public                               :: f
!   .. Parameters ..
Real (Kind=nag_wp), Parameter, Public :: tol0 = 1.0E-3_nag_wp
Integer, Parameter, Public           :: n = 2, nin = 5, nout = 6, npts = 16, &
                                     nwant = 1
Integer, Parameter, Public           :: lrwsav = 350 + 32*n
Contains
Subroutine f(t,n,y,yp,iuser,ruser)

!   .. Scalar Arguments ..
Real (Kind=nag_wp), Intent (In) :: t
Integer, Intent (In)           :: n
!   .. Array Arguments ..
Real (Kind=nag_wp), Intent (Inout) :: ruser(*)
Real (Kind=nag_wp), Intent (In) :: y(n)
Real (Kind=nag_wp), Intent (Out) :: yp(n)
Integer, Intent (Inout)         :: iuser(*)
!   .. Executable Statements ..
yp(1) = y(2)
yp(2) = -y(1)
Return
End Subroutine f
End Module d02psfe_mod

Program d02psfe

!   D02PSF Example Main Program

!   .. Use Statements ..
Use nag_library, Only: d02pff, d02pqf, d02psf, d02ptf, nag_wp
Use d02psfe_mod, Only: f, lrwsav, n, nin, nout, npts, nwant, tol0
!   .. Implicit None Statement ..
Implicit None
!   .. Local Scalars ..
Real (Kind=nag_wp)           :: hnext, hstart, tend, tinc, tnow,      &
                               tol, tstart, twant, waste
Integer                      :: fevals, i,  ideriv, ifail, lwcomm,    &
                               method, stepcost, stepsok
!   .. Local Arrays ..
Real (Kind=nag_wp)           :: ruser(1), thresh(n), yinit(n),      &
                               ynow(n), ypnw(n), ypwant(nwant),      &
                               ywant(nwant)
Real (Kind=nag_wp), Allocatable :: rwsav(:), wcomm(:)
Integer                      :: iuser(1), iwsav(130)
!   .. Intrinsic Procedures ..
Intrinsic                    :: real
!   .. Executable Statements ..
Write (nout,*) 'D02PSF Example Program Results'
!   Skip heading in data file
Read (nin,*)

```

```

lwcomm = n + 5*nwant
Allocate (rwsav(lrwsav),wcomm(lwcomm))

wcomm(1:lwcomm) = 0.0_nag_wp

! Set initial conditions and input for D02PQF

Read (nin,*) method
Read (nin,*) tstart, tend
Read (nin,*) yinit(1:n)
Read (nin,*) hstart
Read (nin,*) thresh(1:n)

! Set output control

tinc = (tend-tstart)/real(npts,kind=nag_wp)

tol = tol0*10.0_nag_wp
Do i = 1, 2
  tol = tol*0.1_nag_wp

! Set up integration.
ifail = 0
Call d02pqf(n,tstart,tend,yinit,tol,thresh,method,hstart,iwsav,rwsav, &
  ifail)

Write (nout,99999) tol
Write (nout,99998)
Write (nout,99997) tstart, yinit(1:n)

! Set up first point at which solution is desired.
twant = tstart + tinc
tnow = tstart

! Integrate by steps until tend is reached or error is encountered.
integ: Do While (tnow<tend)

! Integrate one step to tnow.
ifail = 0
Call d02pff(f,n,tnow,ynow,ypnow,iuser,ruser,iwsav,rwsav,ifail)

! Interpolate at required additional points up to tnow.
interp: Do While (twant<=tnow)

! Interpolate and print solution at t = twant.

  ideriv = 2
  ifail = 0
  Call d02psf(n,twant,ideriv,nwant,ywant,ypwant,f,wcomm,lwcomm, &
    iuser,ruser,iwsav,rwsav,ifail)
  Write (nout,99997) twant, ywant(1), ypwant(1)

! Set next required solution point
  twant = twant + tinc
End Do interp

End Do integ

! Get integration statistics.
ifail = 0
Call d02ptf(fevals,stepcost,waste,stepsok,hnext,iwsav,rwsav,ifail)

Write (nout,99996) fevals

End Do
99999 Format (/,' Calculation with TOL = ',1P,E8.1)

```

```

99998 Format (/, ' t y1 y1''', /)
99997 Format (1X, F6.3, 2(3X, F8.4))
99996 Format (/, ' Cost of the integration in evaluations of F is', I6)

End Program d02psfe

```

10.2 Program Data

```

D02PSF Example Program Data
  2 -1 : n, method
  0.0 6.28318530717958647692 : tstart, tend
  0.0 1.0 : yinit(1:n)
  0.0 : hstart
  1.0E-8 1.0E-8 : thresh(1:n)

```

10.3 Program Results

D02PSF Example Program Results

Calculation with TOL = 1.0E-03

t	y1	y1'
0.000	0.0000	1.0000
0.393	0.3827	0.9239
0.785	0.7071	0.7071
1.178	0.9239	0.3826
1.571	1.0000	-0.0001
1.963	0.9238	-0.3828
2.356	0.7070	-0.7073
2.749	0.3825	-0.9240
3.142	-0.0002	-0.9999
3.534	-0.3829	-0.9238
3.927	-0.7072	-0.7069
4.320	-0.9239	-0.3823
4.712	-0.9999	0.0004
5.105	-0.9236	0.3830
5.498	-0.7068	0.7073
5.890	-0.3823	0.9239

Cost of the integration in evaluations of F is 152

Calculation with TOL = 1.0E-04

t	y1	y1'
0.000	0.0000	1.0000
0.393	0.3827	0.9239
0.785	0.7071	0.7071
1.178	0.9239	0.3827
1.571	1.0000	-0.0000
1.963	0.9239	-0.3827
2.356	0.7071	-0.7071
2.749	0.3827	-0.9239
3.142	-0.0000	-1.0000
3.534	-0.3827	-0.9239
3.927	-0.7071	-0.7071
4.320	-0.9239	-0.3827
4.712	-1.0000	0.0000
5.105	-0.9238	0.3827
5.498	-0.7071	0.7071
5.890	-0.3826	0.9239

Cost of the integration in evaluations of F is 231

Example Program
Simple Sine Solution, TOL = 0.001

