

# NAG Library Routine Document

## E04BBF/E04BBA

**Note:** before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

### 1 Purpose

E04BBF/E04BBA searches for a minimum, in a given finite interval, of a continuous function of a single variable, using function and first derivative values. The method (based on cubic interpolation) is intended for functions which have a continuous first derivative (although it will usually work if the derivative has occasional discontinuities).

E04BBA is a version of E04BBF that has additional arguments in order to make it safe for use in multithreaded applications (see Section 5).

### 2 Specification

#### 2.1 Specification for E04BBF

```
SUBROUTINE E04BBF (FUNCT, E1, E2, A, B, MAXCAL, X, F, G, IFAIL)
INTEGER          MAXCAL, IFAIL
REAL (KIND=nag_wp) E1, E2, A, B, X, F, G
EXTERNAL        FUNCT
```

#### 2.2 Specification for E04BBA

```
SUBROUTINE E04BBA (FUNCT, E1, E2, A, B, MAXCAL, X, F, G, IUSER, RUSER, &
IFAIL)
INTEGER          MAXCAL, IUSER(*), IFAIL
REAL (KIND=nag_wp) E1, E2, A, B, X, F, G, RUSER(*)
EXTERNAL        FUNCT
```

### 3 Description

E04BBF/E04BBA is applicable to problems of the form:

$$\text{Minimize } F(x) \quad \text{subject to} \quad a \leq x \leq b$$

when the first derivative  $\frac{dF}{dx}$  can be calculated. The routine normally computes a sequence of  $x$  values which tend in the limit to a minimum of  $F(x)$  subject to the given bounds. It also progressively reduces the interval  $[a, b]$  in which the minimum is known to lie. It uses the safeguarded cubic-interpolation method described in Gill and Murray (1973).

You must supply a FUNCT to evaluate  $F(x)$  and  $\frac{dF}{dx}$ . The arguments E1 and E2 together specify the accuracy

$$Tol(x) = E1 \times |x| + E2$$

to which the position of the minimum is required. Note that FUNCT is never called at a point which is closer than  $Tol(x)$  to a previous point.

If the original interval  $[a, b]$  contains more than one minimum, E04BBF/E04BBA will normally find one of the minima.

## 4 References

Gill P E and Murray W (1973) Safeguarded steplength algorithms for optimization using descent methods *NPL Report NAC 37* National Physical Laboratory

## 5 Arguments

1: FUNCT – SUBROUTINE, supplied by the user. *External Procedure*

You must supply this routine to calculate the values of  $F(x)$  and  $\frac{dF}{dx}$  at any point  $x$  in  $[a, b]$ .

It should be tested separately before being used in conjunction with E04BBF/E04BBA.

The specification of FUNCT for E04BBF is:

```
SUBROUTINE FUNCT (XC, FC, GC)
REAL (KIND=nag_wp) XC, FC, GC
```

The specification of FUNCT for E04BBA is:

```
SUBROUTINE FUNCT (XC, FC, GC, IUSER, RUSER)
INTEGER IUSER(*)
REAL (KIND=nag_wp) XC, FC, GC, RUSER(*)
```

1: XC – REAL (KIND=nag\_wp) *Input*

*On entry:* the point  $x$  at which the values of  $F$  and  $\frac{dF}{dx}$  are required.

2: FC – REAL (KIND=nag\_wp) *Output*

*On exit:* must be set to the value of the function  $F$  at the current point  $x$ .

3: GC – REAL (KIND=nag\_wp) *Output*

*On exit:* must be set to the value of the first derivative  $\frac{dF}{dx}$  at the current point  $x$ .

**Note:** the following are additional arguments for specific use with E04BBA. Users of E04BBF therefore need not read the remainder of this description.

4: IUSER(\*) – INTEGER array *User Workspace*

5: RUSER(\*) – REAL (KIND=nag\_wp) array *User Workspace*

FUNCT is called with the arguments IUSER and RUSER as supplied to E04BBF/E04BBA. You should use the arrays IUSER and RUSER to supply information to FUNCT.

FUNCT must either be a module subprogram USED by, or declared as EXTERNAL in, the (sub) program from which E04BBF/E04BBA is called. Arguments denoted as *Input* must **not** be changed by this procedure.

2: E1 – REAL (KIND=nag\_wp) *Input/Output*

*On entry:* the relative accuracy to which the position of a minimum is required. (Note that, since E1 is a relative tolerance, the scaling of  $x$  is automatically taken into account.)

E1 should be no smaller than  $2\epsilon$ , and preferably not much less than  $\sqrt{\epsilon}$ , where  $\epsilon$  is the **machine precision**.

*On exit:* if you set E1 to 0.0 (or to any value less than  $\epsilon$ ), E1 will be reset to the default value  $\sqrt{\epsilon}$  before starting the minimization process.

- 3: E2 – REAL (KIND=nag\_wp) Input/Output  
*On entry:* the absolute accuracy to which the position of a minimum is required. E2 should be no smaller than  $2\epsilon$ .  
*On exit:* if you set E2 to 0.0 (or to any value less than  $\epsilon$ ), E2 will be reset to the default value  $\sqrt{\epsilon}$ .
- 4: A – REAL (KIND=nag\_wp) Input/Output  
*On entry:* the lower bound  $a$  of the interval containing a minimum.  
*On exit:* an improved lower bound on the position of the minimum.
- 5: B – REAL (KIND=nag\_wp) Input/Output  
*On entry:* the upper bound  $b$  of the interval containing a minimum.  
*On exit:* an improved upper bound on the position of the minimum.
- 6: MAXCAL – INTEGER Input/Output  
*On entry:* the maximum number of calls of FUNCT to be allowed.  
*Constraint:*  $\text{MAXCAL} \geq 2$ . (Few problems will require more than 20.)  
 There will be an error exit (see Section 6) after MAXCAL calls of FUNCT  
*On exit:* the total number of times that FUNCT was actually called.
- 7: X – REAL (KIND=nag\_wp) Output  
*On exit:* the estimated position of the minimum.
- 8: F – REAL (KIND=nag\_wp) Output  
*On exit:* the function value at the final point given in X.
- 9: G – REAL (KIND=nag\_wp) Output  
*On exit:* the value of the first derivative at the final point in X.
- 10: IFAIL – INTEGER Input/Output  
**Note:** for E04BBA, IFAIL does not occur in this position in the argument list. See the additional arguments described below.  
*On entry:* IFAIL must be set to 0, -1 or 1. If you are unfamiliar with this argument you should refer to Section 3.4 in How to Use the NAG Library and its Documentation for details.  
 For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, because for this routine the values of the output arguments may be useful even if  $\text{IFAIL} \neq 0$  on exit, the recommended value is -1. **When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.**  
*On exit:*  $\text{IFAIL} = 0$  unless the routine detects an error or a warning has been flagged (see Section 6).
- Note:** the following are additional arguments for specific use with E04BBA. Users of E04BBF therefore need not read the remainder of this description.
- 11: IUSER(\*) – INTEGER array User Workspace  
 12: RUSER(\*) – REAL (KIND=nag\_wp) array User Workspace  
 IUSER and RUSER are not used by E04BBF/E04BBA, but are passed directly to FUNCT and should be used to pass information to this routine.

13: IFAIL – INTEGER

Input/Output

**Note:** see the argument description for IFAIL above.

## 6 Error Indicators and Warnings

If on entry  $IFAIL = 0$  or  $-1$ , explanatory error messages are output on the current error message unit (as defined by X04AAF).

**Note:** E04BBF/E04BBA may return useful information for one or more of the following detected errors or warnings.

Errors or warnings detected by the routine:

IFAIL = 1

On entry,  $(A + E2) \geq B$ ,  
or  $MAXCAL < 2$ .

IFAIL = 2

The number of calls of FUNCT has exceeded MAXCAL. This may have happened simply because MAXCAL was set too small for a particular problem, or may be due to a mistake in FUNCT. If no mistake can be found in FUNCT, restart E04BBF/E04BBA (preferably with the values of A and B given on exit from the previous call of E04BBF/E04BBA).

IFAIL = -99

An unexpected error has been triggered by this routine. Please contact NAG.

See Section 3.9 in How to Use the NAG Library and its Documentation for further information.

IFAIL = -399

Your licence key may have expired or may not have been installed correctly.

See Section 3.8 in How to Use the NAG Library and its Documentation for further information.

IFAIL = -999

Dynamic memory allocation failed.

See Section 3.7 in How to Use the NAG Library and its Documentation for further information.

## 7 Accuracy

If  $F(x)$  is  $\delta$ -unimodal for some  $\delta < Tol(x)$ , where  $Tol(x) = E1 \times |x| + E2$ , then, on exit,  $x$  approximates the minimum of  $F(x)$  in the original interval  $[a, b]$  with an error less than  $3 \times Tol(x)$ .

## 8 Parallelism and Performance

E04BBF/E04BBA is not threaded in any implementation.

## 9 Further Comments

Timing depends on the behaviour of  $F(x)$ , the accuracy demanded and the length of the interval  $[a, b]$ . Unless  $F(x)$  and  $\frac{dF}{dx}$  can be evaluated very quickly, the run time will usually be dominated by the time spent in FUNCT.

If  $F(x)$  has more than one minimum in the original interval  $[a, b]$ , E04BBF/E04BBA will determine an approximation  $x$  (and improved bounds  $a$  and  $b$ ) for one of the minima.

If E04BBF/E04BBA finds an  $x$  such that  $F(x - \delta_1) > F(x) < F(x + \delta_2)$  for some  $\delta_1, \delta_2 \geq Tol(x)$ , the interval  $[x - \delta_1, x + \delta_2]$  will be regarded as containing a minimum, even if  $F(x)$  is less than  $F(x - \delta_1)$  and  $F(x + \delta_2)$  only due to rounding errors in the subroutine. Therefore FUNCT should be programmed to calculate  $F(x)$  as accurately as possible, so that E04BBF/E04BBA will not be liable to find a spurious minimum. (For similar reasons,  $\frac{dF}{dx}$  should be evaluated as accurately as possible.)

## 10 Example

A sketch of the function

$$F(x) = \frac{\sin x}{x}$$

shows that it has a minimum somewhere in the range  $[3.5, 5.0]$ . The following program shows how E04BBF/E04BBA can be used to obtain a good approximation to the position of a minimum.

### 10.1 Program Text

*the following program illustrates the use of E04BBF. An equivalent program illustrating the use of E04BBA is available with the supplied Library and is also available from the NAG web site.*

```

!   E04BBF Example Program Text
!   Mark 26 Release. NAG Copyright 2016.
!   Module e04bbfe_mod

!       E04BBF Example Program Module:
!           Parameters and User-defined Routines

!       .. Use Statements ..
!       Use nag_library, Only: nag_wp
!       .. Implicit None Statement ..
!       Implicit None
!       .. Accessibility Statements ..
!       Private
!       Public                                :: funct
!       .. Parameters ..
!       Integer, Parameter, Public           :: nout = 6
Contains
!       Subroutine funct(xc,fc,gc)
!           Routine to evaluate F(x) and dF/dx at any point in (A, B)

!           .. Scalar Arguments ..
!           Real (Kind=nag_wp), Intent (Out) :: fc, gc
!           Real (Kind=nag_wp), Intent (In)  :: xc
!           .. Intrinsic Procedures ..
!           Intrinsic                        :: cos, sin
!           .. Executable Statements ..
!           fc = sin(xc)/xc
!           gc = (cos(xc)-fc)/xc

!           Return

!       End Subroutine funct
!       End Module e04bbfe_mod
!       Program e04bbfe

!       E04BBF Example Main Program

!       .. Use Statements ..
!       Use nag_library, Only: e04bbf, nag_wp
!       Use e04bbfe_mod, Only: funct, nout
!       .. Implicit None Statement ..
!       Implicit None
!       .. Local Scalars ..
!       Real (Kind=nag_wp)                :: a, b, e1, e2, f, g, x
!       Integer                            :: ifail, maxcal
!       .. Executable Statements ..

```

```

      Write (nout,*) 'E04BBF Example Program Results'

!      E1 and E2 are set to zero so that E04BBF will reset them to
!      their default values

      e1 = 0.0_nag_wp
      e2 = 0.0_nag_wp

!      The minimum is known to lie in the range (3.5, 5.0)

      a = 3.5_nag_wp
      b = 5.0_nag_wp

!      Allow 30 calls of FUNCT

      maxcal = 30

      ifail = -1
      Call e04bbf(funcnt,e1,e2,a,b,maxcal,x,f,g,ifail)

      Select Case (ifail)
      Case (0,2)
        Write (nout,*)
        Write (nout,99999) 'The minimum lies in the interval', a, ' to', b
        Write (nout,99999) 'Its estimated position is', x, ', '
        Write (nout,99998) 'where the function value is ', f
        Write (nout,99997) 'and the gradient is ', g, ' (machine dependent)'
        Write (nout,99996) maxcal, ' calls of FUNCT were required'
      End Select

99999 Format (1X,A,F11.8,A,F11.8)
99998 Format (1X,A,F7.4)
99997 Format (1X,A,1P,E8.1,A)
99996 Format (1X,I2,A)
      End Program e04bbfe

```

## 10.2 Program Data

None.

## 10.3 Program Results

E04BBF Example Program Results

The minimum lies in the interval 4.49340946 to 4.49340952  
 Its estimated position is 4.49340946,  
 where the function value is -0.2172  
 and the gradient is -3.8E-16 (machine dependent)  
 6 calls of FUNCT were required

---