

NAG Library Routine Document

F01VEF (DTRTTF)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

F01VEF (DTRTTF) copies a real triangular matrix, stored in a full format array, to a Rectangular Full Packed (RFP) format array.

2 Specification

```
SUBROUTINE F01VEF (TRANSR, UPLO, N, A, LDA, AR, INFO)
  INTEGER          N, LDA, INFO
  REAL (KIND=nag_wp) A(LDA,*), AR(N*(N+1)/2)
  CHARACTER(1)    TRANSR, UPLO
```

The routine may be called by its LAPACK name *dtrttf*.

3 Description

F01VEF (DTRTTF) packs a real n by n triangular matrix A , stored conventionally in a full format array, into RFP format. This routine is intended for possible use in conjunction with routines from Chapters F06, F07 and F16 where some routines that use triangular matrices store them in RFP format. The RFP storage format is described in Section 3.3.3 in the F07 Chapter Introduction.

4 References

Gustavson F G, Waśniewski J, Dongarra J J and Langou J (2010) Rectangular full packed format for Cholesky's algorithm: factorization, solution, and inversion *ACM Trans. Math. Software* **37**, 2

5 Arguments

- 1: TRANSR – CHARACTER(1) *Input*
On entry: specifies whether the normal RFP representation of A or its transpose is stored.
 TRANSR = 'N'
 The RFP representation of the matrix A is stored.
 TRANSR = 'T'
 The transpose of the RFP representation of the matrix A is stored.
Constraint: TRANSR = 'N' or 'T'.
- 2: UPLO – CHARACTER(1) *Input*
On entry: specifies whether A is upper or lower triangular.
 UPLO = 'U'
 A is upper triangular.
 UPLO = 'L'
 A is lower triangular.
Constraint: UPLO = 'U' or 'L'.

- 3: N – INTEGER *Input*
On entry: n , the order of the matrix A .
Constraint: $N \geq 0$.
- 4: A(LDA,*) – REAL (KIND=nag_wp) array *Input*
Note: the second dimension of the array A must be at least N .
On entry: the triangular matrix A .
 If UPLO = 'U', A is upper triangular and the elements of the array below the diagonal are not referenced.
 If UPLO = 'L', A is lower triangular and the elements of the array above the diagonal are not referenced.
- 5: LDA – INTEGER *Input*
On entry: the first dimension of the array A as declared in the (sub)program from which F01VEF (DTRTTF) is called.
Constraint: $LDA \geq \max(1, N)$.
- 6: AR($N \times (N + 1)/2$) – REAL (KIND=nag_wp) array *Output*
On exit: the upper or lower n by n triangular matrix A (as specified by UPLO) in either normal or transposed RFP format (as specified by TRANSR). The storage format is described in Section 3.3.3 in the F07 Chapter Introduction.
- 7: INFO – INTEGER *Output*
On exit: INFO = 0 unless the routine detects an error (see Section 6).

6 Error Indicators and Warnings

INFO < 0

If INFO = $-i$, argument i had an illegal value. An explanatory message is output, and execution of the program is terminated.

7 Accuracy

Not applicable.

8 Parallelism and Performance

F01VEF (DTRTTF) is not threaded in any implementation.

9 Further Comments

None.

10 Example

This example reads in a triangular matrix and copies it to RFP format.

10.1 Program Text

```

Program f01vefe

!      F01VEF Example Program Text
!
!      Mark 26 Release. NAG Copyright 2016.
!
!      .. Use Statements ..
Use nag_library, Only: dtrttf, nag_wp, x04cbf
!      .. Implicit None Statement ..
Implicit None
!      .. Parameters ..
Integer, Parameter          :: incl = 1, indent = 0, ncols = 80,    &
                             nin = 5, nout = 6
Character (1), Parameter   :: diag = 'N', intlabel = 'I',        &
                             matrix = 'G', nolabel = 'N'
Character (4), Parameter   :: form = 'F5.2'
!      .. Local Scalars ..
Integer                    :: i, ifail, info, k, lar1, lar2, lda,  &
                             lenar, n, q
Character (47)             :: title
Character (1)              :: transr, uplo
!      .. Local Arrays ..
Real (Kind=nag_wp), Allocatable :: a(:,,:), ar(:)
Character (1)              :: clabs(1), rlabs(1)
!      .. Executable Statements ..
Write (nout,*) 'F01VEF Example Program Results'
!      Skip heading in data file
Read (nin,*)
Write (nout,*)
Flush (nout)
Read (nin,*) n, uplo, transr
lda = n
lenar = n*(n+1)/2
Allocate (a(lda,n),ar(lenar))

!      Read a triangular matrix of order n into array A
Do i = 1, n
    Read (nin,*) a(i,i:n)
End Do

!      Print the unpacked array A
title = 'Unpacked Matrix A:'
ifail = 0
Call x04cbf(uplo,diag,n,n,a,lda,form,title,intlabel,rlabs,intlabel,    &
            clabs,ncols,indent,ifail)

Write (nout,*)
Flush (nout)

!      Convert to Rectangular Full Packed form
!      The NAG name equivalent of dtrttf is f01vef
Call dtrttf(transr,uplo,n,a,lda,ar,info)

!      Print the Rectangular Full Packed array
title = 'RFP Packed Array AR:'
ifail = 0
Call x04cbf(matrix,diag,lenar,incl,ar,lenar,form,title,intlabel,rlabs,    &
            nolabel,clabs,ncols,indent,ifail)

Write (nout,*)
Flush (nout)

!      Print the Rectangular Full Packed array showing how the elements are
!      arranged.
title = 'RFP Packed Array AR (graphical representation):'
k = n/2
q = n - k
If (transr=='N' .Or. transr=='n') Then
    lar1 = 2*k + 1

```

```

      lar2 = q
    Else
      lar1 = q
      lar2 = 2*k + 1
    End If

    ifail = 0
    Call x04cbf(matrix,diag,lar1,lar2,ar,lar1,form,title,intlabel,rlabs,      &
      intlabel,clabs,ncols,indent,ifail)

  End Program f01vefe

```

10.2 Program Data

F01VEF Example Program Data

```

4      'U'  'N'      : n, uplo, transr
1.1  1.2  1.3  1.4
      2.2  2.3  2.4
           3.3  3.4
                   4.4      : Upper matrix A

```

10.3 Program Results

F01VEF Example Program Results

Unpacked Matrix A:

```

      1      2      3      4
1  1.10  1.20  1.30  1.40
2           2.20  2.30  2.40
3                3.30  3.40
4                        4.40

```

RFP Packed Array AR:

```

1  1.30
2  2.30
3  3.30
4  1.10
5  1.20
6  1.40
7  2.40
8  3.40
9  4.40
10 2.20

```

RFP Packed Array AR (graphical representation):

```

      1      2
1  1.30  1.40
2  2.30  2.40
3  3.30  3.40
4  1.10  4.40
5  1.20  2.20

```
