

NAG Library Routine Document

F07FHF (DPORFS)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

F07FHF (DPORFS) returns error bounds for the solution of a real symmetric positive definite system of linear equations with multiple right-hand sides, $AX = B$. It improves the solution by iterative refinement, in order to reduce the backward error as much as possible.

2 Specification

```

SUBROUTINE F07FHF (UPLO, N, NRHS, A, LDA, AF, LDAF, B, LDB, X, LDX,      &
                  FERR, BERR, WORK, IWORK, INFO)
INTEGER            N, NRHS, LDA, LDAF, LDB, LDX, IWORK(N), INFO
REAL (KIND=nag_wp) A(LDA,*), AF(LDAF,*), B(LDB,*), X(LDX,*),      &
                  FERR(NRHS), BERR(NRHS), WORK(3*N)
CHARACTER(1)      UPLO

```

The routine may be called by its LAPACK name *dporsf*.

3 Description

F07FHF (DPORFS) returns the backward errors and estimated bounds on the forward errors for the solution of a real symmetric positive definite system of linear equations with multiple right-hand sides $AX = B$. The routine handles each right-hand side vector (stored as a column of the matrix B) independently, so we describe the function of F07FHF (DPORFS) in terms of a single right-hand side b and solution x .

Given a computed solution x , the routine computes the *component-wise backward error* β . This is the size of the smallest relative perturbation in each element of A and b such that x is the exact solution of a perturbed system

$$(A + \delta A)x = b + \delta b$$

$$|\delta a_{ij}| \leq \beta |a_{ij}| \quad \text{and} \quad |\delta b_i| \leq \beta |b_i|.$$

Then the routine estimates a bound for the *component-wise forward error* in the computed solution, defined by:

$$\max_i |x_i - \hat{x}_i| / \max_i |x_i|$$

where \hat{x} is the true solution.

For details of the method, see the F07 Chapter Introduction.

4 References

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

5 Arguments

- 1: UPLO – CHARACTER(1) *Input*
On entry: specifies whether the upper or lower triangular part of A is stored and how A is to be factorized.
 UPLO = 'U'
 The upper triangular part of A is stored and A is factorized as $U^T U$, where U is upper triangular.
 UPLO = 'L'
 The lower triangular part of A is stored and A is factorized as LL^T , where L is lower triangular.
Constraint: UPLO = 'U' or 'L'.
- 2: N – INTEGER *Input*
On entry: n , the order of the matrix A .
Constraint: $N \geq 0$.
- 3: NRHS – INTEGER *Input*
On entry: r , the number of right-hand sides.
Constraint: NRHS ≥ 0 .
- 4: A(LDA,*) – REAL (KIND=nag_wp) array *Input*
Note: the second dimension of the array A must be at least $\max(1, N)$.
On entry: the n by n original symmetric positive definite matrix A as supplied to F07FDF (DPOTRF).
- 5: LDA – INTEGER *Input*
On entry: the first dimension of the array A as declared in the (sub)program from which F07FHF (DPORFS) is called.
Constraint: LDA $\geq \max(1, N)$.
- 6: AF(LDAF,*) – REAL (KIND=nag_wp) array *Input*
Note: the second dimension of the array AF must be at least $\max(1, N)$.
On entry: the Cholesky factor of A , as returned by F07FDF (DPOTRF).
- 7: LDAF – INTEGER *Input*
On entry: the first dimension of the array AF as declared in the (sub)program from which F07FHF (DPORFS) is called.
Constraint: LDAF $\geq \max(1, N)$.
- 8: B(LDB,*) – REAL (KIND=nag_wp) array *Input*
Note: the second dimension of the array B must be at least $\max(1, NRHS)$.
On entry: the n by r right-hand side matrix B .
- 9: LDB – INTEGER *Input*
On entry: the first dimension of the array B as declared in the (sub)program from which F07FHF (DPORFS) is called.
Constraint: LDB $\geq \max(1, N)$.

- 10: X(LDX,*) – REAL (KIND=nag_wp) array Input/Output
Note: the second dimension of the array X must be at least $\max(1, \text{NRHS})$.
On entry: the n by r solution matrix X , as returned by F07FEF (DPOTRS).
On exit: the improved solution matrix X .
- 11: LDX – INTEGER Input
On entry: the first dimension of the array X as declared in the (sub)program from which F07FHF (DPORFS) is called.
Constraint: $\text{LDX} \geq \max(1, N)$.
- 12: FERR(NRHS) – REAL (KIND=nag_wp) array Output
On exit: FERR(j) contains an estimated error bound for the j th solution vector, that is, the j th column of X , for $j = 1, 2, \dots, r$.
- 13: BERR(NRHS) – REAL (KIND=nag_wp) array Output
On exit: BERR(j) contains the component-wise backward error bound β for the j th solution vector, that is, the j th column of X , for $j = 1, 2, \dots, r$.
- 14: WORK(3 × N) – REAL (KIND=nag_wp) array Workspace
- 15: IWORK(N) – INTEGER array Workspace
- 16: INFO – INTEGER Output
On exit: INFO = 0 unless the routine detects an error (see Section 6).

6 Error Indicators and Warnings

INFO < 0

If INFO = $-i$, argument i had an illegal value. An explanatory message is output, and execution of the program is terminated.

7 Accuracy

The bounds returned in FERR are not rigorous, because they are estimated, not computed exactly; but in practice they almost always overestimate the actual error.

8 Parallelism and Performance

F07FHF (DPORFS) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

F07FHF (DPORFS) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this routine. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

For each right-hand side, computation of the backward error involves a minimum of $4n^2$ floating-point operations. Each step of iterative refinement involves an additional $6n^2$ operations. At most five steps of iterative refinement are performed, but usually only one or two steps are required.

Estimating the forward error involves solving a number of systems of linear equations of the form $Ax = b$; the number is usually 4 or 5 and never more than 11. Each solution involves approximately $2n^2$ operations.

The complex analogue of this routine is F07FVF (ZPORFS).

10 Example

This example solves the system of equations $AX = B$ using iterative refinement and to compute the forward and backward error bounds, where

$$A = \begin{pmatrix} 4.16 & -3.12 & 0.56 & -0.10 \\ -3.12 & 5.03 & -0.83 & 1.18 \\ 0.56 & -0.83 & 0.76 & 0.34 \\ -0.10 & 1.18 & 0.34 & 1.18 \end{pmatrix} \quad \text{and} \quad B = \begin{pmatrix} 8.70 & 8.30 \\ -13.35 & 2.13 \\ 1.89 & 1.61 \\ -4.14 & 5.00 \end{pmatrix}.$$

Here A is symmetric positive definite and must first be factorized by F07FDF (DPOTRF).

10.1 Program Text

```

Program f07fhfe
!      F07FHF Example Program Text
!
!      Mark 26 Release. NAG Copyright 2016.
!
!      .. Use Statements ..
      Use nag_library, Only: dporfs, dpotrf, dpotrs, f06qff, nag_wp, x04caf
!      .. Implicit None Statement ..
      Implicit None
!      .. Parameters ..
      Integer, Parameter          :: nin = 5, nout = 6
!      .. Local Scalars ..
      Integer                     :: i, ifail, info, lda, ldaf, ldb, ldx, &
                                   n, nrhs
      Character (1)               :: uplo
!      .. Local Arrays ..
      Real (Kind=nag_wp), Allocatable :: a(:,,:), af(:,,:), b(:,,:), berr(:),      &
                                   ferr(:), work(:), x(:,,:)
      Integer, Allocatable         :: iwork(:)
!      .. Executable Statements ..
      Write (nout,*) 'F07FHF Example Program Results'
!      Skip heading in data file
      Read (nin,*)
      Read (nin,*) n, nrhs
      lda = n
      ldaf = n
      ldb = n
      ldx = n
      Allocate (a(lda,n),af(ldaf,n),b(ldb,nrhs),berr(nrhs),ferr(nrhs),      &
                work(3*n),x(ldx,n),iwork(n))
!
!      Read A and B from data file, and copy A to AF and B to X
!
      Read (nin,*) uplo
      If (uplo=='U') Then
        Read (nin,*) (a(i,i:n),i=1,n)
      Else If (uplo=='L') Then
        Read (nin,*) (a(i,1:i),i=1,n)
      End If
      Read (nin,*) (b(i,1:nrhs),i=1,n)

```

```

      Call f06qff(uplo,n,n,a,lda,af,ldaf)

      x(1:n,1:nrhs) = b(1:n,1:nrhs)

!      Factorize A in the array AF
!      The NAG name equivalent of dpotrf is f07fdf
      Call dpotrf(uplo,n,af,ldaf,info)

      Write (nout,*)
      Flush (nout)
      If (info==0) Then

!          Compute solution in the array X
!          The NAG name equivalent of dpotrs is f07fef
          Call dpotrs(uplo,n,nrhs,af,ldaf,x,ldx,info)

!          Improve solution, and compute backward errors and
!          estimated bounds on the forward errors

!          The NAG name equivalent of dporfs is f07fhf
          Call dporfs(uplo,n,nrhs,a,lda,af,ldaf,b,ldb,x,ldx,ferr,berr,work,
                    iwork,info)

!          Print solution

!          ifail: behaviour on error exit
!          =0 for hard exit, =1 for quiet-soft, =-1 for noisy-soft
          ifail = 0
          Call x04caf('General',' ',n,nrhs,x,ldx,'Solution(s)',ifail)

          Write (nout,*)
          Write (nout,*) 'Backward errors (machine-dependent)'
          Write (nout,99999) berr(1:nrhs)
          Write (nout,*) 'Estimated forward error bounds (machine-dependent)'
          Write (nout,99999) ferr(1:nrhs)
      Else
          Write (nout,*) 'A is not positive definite'
      End If

99999 Format ((3X,1P,7E11.1))
      End Program f07fhfe

```

10.2 Program Data

F07FHF Example Program Data

```

  4  2          :Values of N and NRHS
  'L'          :Value of UPLO
  4.16
 -3.12  5.03
  0.56 -0.83  0.76
 -0.10  1.18  0.34  1.18  :End of matrix A
  8.70  8.30
 -13.35  2.13
  1.89  1.61
 -4.14  5.00          :End of matrix B

```

10.3 Program Results

F07FHF Example Program Results

```

Solution(s)
           1           2
  1      1.0000      4.0000
  2     -1.0000      3.0000
  3      2.0000      2.0000
  4     -3.0000      1.0000

```

Backward errors (machine-dependent)

7.6E-17 5.0E-17

Estimated forward error bounds (machine-dependent)

2.4E-14 2.3E-14
