

NAG Library Routine Document

F16JQF (BLAS_DAMAX_VAL)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

F16JQF (BLAS_DAMAX_VAL) computes, with respect to absolute value, the largest component of a real vector, along with the index of that component.

2 Specification

```
SUBROUTINE F16JQF (N, X, INCX, K, R)
  INTEGER          N, INCX, K
  REAL (KIND=nag_wp) X(1+(N-1)*ABS(INCX)), R
```

The routine may be called by its BLAST name *blas_damax_val*.

3 Description

F16JQF (BLAS_DAMAX_VAL) computes, with respect to absolute value, the largest component, r , of an n -element real vector x , and determines the smallest index, k , such that

$$r = |x_k| = \max_j |x_j|.$$

4 References

Basic Linear Algebra Subprograms Technical (BLAST) Forum (2001) *Basic Linear Algebra Subprograms Technical (BLAST) Forum Standard* University of Tennessee, Knoxville, Tennessee <http://www.netlib.org/blas/blast-forum/blas-report.pdf>

5 Arguments

- 1: N – INTEGER *Input*
On entry: n , the number of elements in x .
- 2: X(1 + (N – 1) × |INCX|) – REAL (KIND=nag_wp) array *Input*
On entry: the n -element vector x .
If INCX > 0, x_i must be stored in X(($i - 1$) × INCX + 1), for $i = 1, 2, \dots, N$.
If INCX < 0, x_i must be stored in X((N – i) × |INCX| + 1), for $i = 1, 2, \dots, N$.
Intermediate elements of X are not referenced. If N = 0, X is not referenced.
- 3: INCX – INTEGER *Input*
On entry: the increment in the subscripts of X between successive elements of x .
Constraint: INCX ≠ 0.
- 4: K – INTEGER *Output*
On exit: k , the index, from the set {1, 2, ..., N}, of the largest component of x with respect to absolute value. If N ≤ 0 on input then K is returned as 0.

5: R – REAL (KIND=nag_wp)

Output

On exit: r , the largest component of x with respect to absolute value. If $N \leq 0$ on input then R is returned as 0.0.

6 Error Indicators and Warnings

If $INCX = 0$, an error message is printed and program execution is terminated.

7 Accuracy

The BLAS standard requires accurate implementations which avoid unnecessary over/underflow (see Section 2.7 of Basic Linear Algebra Subprograms Technical (BLAST) Forum (2001)).

8 Parallelism and Performance

F16JQF (BLAS_DAMAX_VAL) is not threaded in any implementation.

9 Further Comments

None.

10 Example

This example computes the largest component with respect to absolute value and index of that component for the vector

$$x = (1, 10, 11, -2, 9)^T.$$

10.1 Program Text

```

Program f16jqfe
!      F16JQF Example Program Text
!      Mark 26 Release. NAG Copyright 2016.
!
!      .. Use Statements ..
Use nag_library, Only: blas_damax_val, nag_wp
!      .. Implicit None Statement ..
Implicit None
!      .. Parameters ..
Integer, Parameter          :: nin = 5, nout = 6
!      .. Local Scalars ..
Real (Kind=nag_wp)         :: r
Integer                    :: i, incx, ix, k, n
!      .. Local Arrays ..
Real (Kind=nag_wp), Allocatable :: x(:)
!      .. Intrinsic Procedures ..
Intrinsic                  :: abs
!      .. Executable Statements ..
Write (nout,*) 'F16JQF Example Program Results'

!      Skip heading in data file
Read (nin,*)

      Read (nin,*) n, incx
      Allocate (x(1+(n-1)*abs(incx)))

!      Read the vector x and store forwards or backwards
!      as determined by incx.
      If (incx>0) Then
         ix = 1
      Else

```

```

      ix = 1 - (n-1)*incx
End If

Do i = 1, n
  Read (nin,*) x(ix)
  ix = ix + incx
End Do

! Find k = argmax(abs(x)) and r = max(abs(x)).

Call blas_damax_val(n,x,incx,k,r)

Write (nout,*)
Write (nout,99999) k
Write (nout,99998) r

99999 Format (1X,'Index of absolutely largest component of x is',I3)
99998 Format (1X,'Absolutely largest component of x is',F12.5)
End Program f16jqfe

```

10.2 Program Data

F16JQF Example Program Data

```

5 1 : n and incx
1.0
10.0
11.0
-2.0
9.0 : Vector x

```

10.3 Program Results

F16JQF Example Program Results

```

Index of absolutely largest component of x is 3
Absolutely largest component of x is 11.00000

```
