

NAG Library Function Document

nag_1d_spline_fit (e02bec)

1 Purpose

nag_1d_spline_fit (e02bec) computes a cubic spline approximation to an arbitrary set of data points. The knots of the spline are located automatically, but a single argument must be specified to control the trade-off between closeness of fit and smoothness of fit.

2 Specification

```
#include <nag.h>
#include <nage02.h>

void nag_1d_spline_fit (Nag_Start start, Integer m, const double x[],
    const double y[], const double weights[], double s, Integer nest,
    double *fp, Nag_Comm *warmstartinf, Nag_Spline *spline, NagError *fail)
```

3 Description

nag_1d_spline_fit (e02bec) determines a smooth cubic spline approximation $s(x)$ to the set of data points (x_r, y_r) , with weights w_r , for $r = 1, 2, \dots, m$.

The spline is given in the B-spline representation

$$s(x) = \sum_{i=1}^{n-4} c_i N_i(x), \quad (1)$$

where $N_i(x)$ denotes the normalized cubic B-spline defined upon the knots $\lambda_i, \lambda_{i+1}, \dots, \lambda_{i+4}$.

The total number n of these knots and their values $\lambda_1, \dots, \lambda_n$ are chosen automatically by the function. The knots $\lambda_5, \dots, \lambda_{n-4}$ are the interior knots; they divide the approximation interval $[x_1, x_m]$ into $n - 7$ sub-intervals. The coefficients c_1, c_2, \dots, c_{n-4} are then determined as the solution of the following constrained minimization problem:

minimize

$$\eta = \sum_{i=5}^{n-4} \delta_i^2 \quad (2)$$

subject to the constraint

$$\theta = \sum_{r=1}^m \epsilon_r^2 \leq S, \quad (3)$$

where δ_i stands for the discontinuity jump in the third order derivative of $s(x)$ at the interior knot λ_i ,
 ϵ_r denotes the weighted residual $w_r(y_r - s(x_r))$,
 and S is a non-negative number to be specified by you.

The quantity η can be seen as a measure of the (lack of) smoothness of $s(x)$, while closeness of fit is measured through θ . By means of the argument S , ‘the smoothing factor’, you can then control the balance between these two (usually conflicting) properties. If S is too large, the spline will be too smooth and signal will be lost (underfit); if S is too small, the spline will pick up too much noise (overfit). In the extreme cases the function will return an interpolating spline ($\theta = 0$) if S is set to zero, and the weighted least squares cubic polynomial ($\eta = 0$) if S is set very large. Experimenting with S values between these two extremes should result in a good compromise. (See Section 9.2 for advice on choice of S .)

The method employed is outlined in Section 9.3 and fully described in Dierckx (1975), Dierckx (1981) and Dierckx (1982). It involves an adaptive strategy for locating the knots of the cubic spline (depending on the function underlying the data and on the value of S), and an iterative method for solving the constrained minimization problem once the knots have been determined.

Values of the computed spline, or of its derivatives or definite integral, can subsequently be computed by calling `nag_1d_spline_evaluate` (e02bbc), `nag_1d_spline_deriv` (e02bcc) or `nag_1d_spline_intg` (e02bdc), as described in Section 9.4.

4 References

Dierckx P (1975) An algorithm for smoothing, differentiating and integration of experimental data using spline functions *J. Comput. Appl. Math.* **1** 165–184

Dierckx P (1981) An improved algorithm for curve fitting with spline functions *Report TW54* Department of Computer Science, Katholieke Univerciteit Leuven

Dierckx P (1982) A fast algorithm for smoothing data on a rectangular grid while using spline functions *SIAM J. Numer. Anal.* **19** 1286–1304

Reinsch C H (1967) Smoothing by spline functions *Numer. Math.* **10** 177–183

5 Arguments

1: **start** – Nag_Start *Input*

On entry: must be set to Nag_Cold or Nag_Warm.

start = Nag_Cold

The function will build up the knot set starting with no interior knots. No values need be assigned to the argument **spline**→**n**, and memory will be allocated internally to **spline**→**lamda**, **spline**→**c**, **warmstartinf**→**nag_w** and **warmstartinf**→**nag_iw**.

start = Nag_Warm

The function will restart the knot-placing strategy using the knots found in a previous call of the function. In this case, all arguments except **s** must be unchanged from that previous call. This warm start can save much time in searching for a satisfactory value of the smoothing factor S .

Constraint: **start** = Nag_Cold or Nag_Warm.

2: **m** – Integer *Input*

On entry: m , the number of data points.

Constraint: $m \geq 4$.

3: **x[m]** – const double *Input*

On entry: **x**[$r-1$] holds the value x_r of the independent variable (abscissa) x , for $r = 1, 2, \dots, m$.

Constraint: $x_1 < x_2 < \dots < x_m$.

4: **y[m]** – const double *Input*

On entry: **y**[$r-1$] holds the value y_r of the dependent variable (ordinate) y , for $r = 1, 2, \dots, m$.

5: **weights[m]** – const double *Input*

On entry: the values w_r of the weights, for $r = 1, 2, \dots, m$. For advice on the choice of weights, see Section 2.1.2 in the e02 Chapter Introduction.

Constraint: **weights**[$r-1$] > 0.0 , for $r = 1, 2, \dots, m$.

- 6: **s** – double *Input*
On entry: the smoothing factor, S .
 If $S = 0.0$, the function returns an interpolating spline.
 If S is smaller than *machine precision*, it is assumed equal to zero.
 For advice on the choice of S , see Sections 3 and 9.2.
Constraint: $s \geq 0.0$.
- 7: **nest** – Integer *Input*
On entry: an overestimate for the number, n , of knots required.
Constraint: **nest** ≥ 8 . In most practical situations, **nest** = $m/2$ is sufficient. **nest** never needs to be larger than $m + 4$, the number of knots needed for interpolation ($s = 0.0$).
- 8: **fp** – double * *Output*
On exit: the sum of the squared weighted residuals, θ , of the computed spline approximation. If **fp** = 0.0, this is an interpolating spline. **fp** should equal **s** within a relative tolerance of 0.001 unless $n = 8$ when the spline has no interior knots and so is simply a cubic polynomial. For knots to be inserted, **s** must be set to a value below the value of **fp** produced in this case.
- 9: **warmstartinf** – Nag_Comm *
 Pointer to structure of type Nag_Comm with the following members:
- nag_w** – double * *Input*
On entry: if the warm start option is used, the values **nag_w**[0], ..., **nag_w**[**spline** → $n - 1$] must be left unchanged from the previous call.
- nag_iw** – Integer * *Input*
On entry: if the warm start option is used, the values **nag_iw**[0], ..., **nag_iw**[**spline** → $n - 1$] must be left unchanged from the previous call.
- Note that when the information contained in the pointers **nag_w** and **nag_iw** is no longer of use, or before a new call to nag_1d_spline_fit (e02bec) with the same **warmstartinf**, you should free this storage using the NAG macro NAG_FREE. This storage will have been allocated only if this function returns with **fail.code** = NE_NOERROR, NE_SPLINE_COEFF_CONV or NE_NUM_KNOTS_1D_GT.
- 10: **spline** – Nag_Spline *
 Pointer to structure of type Nag_Spline with the following members:
- n** – Integer *Input/Output*
On entry: if the warm start option is used, the value of **n** must be left unchanged from the previous call.
On exit: the total number, n , of knots of the computed spline.
- lamda** – double * *Input/Output*
On entry: a pointer to which, if **start** = Nag_Cold, memory of size **nest** is internally allocated. If the warm start option is used, the values **lamda**[0], **lamda**[1], ..., **lamda**[**n** - 1] must be left unchanged from the previous call.
On exit: the knots of the spline, i.e., the positions of the interior knots **lamda**[4], **lamda**[5], ..., **lamda**[**n** - 5] as well as the positions of the additional knots **lamda**[0] = **lamda**[1] = **lamda**[2] = **lamda**[3] = **x**[0] and **lamda**[**n** - 4] = **lamda**[**n** - 3] = **lamda**[**n** - 2] = **lamda**[**n** - 1] = **x**[**m** - 1] needed for the B-spline representation.

c – double *

Output

On exit: a pointer to which, if **start** = Nag_Cold, memory of size **nest** – 4 is internally allocated. **c**[*i* – 1] holds the coefficient c_i of the B-spline $N_i(x)$ in the spline approximation $s(x)$, for $i = 1, 2, \dots, n - 4$.

Note that when the information contained in the pointers **lamda** and **c** is no longer of use, or before a new call to `nag_1d_spline_fit` (e02bec) with the same **spline**, you should free this storage using the NAG macro `NAG_FREE`. This storage will have been allocated only if this function returns with **fail.code** = NE_NOERROR, NE_SPLINE_COEFF_CONV, or NE_NUM_KNOTS_1D_GT.

11: **fail** – NagError *

Input/Output

The NAG error argument (see Section 2.7 in How to Use the NAG Library and its Documentation).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

NE_BAD_PARAM

On entry, argument **start** had an illegal value.

NE_ENUMTYPE_WARM

start = Nag_Warm at the first call of this function. **start** must be set to **start** = Nag_Cold at the first call.

NE_INT_ARG_LT

On entry, **m** = $\langle value \rangle$.

Constraint: **m** ≥ 4 .

On entry, **nest** = $\langle value \rangle$.

Constraint: **nest** ≥ 8 .

NE_NOT_STRICTLY_INCREASING

The sequence **x** is not strictly increasing: $\mathbf{x}[\langle value \rangle] = \langle value \rangle$, $\mathbf{x}[\langle value \rangle] = \langle value \rangle$.

NE_NUM_KNOTS_1D_GT

The number of knots needed is greater than **nest**, **nest** = $\langle value \rangle$. If **nest** is already large, say **nest** $> \mathbf{m}/2$, this may indicate that possibly **s** is too small: **s** = $\langle value \rangle$.

NE_REAL_ARG_LT

On entry, **s** = $\langle value \rangle$.

Constraint: **s** ≥ 0.0 .

NE_SF_D_K_CONS

On entry, **nest** = $\langle value \rangle$, **s** = $\langle value \rangle$, **m** = $\langle value \rangle$.

Constraint: **nest** $\geq \mathbf{m} + 4$ when **s** = 0.0.

NE_SPLINE_COEFF_CONV

The iterative process has failed to converge. Possibly **s** is too small: **s** = $\langle value \rangle$.

NE_WEIGHTS_NOT_POSITIVE

On entry, the weights are not strictly positive: **weights**[*value*] = *value*.

If the function fails with an error exit of NE_SPLINE_COEFF_CONV or NE_NUM_KNOTS_1D_GT, a spline approximation is returned, but it fails to satisfy the fitting criterion (see (2) and (3)) – perhaps by only a small amount, however.

7 Accuracy

On successful exit, the approximation returned is such that its weighted sum of squared residuals θ (as in (3)) is equal to the smoothing factor S , up to a specified relative tolerance of 0.001 – except that if $n = 8$, θ may be significantly less than S : in this case the computed spline is simply a weighted least squares polynomial approximation of degree 3, i.e., a spline with no interior knots.

8 Parallelism and Performance

nag_1d_spline_fit (e02bec) is not threaded in any implementation.

9 Further Comments**9.1 Timing**

The time taken for a call of nag_1d_spline_fit (e02bec) depends on the complexity of the shape of the data, the value of the smoothing factor S , and the number of data points. If nag_1d_spline_fit (e02bec) is to be called for different values of S , much time can be saved by setting **start** = Nag_Warm after the first call.

9.2 Choice of S

If the weights have been correctly chosen (see Section 2.1.2 in the e02 Chapter Introduction), the standard deviation of $w_r y_r$ would be the same for all r , equal to σ , say. In this case, choosing the smoothing factor S in the range $\sigma^2(m \pm \sqrt{2m})$, as suggested by Reinsch (1967), is likely to give a good start in the search for a satisfactory value. Otherwise, experimenting with different values of S will be required from the start, taking account of the remarks in Section 3.

In that case, in view of computation time and memory requirements, it is recommended to start with a very large value for S and so determine the least squares cubic polynomial; the value returned in **fp**, call it θ_0 , gives an upper bound for S . Then progressively decrease the value of S to obtain closer fits – say by a factor of 10 in the beginning, i.e., $S = \theta_0/10$, $S = \theta_0/100$, and so on, and more carefully as the approximation shows more details.

The number of knots of the spline returned, and their location, generally depend on the value of S and on the behaviour of the function underlying the data. However, if nag_1d_spline_fit (e02bec) is called with **start** = Nag_Warm, the knots returned may also depend on the smoothing factors of the previous calls. Therefore if, after a number of trials with different values of S and **start** = Nag_Warm, a fit can finally be accepted as satisfactory, it may be worthwhile to call nag_1d_spline_fit (e02bec) once more with the selected value for S but now using **start** = Nag_Cold. Often, nag_1d_spline_fit (e02bec) then returns an approximation with the same quality of fit but with fewer knots, which is therefore better if data reduction is also important.

9.3 Outline of Method Used

If $S = 0$, the requisite number of knots is known in advance, i.e., $n = m + 4$; the interior knots are located immediately as $\lambda_i = x_{i-2}$, for $i = 5, 6, \dots, n - 4$. The corresponding least squares spline (see nag_1d_spline_fit_knots (e02bac)) is then an interpolating spline and therefore a solution of the problem.

If $S > 0$, a suitable knot set is built up in stages (starting with no interior knots in the case of a cold start but with the knot set found in a previous call if a warm start is chosen). At each stage, a spline is fitted to the data by least squares (see nag_1d_spline_fit_knots (e02bac)) and θ , the weighted sum of

squares of residuals, is computed. If $\theta > S$, new knots are added to the knot set to reduce θ at the next stage. The new knots are located in intervals where the fit is particularly poor, their number depending on the value of S and on the progress made so far in reducing θ . Sooner or later, we find that $\theta \leq S$ and at that point the knot set is accepted. The function then goes on to compute the (unique) spline which has this knot set and which satisfies the full fitting criterion specified by (2) and (3). The theoretical solution has $\theta = S$. The function computes the spline by an iterative scheme which is ended when $\theta = S$ within a relative tolerance of 0.001. The main part of each iteration consists of a linear least squares computation of special form, done in a similarly stable and efficient manner as in `nag_1d_spline_fit_knots` (e02bac).

An exception occurs when the function finds at the start that, even with no interior knots ($n = 8$), the least squares spline already has its weighted sum of squares of residuals $\leq S$. In this case, since this spline (which is simply a cubic polynomial) also has an optimal value for the smoothness measure η , namely zero, it is returned at once as the (trivial) solution. It will usually mean that S has been chosen too large.

For further details of the algorithm and its use, see Dierckx (1981).

9.4 Evaluation of Computed Spline

The value of the computed spline at a given value \mathbf{x} may be obtained in the double variable \mathbf{s} by the call:

```
nag_1d_spline_evaluate(x, &s, &spline, &fail)
```

where **spline** is a structure of type `Nag_Spline` which is the output argument of `nag_1d_spline_fit` (e02bec).

The values of the spline and its first three derivatives at a given value \mathbf{x} may be obtained in the array \mathbf{s} of dimension at least 4 by the call:

```
nag_1d_spline_deriv(derivs, x, s, &spline, &fail)
```

where, if **derivs** = `Nag_LeftDerivs`, left-hand derivatives are computed and, if **derivs** = `Nag_RightDerivs`, right-hand derivatives are calculated. The value of **derivs** is only relevant if \mathbf{x} is an interior knot (see `nag_1d_spline_deriv` (e02bcc)).

The value of the definite integral of the spline over the interval $\mathbf{x}[0]$ to $\mathbf{x}[\mathbf{m} - 1]$ can be obtained in the variable **integral** by the call:

```
nag_1d_spline_intg(&spline, &integral, &fail)
```

see `nag_1d_spline_intg` (e02bdc).

10 Example

This example reads in a set of data values, followed by a set of values of \mathbf{s} . For each value of \mathbf{s} it calls `nag_1d_spline_fit` (e02bec) to compute a spline approximation, and prints the values of the knots and the B-spline coefficients c_i .

The program includes code to evaluate the computed splines, by calls to `nag_1d_spline_evaluate` (e02bbc), at the points x_r and at points mid-way between them. These values are not printed out, however; instead the results are illustrated by plots of the computed splines, together with the data points (indicated by \times) and the positions of the knots (indicated by vertical lines): the effect of decreasing \mathbf{s} can be clearly seen.

10.1 Program Text

```
/* nag_1d_spline_fit (e02bec) Example Program.
 *
 * NAGPRODCODE Version.
 *
 * Copyright 2016 Numerical Algorithms Group.
 *
 * Mark 26, 2016.
 *
 */
```

```

*/

#include <nag.h>
#include <stdio.h>
#include <nag_stdlib.h>
#include <nage02.h>

int main(void)
{
  Integer exit_status = 0, j, m, nest, r;
  NagError fail;
  Nag_Comm warmstartinf;
  Nag_Spline spline;
  Nag_Start start;
  double fp, s, *sp = 0, txr, *weights = 0, *x = 0, *y = 0;

  INIT_FAIL(fail);

  /* Initialize spline */
  spline.lamda = 0;
  spline.c = 0;

  warmstartinf.nag_w = 0;
  warmstartinf.nag_iw = 0;

  printf("nag_ld_spline_fit (e02bec) Example Program Results\n");
#ifdef _WIN32
  scanf_s("%*[\n]"); /* Skip heading in data file */
#else
  scanf("%*[\n]"); /* Skip heading in data file */
#endif
  /* Input the number of data points, followed by the data
   * points x, the function values y and the weights w.
   */
#ifdef _WIN32
  scanf_s("%" NAG_IFMT " ", &m);
#else
  scanf("%" NAG_IFMT " ", &m);
#endif
  nest = m + 4;
  if (m >= 4) {
    if (!(weights = NAG_ALLOC(m, double)) ||
        !(x = NAG_ALLOC(m, double)) ||
        !(y = NAG_ALLOC(m, double)) || !(sp = NAG_ALLOC(2 * m - 1, double)))
    {
      printf("Allocation failure\n");
      exit_status = -1;
      goto END;
    }
  }
  else {
    printf("Invalid m.\n");
    exit_status = 1;
    return exit_status;
  }
  start = Nag_Cold;
  for (r = 0; r < m; r++)
#ifdef _WIN32
    scanf_s("%lf%lf%lf", &x[r], &y[r], &weights[r]);
#else
    scanf("%lf%lf%lf", &x[r], &y[r], &weights[r]);
#endif
  /* Read in successive values of s until end of data file. */
#ifdef _WIN32
  while (scanf_s("%lf", &s) != EOF)
#else
  while (scanf("%lf", &s) != EOF)
#endif
  {
    /* Determine the spline approximation. */
    /* nag_ld_spline_fit (e02bec).

```

```

    * Least squares cubic spline curve fit, automatic knot
    * placement, one variable
    */
nag_ld_spline_fit(start, m, x, y, weights, s, nest, &fp,
                  &warmstartinf, &spline, &fail);
if (fail.code != NE_NOERROR) {
    printf("Error from nag_ld_spline_fit (e02bec).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

/* Evaluate the spline at each x point and midway
 * between x points, saving the results in sp.
 */
for (r = 0; r < m; r++) {
    /* nag_ld_spline_evaluate (e02bbc).
     * Evaluation of fitted cubic spline, function only
     */
    nag_ld_spline_evaluate(x[r], &sp[(r - 1) * 2 + 2], &spline, &fail);
    if (fail.code != NE_NOERROR) {
        printf("Error from nag_ld_spline_fit (e02bec).\n%s\n", fail.message);
        exit_status = 1;
        goto END;
    }
}

for (r = 0; r < m - 1; r++) {
    txr = (x[r] + x[r + 1]) / 2;
    /* nag_ld_spline_evaluate (e02bbc), see above. */
    nag_ld_spline_evaluate(txr, &sp[r * 2 + 1], &spline, &fail);
    if (fail.code != NE_NOERROR) {
        printf("Error from nag_ld_spline_evaluate (e02bbc).\n%s\n",
              fail.message);
        exit_status = 1;
        goto END;
    }
}

/* Output the results. */
printf("\nCalling with smoothing factor s = %12.3e\n", s);
printf("\nNumber of distinct knots = %" NAG_IFMT "\n\n", spline.n - 6);
printf("Distinct knots located at \n\n");
for (j = 3; j < spline.n - 3; j++)
    printf("%8.4f%s", spline.lamda[j],
          (j - 3) % 6 == 5 || j == spline.n - 4 ? "\n" : " ");
printf("\n\n      J      B-spline coeff c\n\n");
for (j = 0; j < spline.n - 4; ++j)
    printf(" %3" NAG_IFMT " %13.4f\n", j + 1, spline.c[j]);
printf("\nWeighted sum of squared residuals fp = %12.3e\n", fp);
if (fp == 0.0)
    printf("The spline is an interpolating spline\n");
else if (spline.n == 8)
    printf("The spline is the weighted least squares cubic" "polynomial\n");
start = Nag_Warm;
}

/* Free memory allocated in spline and warmstartinf */
END:
NAG_FREE(spline.lamda);
NAG_FREE(spline.c);
NAG_FREE(warmstartinf.nag_w);
NAG_FREE(warmstartinf.nag_iw);
NAG_FREE(weights);
NAG_FREE(x);
NAG_FREE(y);
NAG_FREE(sp);
return exit_status;
}

```


10.2 Program Data

```
nag_1d_spline_fit (e02bec) Example Program Data
15
0.0000E+00 -1.1000E+00 1.00
5.0000E-01 -3.7200E-01 2.00
1.0000E+00 4.3100E-01 1.50
1.5000E+00 1.6900E+00 1.00
2.0000E+00 2.1100E+00 3.00
2.5000E+00 3.1000E+00 1.00
3.0000E+00 4.2300E+00 0.50
4.0000E+00 4.3500E+00 1.00
4.5000E+00 4.8100E+00 2.00
5.0000E+00 4.6100E+00 2.50
5.5000E+00 4.7900E+00 1.00
6.0000E+00 5.2300E+00 3.00
7.0000E+00 6.3500E+00 1.00
7.5000E+00 7.1900E+00 2.00
8.0000E+00 7.9700E+00 1.00
1.0
0.5
0.1
```

10.3 Program Results

```
nag_1d_spline_fit (e02bec) Example Program Results
```

```
Calling with smoothing factor s = 1.000e+00
```

```
Number of distinct knots = 3
```

```
Distinct knots located at
```

```
0.0000 4.0000 8.0000
```

J	B-spline coeff c
1	-1.3201
2	1.3542
3	5.5510
4	4.7031
5	8.2277

```
Weighted sum of squared residuals fp = 1.000e+00
```

```
Calling with smoothing factor s = 5.000e-01
```

```
Number of distinct knots = 7
```

```
Distinct knots located at
```

```
0.0000 1.0000 2.0000 4.0000 5.0000 6.0000
8.0000
```

J	B-spline coeff c
1	-1.1072
2	-0.6571
3	0.4350
4	2.8061
5	4.6824
6	4.6416
7	5.1976
8	6.9008
9	7.9979

```
Weighted sum of squared residuals fp = 5.001e-01
```

Calling with smoothing factor $s = 1.000e-01$

Number of distinct knots = 10

Distinct knots located at

0.0000	1.0000	1.5000	2.0000	3.0000	4.0000
4.5000	5.0000	6.0000	8.0000		

J	B-spline coeff c
1	-1.0900
2	-0.6422
3	0.0369
4	1.6353
5	2.1274
6	4.5526
7	4.2225
8	4.9108
9	4.4159
10	5.4794
11	6.8308
12	7.9935

Weighted sum of squared residuals $fp = 1.000e-01$

Example Program
Calculation and Evaluation of B-splines Representation
Smoothing Factor $S=1.0$



