

# NAG Library Function Document

## nag\_log\_beta (s14cbc)

### 1 Purpose

nag\_log\_beta (s14cbc) returns the value of the logarithm of the beta function,  $\ln B(a, b)$ , via the routine name.

### 2 Specification

```
#include <nag.h>
#include <nags.h>
double nag_log_beta (double a, double b, NagError *fail)
```

### 3 Description

nag\_log\_beta (s14cbc) calculates values for  $\ln B(a, b)$  where  $B$  is the beta function given by

$$B(a, b) = \int_0^1 t^{a-1} (1-t)^{b-1} dt$$

or equivalently

$$B(a, b) = \frac{\Gamma(a)\Gamma(b)}{\Gamma(a+b)}$$

and  $\Gamma(x)$  is the gamma function. Note that the beta function is symmetric, so that  $B(a, b) = B(b, a)$ .

In order to efficiently obtain accurate results several methods are used depending on the parameters  $a$  and  $b$ .

Let  $a_0 = \min(a, b)$  and  $b_0 = \max(a, b)$ . Then:

for  $a_0 \geq 8$ ,

$$\ln B = 0.5 \ln(2\pi) - 0.5 \ln(b_0) + \Delta(a_0) + \Delta(b_0) - \Delta(a_0 + b_0) - u - v;$$

where

$$\Delta(a_0) = \ln \Gamma(a_0) - (a_0 - 0.5) \ln a_0 + a_0 - 0.5 \ln(2\pi),$$

$$u = -(a_0 - 0.5) \ln \left[ \frac{a_0}{a_0 + b_0} \right] \quad \text{and}$$

$$v = b_0 \ln \left( 1 + \frac{a_0}{b_0} \right).$$

for  $a_0 < 1$ ,

for  $b_0 \geq 8$ ,

$$\ln B = \ln \Gamma(a_0) + \ln \frac{\Gamma(b_0)}{\Gamma(a_0 + b_0)};$$

for  $b_0 < 8$ ,

$$\ln B = \ln \Gamma(a_0) + \ln \Gamma(b_0) - \ln \Gamma(a_0 + b_0);$$

for  $2 < a_0 < 8$ ,  $a_0$  is reduced to the interval  $[1, 2]$  by  $B(a, b) = \frac{a_0-1}{a_0+b_0-1} B(a_0-1, b_0)$ ;

for  $1 \leq a_0 \leq 2$ ,  
 for  $b_0 \geq 8$ ,

$$\ln B = \ln \Gamma(a_0) + \ln \frac{\Gamma(b_0)}{\Gamma(a_0 + b_0)};$$

for  $2 < b_0 < 8$ ,  $b_0$  is reduced to the interval  $[1, 2]$ ;  
 for  $b_0 \leq 2$ ,

$$\ln B = \ln \Gamma(a_0) + \ln \Gamma(b_0) - \ln \Gamma(a_0 + b_0).$$

nag\_log\_beta (s14cbc) is derived from BETALN in DiDonato and Morris (1992).

## 4 References

DiDonato A R and Morris A H (1992) Algorithm 708: Significant digit computation of the incomplete beta function ratios *ACM Trans. Math. Software* **18** 360–373

## 5 Arguments

- 1: **a** – double *Input*  
*On entry:* the argument  $a$  of the function.  
*Constraint:* **a** > 0.0.
- 2: **b** – double *Input*  
*On entry:* the argument  $b$  of the function.  
*Constraint:* **b** > 0.0.
- 3: **fail** – NagError \* *Input/Output*  
 The NAG error argument (see Section 2.7 in How to Use the NAG Library and its Documentation).

## 6 Error Indicators and Warnings

### NE\_ALLOC\_FAIL

Dynamic memory allocation failed.  
 See Section 3.2.1.2 in How to Use the NAG Library and its Documentation for further information.

### NE\_INTERNAL\_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.  
 See Section 3.6.6 in How to Use the NAG Library and its Documentation for further information.

### NE\_NO\_LICENCE

Your licence key may have expired or may not have been installed correctly.  
 See Section 3.6.5 in How to Use the NAG Library and its Documentation for further information.

### NE\_REAL

*On entry,* **a** =  $\langle value \rangle$ .  
*Constraint:* **a** > 0.0.

On entry,  $\mathbf{b} = \langle \text{value} \rangle$ .  
 Constraint:  $\mathbf{b} > 0.0$ .

## 7 Accuracy

nag\_log\_beta (s14cbc) should produce full relative accuracy for all input arguments.

## 8 Parallelism and Performance

nag\_log\_beta (s14cbc) is not threaded in any implementation.

## 9 Further Comments

None.

## 10 Example

This example reads values of the arguments  $a$  and  $b$  from a file, evaluates the function and prints the results.

### 10.1 Program Text

```

/* nag_log_beta (s14cbc) Example Program.
 *
 * NAGPRODCODE Version.
 *
 * Copyright 2016 Numerical Algorithms Group.
 *
 * Mark 26, 2016.
 */

#include <nag.h>
#include <stdio.h>
#include <nag_stdlib.h>
#include <nags.h>

int main(void)
{
  Integer exit_status = 0;
  double a, b, lb;
  NagError fail;

  INIT_FAIL(fail);

  /* Skip heading in data file */
#ifdef _WIN32
  scanf_s("%*[\n]");
#else
  scanf("%*[\n]");
#endif
  printf("nag_log_beta (s14cbc) Example Program Results\n");
  printf("  a      b      ln(beta(a,b))\n");
#ifdef _WIN32
  while (scanf_s("%lf %lf", &a, &b) != EOF)
#else
  while (scanf("%lf %lf", &a, &b) != EOF)
#endif
  {
    /* nag_log_beta (s14cbc).
     * Log Beta function ln(beta(a,b))
     */
    lb = nag_log_beta(a, b, &fail);
    if (fail.code != NE_NOERROR) {
      printf("Error from nag_log_beta (s14cbc).\n%s\n", fail.message);
      exit_status = 1;
    }
  }
}

```

```
        goto END;
    }
    printf("%5.2f %5.2f %12.4e\n", a, b, lb);
}

END:
    return exit_status;
}
```

## 10.2 Program Data

nag\_log\_beta (s14cbc) Example Program Data

```
0.2  1.0
0.6  1.0
1.0  0.2
1.0  1.0
2.0  2.0
5.0  5.0
6.0  2.0
6.0  3.0
```

## 10.3 Program Results

nag\_log\_beta (s14cbc) Example Program Results

a	b	ln(beta(a,b))
0.20	1.00	1.6094e+00
0.60	1.00	5.1083e-01
1.00	0.20	1.6094e+00
1.00	1.00	0.0000e+00
2.00	2.00	-1.7918e+00
5.00	5.00	-6.4457e+00
6.00	2.00	-3.7377e+00
6.00	3.00	-5.1240e+00

---