

## NAG Library Routine Document

### F07AAF (DGESV)

**Note:** before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

#### 1 Purpose

F07AAF (DGESV) computes the solution to a real system of linear equations

$$AX = B,$$

where  $A$  is an  $n$  by  $n$  matrix and  $X$  and  $B$  are  $n$  by  $r$  matrices.

#### 2 Specification

```
SUBROUTINE F07AAF (N, NRHS, A, LDA, IPIV, B, LDB, INFO)
  INTEGER          N, NRHS, LDA, IPIV(N), LDB, INFO
  REAL (KIND=nag_wp) A(LDA,*), B(LDB,*)
```

The routine may be called by its LAPACK name *dgesv*.

#### 3 Description

F07AAF (DGESV) uses the  $LU$  decomposition with partial pivoting and row interchanges to factor  $A$  as

$$A = PLU,$$

where  $P$  is a permutation matrix,  $L$  is unit lower triangular, and  $U$  is upper triangular. The factored form of  $A$  is then used to solve the system of equations  $AX = B$ .

#### 4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia <http://www.netlib.org/lapack/lug>

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

#### 5 Arguments

- 1: N – INTEGER *Input*  
*On entry:*  $n$ , the number of linear equations, i.e., the order of the matrix  $A$ .  
*Constraint:*  $N \geq 0$ .
- 2: NRHS – INTEGER *Input*  
*On entry:*  $r$ , the number of right-hand sides, i.e., the number of columns of the matrix  $B$ .  
*Constraint:*  $NRHS \geq 0$ .
- 3: A(LDA,\*) – REAL (KIND=nag\_wp) array *Input/Output*  
**Note:** the second dimension of the array  $A$  must be at least  $\max(1, N)$ .  
*On entry:* the  $n$  by  $n$  coefficient matrix  $A$ .

*On exit:* the factors  $L$  and  $U$  from the factorization  $A = PLU$ ; the unit diagonal elements of  $L$  are not stored.

4: LDA – INTEGER *Input*

*On entry:* the first dimension of the array  $A$  as declared in the (sub)program from which F07AAF (DGESV) is called.

*Constraint:*  $LDA \geq \max(1, N)$ .

5: IPIV(N) – INTEGER array *Output*

*On exit:* if no constraints are violated, the pivot indices that define the permutation matrix  $P$ ; at the  $i$ th step row  $i$  of the matrix was interchanged with row  $IPIV(i)$ .  $IPIV(i) = i$  indicates a row interchange was not required.

6: B(LDB, \*) – REAL (KIND=nag\_wp) array *Input/Output*

**Note:** the second dimension of the array  $B$  must be at least  $\max(1, NRHS)$ .

*On entry:* the  $n$  by  $r$  right-hand side matrix  $B$ .

*On exit:* if  $INFO = 0$ , the  $n$  by  $r$  solution matrix  $X$ .

7: LDB – INTEGER *Input*

*On entry:* the first dimension of the array  $B$  as declared in the (sub)program from which F07AAF (DGESV) is called.

*Constraint:*  $LDB \geq \max(1, N)$ .

8: INFO – INTEGER *Output*

*On exit:*  $INFO = 0$  unless the routine detects an error (see Section 6).

## 6 Error Indicators and Warnings

$INFO < 0$

If  $INFO = -i$ , argument  $i$  had an illegal value. An explanatory message is output, and execution of the program is terminated.

$INFO > 0$

Element  $\langle value \rangle$  of the diagonal is exactly zero. The factorization has been completed, but the factor  $U$  is exactly singular, so the solution could not be computed.

## 7 Accuracy

The computed solution for a single right-hand side,  $\hat{x}$ , satisfies the equation of the form

$$(A + E)\hat{x} = b,$$

where

$$\|E\|_1 = O(\epsilon)\|A\|_1$$

and  $\epsilon$  is the *machine precision*. An approximate error bound for the computed solution is given by

$$\frac{\|\hat{x} - x\|_1}{\|x\|_1} \leq \kappa(A) \frac{\|E\|_1}{\|A\|_1}$$

where  $\kappa(A) = \|A^{-1}\|_1 \|A\|_1$ , the condition number of  $A$  with respect to the solution of the linear equations. See Section 4.4 of Anderson *et al.* (1999) for further details.

Following the use of F07AAF (DGESV), F07AGF (DGECON) can be used to estimate the condition number of  $A$  and F07AHF (DGERFS) can be used to obtain approximate error bounds. Alternatives to F07AAF (DGESV), which return condition and error estimates directly are F04BAF and F07ABF (DGESVX).

## 8 Parallelism and Performance

F07AAF (DGESV) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

F07AAF (DGESV) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this routine. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

## 9 Further Comments

The total number of floating-point operations is approximately  $\frac{2}{3}n^3 + 2n^2r$ , where  $r$  is the number of right-hand sides.

The complex analogue of this routine is F07ANF (ZGESV).

## 10 Example

This example solves the equations

$$Ax = b,$$

where  $A$  is the general matrix

$$A = \begin{pmatrix} 1.80 & 2.88 & 2.05 & -0.89 \\ 5.25 & -2.95 & -0.95 & -3.80 \\ 1.58 & -2.69 & -2.90 & -1.04 \\ -1.11 & -0.66 & -0.59 & 0.80 \end{pmatrix} \quad \text{and} \quad b = \begin{pmatrix} 9.52 \\ 24.35 \\ 0.77 \\ -6.22 \end{pmatrix}.$$

Details of the  $LU$  factorization of  $A$  are also output.

### 10.1 Program Text

```

Program f07aafe
!      F07AAF Example Program Text
!
!      Mark 26 Release. NAG Copyright 2016.
!
!      .. Use Statements ..
Use nag_library, Only: dgesv, nag_wp, x04caf
!      .. Implicit None Statement ..
Implicit None
!      .. Parameters ..
Integer, Parameter          :: nin = 5, nout = 6
!      .. Local Scalars ..
Integer                     :: i, ifail, info, lda, ldb, n
!      .. Local Arrays ..
Real (Kind=nag_wp), Allocatable :: a(:,,:), b(:)
Integer, Allocatable        :: ipiv(:)
!      .. Executable Statements ..
Write (nout,*) 'F07AAF Example Program Results'
Write (nout,*)
!      Skip heading in data file
Read (nin,*)
Read (nin,*) n

```

```

      lda = n
      ldb = n
      Allocate (a(lda,n),b(ldb),ipiv(n))

!      Read A and B from data file

      Read (nin,*)(a(i,1:n),i=1,n)
      Read (nin,*) b(1:n)

!      Solve the equations Ax = b for x

!      The NAG name equivalent of dgesv is f07aaf
      Call dgesv(n,1,a,lda,ipiv,b,ldb,info)

      If (info==0) Then

!      Print solution

      Write (nout,*) 'Solution'
      Write (nout,99999) b(1:n)

!      Print details of factorization

      Write (nout,*)
      Flush (nout)

!      ifail: behaviour on error exit
!      =0 for hard exit, =1 for quiet-soft, =-1 for noisy-soft
      ifail = 0
      Call x04caf('General',' ',n,n,a,lda,'Details of factorization',ifail)

!      Print pivot indices

      Write (nout,*)
      Write (nout,*) 'Pivot indices'
      Write (nout,99998) ipiv(1:n)

      Else
        Write (nout,99997) 'The (' , info, ', ', info, ')',
          ' element of the factor U is zero' &
      End If

99999 Format ((3X,7F11.4))
99998 Format ((3X,7I11))
99997 Format (1X,A,I3,A,I3,A,A)
      End Program f07aaf

```

## 10.2 Program Data

F07AAF Example Program Data

```

4                                     :Value of N

1.80  2.88  2.05 -0.89
5.25 -2.95 -0.95 -3.80
1.58 -2.69 -2.90 -1.04
-1.11 -0.66 -0.59  0.80  :End of matrix A

9.52  24.35  0.77 -6.22  :End of vector b

```

## 10.3 Program Results

F07AAF Example Program Results

```

Solution
      1.0000      -1.0000      3.0000      -5.0000

Details of factorization
      1          2          3          4
1      5.2500      -2.9500      -0.9500      -3.8000

```

2	0.3429	3.8914	2.3757	0.4129
3	0.3010	-0.4631	-1.5139	0.2948
4	-0.2114	-0.3299	0.0047	0.1314

Pivot indices

2	2	3	4
---	---	---	---

---