

# NAG Library Routine Document

## F07MDF (DSYTRF)

**Note:** before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

### 1 Purpose

F07MDF (DSYTRF) computes the Bunch–Kaufman factorization of a real symmetric indefinite matrix.

### 2 Specification

```
SUBROUTINE F07MDF (UPLO, N, A, LDA, IPIV, WORK, LWORK, INFO)
  INTEGER          N, LDA, IPIV(*), LWORK, INFO
  REAL (KIND=nag_wp) A(LDA,*), WORK(max(1,LWORK))
  CHARACTER(1)    UPLO
```

The routine may be called by its LAPACK name *dsytrf*.

### 3 Description

F07MDF (DSYTRF) factorizes a real symmetric matrix  $A$ , using the Bunch–Kaufman diagonal pivoting method.  $A$  is factorized as either  $A = PU DU^T P^T$  if  $UPLO = 'U'$  or  $A = PL DL^T P^T$  if  $UPLO = 'L'$ , where  $P$  is a permutation matrix,  $U$  (or  $L$ ) is a unit upper (or lower) triangular matrix and  $D$  is a symmetric block diagonal matrix with 1 by 1 and 2 by 2 diagonal blocks;  $U$  (or  $L$ ) has 2 by 2 unit diagonal blocks corresponding to the 2 by 2 blocks of  $D$ . Row and column interchanges are performed to ensure numerical stability while preserving symmetry.

This method is suitable for symmetric matrices which are not known to be positive definite. If  $A$  is in fact positive definite, no interchanges are performed and no 2 by 2 blocks occur in  $D$ .

### 4 References

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

### 5 Arguments

1: UPLO – CHARACTER(1) *Input*

*On entry:* specifies whether the upper or lower triangular part of  $A$  is stored and how  $A$  is to be factorized.

UPLO = 'U'

The upper triangular part of  $A$  is stored and  $A$  is factorized as  $PU DU^T P^T$ , where  $U$  is upper triangular.

UPLO = 'L'

The lower triangular part of  $A$  is stored and  $A$  is factorized as  $PL DL^T P^T$ , where  $L$  is lower triangular.

*Constraint:* UPLO = 'U' or 'L'.

2: N – INTEGER *Input*

*On entry:*  $n$ , the order of the matrix  $A$ .

*Constraint:*  $N \geq 0$ .

3: A(LDA,\*) – REAL (KIND=nag\_wp) array Input/Output

**Note:** the second dimension of the array A must be at least  $\max(1, N)$ .

*On entry:* the  $n$  by  $n$  symmetric indefinite matrix  $A$ .

If UPLO = 'U', the upper triangular part of  $A$  must be stored and the elements of the array below the diagonal are not referenced.

If UPLO = 'L', the lower triangular part of  $A$  must be stored and the elements of the array above the diagonal are not referenced.

*On exit:* the upper or lower triangle of  $A$  is overwritten by details of the block diagonal matrix  $D$  and the multipliers used to obtain the factor  $U$  or  $L$  as specified by UPLO.

4: LDA – INTEGER Input

*On entry:* the first dimension of the array A as declared in the (sub)program from which F07MDF (DSYTRF) is called.

*Constraint:*  $LDA \geq \max(1, N)$ .

5: IPIV(\*) – INTEGER array Output

**Note:** the dimension of the array IPIV must be at least  $\max(1, N)$ .

*On exit:* details of the interchanges and the block structure of  $D$ . More precisely,

if  $IPIV(i) = k > 0$ ,  $d_{ii}$  is a 1 by 1 pivot block and the  $i$ th row and column of  $A$  were interchanged with the  $k$ th row and column;

if UPLO = 'U' and  $IPIV(i-1) = IPIV(i) = -l < 0$ ,  $\begin{pmatrix} d_{i-1,i-1} & \bar{d}_{i,i-1} \\ \bar{d}_{i,i-1} & d_{ii} \end{pmatrix}$  is a 2 by 2 pivot block and the  $(i-1)$ th row and column of  $A$  were interchanged with the  $l$ th row and column;

if UPLO = 'L' and  $IPIV(i) = IPIV(i+1) = -m < 0$ ,  $\begin{pmatrix} d_{ii} & d_{i+1,i} \\ d_{i+1,i} & d_{i+1,i+1} \end{pmatrix}$  is a 2 by 2 pivot block and the  $(i+1)$ th row and column of  $A$  were interchanged with the  $m$ th row and column.

6: WORK(max(1, LWORK)) – REAL (KIND=nag\_wp) array Workspace

*On exit:* if INFO = 0, WORK(1) contains the minimum value of LWORK required for optimum performance.

7: LWORK – INTEGER Input

*On entry:* the dimension of the array WORK as declared in the (sub)program from which F07MDF (DSYTRF) is called, unless LWORK = -1, in which case a workspace query is assumed and the routine only calculates the optimal dimension of WORK (using the formula given below).

*Suggested value:* for optimum performance LWORK should be at least  $N \times nb$ , where  $nb$  is the **block size**.

*Constraint:*  $LWORK \geq 1$  or  $LWORK = -1$ .

8: INFO – INTEGER Output

*On exit:* INFO = 0 unless the routine detects an error (see Section 6).

## 6 Error Indicators and Warnings

INFO < 0

If INFO =  $-i$ , argument  $i$  had an illegal value. An explanatory message is output, and execution of the program is terminated.

INFO > 0

Element  $\langle value \rangle$  of the diagonal is exactly zero. The factorization has been completed, but the block diagonal matrix  $D$  is exactly singular, and division by zero will occur if it is used to solve a system of equations.

## 7 Accuracy

If UPLO = 'U', the computed factors  $U$  and  $D$  are the exact factors of a perturbed matrix  $A + E$ , where

$$|E| \leq c(n)\epsilon P|U||D||U^T|P^T,$$

$c(n)$  is a modest linear function of  $n$ , and  $\epsilon$  is the *machine precision*.

If UPLO = 'L', a similar statement holds for the computed factors  $L$  and  $D$ .

## 8 Parallelism and Performance

F07MDF (DSYTRF) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this routine. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

## 9 Further Comments

The elements of  $D$  overwrite the corresponding elements of  $A$ ; if  $D$  has 2 by 2 blocks, only the upper or lower triangle is stored, as specified by UPLO.

The unit diagonal elements of  $U$  or  $L$  and the 2 by 2 unit diagonal blocks are not stored. The remaining elements of  $U$  or  $L$  are stored in the corresponding columns of the array A, but additional row interchanges must be applied to recover  $U$  or  $L$  explicitly (this is seldom necessary). If IPIV( $i$ ) =  $i$ , for  $i = 1, 2, \dots, n$  (as is the case when  $A$  is positive definite), then  $U$  or  $L$  is stored explicitly (except for its unit diagonal elements which are equal to 1).

The total number of floating-point operations is approximately  $\frac{1}{3}n^3$ .

A call to F07MDF (DSYTRF) may be followed by calls to the routines:

F07MEF (DSYTRS) to solve  $AX = B$ ;

F07MGF (DSYCON) to estimate the condition number of  $A$ ;

F07MJF (DSYTRI) to compute the inverse of  $A$ .

The complex analogues of this routine are F07MRF (ZHETRF) for Hermitian matrices and F07NRF (ZSYTRF) for symmetric matrices.

## 10 Example

This example computes the Bunch–Kaufman factorization of the matrix  $A$ , where

$$A = \begin{pmatrix} 2.07 & 3.87 & 4.20 & -1.15 \\ 3.87 & -0.21 & 1.87 & 0.63 \\ 4.20 & 1.87 & 1.15 & 2.06 \\ -1.15 & 0.63 & 2.06 & -1.81 \end{pmatrix}.$$

### 10.1 Program Text

```

Program f07mdfe

!      F07MDF Example Program Text

!      Mark 26 Release. NAG Copyright 2016.

!      .. Use Statements ..
Use nag_library, Only: dsytrf, nag_wp, x04caf
!      .. Implicit None Statement ..
Implicit None
!      .. Parameters ..
Integer, Parameter          :: nin = 5, nout = 6
!      .. Local Scalars ..
Integer                    :: i, ifail, info, lda, lwork, n
Character (1)              :: uplo
!      .. Local Arrays ..
Real (Kind=nag_wp), Allocatable :: a(:,,:), work(:)
Integer, Allocatable       :: ipiv(:)
!      .. Executable Statements ..
Write (nout,*) 'F07MDF Example Program Results'
!      Skip heading in data file
Read (nin,*)
Read (nin,*) n
lda = n
lwork = 64*n
Allocate (a(lda,n),work(lwork),ipiv(n))

!      Read A from data file

Read (nin,*) uplo
If (uplo=='U') Then
  Read (nin,*)(a(i,i:n),i=1,n)
Else If (uplo=='L') Then
  Read (nin,*)(a(i,1:i),i=1,n)
End If

!      Factorize A
!      The NAG name equivalent of dsytrf is f07mdf
Call dsytrf(uplo,n,a,lda,ipiv,work,lwork,info)

Write (nout,*)
Flush (nout)

!      Print details of factorization

!      ifail: behaviour on error exit
!      =0 for hard exit, =1 for quiet-soft, =-1 for noisy-soft
ifail = 0
Call x04caf(uplo,'Nonunit',n,n,a,lda,'Details of factorization',ifail)

!      Print pivot indices

Write (nout,*)
Write (nout,*) 'IPIV'
Write (nout,99999) ipiv(1:n)

If (info/=0) Then

```

```

      Write (nout,*) 'The factor D is singular'
    End If

99999 Format ((3X,7I11))
    End Program f07mdfe

```

## 10.2 Program Data

```

F07MDF Example Program Data
  4                               :Value of N
  'L'                             :Value of UPLO
  2.07
  3.87 -0.21
  4.20  1.87  1.15
 -1.15  0.63  2.06 -1.81 :End of matrix A

```

## 10.3 Program Results

F07MDF Example Program Results

Details of factorization

	1	2	3	4
1	2.0700			
2	4.2000	1.1500		
3	0.2230	0.8115	-2.5907	
4	0.6537	-0.5960	0.3031	0.4074

IPIV				
	-3	-3	3	4

---